PRODUCT & RELIABILITY REVIEW

A strong preview.
Make saving and recovery safer next.

18 October 2026 · Review baseline: BailaCue 0.2.5 / build8.

Source and UX review, prior native screenshots, current unit/browser checks and synthetic failure reproductions; no production database writes or private user media access.

What is already strong

- Provider/account/file identity and explicit folder selection preserve separate Salsa/Bachata sources and prevent silent upload redirection.
- Native trims create new files; existing Android evidence verifies output duration, original-byte preservation and explicit Photos saving.
- App-scoped sessions, server-derived owner IDs and metadata-only sync limit the credentials and device paths exposed to the app or sync store.
- The release workflow gates APK publication on native acceptance, with public-byte checks recorded separately.

These are source/design strengths supported by existing preview tests, not a certification of live provider or production security behavior.

First priorities

1. Protect device-only clips and metadata during restore
2. Make logout and cleanup failure-safe
3. Make confirmed online saves durable before deleting the phone file
4. Preserve pending imports and editor drafts when device lock activates
5. Then simplify player/onboarding and scale large libraries

The requested rating-led Salsa/Bachata daily mix is implemented in the new source. Other findings remain recommendations; no broad fixes or production changes were silently applied.

BailaCue or BailaQue?

The owner chose to keep BailaCue. Cue expresses a practice prompt in English. Que is generally read keh in Spanish and may need pronunciation/spelling reinforcement. This is a naming recommendation, not a trademark or store-availability search.

A display-name change can preserve the installed package, signing certificate, OAuth registration and existing local data; do not rename internal identifiers merely for branding.

High · Sync · A01

Cloud restore can hide local-only clips

Restoring an older cloud snapshot replaces the entire video list. A local-only clip absent from that snapshot disappears from the library even though its phone file remains. No merge preview or undo is offered.

Improve: Keep local-only entries or archive them, show a restore preview and create a recoverable local backup before replacing metadata.

Reproduced with the real restoreSnapshot function and synthetic metadata: one local entry became zero.

open · src/core/sync.ts:66; src/app/account.tsx:215

High · Accounts · A02

A cleanup failure can prevent sign-out

Sign-out is reached only after reminders, file deletions, provider disconnects and library removal. A filesystem/provider error aborts cleanup before clearing the app session.

Improve: Make session teardown unconditional, track cleanup failures separately and retry leftover file removal. Explicitly identify unsynced/local-only material before destructive account cleanup.

Injected a filesystem failure into the actual cleanup function; account.logout was never reached. No real account or file was deleted.

open · src/app/account.tsx:54; src/services/account.tsx:102

High · Uploads · A03

Online-only cleanup runs before durable metadata commit

The provider has the completed video, but React state updates are persisted later through a queued effect. A force-stop or storage write failure after local file deletion can leave stale local references or lose recent metadata. This does not mean the confirmed cloud MP4 is deleted.

Improve: Persist a confirmed-upload receipt and the new library entry before removing the local file. Make cleanup a recoverable transaction with a journal.

Ordering confirmed in source. The force-stop/storage-failure scenario has not been reproduced on a physical phone.

open · src/app/transfer/[id].tsx:127; src/services/store.tsx:56

Medium · Sync · A04

Snapshots lack structural runtime validation

Server validation checks object size and forbidden keys, but an incomplete/version-incompatible object can be saved. Restore assumes arrays exist and can throw.

Improve: Validate snapshots against a versioned runtime schema on both sides; reject malformed payloads before changing the device library and retain a last-known-good copy.

The real restoreSnapshot({version:1}, local) threw a missing-map error. Production was not queried or modified.

open · supabase/functions/bailacue-api/handler.ts:315; src/core/sync.ts:60

Medium · Offline storage · A05

Expired authentication is treated like revoked file permission

Provider reauth errors enter the same download-deletion path as missing/restricted files. A temporary login problem can remove a useful offline download.

Improve: Distinguish expired sign-in from confirmed permission revocation. Request reconnect without deleting the file solely because of token expiry; keep explicit provider restriction handling.

Source review

open · src/services/cloud/playback.ts:55

Medium · Performance · A06

Large libraries render every card and scans repeatedly search arrays

The library uses ScrollView with map, and reconciliation repeatedly uses findIndex. Work grows with the full library rather than visible items.

Improve: Use a virtualized list, indexed maps for provider identities, memoized search and bounded thumbnail caches. Benchmark 100, 1000 and 10000 videos before setting performance claims.

Illustrative Node workspace scan benchmark without provider I/O:100 videos=1.93ms;1000=9.11ms;5000=97.84ms;10000=403.60ms. Single runs, not a phone/render/memory performance guarantee.

open · src/app/(tabs)/library.tsx:110; src/components/ui.tsx:343; src/core/sources.ts:39

Medium · Library · A07

Online videos miss useful thumbnail previews

Provider thumbnails are available in mapped metadata but not assigned when a new remote library video is created. Many online cards show the generic play placeholder.

Improve: Fetch/cache authenticated thumbnails securely, preserve placeholders on failure and avoid persisting tokens or expiring media links.

Source review

open · src/core/sources.ts:57; src/components/VideoCard.tsx:39

Medium · Onboarding · A08

Provider registration and reconnect flows need a simpler user journey

The app still requires one-time app-level OAuth registration and users can encounter app-key/setup terminology. Multiple Google connections also require careful account switching: token lookup explicitly refuses the wrong current Google user.

Improve: Finish app-owner registration, guide users through connect, select Salsa/Bachata folders and upload permission in one flow, and show the account identity on every reconnect. Test real consent and expiry with both folders.

Source review and existing mocked tests only; real Google/Dropbox transfers remain unverified here.

open · src/app/storage.tsx:237; src/services/cloud/accounts.ts:62

Medium · Player design · A09

Player, trim, storage and notes compete in one long page

Common playback actions and less frequent settings share the same scrolling surface. Editing or adding notes can push the video out of view.

Improve: Keep a compact player/control dock visible and organize Practice, Trim and Notes into focused panels. Use a bottom sheet for storage/destination selection rather than repeated tall cards.

Source review

open · src/app/video/[id].tsx:257

Medium · Daily Picks · A10

Ratings should lead and Salsa/Bachata need separate daily slots

The previous score allowed label/feedback bonuses to outweigh star ratings, and a single total count did not guarantee one video of each style.

Improve: Use rating-first ranking within each style, independent cooldown fallback, a minimum rating, explicit refresh and empty slots when no eligible video exists.

Ten new unit cases and a browser journey cover rating priority, one-per-style, thresholds, cooldown, persistence and explicit refresh. Google ARTEMIS build9 also passed actual rated imports and both native style picks.

implemented and verified in published 0.2.6/build9 · src/core/recommendations.ts:1; src/app/(tabs)/settings.tsx:1

Medium · Local media · A11

Unfinished imports need recovery and cleanup

A picked/recorded video is retained in owned storage before its metadata is saved. An interrupted import can leave an unreferenced file, and there is no startup recovery journal.

Improve: Persist import drafts and recover or remove abandoned owned files after a safe grace period. Include exports and partial transfers in the same storage manager.

Source review

open · src/services/media.native.ts:16; src/app/(tabs)/upload.tsx:27

Low · Labels · A12

Preference labels use a different input model

Import, folder and video labels have a searchable picker, while favorite labels use comma-separated text. Artist names containing commas are awkward and suggestions are inconsistent.

Improve: Reuse the existing label picker for preferences and offer searchable artist/type filters in Library.

Source review

open · src/app/(tabs)/settings.tsx:74; src/components/LabelPicker.tsx:1

Medium · Accessibility · A13

Weekday labels and large-text layouts need device review

Weekday chips expose repeated S/T letters without full weekday accessibility names. Several horizontal rows depend on compact text. A physical TalkBack/Dynamic Type review has not been done.

Improve: Give weekdays full accessible names, test large system text/landscape and announce upload/export state changes. Test all critical controls with TalkBack and VoiceOver.

Weekday naming confirmed in source; screen-reader and large-text device outcomes are not claimed.

open · src/app/(tabs)/settings.tsx:148; src/components/ui.tsx:139

Medium · Practice timer · A14

Active sessions are not recovered after process termination

Running state and elapsed time live in component memory. Delayed timer callbacks can also add more than the intended focus interval.

Improve: Persist an active-session record, cap elapsed time at its deadline and offer resume/discard after interruption. Add interruption/clock-change cases.

Source review

open · src/app/(tabs)/practice.tsx:23; src/app/(tabs)/practice.tsx:41

Medium · Privacy · A15

App-switcher and screenshot privacy need explicit validation

The lock resets on background only. Inactive transitions and app-switcher snapshots require platform-specific checking; current tests do not demonstrate their protection.

Improve: Review inactive-state masking and platform snapshot protection, with a clear user setting and physical-device validation.

Validation gap, not a demonstrated privacy leak.

open · src/components/PrivacyGate.tsx:13

Medium · Dependencies · A16

Dependency audit requires SDK-compatible triage

npm audit --omit=dev reported 29 affected dependency entries (20 high, 9 moderate) linked to three underlying advisories. Build-tool dependencies are included by the package tree; this is not evidence of 29 exploitable mobile-app flaws.

Improve: Trace each advisory to shipped/runtime use versus tooling, update within Expo SDK compatibility, and review a native dependency inventory. Do not apply the suggested force downgrade to old Expo/React Native majors.

Actual npm audit and dependency-path inspection. No exploit was attempted.

open · package-lock.json:1

Medium · Account security · A17

Shared-identity password resets need scoped-session revocation validation

BailaCue opaque sessions live for 30 days and are checked against their own session table. The in-app password action deletes them, but this source does not show a hook invalidating them after a password reset/change performed elsewhere in shared Me+.

Improve: Verify any existing server-side identity/session-version hook, then ensure external password recovery and security revocation invalidate BailaCue sessions too. Add an integration case without changing unrelated health/auth policies.

Source-level validation gap. The existing production Me+ reset/hook behavior was not inspected and no real account recovery was performed.

open · supabase/functions/bailacue-api/handler.ts:235; supabase/functions/bailacue-api/handler.ts:254; supabase/functions/bailacue-api/handler.ts:292

High · Device lock and import recovery · A18

Background locking can unmount a pending import or editor

With device lock enabled, background changes replace the routed screen tree with the lock UI. Android can report background while a system picker/camera activity is open. Local component state can therefore be discarded while that operation is pending, and returning/unlocking can mount a fresh empty form.

Improve: Preserve the routed tree behind a privacy overlay, and persist import/edit drafts. Lock on appropriate transitions without destroying pending operation state. Validate picker, camera and OAuth round-trips with device lock enabled.

Conditional source risk supported by official AppState documentation. Not reproduced on a physical phone or an emulator with biometrics configured.

open · src/components/PrivacyGate.tsx:13; src/components/PrivacyGate.tsx:31; src/app/(tabs)/upload.tsx:27; https://reactnative.dev/docs/appstate

Evidence and limits

Fresh TypeScript, lint and all 100 existing tests passed before the new feature work.

110 tests /11 suites, five Chromium journeys, type/lint, Expo Doctor and web export passed. Build9 passed all11 ARTEMIS checks and published; public bytes match the tested APK.

Historical build8 passed ten ARTEMIS checks. The current build9 independently passed all11 checks.

29 dependency entries trace to three advisories; many are in tooling. This does not establish mobile exploitability.

Live provider transfers, two-user account acceptance, physical accessibility/notification/privacy testing and iOS remain unverified.

Machine-readable findings and source references · Build9 evidence and remaining validation gaps