

Recovery from Security Intrusions in Cloud Computing



Dário Nascimento

68210 - MERC
Instituto Superior Técnico
Universidade de Lisboa

Supervisor:

Prof. Miguel Pupo Correia

Agenda

1 Motivation

Motivation

2 Related Work

Related Work

3 Proposed
Solution

Proposed Solution

Goals
Architecture
Evaluation

Goals

Architecture

Evaluation

4 Conclusion

Conclusion

Schedule
Conclusion

Schedule

Conclusion



1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Increasing number of critical applications in Cloud

Intent to compromise:

- Confidentiality
- Integrity
- Availability

Intrusion:

- Intentional vulnerability exploitation
- Malicious fault

Recover the application **integrity** to prevent **losses**

Motivation

1 Motivation


2 Related Work

3 Proposed Solution

Goals
Architecture
Evaluation

4 Conclusion

Schedule
Conclusion



Motivation

1 Motivation

2 Related Work


3 Proposed Solution

Goals
Architecture
Evaluation

4 Conclusion

Schedule
Conclusion

- Software flaws
- New attack methods
- Configuration and usage mistakes (malicious or accidental)
- Legitimate requests



1 Motivation

2 Related Work


3 Proposed Solution

Goals
Architecture
Evaluation

4 Conclusion

Schedule
Conclusion

Intrusions and failures happen!



1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

How to recover from intrusions in PaaS?



1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Accept intrusions and remove their effects

- Identify the intrusion effects
- Remove intrusion effects
- Recover the application integrity
- Tolerate intrusions: recovery without exposing downtime ¹
- Recover from user and administrator mistakes

¹Does not replace the prevention and tolerance



1. Identification of intrusion effects

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Goal: Identify the intrusion actions or objects

- IDS: *[Taser, ITDB, Phoenix, Retro, Dare, Goel et al., Undo for Operators]*
- Software update *[Warp, Aire]*

1. Identification of intrusion effects

1 Motivation


2 Related Work

3 Proposed Solution

Goals
Architecture
Evaluation

4 Conclusion

Schedule
Conclusion





2. Remove intrusion effects

1 Motivation

2 Related Work

3 Proposed Solution

Goals
Architecture
Evaluation


4 Conclusion

Schedule
Conclusion

- Versioning [*Phoenix, Warp, Aire*]
- Snapshot [*Taser, Retro, Date, Undo for Operators*]
- Compensation [*Goel et al, ITDB*]

storage vs computing

3. Recover the application integrity



- No replay [*Taser, ITDB, Phoenix*]
- Taint via replay [*Retro, Dare, Goel et al, Warp, Aire*]
- Replay all [*Undo for Operators*]

Recovery: Where?

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- Operating system [*Taser, Retro*]:
 - System calls, files and sockets
- Database [*ITDB, Phoenix*]:
 - Read and write sets: table, table block, row or field
- Web Applications [*Goel et al, Warp, Aire, Undo for Operators*]:
 - User requests and database transactions

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- **Scalability**

- Single database and server

- **Integration**

- Lack of generic application support
- Configuration per application

- **Application downtime**

1 Motivation

2 Related Work

3 Proposed
Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Shuttle: Intrusion recovery service for PaaS

- PaaS Integration
 - Standard architecture for Web Applications
 - Service-oriented database access through provided libraries
 - Service available without setup and configuration
- NoSQL databases

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Remove the effects of:

- Software flaws
- Corrupted requests and data
- Intrusions in PaaS instances

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- Support software updates
- Low runtime overhead
- NoSQL database snapshot
- Recover without stopping the application



Architecture: Overview

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

1. Records the user requests
2. Tracks the dependencies between requests using the database
3. Loads a snapshot
4. Replays the legitimate user requests

Architecture: Recording

1 Motivation

2 Related Work

3 Proposed Solution

Goals


Architecture

Evaluation

4 Conclusion

Schedule

Conclusion



Architecture: Recovery

1. Load a previous snapshot in background
2. Get the requests order using the graph
3. Send the requests in parallel using the replay nodes

1 Motivation

2 Related Work

3 Proposed Solution

Goals


Architecture

Evaluation

4 Conclusion

Schedule

Conclusion





Architecture: PaaS

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- PaaS controller lunches new database and application instances
- Clean images: replace corrupted instances
- Pay-per-use model
- Virtually unlimited computing and storage resources

Architecture: Branching

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture


Evaluation

4 Conclusion

Schedule

Conclusion

- Support multiple recovery branches
- The branch is defined by the request header



1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- **Prototype:** Java Servlet (Spring Framework) version of Question & Answers System
- **Data:** Data crawled from Stackoverflow.com
- **Database:** Cassandra and Voldemort (Key-Value store, DynamoDB)
- **PaaS:** OpenShift, AppScale (Google App Engine)
- **IaaS:** OpenStack and Amazon Web Services or Google Cloud Platform

1 Motivation

2 Related Work

3 Proposed Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

- **Record impact:** Delay, throughput, resource usage, maximum load
- **Replay:** Precision, recall, duration and scalability
- **Integrity and Availability:** Corrupted and unavailable data during recovery
- **Concurrency:** Correctness and performance improvement
- **Cost:** Monetary cost in a public cloud provider

Schedule

1 Motivation


2 Related Work

3 Proposed Solution

Goals
Architecture
Evaluation

4 Conclusion

Schedule
Conclusion



1 Motivation

2 Related Work

3 Proposed
Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Shuttle is the first:

- Intrusion recovery service for PaaS using replay
- To NoSQL databases and snapshotting
- To concern the parallel replay

Amongst the first:

- To incorporate the instance renewing
- To recover without application downtime



1 Motivation

2 Related Work

3 Proposed
Solution

Goals

Architecture

Evaluation

4 Conclusion

Schedule

Conclusion

Thank you for your attention