

Neomutt Default Functions and Bindings

David Nebauer

8 October 2022

Table 1: Generic

Key	Function	Description
^L	select-entry	select the current entry
	refresh	clear and redraw the screen
/	select-entry	select the current entry
	search-reverse	search backwards for a regular expression
!	shell-escape	invoke a command in a subshell
*	last-entry	move to the last entry
/	search	search for a regular expression
1	jump	jump to an index number
2	jump	jump to an index number
3	jump	jump to an index number
4	jump	jump to an index number
5	jump	jump to an index number
6	jump	jump to an index number
7	jump	jump to an index number
8	jump	jump to an index number
9	jump	jump to an index number
:	enter-command	enter a neomuttrc command
;	tag-prefix	apply next function to tagged messages
<	previous-line	scroll up one line
=	first-entry	move to the first entry
>	next-line	scroll down one line
?	help	this screen
H	top-page	move to the top of the page
L	bottom-page	move to the bottom of the page
M	middle-page	move to the middle of the page
Z	previous-page	move to the previous page
[half-up	scroll up 1/2 page
]	half-down	scroll down 1/2 page
j	next-entry	move to the next entry
k	previous-entry	move to the previous entry

Key	Function	Description
n	search-next	search for next match
t	tag-entry	tag the current entry
z	next-page	move to the next page
	next-entry	move to the next entry
	previous-entry	move to the previous entry
	previous-page	move to the previous page
	next-page	move to the next page
	first-entry	move to the first entry
	next-page	move to the next page
	previous-page	move to the previous page
	select-entry	select the current entry
	last-entry	move to the last entry

Table 2: Index

Key	Function	Description
^D	delete-thread	delete all messages in thread
^E	edit-type	edit attachment content type
^F	forget-passphrase	wipe passphrases from memory
	next-new-then-unread	jump to the next new or unread message
	display-message	display a message
^K	extract-keys	extract supported public keys
	display-message	display a message
^N	next-thread	jump to the next thread
^P	previous-thread	jump to previous thread
^R	read-thread	mark the current thread as read
^T	untag-pattern	untag messages matching a pattern
^U	undelele-thread	undelele all messages in thread
	previous-new-then-unread	jump to the previous new or unread message
C	decode-copy	make decoded (text/plain) copy
P	check-traditional-pgp	check for classic PGP
V	collapse-all	collapse/uncollapse all threads
c	change-folder-readonly	open a different folder in read only mode
d	delete-subthread	delete all messages in subthread
e	resend-message	use the current message as a template for a new one
i	change-newsgroup-readonly	open a different newsgroup in read only mode
k	mail-key	mail a PGP public key
l	show-limit	show currently active limit pattern
n	next-subthread	jump to the next subthread
p	previous-subthread	jump to previous subthread

Key	Function	Description
r	read-subthread	mark the current subthread as read
s	decode-save	make decoded copy (text/plain) and delete
t	tag-thread	tag the current thread
u	undelele-subthread	undelele all messages in subthread
v	collapse-thread	collapse/uncollapse current thread
	display-message	display a message
#	break-thread	break the thread in two
\$	sync-mailbox	save changes to mailbox
%	toggle-write	toggle whether the mailbox will be rewritten
&	link-threads	link tagged message to the current one
.	mailbox-list	list mailboxes with new mail
@	display-address	display full address of sender
A	autocrypt-acct-menu	manage autocrypt accounts
C	copy-message	copy a message to a file/mailbox
D	delete-pattern	delete messages matching a pattern
F	flag-message	toggle a message's 'important' flag
G	fetch-mail	retrieve mail from POP server
J	next-entry	move to the next entry
K	previous-entry	move to the previous entry
L	list-reply	reply to specified mailing list
M	show-log-messages	show log (and debug) messages
N	toggle-new	toggle a message's 'new' flag
O	sort-reverse	sort messages in reverse order
P	parent-message	jump to parent message in thread
Q	query	query external program for addresses
R	recall-message	recall a postponed message
T	tag-pattern	tag messages matching a pattern

Key	Function	Description
U	undelete-pattern	undelete messages matching a pattern
V	show-version	show the NeoMutt version number and date
W	clear-flag	clear a status flag from a message
Y	edit-label	add, change, or delete a message's label
a	create-alias	create an alias from a message sender
b	bounce-message	re-mail a message to another user
c	change-folder	open a different folder
d	delete-message	delete the current entry
e	edit-or-view-raw-message	edit the raw message if the mailbox is not read-only, otherwise view it
f	forward-message	forward a message with comments
g	group-reply	reply to all recipients
h	display-toggle-weed	display message and toggle header weeding
i	change-newsgroup	open a different newsgroup
j	next-undeleted	move to the next undeleted message
k	previous-undeleted	move to the previous undeleted message
l	limit	show only messages matching a pattern
m	mail	compose a new mail message
o	sort-mailbox	sort messages
p	print-message	print the current entry
q	quit	save changes to mailbox and quit
r	reply	reply to a message
s	save-message	save message/attachment to a mailbox/file

Key	Function	Description
u	undelete-message	undelete the current entry
v	view-attachments	show MIME attachments
w	set-flag	set a status flag on a message
x	exit	exit this menu
	pipe-entry	pipe message/attachment to a shell command
~	mark-message	create a hotkey macro for the current message
	next-undeleted	move to the next undeleted message
	previous-undeleted	move to the previous undeleted message
	display-message	display a message
	alias-dialog	open the aliases dialog
	catchup	mark all articles in newsgroup as read
	change-vfolder	open a different virtual folder
	compose-to-sender	compose new message to the current message sender
	decrypt-copy	make decrypted copy
	decrypt-save	make decrypted copy and delete
	edit	edit the raw message (edit and edit-raw-message are synonyms)
	edit-raw-message	edit the raw message (edit and edit-raw-message are synonyms)
	entire-thread	read entire thread of the current message
	followup-message	followup to newsgroup
	forward-to-group	forward to newsgroup
	get-children	get all children of the current message
	get-message	get message with Message-Id
	get-parent	get parent of the current message

Key	Function	Description
	group-chat-reply	reply to all recipients preserving To/Cc
	imap-fetch-mail	force retrieval of mail from IMAP server
	imap-logout-all	logout from all IMAP servers
	limit-current-thread	limit view to current thread
	list-subscribe	subscribe to a mailing list
	list-unsubscribe	unsubscribe from a mailing list
	modify-labels	modify (notmuch/imap) tags
	modify-labels-then-hide	modify (notmuch/imap) tags and then hide message
	modify-tags	modify (notmuch/imap) tags
	modify-tags-then-hide	modify (notmuch/imap) tags and then hide message
	next-new	jump to the next new message
	next-unread	jump to the next unread message
	next-unread-mailbox	open next mailbox with new mail
	post-message	post message to newsgroup
	previous-new	jump to the previous new message
	previous-unread	jump to the previous unread message
	purge-message	delete the current entry, bypassing the trash folder
	purge-thread	delete the current thread, bypassing the trash folder
	quasi-delete	delete from NeoMutt, don't touch on disk
	reconstruct-thread	reconstruct thread containing current message
	root-message	jump to root message in thread
	sidebar-first	move the highlight to the first mailbox

Key	Function	Description
	sidebar-last	move the highlight to the last mailbox
	sidebar-next	move the highlight to next mailbox
	sidebar-next-new	move the highlight to next mailbox with new mail
	sidebar-open	open highlighted mailbox
	sidebar-page-down	scroll the sidebar down 1 page
	sidebar-page-up	scroll the sidebar up 1 page
	sidebar-prev	move the highlight to previous mailbox
	sidebar-prev-new	move the highlight to previous mailbox with new mail
	sidebar-toggle-virtual	toggle between mailboxes and virtual mailboxes
	sidebar-toggle-visible	make the sidebar (in)visible
	tag-subthread	tag the current subthread
	toggle-read	toggle view of read messages
	vfolder-from-query	generate virtual folder from query
	vfolder-from-query-readonly	generate a read-only virtual folder from query
	vfolder-window-backward	shifts virtual folder time window backwards
	vfolder-window-forward	shifts virtual folder time window forwards
	vfolder-window-reset	resets virtual folder time window to the present
	view-raw-message	show the raw message
	check-stats	calculate message statistics for all mailboxes
	current-bottom	move entry to bottom of screen
	current-middle	move entry to middle of screen
	current-top	move entry to top of screen

Key	Function	Description
	end-cond	end of conditional execution (noop)
	jump	jump to an index number
	search-opposite	search for next match in opposite direction
	tag-prefix-cond	apply next function ONLY to tagged messages
	what-key	display the keycode for a key press

Table 3: Pager

Key	Function	Description
^D	delete-thread	delete all messages in thread
^E	edit-type	edit attachment content type
^F	forget-passphrase	wipe passphrases from memory
	next-new-then-unread	jump to the next new or unread message
	next-line	scroll down one line
^K	extract-keys	extract supported public keys
^L	redraw-screen	clear and redraw the screen
	next-line	scroll down one line
^N	next-thread	jump to the next thread
^P	previous-thread	jump to previous thread
^R	read-thread	mark the current thread as read
^U	undelete-thread	undelete all messages in thread
/	search-reverse	search backwards for a regular expression
C	decode-copy	make decoded (text/plain) copy
P	check-traditional-pgp	check for classic PGP
c	change-folder-readonly	open a different folder in read only mode
d	delete-subthread	delete all messages in subthread
e	resend-message	use the current message as a template for a new one
k	mail-key	mail a PGP public key
n	next-subthread	jump to the next subthread
p	previous-subthread	jump to previous subthread
r	read-subthread	mark the current subthread as read
s	decode-save	make decoded copy (text/plain) and delete
u	undelete-subthread	undelete all messages in subthread
	next-page	move to the next page

Key	Function	Description
!	shell-escape	invoke a command in a subshell
#	break-thread	break the thread in two
\$	sync-mailbox	save changes to mailbox
%	toggle-write	toggle whether the mailbox will be rewritten
&	link-threads	link tagged message to the current one
-	previous-page	move to the previous page
.	mailbox-list	list mailboxes with new mail
/	search	search for a regular expression
1	jump	jump to an index number
2	jump	jump to an index number
3	jump	jump to an index number
4	jump	jump to an index number
5	jump	jump to an index number
6	jump	jump to an index number
7	jump	jump to an index number
8	jump	jump to an index number
9	jump	jump to an index number
:	enter-command	enter a neomuttrc command
?	help	this screen
@	display-address	display full address of sender
C	copy-message	copy a message to a file/mailbox
F	flag-message	toggle a message's 'important' flag
H	skip-headers	jump to first line after headers
J	next-entry	move to the next entry
K	previous-entry	move to the previous entry
L	list-reply	reply to specified mailing list
N	mark-as-new	toggle a message's 'new' flag
O	sort-reverse	sort messages in reverse order
P	parent-message	jump to parent message in thread
Q	quit	save changes to mailbox and quit
R	recall-message	recall a postponed message

Key	Function	Description
S	skip-quoted	skip beyond quoted text
T	toggle-quoted	toggle display of quoted text
V	show-version	show the NeoMutt version number and date
W	clear-flag	clear a status flag from a message
Y	edit-label	add, change, or delete a message's label
	search-toggle	toggle search pattern coloring
^	top	jump to the top of the message
a	create-alias	create an alias from a message sender
b	bounce-message	re-mail a message to another user
c	change-folder	open a different folder
d	delete-message	delete the current entry
e	edit-or-view-raw-message	edit the raw message if the mailbox is not read-only, otherwise view it
f	forward-message	forward a message with comments
g	group-reply	reply to all recipients
h	display-toggle-weed	display message and toggle header weeding
i	exit	exit this menu
j	next-undeleted	move to the next undeleted message
k	previous-undeleted	move to the previous undeleted message
m	mail	compose a new mail message
n	search-next	search for next match
o	sort-mailbox	sort messages
p	print-message	print the current entry
q	exit	exit this menu
r	reply	reply to a message

Key	Function	Description
s	save-message	save message/attachment to a mailbox/file
t	tag-message	tag the current entry
u	undelete-message	undelete the current entry
v	view-attachments	show MIME attachments
w	set-flag	set a status flag on a message
x	exit	exit this menu
	pipe-entry	pipe message/attachment to a shell command
	next-undeleted	move to the next undeleted message
	previous-undeleted	move to the previous undeleted message
	previous-undeleted	move to the previous undeleted message
	next-undeleted	move to the next undeleted message
	top	jump to the top of the message
	previous-line	scroll up one line
	next-page	move to the next page
	previous-page	move to the previous page
	next-line	scroll down one line
	bottom	jump to the bottom of the message
	change-newsgroup	open a different newsgroup
	change-newsgroup-readonly	open a different newsgroup in read only mode
	change-vfolder	open a different virtual folder
	check-stats	calculate message statistics for all mailboxes
	compose-to-sender	compose new message to the current message sender
	decrypt-copy	make decrypted copy

Key	Function	Description
	decrypt-save edit	make decrypted copy and delete edit the raw message (edit and edit-raw-message are synonyms)
	edit-raw-message	edit the raw message (edit and edit-raw-message are synonyms)
	entire-thread	read entire thread of the current message
	followup-message	followup to newsgroup
	forward-to-group	forward to newsgroup
	group-chat-reply	reply to all recipients preserving To/Cc
	half-down	scroll down 1/2 page
	half-up	scroll up 1/2 page
	imap-fetch-mail	force retrieval of mail from IMAP server
	imap-logout-all	logout from all IMAP servers
	jump	jump to an index number
	list-subscribe	subscribe to a mailing list
	list-unsubscribe	unsubscribe from a mailing list
	modify-labels	modify (notmuch/imap) tags
	modify-labels-then-hide	modify (notmuch/imap) tags and then hide message
	modify-tags	modify (notmuch/imap) tags
	modify-tags-then-hide	modify (notmuch/imap) tags and then hide message
	next-new	jump to the next new message
	next-unread	jump to the next unread message
	next-unread-mailbox	open next mailbox with new mail
	post-message	post message to newsgroup
	previous-new	jump to the previous new message
	previous-new-then- unread	jump to the previous new or unread message

Key	Function	Description
	previous-unread	jump to the previous unread message
	print-entry	print the current entry
	purge-message	delete the current entry, bypassing the trash folder
	purge-thread	delete the current thread, bypassing the trash folder
	quasi-delete	delete from NeoMutt, don't touch on disk
	reconstruct-thread	reconstruct thread containing current message
	root-message	jump to root message in thread
	save-entry	save message/attachment to a mailbox/file
	search-opposite	search for next match in opposite direction
	show-log-messages	show log (and debug) messages
	sidebar-first	move the highlight to the first mailbox
	sidebar-last	move the highlight to the last mailbox
	sidebar-next	move the highlight to next mailbox
	sidebar-next-new	move the highlight to next mailbox with new mail
	sidebar-open	open highlighted mailbox
	sidebar-page-down	scroll the sidebar down 1 page
	sidebar-page-up	scroll the sidebar up 1 page
	sidebar-prev	move the highlight to previous mailbox
	sidebar-prev-new	move the highlight to previous mailbox with new mail

Key	Function	Description
	sidebar-toggle-virtual	toggle between mailboxes and virtual mailboxes
	sidebar-toggle-visible	make the sidebar (in)visible
	vfolder-from-query	generate virtual folder from query
	vfolder-from-query-readonly	a read-only virtual folder from query
	view-raw-message	show the raw message
	what-key	display the keycode for a key press
	error-history	show log (and debug) messages

Table 4: Attachments

Key	Function	Description
^E	edit-type	edit attachment content type
^F	forget-passphrase	wipe passphrases from memory
	view-attach	view attachment using mailcap entry if necessary
^K	extract-keys	extract supported public keys
	view-attach	view attachment using mailcap entry if necessary
P	check-traditional-pgp	check for classic PGP
e	resend-message	use the current message as a template for a new one
L	list-reply	reply to specified mailing list
T	view-text	view attachment as text
b	bounce-message	re-mail a message to another user
d	delete-entry	delete the current entry
f	forward-message	forward a message with comments
g	group-reply	reply to all recipients
h	display-toggle-weed	display message and toggle header weeding
m	view-mailcap	force viewing of attachment using mailcap
p	print-entry	print the current entry
q	exit	exit this menu
r	reply	reply to a message
s	save-entry	save message/attachment to a mailbox/file
u	undelete-entry	undelete the current entry
v	collapse-parts	toggle display of subparts
	pipe-entry	pipe message/attachment to a shell command

Key	Function	Description
	view-attach	view attachment using mailcap entry if necessary
	compose-to-sender	compose new message to the current message sender
	followup-message	followup to newsgroup
	forward-to-group	forward to newsgroup
	group-chat-reply	reply to all recipients preserving To/Cc
	list-subscribe	subscribe to a mailing list
	list-unsubscribe	unsubscribe from a mailing list
	view-pager	view attachment in pager using copiousoutput mailcap
	check-stats	calculate message statistics for all mailboxes
	current-bottom	move entry to bottom of screen
	current-middle	move entry to middle of screen
	current-top	move entry to top of screen
	end-cond	end of conditional execution (noop)
	jump	jump to an index number
	search-opposite	search for next match in opposite direction
	show-log-messages	show log (and debug) messages
	tag-prefix-cond	apply next function ONLY to tagged messages
	what-key	display the keycode for a key press
	error-history	show log (and debug) messages