Date :

```
Interface Moveable{
  void Move up();
  void movedown();
  void move left();
  void moveright();
}
class Moveable Point implements Moveable {
  int x;
  int y;
  int x speed;
  int y speed;
  Moveable Point (int x, int y, int xspeed, int y speed)
    this.x = x;
    This.y = y;
    This.xspeed = xspeed;
    this.yspeed = y speed;
  }
  public void moveup() {
      y += yspeed;
  }
  public void movedown() {
      y -= yspeed;
  }
```

Vinlab

Date :

```
public void moveleft.(){
    x -= xspeed;
}
Public void moveright () {
    x += xspeed;
}
public String toString (){
  return "(" + x + ", " + y + ")";
}
}
class MoveableCircle implements Moveable {
 int radius;
 MoveablePoint center;
 MoveableCircle (MoveablePoint center, int radius){
    This.center = center;
    This. radius = radius;
 }
    public void moveup () {
    center.moveup ();
}
    publicvoid movedown (){
    center. movedown ();
}
```

Vinlab Paper

Date :

```
    public void moveleft (){
    center. moveleft ();
  }
  public void moveright (){
    center. moveright ();
  }
  public String toString () {
    return "circle radius = " + radius + " center = " + center
  }
}
public class Main{
    public static void main (String[] args){
        Moveable Point p = new Moveable Point (0, 0, 2, 3);
        Moveable Circle c = new Moveable circle (p, 5);
    system. out. println (c);
    c. moveRight ();
    c. moveup ();
    system. out. println (c);
```