

## Regarding SERVLET CONFIG

A servlet specific configuration object created by a servlet container to pass information to a servlet during initialization. To supply servlet specific init parameters

1. Represents Servlet specific configuration.

Defined in `javax.servlet.ServletConfig` -- interface.

2. Who creates its instance ?

Web container(WC)

3. When ?

After WC creates servlet instance(via def constr), `ServletConfig` instance is created & then it invokes `init()` method of the servlet.

4. Usage

To store servlet specific init parameters.

(i.e the init-param is accessible to one servlet only or you can say that the init-param data is private for a particular servlet.)

5. Where to add servlet specific init parameters?

Can be added either in `web.xml` or `@WebServlet` annotation.

XML Tags

```
<servlet>
  <servlet-name>init</servlet-name>
  <servlet-class>ex.TestInitParam</servlet-class>
  <init-param>
    <param-name>name</param-name>
    <param-value>value</param-value>
  </init-param>
</servlet>
<servlet-mapping>
  <servlet-name>init</servlet-name>
  <url-pattern>/test_init</url-pattern>
</servlet-mapping>
```

OR

```
@WebServlet(value="/test",
initParams={@WebInitParam(name="nm1",value="val1"),@WebInitParam(name="nm2",value="val2")})
public class MyServlet extends HttpServlet {....}
```

6. How to access servlet specific init params from a servlet ?

6.1 Override `init()` method

6.2 Get `ServletConfig`

Method of Servlet i/f

```
public ServletConfig getServletConfig()
```

6.3 Get the init params from `ServletConfig`

Method of `ServletConfig` i/f

```
String getInitparameter(String paramName) : rets the param value.
```