

Expression Language implicit variables(case sensitive)

Maps
pageScope
requestScope
sessionScope
applicationScope

1. `pageContext` : `PageContext` object (`javax.servlet.jsp.PageContext`) asso. with current page.
2. `pageScope` - a Map that contains page-scoped attribute names and their values.
3. `requestScope` - a Map that contains request-scoped attribute names and their values.
4. `sessionScope` - a Map that contains session-scoped attribute names and their values.
5. `applicationScope` - a Map that contains application-scoped attribute names and their values.
6. `param` - a Map that contains rq. parameter names to a single String parameter value (obtained by calling `ServletRequest.getParameter(String name)`).
7. `paramValues` - a Map that contains rq. param name to a `String[]` of all values for that parameter (similar to calling `ServletRequest.getParameterValues(name)`).
8. `initParam` - a Map that contains context initialization parameter names and their String value (obtained by calling `ServletContext.getInitParameter(String name)`).
eg : `${initParam.db_drvr}`

9. `cookie` : Map.Entry of cookies. (entrySet of cookies)
eg : `${cookie.cookieName.value}`

key ---cookie name

value ---`javax.servlet.http.Cookie`

`${cookie.JSESSIONID.value}`
---`cookie.get("JSESSIONID").getValue()`

10. To retrieve err details from Error handling page.
ERR causing URI : `${pageContext.errorData.requestURI}`
ERR code : `${pageContext.errorData.statusCode}`
ERR Mesg : `${pageContext.exception.message}`
Throwable : `${pageContext.errorData.throwable}`
Throwable Root cause: `${pageContext.errorData.throwable.cause}`

eg :
`<c:set var="abc" scope="session" value="Hello User...."/>`
`${sessionScope.abc}`