

**Exercise for MA-INF 2201 Computer Vision WS18/19**  
**10.11.2018**  
**Submission on 17.11.2018**

1. A function is *submodular* when it satisfies the equation:

$$P(\beta, \gamma) + P(\alpha, \delta) - P(\beta, \delta) - P(\alpha, \gamma) \geq 0$$

for all  $\alpha, \beta, \gamma, \delta$  such that  $\beta > \alpha$  and  $\delta > \gamma$ . Show that:

- 1.1. the *Quadratic Function*  $P(\omega_m, \omega_n) = c(\omega_m - \omega_n)^2$  is *submodular*, (2 points)
  - 1.2. the *Potts model*  $P(\omega_m, \omega_n) = c(1 - \delta(\omega_m - \omega_n))$  is not *submodular*, by providing a counter-example to the above criterion. (2 points)
2. Provide a graph structure using the *alpha expansion* method that encodes the initial state of 6 nodes (a,b,c,d,e,f) with initial states  $\beta\beta\gamma\alpha\alpha\gamma$  for the case where the label  $\alpha$  is expanded. (4 points)
3. Denoise the binary image using a Markov random field. For cut, use max-flow/min-cut algorithm. Read a noisy binary image *noise.png*.
- (a) Create a graph for the image using all the pixels as nodes. Each pixel (node) are connected to the “source node” and the “sink node” with directed edges as well as the directed edges between its left, top, right and bottom neighboring pixel. (2 points)
  - (b) The Unaries are defined by.

$$\begin{aligned} P(x_n | w_n = 0) &= \text{Bern}_{x_n}[\rho] \\ P(x_n | w_n = 1) &= \text{Bern}_{x_n}[1 - \rho] \\ U_n(w_n) &= -\log(P(x_n | w_n)) \end{aligned}$$

where  $\rho = 0.6$ . Use the following, three combination of pairwise values and display all three denoised outputs: (5 points)

- i.  $P[w_m = 0, w_n = 0] = P[w_m = 1, w_n = 1] = 0.01$  and  $P[w_m = 0, w_n = 1] = P[w_m = 1, w_n = 0] = 0.15$
- ii.  $P[w_m = 0, w_n = 0] = P[w_m = 1, w_n = 1] = 0.01$  and  $P[w_m = 0, w_n = 1] = P[w_m = 1, w_n = 0] = 0.3$
- iii.  $P[w_m = 0, w_n = 0] = P[w_m = 1, w_n = 1] = 0.01$  and  $P[w_m = 0, w_n = 1] = P[w_m = 1, w_n = 0] = 0.6$

*Note:* For min-cut/max-flow algorithm install “PyMaxflow”

4. Extend the algorithm in 3 for a grayscale image *noise2.png* using Alpha Expansion Algorithm. There are only three labels  $[l_1, l_2, l_3]$  where  $l_1 = 1, l_2 = 2, l_3 = 3$  corresponding to grey values of (0,128,255) respectively. Unary costs are defined as:

$$\begin{aligned} P(x_n = l_i | w_n = l_i) &= \rho_{l_i} \\ P(x_n = l_j | w_n = l_i) &= \frac{(1 - \rho_{l_i})}{2} \quad \forall i \neq j \end{aligned}$$

where,  $\rho_{l_i} = 0.8$ . Define the pairwise cost using Potts Model:  $P(\omega_m, \omega_n) = (1 - \delta(\omega_m - \omega_n))$  (5 points)