

Lab Part 0

Short Course

Timing the spatialProcess function

Motivation for problems as problem size gets large

Note: loading **LatticeKrig** package automatically loads **fields**.


```
set.seed(222)
tabSP<- NULL
nObs<- c( 100,200,400,500,750,1000,1500,2500)
for( n in nObs ){
  x<- cbind( seq( 0,1,,n))
  Sigma<- Matern( rdist(x,x)/.15, smoothness = 1.0)
  U<- rnorm(n)
  E<- rnorm(n)
  # add in a linear part too to match fitting
  y<- (1 + x) + t(chol(Sigma))%*%U + .05*E
  # fix the range to compare with example later on
  elapsedTime<- system.time(
    out<- spatialProcess( x,y, aRange=.15 )
  )
  #print(c( n,elapsedTime[3]) )
  tabSP<- rbind( tabSP, c( n,elapsedTime[3]) )
}

print( tabSP)
```

```
##           elapsed
## [1,]  100    0.054
## [2,]  200    0.178
## [3,]  400    0.792
## [4,]  500    1.251
## [5,]  750    2.844
## [6,] 1000    4.226
## [7,] 1500    9.862
## [8,] 2500   27.192
```

Take a look at a log-log plot. Linear in log-log means a polynomial relationship.

```
plot( tabSP, log="xy", xlab="n", ylab="time (seconds)",
      col="grey", pch=16)
```



```
y<- log10(tabSP[,2])
x<- log10(tabSP[,1])
lm( y~x)
```

```
##
## Call:
## lm(formula = y ~ x)
##
## Coefficients:
## (Intercept)          x
##      -5.174       1.944
```

Timing just the Cholesky

Focusing just on the Cholesky decomposition – theoretically the most time consuming step. Use a test matrix that has lots of zeroes and compare timing to sparse Cholesky decomposition.

```
sizes<- c(100, 200, 400, 500, 750, 1000, 2000, 3000, 4000, 5000, 8000, 10000)
NTotal<- length( sizes)
tabChol<- matrix( NA, nrow= NTotal, ncol=4)
dimnames(tabChol)<- list( NULL, c("N","Dense",
                                "Sparse","speedup"))


for(k in 1:NTotal) {
  N<- sizes[k]
  #weights are a 4th difference
  # sparse matrix construction using LatticeKrig utility
  SMat <- LKDiag( c(1, -10, 27, -10, 1), N)
  # convert to full ( now the zeroes are consider real values)
  FMat <- spam2full(SMat)
  # dense matrix Cholesky
  startTime <- Sys.time() #
  FChol <- chol(FMat)
  deltaF<- as.numeric(Sys.time() - startTime) #
  # sparse matrix Cholesky
  startTime <- Sys.time()
  SChol <- chol(SMat)
  deltaS<- as.numeric(Sys.time() - startTime )
  tabChol[k,]<- c(N,deltaF, deltaS, deltaF/deltaS )
}
print( tabChol)
```

##		N	Dense	Sparse	speedup
##	[1,]	100	7.009506e-05	0.0011270046	0.0621959
##	[2,]	200	9.860992e-04	0.0084390640	0.1168494
##	[3,]	400	1.612186e-03	0.0002751350	5.8596187
##	[4,]	500	1.281023e-03	0.0002861023	4.4775000
##	[5,]	750	2.623796e-03	0.0003969669	6.6096096
##	[6,]	1000	3.937960e-03	0.0005118847	7.6930601
##	[7,]	2000	2.718496e-02	0.0008409023	32.3283244
##	[8,]	3000	8.675098e-02	0.0010418892	83.2631579
##	[9,]	4000	2.054529e-01	0.0013468266	152.5459373
##	[10,]	5000	4.343090e-01	0.0016679764	260.3807890
##	[11,]	8000	1.495651e+00	0.0025460720	587.4346849
##	[12,]	10000	2.784804e+00	0.0034070015	817.3768369

Log- log plot to look for polynomial dependence

```
matplot( tabChol[,1], tabChol[,2:3], type="p", pch=c( "D","S"),
xlab="N", ylab="time (sec)", log="xy")
title("Cholesky timing dense (D) vs sparse (S)
      for matrix with 2 off-diagonal bands ")
```

Cholesky timing dense (D) vs sparse (S) for matrix with 2 off-diagonal bands



On your own . . .

1. Extrapolating from the smaller sample results in **tabS** estimate the time for **spatialProcess** to handle a problem of size 26000 (about the size of the CO2 data set.)
2. Is the time for `spatialProcess (tabSP[,2])` linearly related to the time for the Cholesky decomposition (`tabChol[1:6, 2]`)?