

Overview

TestSeries information	
Name:	OSC_Imported/longitudinal_feature/ACC/ACC_OSC_Regression.ts
Last Change:	2026-06-30 15:01:57 TungNV68
Description:	
TestSeries started:	2026-06-30 15:05:18
TestSeries end:	2026-06-30 15:26:12
Duration:	0h 20min 54s

Application information	
Project Directory:	C:/CM_Projects/ADAS_Demo1
Name & Path:	CarMaker 15.1 - Car_Generic (build 3) (C:\IPG\carmaker\win64-15.1\bin\CarMaker.win64.exe)
Version:	15.1 (2026-05-05 10:41:09)
Host:	CPP00372923B (OS: win32)
Program started:	2026-06-30 11:50:49 by user TungNV68
Session log file:	SimOutput/ CPP00372923B/Log/ CPP00372923B_20260630_105049.log

Report information	
GUI Version:	CarMaker Office 15.1
Author:	
Date of Creation:	2026-06-30 15:30:09

Remarks

Result Summary

Overall Results

Number of Tests:	95	100.0 %	
Tests passed:	0	0.0 %	✓
Tests skipped:	0	0.0 %	⏸
Tests with warning:	0	0.0 %	⚠
Tests failed:	91	95.8 %	⚡
Tests with error:	4	4.2 %	⚡
Tests not executed:	0	0.0 %	○

Detailed Results

ID	Test	Result
1	GROUP: longitudinal_feature / ACC	
1.1	OSC_Imported/longitudinal_feature/ACC/acc_csc_001	
1.1.1	acc_csc_001_ds001	⚡
1.1.2	acc_csc_001_ds002	⚡
1.1.3	acc_csc_001_ds003	⚡
1.1.4	acc_csc_001_ds004	⚡
1.1.5	acc_csc_001_ds005	⚡
1.2	OSC_Imported/longitudinal_feature/ACC/acc_csc_002	
1.2.1	acc_csc_002_ds001	⚡
1.2.2	acc_csc_002_ds002	⚡
1.2.3	acc_csc_002_ds003	⚡
1.2.4	acc_csc_002_ds004	⚡
1.2.5	acc_csc_002_ds005	⚡
1.3	OSC_Imported/longitudinal_feature/ACC/acc_csc_003	
1.3.1	acc_csc_003_ds001	⚡
1.3.2	acc_csc_003_ds002	⚡
1.3.3	acc_csc_003_ds003	⚡
1.3.4	acc_csc_003_ds004	⚡
1.3.5	acc_csc_003_ds005	⚡
1.4	OSC_Imported/longitudinal_feature/ACC/acc_csc_004	
1.4.1	acc_csc_004_ds001	⚡
1.4.2	acc_csc_004_ds002	⚡
1.4.3	acc_csc_004_ds003	⚡
1.4.4	acc_csc_004_ds004	⚡
1.4.5	acc_csc_004_ds005	⚡
1.5	OSC_Imported/longitudinal_feature/ACC/acc_csc_005	
1.5.1	acc_csc_005_ds001	⚡
1.5.2	acc_csc_005_ds002	⚡
1.5.3	acc_csc_005_ds003	⚡
1.5.4	acc_csc_005_ds004	⚡
1.5.5	acc_csc_005_ds005	⚡
1.6	OSC_Imported/longitudinal_feature/ACC/acc_csc_006	
1.6.1	acc_csc_006_ds001	⚡
1.6.2	acc_csc_006_ds002	⚡
1.6.3	acc_csc_006_ds003	⚡
1.6.4	acc_csc_006_ds004	⚡
1.6.5	acc_csc_006_ds005	⚡
1.7	OSC_Imported/longitudinal_feature/ACC/acc_csc_007	

ID	Test	Result
1.7.1	acc_csc_007_ds001	
1.7.2	acc_csc_007_ds002	
1.7.3	acc_csc_007_ds003	
1.7.4	acc_csc_007_ds004	
1.7.5	acc_csc_007_ds005	
1.8	OSC_Imported/longitudinal_feature/ACC/acc_csc_008	
1.8.1	acc_csc_008_ds001	
1.8.2	acc_csc_008_ds002	
1.8.3	acc_csc_008_ds003	
1.8.4	acc_csc_008_ds004	
1.8.5	acc_csc_008_ds005	
1.9	OSC_Imported/longitudinal_feature/ACC/acc_csc_009	
1.9.1	acc_csc_009_ds001	
1.9.2	acc_csc_009_ds002	
1.9.3	acc_csc_009_ds003	
1.9.4	acc_csc_009_ds004	
1.9.5	acc_csc_009_ds005	
1.10	OSC_Imported/longitudinal_feature/ACC/acc_csc_010	
1.10.1	acc_csc_010_ds001	
1.10.2	acc_csc_010_ds002	
1.10.3	acc_csc_010_ds003	
1.10.4	acc_csc_010_ds004	
1.10.5	acc_csc_010_ds005	
1.11	OSC_Imported/longitudinal_feature/ACC/acc_csc_011	
1.11.1	acc_csc_011_ds001	
1.11.2	acc_csc_011_ds002	
1.11.3	acc_csc_011_ds003	
1.11.4	acc_csc_011_ds004	
1.11.5	acc_csc_011_ds005	
1.12	OSC_Imported/longitudinal_feature/ACC/acc_csc_012	
1.12.1	acc_csc_012_ds001	
1.12.2	acc_csc_012_ds002	
1.12.3	acc_csc_012_ds003	
1.12.4	acc_csc_012_ds004	
1.12.5	acc_csc_012_ds005	
1.13	OSC_Imported/longitudinal_feature/ACC/acc_csc_013	
1.13.1	acc_csc_013_ds001	
1.13.2	acc_csc_013_ds002	
1.13.3	acc_csc_013_ds003	
1.13.4	acc_csc_013_ds004	
1.13.5	acc_csc_013_ds005	
1.14	OSC_Imported/longitudinal_feature/ACC/acc_csc_014	
1.14.1	acc_csc_014_ds001	
1.14.2	acc_csc_014_ds002	
1.14.3	acc_csc_014_ds003	
1.14.4	acc_csc_014_ds004	
1.14.5	acc_csc_014_ds005	
1.15	OSC_Imported/longitudinal_feature/ACC/acc_csc_015	
1.15.1	acc_csc_015_ds001	
1.15.2	acc_csc_015_ds002	
1.15.3	acc_csc_015_ds003	
1.15.4	acc_csc_015_ds004	
1.15.5	acc_csc_015_ds005	
1.16	OSC_Imported/longitudinal_feature/ACC/acc_csc_016	

ID	Test	Result
1.16.1	acc_csc_016_ds001	
1.16.2	acc_csc_016_ds002	
1.16.3	acc_csc_016_ds003	
1.16.4	acc_csc_016_ds004	
1.16.5	acc_csc_016_ds005	
1.17	OSC_Imported/longitudinal_feature/ACC/acc_csc_017	
1.17.1	acc_csc_017_ds001	
1.17.2	acc_csc_017_ds002	
1.17.3	acc_csc_017_ds003	
1.17.4	acc_csc_017_ds004	
1.17.5	acc_csc_017_ds005	
1.18	OSC_Imported/longitudinal_feature/ACC/acc_csc_018	
1.18.1	acc_csc_018_ds001	
1.18.2	acc_csc_018_ds002	
1.18.3	acc_csc_018_ds003	
1.18.4	acc_csc_018_ds004	
1.18.5	acc_csc_018_ds005	
1.19	OSC_Imported/longitudinal_feature/ACC/acc_csc_019	
1.19.1	acc_csc_019_ds001	
1.19.2	acc_csc_019_ds002	
1.19.3	acc_csc_019_ds003	
1.19.4	acc_csc_019_ds004	
1.19.5	acc_csc_019_ds005	

Detailed Results

1.1

Test # 1.1
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001

Characteristics

Name	Description
acc_csc_001_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_001_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_001_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_001_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_001_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_001_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_001_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_001_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_001_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_001_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_001_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_001_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_001_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_001_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_001_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_001_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_001_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_001_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_001_SafeDist	34.5021	34.5021	41.8847	51.4824	60.2934
acc_csc_001_SafeDistViolated	0.0	0.0	0.0	0.0	0.0
acc_csc_001_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_001_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_001_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_001_ComfortAx	-0.00072044	-0.00071733	-0.004	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
	9	8			
acc_csc_001_ComfortAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_001_EmergencyAx	-0.000720449	-0.000717338	-0.004	-0.004	-0.004
acc_csc_001_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_001_Jerk	3.93592e-007	2.51379e-006	0.0	0.0	0.0
acc_csc_001_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_001_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_001_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_001_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_001_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_001_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_001 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_001 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_001 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_001 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_001 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_001 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_001 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_001 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_001 - Safe Distance Consistency	✓	✓	✓	✓	✓
acc_csc_001 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_001 - Comfort Deceleration Limit	✓	✓	✓	✓	✓
acc_csc_001 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_001 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_001 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_001 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_001 - Impact Speed	✓	✓	✓	✓	✓

1.1.1

Test # 1.1.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001 └ acc_csc_001_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_001
Description:	TestRun converted from acc_csc_001_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TVSpeed	8
NValue	TV_initPos	35
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_001_140523.erg

Characteristics

Name	Value
acc_csc_001_ActualDist	999.0
acc_csc_001_SafeDist	34.50207129
acc_csc_001_SafeDistViolated	0.0
acc_csc_001_TTC	0.0
acc_csc_001_TTCWarnEver	0.0

Name	Value
acc_csc_001_TTCBadEver	0.0
acc_csc_001_ComfortAx	-0.0007204493223
acc_csc_001_ComfortAxOutOfBoundEver	0.0
acc_csc_001_EmergencyAx	-0.0007204493223
acc_csc_001_EmergencyAxOutOfBoundEver	0.0
acc_csc_001_Jerk	3.935923587e-007
acc_csc_001_JerkOverLimitEver	1.0
acc_csc_001_NoCollDist	999.0
acc_csc_001_NoCollDistViolatedEver	0.0
acc_csc_001_CollisionFlag	0.0
acc_csc_001_ImpactSpeed	0.0
acc_csc_001_CollisionEver	0.0

Criteria

Name	Result
acc_csc_001 - Safe Distance Consistency	✓
acc_csc_001 - Time To Collision	✓
acc_csc_001 - Comfort Deceleration Limit	✓
acc_csc_001 - Emergency Deceleration Bound	✓
acc_csc_001 - Jerk Limit	⚡
acc_csc_001 - No Collision Distance	✓
acc_csc_001 - Collision Flag	✓
acc_csc_001 - Impact Speed	✓

1.1.2

Test # 1.1.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001 └ acc_csc_001_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_001
Description:	TestRun converted from acc_csc_001_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	50
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_001_140535.erg

Characteristics

Name	Value
acc_csc_001_ActualDist	999.0
acc_csc_001_SafeDist	34.50206235
acc_csc_001_SafeDistViolated	0.0
acc_csc_001_TTC	0.0
acc_csc_001_TTCWarnEver	0.0

Name	Value
acc_csc_001_TTCBadEver	0.0
acc_csc_001_ComfortAx	-0.0007173379482
acc_csc_001_ComfortAxOutOfBoundEver	0.0
acc_csc_001_EmergencyAx	-0.0007173379482
acc_csc_001_EmergencyAxOutOfBoundEver	0.0
acc_csc_001_Jerk	2.513792197e-006
acc_csc_001_JerkOverLimitEver	1.0
acc_csc_001_NoCollDist	999.0
acc_csc_001_NoCollDistViolatedEver	0.0
acc_csc_001_CollisionFlag	0.0
acc_csc_001_ImpactSpeed	0.0
acc_csc_001_CollisionEver	0.0

Criteria

Name	Result
acc_csc_001 - Safe Distance Consistency	✓
acc_csc_001 - Time To Collision	✓
acc_csc_001 - Comfort Deceleration Limit	✓
acc_csc_001 - Emergency Deceleration Bound	✓
acc_csc_001 - Jerk Limit	⚡
acc_csc_001 - No Collision Distance	✓
acc_csc_001 - Collision Flag	✓
acc_csc_001 - Impact Speed	✓

1.1.3

Test # 1.1.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001 └ acc_csc_001_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_001
Description:	TestRun converted from acc_csc_001_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	15
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_001_140547.erg

Characteristics

Name	Value
acc_csc_001_ActualDist	999.0
acc_csc_001_SafeDist	41.88468438
acc_csc_001_SafeDistViolated	0.0
acc_csc_001_TTC	0.0
acc_csc_001_TTCWarnEver	0.0

Name	Value
acc_csc_001_TTCBadEver	0.0
acc_csc_001_ComfortAx	-0.004
acc_csc_001_ComfortAxOutOfBoundEver	0.0
acc_csc_001_EmergencyAx	-0.004
acc_csc_001_EmergencyAxOutOfBoundEver	0.0
acc_csc_001_Jerk	0.0
acc_csc_001_JerkOverLimitEver	1.0
acc_csc_001_NoCollDist	999.0
acc_csc_001_NoCollDistViolatedEver	0.0
acc_csc_001_CollisionFlag	0.0
acc_csc_001_ImpactSpeed	0.0
acc_csc_001_CollisionEver	0.0

Criteria

Name	Result
acc_csc_001 - Safe Distance Consistency	✓
acc_csc_001 - Time To Collision	✓
acc_csc_001 - Comfort Deceleration Limit	✓
acc_csc_001 - Emergency Deceleration Bound	✓
acc_csc_001 - Jerk Limit	⚡
acc_csc_001 - No Collision Distance	✓
acc_csc_001 - Collision Flag	✓
acc_csc_001 - Impact Speed	✓

1.1.4

Test # 1.1.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001 └ acc_csc_001_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_001
Description:	TestRun converted from acc_csc_001_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	20
NValue	TV_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_001_140559.erg

Characteristics

Name	Value
acc_csc_001_ActualDist	999.0
acc_csc_001_SafeDist	51.48244855
acc_csc_001_SafeDistViolated	0.0
acc_csc_001_TTC	0.0
acc_csc_001_TTCWarnEver	0.0

Name	Value
acc_csc_001_TTCBadEver	0.0
acc_csc_001_ComfortAx	-0.004
acc_csc_001_ComfortAxOutOfBoundEver	0.0
acc_csc_001_EmergencyAx	-0.004
acc_csc_001_EmergencyAxOutOfBoundEver	0.0
acc_csc_001_Jerk	0.0
acc_csc_001_JerkOverLimitEver	1.0
acc_csc_001_NoCollDist	999.0
acc_csc_001_NoCollDistViolatedEver	0.0
acc_csc_001_CollisionFlag	0.0
acc_csc_001_ImpactSpeed	0.0
acc_csc_001_CollisionEver	0.0

Criteria

Name	Result
acc_csc_001 - Safe Distance Consistency	✓
acc_csc_001 - Time To Collision	✓
acc_csc_001 - Comfort Deceleration Limit	✓
acc_csc_001 - Emergency Deceleration Bound	✓
acc_csc_001 - Jerk Limit	⚡
acc_csc_001 - No Collision Distance	✓
acc_csc_001 - Collision Flag	✓
acc_csc_001 - Impact Speed	✓

1.1.5

Test # 1.1.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_001 └ acc_csc_001_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_001
Description:	TestRun converted from acc_csc_001_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	24
NValue	TV_initPos	110
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_001_140611.erg

Characteristics

Name	Value
acc_csc_001_ActualDist	999.0
acc_csc_001_SafeDist	60.29343867
acc_csc_001_SafeDistViolated	0.0
acc_csc_001_TTC	0.0
acc_csc_001_TTCWarnEver	0.0

Name	Value
acc_csc_001_TTCBadEver	0.0
acc_csc_001_ComfortAx	-0.004
acc_csc_001_ComfortAxOutOfBoundEver	0.0
acc_csc_001_EmergencyAx	-0.004
acc_csc_001_EmergencyAxOutOfBoundEver	0.0
acc_csc_001_Jerk	0.0
acc_csc_001_JerkOverLimitEver	1.0
acc_csc_001_NoCollDist	999.0
acc_csc_001_NoCollDistViolatedEver	0.0
acc_csc_001_CollisionFlag	0.0
acc_csc_001_ImpactSpeed	0.0
acc_csc_001_CollisionEver	0.0

Criteria

Name	Result
acc_csc_001 - Safe Distance Consistency	✓
acc_csc_001 - Time To Collision	✓
acc_csc_001 - Comfort Deceleration Limit	✓
acc_csc_001 - Emergency Deceleration Bound	✓
acc_csc_001 - Jerk Limit	⚡
acc_csc_001 - No Collision Distance	✓
acc_csc_001 - Collision Flag	✓
acc_csc_001 - Impact Speed	✓

1.2

Test # 1.2
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002

Characteristics

Name	Description
acc_csc_002_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_002_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_002_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_002_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_002_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_002_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_002_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_002_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_002_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_002_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_002_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_002_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_002_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_002_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_002_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_002_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_002_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_002_ActualDist	25.9326	999.0	999.0	64.2743	999.0
acc_csc_002_SafeDist	15.8679	25.9196	35.2183	35.3661	44.9864
acc_csc_002_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_002_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_002_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_002_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_002_ComfortAx	0.0	2.8	-0.004	-0.301262	-0.004
acc_csc_002_ComfortAxOutOfBoundEver	0.0	1.0	1.0	1.0	1.0
acc_csc_002_EmergencyAx	0.0	2.8	-0.004	-0.301262	-0.004
acc_csc_002_EmergencyAxOutOfBou	0.0	0.0	0.0	0.0	0.0

Name	# 1	# 2	# 3	# 4	# 5
ndEver					
acc_csc_002_Jerk	0.0	0.0	0.0	0.222771	0.0
acc_csc_002_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_002_NoCollDist	25.9326	999.0	999.0	64.2743	999.0
acc_csc_002_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_002_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_002_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_002_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_002 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_002 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_002 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_002 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_002 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_002 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_002 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_002 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_002 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_002 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_002 - Comfort Deceleration Limit	✓	⚡	⚡	⚡	⚡
acc_csc_002 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_002 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_002 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_002 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_002 - Impact Speed	✓	✓	✓	✓	✓

1.2.1

Test # 1.2.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002 └ acc_csc_002_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_002
Description:	TestRun converted from acc_csc_002_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TVSpeed	7
NValue	TV_initPos	45
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_002_140623.erg

Characteristics

Name	Value
acc_csc_002_ActualDist	25.93263825
acc_csc_002_SafeDist	15.86794645
acc_csc_002_SafeDistViolated	1.0
acc_csc_002_TTC	0.0
acc_csc_002_TTCWarnEver	0.0

Name	Value
acc_csc_002_TTCBadEver	0.0
acc_csc_002_ComfortAx	0.0
acc_csc_002_ComfortAxOutOfBoundEver	0.0
acc_csc_002_EmergencyAx	0.0
acc_csc_002_EmergencyAxOutOfBoundEver	0.0
acc_csc_002_Jerk	0.0
acc_csc_002_JerkOverLimitEver	1.0
acc_csc_002_NoCollDist	25.93263825
acc_csc_002_NoCollDistViolatedEver	0.0
acc_csc_002_CollisionFlag	0.0
acc_csc_002_ImpactSpeed	0.0
acc_csc_002_CollisionEver	0.0

Criteria

Name	Result
acc_csc_002 - Safe Distance Consistency	
acc_csc_002 - Time To Collision	
acc_csc_002 - Comfort Deceleration Limit	
acc_csc_002 - Emergency Deceleration Bound	
acc_csc_002 - Jerk Limit	
acc_csc_002 - No Collision Distance	
acc_csc_002 - Collision Flag	
acc_csc_002 - Impact Speed	

1.2.2

Test # 1.2.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002 └ acc_csc_002_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_002
Description:	TestRun converted from acc_csc_002_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	60
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_002_140635.erg

Characteristics

Name	Value
acc_csc_002_ActualDist	999.0
acc_csc_002_SafeDist	25.91961335
acc_csc_002_SafeDistViolated	1.0
acc_csc_002_TTC	0.0
acc_csc_002_TTCWarnEver	0.0

Name	Value
acc_csc_002_TTCBadEver	0.0
acc_csc_002_ComfortAx	2.8
acc_csc_002_ComfortAxOutOfBoundEver	1.0
acc_csc_002_EmergencyAx	2.8
acc_csc_002_EmergencyAxOutOfBoundEver	0.0
acc_csc_002_Jerk	0.0
acc_csc_002_JerkOverLimitEver	1.0
acc_csc_002_NoCollDist	999.0
acc_csc_002_NoCollDistViolatedEver	0.0
acc_csc_002_CollisionFlag	0.0
acc_csc_002_ImpactSpeed	0.0
acc_csc_002_CollisionEver	0.0

Criteria

Name	Result
acc_csc_002 - Safe Distance Consistency	
acc_csc_002 - Time To Collision	
acc_csc_002 - Comfort Deceleration Limit	
acc_csc_002 - Emergency Deceleration Bound	
acc_csc_002 - Jerk Limit	
acc_csc_002 - No Collision Distance	
acc_csc_002 - Collision Flag	
acc_csc_002 - Impact Speed	

1.2.3

Test # 1.2.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002 └ acc_csc_002_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_002
Description:	TestRun converted from acc_csc_002_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_002_140647.erg

Characteristics

Name	Value
acc_csc_002_ActualDist	999.0
acc_csc_002_SafeDist	35.21827893
acc_csc_002_SafeDistViolated	1.0
acc_csc_002_TTC	0.0
acc_csc_002_TTCWarnEver	0.0

Name	Value
acc_csc_002_TTCBadEver	0.0
acc_csc_002_ComfortAx	-0.004
acc_csc_002_ComfortAxOutOfBoundEver	1.0
acc_csc_002_EmergencyAx	-0.004
acc_csc_002_EmergencyAxOutOfBoundEver	0.0
acc_csc_002_Jerk	0.0
acc_csc_002_JerkOverLimitEver	1.0
acc_csc_002_NoCollDist	999.0
acc_csc_002_NoCollDistViolatedEver	0.0
acc_csc_002_CollisionFlag	0.0
acc_csc_002_ImpactSpeed	0.0
acc_csc_002_CollisionEver	0.0

Criteria

Name	Result
acc_csc_002 - Safe Distance Consistency	
acc_csc_002 - Time To Collision	
acc_csc_002 - Comfort Deceleration Limit	
acc_csc_002 - Emergency Deceleration Bound	
acc_csc_002 - Jerk Limit	
acc_csc_002 - No Collision Distance	
acc_csc_002 - Collision Flag	
acc_csc_002 - Impact Speed	

1.2.4

Test # 1.2.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002 └ acc_csc_002_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_002
Description:	TestRun converted from acc_csc_002_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	105
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_002_140659.erg

Characteristics

Name	Value
acc_csc_002_ActualDist	64.27429172
acc_csc_002_SafeDist	35.36612753
acc_csc_002_SafeDistViolated	1.0
acc_csc_002_TTC	0.0
acc_csc_002_TTCWarnEver	0.0

Name	Value
acc_csc_002_TTCBadEver	0.0
acc_csc_002_ComfortAx	-0.3012617491
acc_csc_002_ComfortAxOutOfBoundEver	1.0
acc_csc_002_EmergencyAx	-0.3012617491
acc_csc_002_EmergencyAxOutOfBoundEver	0.0
acc_csc_002_Jerk	0.2227707982
acc_csc_002_JerkOverLimitEver	1.0
acc_csc_002_NoCollDist	64.27429172
acc_csc_002_NoCollDistViolatedEver	0.0
acc_csc_002_CollisionFlag	0.0
acc_csc_002_ImpactSpeed	0.0
acc_csc_002_CollisionEver	0.0

Criteria

Name	Result
acc_csc_002 - Safe Distance Consistency	
acc_csc_002 - Time To Collision	
acc_csc_002 - Comfort Deceleration Limit	
acc_csc_002 - Emergency Deceleration Bound	
acc_csc_002 - Jerk Limit	
acc_csc_002 - No Collision Distance	
acc_csc_002 - Collision Flag	
acc_csc_002 - Impact Speed	

1.2.5

Test # 1.2.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_002 └ acc_csc_002_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_002
Description:	TestRun converted from acc_csc_002_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	40.00 0	VelTransitio n 15.000 linear		Ego_cruise_action

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	120
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_002_140711.erg

Characteristics

Name	Value
acc_csc_002_ActualDist	999.0
acc_csc_002_SafeDist	44.98642746
acc_csc_002_SafeDistViolated	1.0
acc_csc_002_TTC	0.0
acc_csc_002_TTCWarnEver	0.0

Name	Value
acc_csc_002_TTCBadEver	0.0
acc_csc_002_ComfortAx	-0.004
acc_csc_002_ComfortAxOutOfBoundEver	1.0
acc_csc_002_EmergencyAx	-0.004
acc_csc_002_EmergencyAxOutOfBoundEver	0.0
acc_csc_002_Jerk	0.0
acc_csc_002_JerkOverLimitEver	1.0
acc_csc_002_NoCollDist	999.0
acc_csc_002_NoCollDistViolatedEver	0.0
acc_csc_002_CollisionFlag	0.0
acc_csc_002_ImpactSpeed	0.0
acc_csc_002_CollisionEver	0.0

Criteria

Name	Result
acc_csc_002 - Safe Distance Consistency	
acc_csc_002 - Time To Collision	
acc_csc_002 - Comfort Deceleration Limit	
acc_csc_002 - Emergency Deceleration Bound	
acc_csc_002 - Jerk Limit	
acc_csc_002 - No Collision Distance	
acc_csc_002 - Collision Flag	
acc_csc_002 - Impact Speed	

1.3

Test # 1.3

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_003

Characteristics

Name	Description
acc_csc_003_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_003_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_003_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_003_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_003_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_003_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_003_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_003_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_003_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_003_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_003_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_003_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_003_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_003_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_003_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_003_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_003_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_003_ActualDist	140.887	999.0	999.0	999.0	999.0
acc_csc_003_SafeDist	15.0	35.0457	46.113	57.4351	69.0002
acc_csc_003_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_003_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_003_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_003_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_003_ComfortAx	0.0	-0.004	-0.004	0.0225655	-5.81689e-005
acc_csc_003_ComfortAxOutOfBoundEver	1.0	1.0	1.0	1.0	1.0
acc_csc_003_EmergencyAx	0.0	-0.004	-0.004	0.0225655	-5.81689e-

Name	# 1	# 2	# 3	# 4	# 5
					005
acc_csc_003_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_003_Jerk	0.0	0.0	0.0	5.35716e-005	0.000400357
acc_csc_003_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_003_NoCollDist	140.887	999.0	999.0	999.0	999.0
acc_csc_003_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_003_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_003_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_003_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_003 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_003 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_003 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_003 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_003 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_003 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_003 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_003 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_003 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_003 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_003 - Comfort Deceleration Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_003 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_003 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_003 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_003 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_003 - Impact Speed	✓	✓	✓	✓	✓

1.3.1

Test # 1.3.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_003 └ acc_csc_003_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_003
Description:	TestRun converted from acc_csc_003_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	45
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_003_140723.erg

Characteristics

Name	Value
acc_csc_003_ActualDist	140.8871315
acc_csc_003_SafeDist	15.0
acc_csc_003_SafeDistViolated	1.0
acc_csc_003_TTC	0.0
acc_csc_003_TTCWarnEver	0.0
acc_csc_003_TTCBadEver	0.0
acc_csc_003_ComfortAx	0.0

Name	Value
acc_csc_003_ComfortAxOutOfBoundEver	1.0
acc_csc_003_EmergencyAx	0.0
acc_csc_003_EmergencyAxOutOfBoundEver	0.0
acc_csc_003_Jerk	0.0
acc_csc_003_JerkOverLimitEver	1.0
acc_csc_003_NoCollDist	140.8871315
acc_csc_003_NoCollDistViolatedEver	0.0
acc_csc_003_CollisionFlag	0.0
acc_csc_003_ImpactSpeed	0.0
acc_csc_003_CollisionEver	0.0

Criteria

Name	Result
acc_csc_003 - Safe Distance Consistency	
acc_csc_003 - Time To Collision	
acc_csc_003 - Comfort Deceleration Limit	
acc_csc_003 - Emergency Deceleration Bound	
acc_csc_003 - Jerk Limit	
acc_csc_003 - No Collision Distance	
acc_csc_003 - Collision Flag	
acc_csc_003 - Impact Speed	

1.3.2

Test # 1.3.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_003 └ acc_csc_003_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_003
Description:	TestRun converted from acc_csc_003_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_003_140735.erg

Characteristics

Name	Value
acc_csc_003_ActualDist	999.0
acc_csc_003_SafeDist	35.0456639
acc_csc_003_SafeDistViolated	1.0
acc_csc_003_TTC	0.0
acc_csc_003_TTCWarnEver	0.0
acc_csc_003_TTCBadEver	0.0
acc_csc_003_ComfortAx	-0.004

Name	Value
acc_csc_003_ComfortAxOutOfBoundEver	1.0
acc_csc_003_EmergencyAx	-0.004
acc_csc_003_EmergencyAxOutOfBoundEver	0.0
acc_csc_003_Jerk	0.0
acc_csc_003_JerkOverLimitEver	1.0
acc_csc_003_NoCollDist	999.0
acc_csc_003_NoCollDistViolatedEver	0.0
acc_csc_003_CollisionFlag	0.0
acc_csc_003_ImpactSpeed	0.0
acc_csc_003_CollisionEver	0.0

Criteria

Name	Result
acc_csc_003 - Safe Distance Consistency	
acc_csc_003 - Time To Collision	
acc_csc_003 - Comfort Deceleration Limit	
acc_csc_003 - Emergency Deceleration Bound	
acc_csc_003 - Jerk Limit	
acc_csc_003 - No Collision Distance	
acc_csc_003 - Collision Flag	
acc_csc_003 - Impact Speed	

1.3.3

Test # 1.3.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_003 └ acc_csc_003_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_003
Description:	TestRun converted from acc_csc_003_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_003_140747.erg

Characteristics

Name	Value
acc_csc_003_ActualDist	999.0
acc_csc_003_SafeDist	46.11303428
acc_csc_003_SafeDistViolated	1.0
acc_csc_003_TTC	0.0
acc_csc_003_TTCWarnEver	0.0
acc_csc_003_TTCBadEver	0.0
acc_csc_003_ComfortAx	-0.004

Name	Value
acc_csc_003_ComfortAxOutOfBoundEver	1.0
acc_csc_003_EmergencyAx	-0.004
acc_csc_003_EmergencyAxOutOfBoundEver	0.0
acc_csc_003_Jerk	0.0
acc_csc_003_JerkOverLimitEver	1.0
acc_csc_003_NoCollDist	999.0
acc_csc_003_NoCollDistViolatedEver	0.0
acc_csc_003_CollisionFlag	0.0
acc_csc_003_ImpactSpeed	0.0
acc_csc_003_CollisionEver	0.0

Criteria

Name	Result
acc_csc_003 - Safe Distance Consistency	
acc_csc_003 - Time To Collision	
acc_csc_003 - Comfort Deceleration Limit	
acc_csc_003 - Emergency Deceleration Bound	
acc_csc_003 - Jerk Limit	
acc_csc_003 - No Collision Distance	
acc_csc_003 - Collision Flag	
acc_csc_003 - Impact Speed	

1.3.4

Test # 1.3.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_003 └ acc_csc_003_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_003
Description:	TestRun converted from acc_csc_003_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	75
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_003_140759.erg

Characteristics

Name	Value
acc_csc_003_ActualDist	999.0
acc_csc_003_SafeDist	57.4351243
acc_csc_003_SafeDistViolated	1.0
acc_csc_003_TTC	0.0
acc_csc_003_TTCWarnEver	0.0
acc_csc_003_TTCBadEver	0.0
acc_csc_003_ComfortAx	0.02256545926

Name	Value
acc_csc_003_ComfortAxOutOfBoundEver	1.0
acc_csc_003_EmergencyAx	0.02256545926
acc_csc_003_EmergencyAxOutOfBoundEver	0.0
acc_csc_003_Jerk	5.357163957e-005
acc_csc_003_JerkOverLimitEver	1.0
acc_csc_003_NoCollDist	999.0
acc_csc_003_NoCollDistViolatedEver	0.0
acc_csc_003_CollisionFlag	0.0
acc_csc_003_ImpactSpeed	0.0
acc_csc_003_CollisionEver	0.0

Criteria

Name	Result
acc_csc_003 - Safe Distance Consistency	
acc_csc_003 - Time To Collision	
acc_csc_003 - Comfort Deceleration Limit	
acc_csc_003 - Emergency Deceleration Bound	
acc_csc_003 - Jerk Limit	
acc_csc_003 - No Collision Distance	
acc_csc_003 - Collision Flag	
acc_csc_003 - Impact Speed	

1.3.5

Test # 1.3.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_003 └ acc_csc_003_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_003
Description:	TestRun converted from acc_csc_003_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_003_140811.erg

Characteristics

Name	Value
acc_csc_003_ActualDist	999.0
acc_csc_003_SafeDist	69.00016724
acc_csc_003_SafeDistViolated	1.0
acc_csc_003_TTC	0.0
acc_csc_003_TTCWarnEver	0.0
acc_csc_003_TTCBadEver	0.0
acc_csc_003_ComfortAx	-5.816889808e-005

Name	Value
acc_csc_003_ComfortAxOutOfBoundEver	1.0
acc_csc_003_EmergencyAx	-5.816889808e-005
acc_csc_003_EmergencyAxOutOfBoundEver	0.0
acc_csc_003_Jerk	0.0004003569529
acc_csc_003_JerkOverLimitEver	1.0
acc_csc_003_NoCollDist	999.0
acc_csc_003_NoCollDistViolatedEver	0.0
acc_csc_003_CollisionFlag	0.0
acc_csc_003_ImpactSpeed	0.0
acc_csc_003_CollisionEver	0.0

Criteria

Name	Result
acc_csc_003 - Safe Distance Consistency	
acc_csc_003 - Time To Collision	
acc_csc_003 - Comfort Deceleration Limit	
acc_csc_003 - Emergency Deceleration Bound	
acc_csc_003 - Jerk Limit	
acc_csc_003 - No Collision Distance	
acc_csc_003 - Collision Flag	
acc_csc_003 - Impact Speed	

1.4

Test # 1.4

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_004

Characteristics

Name	Description
acc_csc_004_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_004_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_004_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_004_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_004_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_004_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_004_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_004_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_004_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_004_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_004_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_004_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_004_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_004_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_004_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_004_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_004_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_004_ActualDist	140.758	999.0	999.0	999.0	999.0
acc_csc_004_SafeDist	15.0	35.0433	46.1138	57.4351	69.0002
acc_csc_004_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_004_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_004_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_004_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_004_ComfortAx	0.0	-0.004	-0.004	0.0225655	-5.81689e-005
acc_csc_004_ComfortAxOutOfBoundEver	1.0	1.0	1.0	1.0	1.0
acc_csc_004_EmergencyAx	0.0	-0.004	-0.004	0.0225655	-5.81689e-

Name	# 1	# 2	# 3	# 4	# 5
					005
acc_csc_004_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_004_Jerk	0.0	0.0	0.0	5.35716e-005	0.000400357
acc_csc_004_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_004_NoCollDist	140.758	999.0	999.0	999.0	999.0
acc_csc_004_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_004_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_004_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_004_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_004 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_004 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_004 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_004 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_004 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_004 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_004 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_004 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_004 - Safe Distance Consistency					
acc_csc_004 - Time To Collision					
acc_csc_004 - Comfort Deceleration Limit					
acc_csc_004 - Emergency Deceleration Bound					
acc_csc_004 - Jerk Limit					
acc_csc_004 - No Collision Distance					
acc_csc_004 - Collision Flag					
acc_csc_004 - Impact Speed					

1.4.1

Test # 1.4.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_004 └ acc_csc_004_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_004
Description:	TestRun converted from acc_csc_004_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	45
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_004_140824.erg

Characteristics

Name	Value
acc_csc_004_ActualDist	140.7576311
acc_csc_004_SafeDist	15.0
acc_csc_004_SafeDistViolated	1.0
acc_csc_004_TTC	0.0
acc_csc_004_TTCWarnEver	0.0
acc_csc_004_TTCBadEver	0.0
acc_csc_004_ComfortAx	0.0

Name	Value
acc_csc_004_ComfortAxOutOfBoundEver	1.0
acc_csc_004_EmergencyAx	0.0
acc_csc_004_EmergencyAxOutOfBoundEver	0.0
acc_csc_004_Jerk	0.0
acc_csc_004_JerkOverLimitEver	1.0
acc_csc_004_NoCollDist	140.7576311
acc_csc_004_NoCollDistViolatedEver	0.0
acc_csc_004_CollisionFlag	0.0
acc_csc_004_ImpactSpeed	0.0
acc_csc_004_CollisionEver	0.0

Criteria

Name	Result
acc_csc_004 - Safe Distance Consistency	
acc_csc_004 - Time To Collision	
acc_csc_004 - Comfort Deceleration Limit	
acc_csc_004 - Emergency Deceleration Bound	
acc_csc_004 - Jerk Limit	
acc_csc_004 - No Collision Distance	
acc_csc_004 - Collision Flag	
acc_csc_004 - Impact Speed	

1.4.2

Test # 1.4.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_004 └ acc_csc_004_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_004
Description:	TestRun converted from acc_csc_004_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_004_140836.erg

Characteristics

Name	Value
acc_csc_004_ActualDist	999.0
acc_csc_004_SafeDist	35.04325655
acc_csc_004_SafeDistViolated	1.0
acc_csc_004_TTC	0.0
acc_csc_004_TTCWarnEver	0.0
acc_csc_004_TTCBadEver	0.0
acc_csc_004_ComfortAx	-0.004

Name	Value
acc_csc_004_ComfortAxOutOfBoundEver	1.0
acc_csc_004_EmergencyAx	-0.004
acc_csc_004_EmergencyAxOutOfBoundEver	0.0
acc_csc_004_Jerk	0.0
acc_csc_004_JerkOverLimitEver	1.0
acc_csc_004_NoCollDist	999.0
acc_csc_004_NoCollDistViolatedEver	0.0
acc_csc_004_CollisionFlag	0.0
acc_csc_004_ImpactSpeed	0.0
acc_csc_004_CollisionEver	0.0

Criteria

Name	Result
acc_csc_004 - Safe Distance Consistency	
acc_csc_004 - Time To Collision	
acc_csc_004 - Comfort Deceleration Limit	
acc_csc_004 - Emergency Deceleration Bound	
acc_csc_004 - Jerk Limit	
acc_csc_004 - No Collision Distance	
acc_csc_004 - Collision Flag	
acc_csc_004 - Impact Speed	

1.4.3

Test # 1.4.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_004 └ acc_csc_004_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_004
Description:	TestRun converted from acc_csc_004_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_004_140848.erg

Characteristics

Name	Value
acc_csc_004_ActualDist	999.0
acc_csc_004_SafeDist	46.11377499
acc_csc_004_SafeDistViolated	1.0
acc_csc_004_TTC	0.0
acc_csc_004_TTCWarnEver	0.0
acc_csc_004_TTCBadEver	0.0
acc_csc_004_ComfortAx	-0.004

Name	Value
acc_csc_004_ComfortAxOutOfBoundEver	1.0
acc_csc_004_EmergencyAx	-0.004
acc_csc_004_EmergencyAxOutOfBoundEver	0.0
acc_csc_004_Jerk	0.0
acc_csc_004_JerkOverLimitEver	1.0
acc_csc_004_NoCollDist	999.0
acc_csc_004_NoCollDistViolatedEver	0.0
acc_csc_004_CollisionFlag	0.0
acc_csc_004_ImpactSpeed	0.0
acc_csc_004_CollisionEver	0.0

Criteria

Name	Result
acc_csc_004 - Safe Distance Consistency	
acc_csc_004 - Time To Collision	
acc_csc_004 - Comfort Deceleration Limit	
acc_csc_004 - Emergency Deceleration Bound	
acc_csc_004 - Jerk Limit	
acc_csc_004 - No Collision Distance	
acc_csc_004 - Collision Flag	
acc_csc_004 - Impact Speed	

1.4.4

Test # 1.4.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_004 └ acc_csc_004_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_004
Description:	TestRun converted from acc_csc_004_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	75
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_004_140900.erg

Characteristics

Name	Value
acc_csc_004_ActualDist	999.0
acc_csc_004_SafeDist	57.4351243
acc_csc_004_SafeDistViolated	1.0
acc_csc_004_TTC	0.0
acc_csc_004_TTCWarnEver	0.0
acc_csc_004_TTCBadEver	0.0
acc_csc_004_ComfortAx	0.02256545926

Name	Value
acc_csc_004_ComfortAxOutOfBoundEver	1.0
acc_csc_004_EmergencyAx	0.02256545926
acc_csc_004_EmergencyAxOutOfBoundEver	0.0
acc_csc_004_Jerk	5.357163957e-005
acc_csc_004_JerkOverLimitEver	1.0
acc_csc_004_NoCollDist	999.0
acc_csc_004_NoCollDistViolatedEver	0.0
acc_csc_004_CollisionFlag	0.0
acc_csc_004_ImpactSpeed	0.0
acc_csc_004_CollisionEver	0.0

Criteria

Name	Result
acc_csc_004 - Safe Distance Consistency	
acc_csc_004 - Time To Collision	
acc_csc_004 - Comfort Deceleration Limit	
acc_csc_004 - Emergency Deceleration Bound	
acc_csc_004 - Jerk Limit	
acc_csc_004 - No Collision Distance	
acc_csc_004 - Collision Flag	
acc_csc_004 - Impact Speed	

1.4.5

Test # 1.4.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_004 └ acc_csc_004_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_004
Description:	TestRun converted from acc_csc_004_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_004_140912.erg

Characteristics

Name	Value
acc_csc_004_ActualDist	999.0
acc_csc_004_SafeDist	69.00016724
acc_csc_004_SafeDistViolated	1.0
acc_csc_004_TTC	0.0
acc_csc_004_TTCWarnEver	0.0
acc_csc_004_TTCBadEver	0.0
acc_csc_004_ComfortAx	-5.816889808e-005

Name	Value
acc_csc_004_ComfortAxOutOfBoundEver	1.0
acc_csc_004_EmergencyAx	-5.816889808e-005
acc_csc_004_EmergencyAxOutOfBoundEver	0.0
acc_csc_004_Jerk	0.0004003569529
acc_csc_004_JerkOverLimitEver	1.0
acc_csc_004_NoCollDist	999.0
acc_csc_004_NoCollDistViolatedEver	0.0
acc_csc_004_CollisionFlag	0.0
acc_csc_004_ImpactSpeed	0.0
acc_csc_004_CollisionEver	0.0

Criteria

Name	Result
acc_csc_004 - Safe Distance Consistency	
acc_csc_004 - Time To Collision	
acc_csc_004 - Comfort Deceleration Limit	
acc_csc_004 - Emergency Deceleration Bound	
acc_csc_004 - Jerk Limit	
acc_csc_004 - No Collision Distance	
acc_csc_004 - Collision Flag	
acc_csc_004 - Impact Speed	

1.5

Test # 1.5
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005

Characteristics

Name	Description
acc_csc_005_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_005_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_005_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_005_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_005_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_005_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_005_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_005_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_005_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_005_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_005_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_005_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_005_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_005_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_005_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_005_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_005_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_005_ActualDist	35.6147	23.4163	999.0	999.0	999.0
acc_csc_005_SafeDist	18.7687	21.0937	35.4014	46.5095	57.7119
acc_csc_005_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_005_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_005_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_005_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_005_ComfortAx	0.0	0.0	-0.004	-0.004	-0.004
acc_csc_005_ComfortAxOutOfBoundEver	0.0	0.0	1.0	1.0	1.0
acc_csc_005_EmergencyAx	0.0	0.0	-0.004	-0.004	-0.004
acc_csc_005_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0

Name	# 1	# 2	# 3	# 4	# 5
ndEver					
acc_csc_005_Jerk	0.0	0.0	0.0	0.0	0.0
acc_csc_005_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_005_NoCollDist	35.6147	23.4163	999.0	999.0	999.0
acc_csc_005_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_005_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_005_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_005_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_005 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_005 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_005 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_005 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_005 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_005 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_005 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_005 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_005 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_005 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_005 - Comfort Deceleration Limit	✓	✓	⚡	⚡	⚡
acc_csc_005 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_005 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_005 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_005 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_005 - Impact Speed	✓	✓	✓	✓	✓

1.5.1

Test # 1.5.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005 └ acc_csc_005_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_005
Description:	TestRun converted from acc_csc_005_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	9
NValue	TV1Speed	8
NValue	TV1_initPos	42
NValue	TV2Speed	7
NValue	TV2_initPos	35
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_005_140924.erg

Characteristics

Name	Value
acc_csc_005_ActualDist	35.61465569
acc_csc_005_SafeDist	18.76866812
acc_csc_005_SafeDistViolated	1.0
acc_csc_005_TTC	0.0
acc_csc_005_TTCWarnEver	0.0

Name	Value
acc_csc_005_TTCBadEver	0.0
acc_csc_005_ComfortAx	0.0
acc_csc_005_ComfortAxOutOfBoundEver	0.0
acc_csc_005_EmergencyAx	0.0
acc_csc_005_EmergencyAxOutOfBoundEver	0.0
acc_csc_005_Jerk	0.0
acc_csc_005_JerkOverLimitEver	1.0
acc_csc_005_NoCollDist	35.61465569
acc_csc_005_NoCollDistViolatedEver	0.0
acc_csc_005_CollisionFlag	0.0
acc_csc_005_ImpactSpeed	0.0
acc_csc_005_CollisionEver	0.0

Criteria

Name	Result
acc_csc_005 - Safe Distance Consistency	
acc_csc_005 - Time To Collision	
acc_csc_005 - Comfort Deceleration Limit	
acc_csc_005 - Emergency Deceleration Bound	
acc_csc_005 - Jerk Limit	
acc_csc_005 - No Collision Distance	
acc_csc_005 - Collision Flag	
acc_csc_005 - Impact Speed	

1.5.2

Test # 1.5.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005 └ acc_csc_005_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_005
Description:	TestRun converted from acc_csc_005_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	11
NValue	TV1Speed	10
NValue	TV1_initPos	52
NValue	TV2Speed	9
NValue	TV2_initPos	40
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_005_140936.erg

Characteristics

Name	Value
acc_csc_005_ActualDist	23.41630817
acc_csc_005_SafeDist	21.09370653
acc_csc_005_SafeDistViolated	1.0
acc_csc_005_TTC	0.0
acc_csc_005_TTCWarnEver	0.0

Name	Value
acc_csc_005_TTCBadEver	0.0
acc_csc_005_ComfortAx	0.0
acc_csc_005_ComfortAxOutOfBoundEver	0.0
acc_csc_005_EmergencyAx	0.0
acc_csc_005_EmergencyAxOutOfBoundEver	0.0
acc_csc_005_Jerk	0.0
acc_csc_005_JerkOverLimitEver	1.0
acc_csc_005_NoCollDist	23.41630817
acc_csc_005_NoCollDistViolatedEver	0.0
acc_csc_005_CollisionFlag	0.0
acc_csc_005_ImpactSpeed	0.0
acc_csc_005_CollisionEver	0.0

Criteria

Name	Result
acc_csc_005 - Safe Distance Consistency	
acc_csc_005 - Time To Collision	
acc_csc_005 - Comfort Deceleration Limit	
acc_csc_005 - Emergency Deceleration Bound	
acc_csc_005 - Jerk Limit	
acc_csc_005 - No Collision Distance	
acc_csc_005 - Collision Flag	
acc_csc_005 - Impact Speed	

1.5.3

Test # 1.5.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005 └ acc_csc_005_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_005
Description:	TestRun converted from acc_csc_005_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TV1Speed	13
NValue	TV1_initPos	58
NValue	TV2Speed	11
NValue	TV2_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_005_140949.erg

Characteristics

Name	Value
acc_csc_005_ActualDist	999.0
acc_csc_005_SafeDist	35.40138612
acc_csc_005_SafeDistViolated	1.0
acc_csc_005_TTC	0.0
acc_csc_005_TTCWarnEver	0.0

Name	Value
acc_csc_005_TTCBadEver	0.0
acc_csc_005_ComfortAx	-0.004
acc_csc_005_ComfortAxOutOfBoundEver	1.0
acc_csc_005_EmergencyAx	-0.004
acc_csc_005_EmergencyAxOutOfBoundEver	0.0
acc_csc_005_Jerk	0.0
acc_csc_005_JerkOverLimitEver	1.0
acc_csc_005_NoCollDist	999.0
acc_csc_005_NoCollDistViolatedEver	0.0
acc_csc_005_CollisionFlag	0.0
acc_csc_005_ImpactSpeed	0.0
acc_csc_005_CollisionEver	0.0

Criteria

Name	Result
acc_csc_005 - Safe Distance Consistency	
acc_csc_005 - Time To Collision	
acc_csc_005 - Comfort Deceleration Limit	
acc_csc_005 - Emergency Deceleration Bound	
acc_csc_005 - Jerk Limit	
acc_csc_005 - No Collision Distance	
acc_csc_005 - Collision Flag	
acc_csc_005 - Impact Speed	

1.5.4

Test # 1.5.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005 └ acc_csc_005_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_005
Description:	TestRun converted from acc_csc_005_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TV1Speed	17
NValue	TV1_initPos	82
NValue	TV2Speed	14
NValue	TV2_initPos	70
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_005_141001.erg

Characteristics

Name	Value
acc_csc_005_ActualDist	999.0
acc_csc_005_SafeDist	46.50949067
acc_csc_005_SafeDistViolated	1.0
acc_csc_005_TTC	0.0
acc_csc_005_TTCWarnEver	0.0

Name	Value
acc_csc_005_TTCBadEver	0.0
acc_csc_005_ComfortAx	-0.004
acc_csc_005_ComfortAxOutOfBoundEver	1.0
acc_csc_005_EmergencyAx	-0.004
acc_csc_005_EmergencyAxOutOfBoundEver	0.0
acc_csc_005_Jerk	0.0
acc_csc_005_JerkOverLimitEver	1.0
acc_csc_005_NoCollDist	999.0
acc_csc_005_NoCollDistViolatedEver	0.0
acc_csc_005_CollisionFlag	0.0
acc_csc_005_ImpactSpeed	0.0
acc_csc_005_CollisionEver	0.0

Criteria

Name	Result
acc_csc_005 - Safe Distance Consistency	
acc_csc_005 - Time To Collision	
acc_csc_005 - Comfort Deceleration Limit	
acc_csc_005 - Emergency Deceleration Bound	
acc_csc_005 - Jerk Limit	
acc_csc_005 - No Collision Distance	
acc_csc_005 - Collision Flag	
acc_csc_005 - Impact Speed	

1.5.5

Test # 1.5.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_005 └ acc_csc_005_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_005
Description:	TestRun converted from acc_csc_005_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TV1Speed	21
NValue	TV1_initPos	98
NValue	TV2Speed	17
NValue	TV2_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_005_141014.erg

Characteristics

Name	Value
acc_csc_005_ActualDist	999.0
acc_csc_005_SafeDist	57.71194279
acc_csc_005_SafeDistViolated	1.0
acc_csc_005_TTC	0.0
acc_csc_005_TTCWarnEver	0.0

Name	Value
acc_csc_005_TTCBadEver	0.0
acc_csc_005_ComfortAx	-0.004
acc_csc_005_ComfortAxOutOfBoundEver	1.0
acc_csc_005_EmergencyAx	-0.004
acc_csc_005_EmergencyAxOutOfBoundEver	0.0
acc_csc_005_Jerk	0.0
acc_csc_005_JerkOverLimitEver	1.0
acc_csc_005_NoCollDist	999.0
acc_csc_005_NoCollDistViolatedEver	0.0
acc_csc_005_CollisionFlag	0.0
acc_csc_005_ImpactSpeed	0.0
acc_csc_005_CollisionEver	0.0

Criteria

Name	Result
acc_csc_005 - Safe Distance Consistency	
acc_csc_005 - Time To Collision	
acc_csc_005 - Comfort Deceleration Limit	
acc_csc_005 - Emergency Deceleration Bound	
acc_csc_005 - Jerk Limit	
acc_csc_005 - No Collision Distance	
acc_csc_005 - Collision Flag	
acc_csc_005 - Impact Speed	

1.6

Test # 1.6
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006

Characteristics

Name	Description
acc_csc_006_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_006_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_006_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_006_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_006_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_006_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_006_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_006_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_006_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_006_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_006_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_006_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_006_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_006_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_006_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_006_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_006_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_006_ActualDist	35.3921	23.6845	999.0	42.0613	6.23063
acc_csc_006_SafeDist	18.8041	21.0723	35.4005	55.6147	49.4245
acc_csc_006_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_006_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_006_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_006_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_006_ComfortAx	0.0	0.0	-0.004	-2.05872	-6.0
acc_csc_006_ComfortAxOutOfBoundEver	0.0	0.0	1.0	1.0	1.0
acc_csc_006_EmergencyAx	0.0	0.0	-0.004	-2.05872	-6.0
acc_csc_006_EmergencyAxOutOfBou	0.0	0.0	0.0	0.0	0.0

Name	# 1	# 2	# 3	# 4	# 5
ndEver					
acc_csc_006_Jerk	0.0	0.0	0.0	0.073561	0.0
acc_csc_006_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_006_NoCollDist	35.3921	23.6845	999.0	42.0613	6.23063
acc_csc_006_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_006_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_006_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_006_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_006 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_006 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_006 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_006 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_006 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_006 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_006 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_006 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_006 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_006 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_006 - Comfort Deceleration Limit	✓	✓	⚡	⚡	⚡
acc_csc_006 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_006 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_006 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_006 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_006 - Impact Speed	✓	✓	✓	✓	✓

1.6.1

Test # 1.6.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006 └ acc_csc_006_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_006
Description:	TestRun converted from acc_csc_006_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	9
NValue	TV1Speed	8
NValue	TV1_initPos	42
NValue	TV2Speed	7
NValue	TV2_initPos	35
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_006_141027.erg

Characteristics

Name	Value
acc_csc_006_ActualDist	35.39208818
acc_csc_006_SafeDist	18.80407234
acc_csc_006_SafeDistViolated	1.0
acc_csc_006_TTC	0.0
acc_csc_006_TTCWarnEver	0.0

Name	Value
acc_csc_006_TTCBadEver	0.0
acc_csc_006_ComfortAx	0.0
acc_csc_006_ComfortAxOutOfBoundEver	0.0
acc_csc_006_EmergencyAx	0.0
acc_csc_006_EmergencyAxOutOfBoundEver	0.0
acc_csc_006_Jerk	0.0
acc_csc_006_JerkOverLimitEver	1.0
acc_csc_006_NoCollDist	35.39208818
acc_csc_006_NoCollDistViolatedEver	0.0
acc_csc_006_CollisionFlag	0.0
acc_csc_006_ImpactSpeed	0.0
acc_csc_006_CollisionEver	0.0

Criteria

Name	Result
acc_csc_006 - Safe Distance Consistency	
acc_csc_006 - Time To Collision	
acc_csc_006 - Comfort Deceleration Limit	
acc_csc_006 - Emergency Deceleration Bound	
acc_csc_006 - Jerk Limit	
acc_csc_006 - No Collision Distance	
acc_csc_006 - Collision Flag	
acc_csc_006 - Impact Speed	

1.6.2

Test # 1.6.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006 └ acc_csc_006_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_006
Description:	TestRun converted from acc_csc_006_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	11
NValue	TV1Speed	10
NValue	TV1_initPos	52
NValue	TV2Speed	9
NValue	TV2_initPos	40
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_006_141040.erg

Characteristics

Name	Value
acc_csc_006_ActualDist	23.68450005
acc_csc_006_SafeDist	21.07230731
acc_csc_006_SafeDistViolated	1.0
acc_csc_006_TTC	0.0
acc_csc_006_TTCWarnEver	0.0

Name	Value
acc_csc_006_TTCBadEver	0.0
acc_csc_006_ComfortAx	0.0
acc_csc_006_ComfortAxOutOfBoundEver	0.0
acc_csc_006_EmergencyAx	0.0
acc_csc_006_EmergencyAxOutOfBoundEver	0.0
acc_csc_006_Jerk	0.0
acc_csc_006_JerkOverLimitEver	1.0
acc_csc_006_NoCollDist	23.68450005
acc_csc_006_NoCollDistViolatedEver	0.0
acc_csc_006_CollisionFlag	0.0
acc_csc_006_ImpactSpeed	0.0
acc_csc_006_CollisionEver	0.0

Criteria

Name	Result
acc_csc_006 - Safe Distance Consistency	
acc_csc_006 - Time To Collision	
acc_csc_006 - Comfort Deceleration Limit	
acc_csc_006 - Emergency Deceleration Bound	
acc_csc_006 - Jerk Limit	
acc_csc_006 - No Collision Distance	
acc_csc_006 - Collision Flag	
acc_csc_006 - Impact Speed	

1.6.3

Test # 1.6.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006 └ acc_csc_006_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_006
Description:	TestRun converted from acc_csc_006_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TV1Speed	13
NValue	TV1_initPos	58
NValue	TV2Speed	11
NValue	TV2_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_006_141052.erg

Characteristics

Name	Value
acc_csc_006_ActualDist	999.0
acc_csc_006_SafeDist	35.40048363
acc_csc_006_SafeDistViolated	1.0
acc_csc_006_TTC	0.0
acc_csc_006_TTCWarnEver	0.0

Name	Value
acc_csc_006_TTCBadEver	0.0
acc_csc_006_ComfortAx	-0.004
acc_csc_006_ComfortAxOutOfBoundEver	1.0
acc_csc_006_EmergencyAx	-0.004
acc_csc_006_EmergencyAxOutOfBoundEver	0.0
acc_csc_006_Jerk	0.0
acc_csc_006_JerkOverLimitEver	1.0
acc_csc_006_NoCollDist	999.0
acc_csc_006_NoCollDistViolatedEver	0.0
acc_csc_006_CollisionFlag	0.0
acc_csc_006_ImpactSpeed	0.0
acc_csc_006_CollisionEver	0.0

Criteria

Name	Result
acc_csc_006 - Safe Distance Consistency	
acc_csc_006 - Time To Collision	
acc_csc_006 - Comfort Deceleration Limit	
acc_csc_006 - Emergency Deceleration Bound	
acc_csc_006 - Jerk Limit	
acc_csc_006 - No Collision Distance	
acc_csc_006 - Collision Flag	
acc_csc_006 - Impact Speed	

1.6.4

Test # 1.6.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006 └ acc_csc_006_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_006
Description:	TestRun converted from acc_csc_006_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TV1Speed	17
NValue	TV1_initPos	82
NValue	TV2Speed	14
NValue	TV2_initPos	70
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_006_141105.erg

Characteristics

Name	Value
acc_csc_006_ActualDist	42.06129857
acc_csc_006_SafeDist	55.61465368
acc_csc_006_SafeDistViolated	1.0
acc_csc_006_TTC	0.0
acc_csc_006_TTCWarnEver	0.0

Name	Value
acc_csc_006_TTCBadEver	0.0
acc_csc_006_ComfortAx	-2.058718849
acc_csc_006_ComfortAxOutOfBoundEver	1.0
acc_csc_006_EmergencyAx	-2.058718849
acc_csc_006_EmergencyAxOutOfBoundEver	0.0
acc_csc_006_Jerk	0.07356097961
acc_csc_006_JerkOverLimitEver	1.0
acc_csc_006_NoCollDist	42.06129857
acc_csc_006_NoCollDistViolatedEver	0.0
acc_csc_006_CollisionFlag	0.0
acc_csc_006_ImpactSpeed	0.0
acc_csc_006_CollisionEver	0.0

Criteria

Name	Result
acc_csc_006 - Safe Distance Consistency	
acc_csc_006 - Time To Collision	
acc_csc_006 - Comfort Deceleration Limit	
acc_csc_006 - Emergency Deceleration Bound	
acc_csc_006 - Jerk Limit	
acc_csc_006 - No Collision Distance	
acc_csc_006 - Collision Flag	
acc_csc_006 - Impact Speed	

1.6.5

Test # 1.6.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_006 └ acc_csc_006_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_006
Description:	TestRun converted from acc_csc_006_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TV1Speed	21
NValue	TV1_initPos	98
NValue	TV2Speed	17
NValue	TV2_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_006_141117.erg

Characteristics

Name	Value
acc_csc_006_ActualDist	6.230629063
acc_csc_006_SafeDist	49.42450476
acc_csc_006_SafeDistViolated	1.0
acc_csc_006_TTC	0.0
acc_csc_006_TTCWarnEver	0.0

Name	Value
acc_csc_006_TTCBadEver	0.0
acc_csc_006_ComfortAx	-6.0
acc_csc_006_ComfortAxOutOfBoundEver	1.0
acc_csc_006_EmergencyAx	-6.0
acc_csc_006_EmergencyAxOutOfBoundEver	0.0
acc_csc_006_Jerk	0.0
acc_csc_006_JerkOverLimitEver	1.0
acc_csc_006_NoCollDist	6.230629063
acc_csc_006_NoCollDistViolatedEver	0.0
acc_csc_006_CollisionFlag	0.0
acc_csc_006_ImpactSpeed	0.0
acc_csc_006_CollisionEver	0.0

Criteria

Name	Result
acc_csc_006 - Safe Distance Consistency	
acc_csc_006 - Time To Collision	
acc_csc_006 - Comfort Deceleration Limit	
acc_csc_006 - Emergency Deceleration Bound	
acc_csc_006 - Jerk Limit	
acc_csc_006 - No Collision Distance	
acc_csc_006 - Collision Flag	
acc_csc_006 - Impact Speed	

1.7

Test # 1.7

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_007

Characteristics

Name	Description
acc_csc_007_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_007_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_007_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_007_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_007_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_007_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_007_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_007_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_007_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_007_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_007_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_007_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_007_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_007_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_007_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_007_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_007_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_007_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_007_SafeDist	46.0833	57.4351	68.9998	50.7557	64.4
acc_csc_007_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_007_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_007_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_007_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_007_ComfortAx	-0.004	0.0225641	6.33938e-005	-0.004	3.67558e-006
acc_csc_007_ComfortAxOutOfBoundEver	1.0	1.0	1.0	1.0	1.0
acc_csc_007_EmergencyAx	-0.004	0.0225641	6.33938e-	-0.004	3.67558e-

Name	# 1	# 2	# 3	# 4	# 5
			005		006
acc_csc_007_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_007_Jerk	0.0	3.59973e-005	0.000459507	0.0	0.00232065
acc_csc_007_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_007_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_007_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_007_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_007_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_007_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_007 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_007 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_007 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_007 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_007 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_007 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_007 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_007 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_007 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_007 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_007 - Comfort Deceleration Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_007 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_007 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_007 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_007 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_007 - Impact Speed	✓	✓	✓	✓	✓

1.7.1

Test # 1.7.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_007 └ acc_csc_007_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_007
Description:	TestRun converted from acc_csc_007_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	12
NValue	TV_initPos	85
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_007_141131.erg

Characteristics

Name	Value
acc_csc_007_ActualDist	999.0
acc_csc_007_SafeDist	46.08327718
acc_csc_007_SafeDistViolated	1.0
acc_csc_007_TTC	0.0
acc_csc_007_TTCWarnEver	0.0
acc_csc_007_TTCBadEver	0.0
acc_csc_007_ComfortAx	-0.004

Name	Value
acc_csc_007_ComfortAxOutOfBoundEver	1.0
acc_csc_007_EmergencyAx	-0.004
acc_csc_007_EmergencyAxOutOfBoundEver	0.0
acc_csc_007_Jerk	0.0
acc_csc_007_JerkOverLimitEver	1.0
acc_csc_007_NoCollDist	999.0
acc_csc_007_NoCollDistViolatedEver	0.0
acc_csc_007_CollisionFlag	0.0
acc_csc_007_ImpactSpeed	0.0
acc_csc_007_CollisionEver	0.0

Criteria

Name	Result
acc_csc_007 - Safe Distance Consistency	
acc_csc_007 - Time To Collision	
acc_csc_007 - Comfort Deceleration Limit	
acc_csc_007 - Emergency Deceleration Bound	
acc_csc_007 - Jerk Limit	
acc_csc_007 - No Collision Distance	
acc_csc_007 - Collision Flag	
acc_csc_007 - Impact Speed	

1.7.2

Test # 1.7.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_007 └ acc_csc_007_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_007
Description:	TestRun converted from acc_csc_007_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	15
NValue	TV_initPos	105
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_007_141143.erg

Characteristics

Name	Value
acc_csc_007_ActualDist	999.0
acc_csc_007_SafeDist	57.43512813
acc_csc_007_SafeDistViolated	1.0
acc_csc_007_TTC	0.0
acc_csc_007_TTCWarnEver	0.0
acc_csc_007_TTCBadEver	0.0
acc_csc_007_ComfortAx	0.02256412794

Name	Value
acc_csc_007_ComfortAxOutOfBoundEver	1.0
acc_csc_007_EmergencyAx	0.02256412794
acc_csc_007_EmergencyAxOutOfBoundEver	0.0
acc_csc_007_Jerk	3.599733418e-005
acc_csc_007_JerkOverLimitEver	1.0
acc_csc_007_NoCollDist	999.0
acc_csc_007_NoCollDistViolatedEver	0.0
acc_csc_007_CollisionFlag	0.0
acc_csc_007_ImpactSpeed	0.0
acc_csc_007_CollisionEver	0.0

Criteria

Name	Result
acc_csc_007 - Safe Distance Consistency	
acc_csc_007 - Time To Collision	
acc_csc_007 - Comfort Deceleration Limit	
acc_csc_007 - Emergency Deceleration Bound	
acc_csc_007 - Jerk Limit	
acc_csc_007 - No Collision Distance	
acc_csc_007 - Collision Flag	
acc_csc_007 - Impact Speed	

1.7.3

Test # 1.7.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_007 └ acc_csc_007_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_007
Description:	TestRun converted from acc_csc_007_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	20
NValue	TV_initPos	115
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_007_141155.erg

Characteristics

Name	Value
acc_csc_007_ActualDist	999.0
acc_csc_007_SafeDist	68.99981774
acc_csc_007_SafeDistViolated	1.0
acc_csc_007_TTC	0.0
acc_csc_007_TTCWarnEver	0.0
acc_csc_007_TTCBadEver	0.0
acc_csc_007_ComfortAx	6.3393804e-005

Name	Value
acc_csc_007_ComfortAxOutOfBoundEver	1.0
acc_csc_007_EmergencyAx	6.3393804e-005
acc_csc_007_EmergencyAxOutOfBoundEver	0.0
acc_csc_007_Jerk	0.0004595068617
acc_csc_007_JerkOverLimitEver	1.0
acc_csc_007_NoCollDist	999.0
acc_csc_007_NoCollDistViolatedEver	0.0
acc_csc_007_CollisionFlag	0.0
acc_csc_007_ImpactSpeed	0.0
acc_csc_007_CollisionEver	0.0

Criteria

Name	Result
acc_csc_007 - Safe Distance Consistency	
acc_csc_007 - Time To Collision	
acc_csc_007 - Comfort Deceleration Limit	
acc_csc_007 - Emergency Deceleration Bound	
acc_csc_007 - Jerk Limit	
acc_csc_007 - No Collision Distance	
acc_csc_007 - Collision Flag	
acc_csc_007 - Impact Speed	

1.7.4

Test # 1.7.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_007 └ acc_csc_007_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_007
Description:	TestRun converted from acc_csc_007_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	22
NValue	TVSpeed	14
NValue	TV_initPos	103
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_007_141206.erg

Characteristics

Name	Value
acc_csc_007_ActualDist	999.0
acc_csc_007_SafeDist	50.75574344
acc_csc_007_SafeDistViolated	1.0
acc_csc_007_TTC	0.0
acc_csc_007_TTCWarnEver	0.0
acc_csc_007_TTCBadEver	0.0
acc_csc_007_ComfortAx	-0.004

Name	Value
acc_csc_007_ComfortAxOutOfBoundEver	1.0
acc_csc_007_EmergencyAx	-0.004
acc_csc_007_EmergencyAxOutOfBoundEver	0.0
acc_csc_007_Jerk	0.0
acc_csc_007_JerkOverLimitEver	1.0
acc_csc_007_NoCollDist	999.0
acc_csc_007_NoCollDistViolatedEver	0.0
acc_csc_007_CollisionFlag	0.0
acc_csc_007_ImpactSpeed	0.0
acc_csc_007_CollisionEver	0.0

Criteria

Name	Result
acc_csc_007 - Safe Distance Consistency	
acc_csc_007 - Time To Collision	
acc_csc_007 - Comfort Deceleration Limit	
acc_csc_007 - Emergency Deceleration Bound	
acc_csc_007 - Jerk Limit	
acc_csc_007 - No Collision Distance	
acc_csc_007 - Collision Flag	
acc_csc_007 - Impact Speed	

1.7.5

Test # 1.7.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_007 └ acc_csc_007_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_007
Description:	TestRun converted from acc_csc_007_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	28
NValue	TVSpeed	18
NValue	TV_initPos	120
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_007_141219.erg

Characteristics

Name	Value
acc_csc_007_ActualDist	999.0
acc_csc_007_SafeDist	64.39998943
acc_csc_007_SafeDistViolated	1.0
acc_csc_007_TTC	0.0
acc_csc_007_TTCWarnEver	0.0
acc_csc_007_TTCBadEver	0.0
acc_csc_007_ComfortAx	3.67558294e-006

Name	Value
acc_csc_007_ComfortAxOutOfBoundEver	1.0
acc_csc_007_EmergencyAx	3.67558294e-006
acc_csc_007_EmergencyAxOutOfBoundEver	0.0
acc_csc_007_Jerk	0.002320653778
acc_csc_007_JerkOverLimitEver	1.0
acc_csc_007_NoCollDist	999.0
acc_csc_007_NoCollDistViolatedEver	0.0
acc_csc_007_CollisionFlag	0.0
acc_csc_007_ImpactSpeed	0.0
acc_csc_007_CollisionEver	0.0

Criteria

Name	Result
acc_csc_007 - Safe Distance Consistency	
acc_csc_007 - Time To Collision	
acc_csc_007 - Comfort Deceleration Limit	
acc_csc_007 - Emergency Deceleration Bound	
acc_csc_007 - Jerk Limit	
acc_csc_007 - No Collision Distance	
acc_csc_007 - Collision Flag	
acc_csc_007 - Impact Speed	

1.8

Test # 1.8

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_008

Characteristics

Name	Description
acc_csc_008_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_008_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_008_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_008_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_008_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_008_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_008_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_008_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_008_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_008_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_008_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_008_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_008_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_008_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_008_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_008_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_008_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_008_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_008_SafeDist	27.6029	34.5021	46	57.4351	69.0003
acc_csc_008_SafeDistViolated	0.0	1.0	1.0	1.0	1.0
acc_csc_008_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_008_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_008_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_008_ComfortAx	-0.00101509	-0.00072018	2.64406e-007	0.0225742	-0.000110614
acc_csc_008_ComfortAxOutOfBoundEver	0.0	0.0	0.0	0.0	1.0
acc_csc_008_EmergencyAx	-0.00101509	-0.00072018	2.64406e-	0.0225742	-0.00011061

Name	# 1	# 2	# 3	# 4	# 5
		1	007		4
acc_csc_008_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_008_Jerk	0.000230458	6.63262e-007	8.62221e-006	9.4561e-005	0.00039499
acc_csc_008_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_008_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_008_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_008_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_008_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_008_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_008 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_008 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_008 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_008 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_008 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_008 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_008 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_008 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_008 - Safe Distance Consistency	✓	⚡	⚡	⚡	⚡
acc_csc_008 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_008 - Comfort Deceleration Limit	✓	✓	✓	✓	⚡
acc_csc_008 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_008 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_008 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_008 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_008 - Impact Speed	✓	✓	✓	✓	✓

1.8.1

Test # 1.8.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_008 └ acc_csc_008_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_008
Description:	TestRun converted from acc_csc_008_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_008_141231.erg

Characteristics

Name	Value
acc_csc_008_ActualDist	999.0
acc_csc_008_SafeDist	27.60291839
acc_csc_008_SafeDistViolated	0.0
acc_csc_008_TTC	0.0
acc_csc_008_TTCWarnEver	0.0
acc_csc_008_TTCBadEver	0.0
acc_csc_008_ComfortAx	-0.001015092219

Name	Value
acc_csc_008_ComfortAxOutOfBoundEver	0.0
acc_csc_008_EmergencyAx	-0.001015092219
acc_csc_008_EmergencyAxOutOfBoundEver	0.0
acc_csc_008_Jerk	0.0002304581471
acc_csc_008_JerkOverLimitEver	1.0
acc_csc_008_NoCollDist	999.0
acc_csc_008_NoCollDistViolatedEver	0.0
acc_csc_008_CollisionFlag	0.0
acc_csc_008_ImpactSpeed	0.0
acc_csc_008_CollisionEver	0.0

Criteria

Name	Result
acc_csc_008 - Safe Distance Consistency	✓
acc_csc_008 - Time To Collision	✓
acc_csc_008 - Comfort Deceleration Limit	✓
acc_csc_008 - Emergency Deceleration Bound	✓
acc_csc_008 - Jerk Limit	⚡
acc_csc_008 - No Collision Distance	✓
acc_csc_008 - Collision Flag	✓
acc_csc_008 - Impact Speed	✓

1.8.2

Test # 1.8.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_008 └ acc_csc_008_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_008
Description:	TestRun converted from acc_csc_008_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_008_141243.erg

Characteristics

Name	Value
acc_csc_008_ActualDist	999.0
acc_csc_008_SafeDist	34.50207052
acc_csc_008_SafeDistViolated	1.0
acc_csc_008_TTC	0.0
acc_csc_008_TTCWarnEver	0.0
acc_csc_008_TTCBadEver	0.0
acc_csc_008_ComfortAx	-0.000720181382

Name	Value
acc_csc_008_ComfortAxOutOfBoundEver	0.0
acc_csc_008_EmergencyAx	-0.000720181382
acc_csc_008_EmergencyAxOutOfBoundEver	0.0
acc_csc_008_Jerk	6.632618011e-007
acc_csc_008_JerkOverLimitEver	1.0
acc_csc_008_NoCollDist	999.0
acc_csc_008_NoCollDistViolatedEver	0.0
acc_csc_008_CollisionFlag	0.0
acc_csc_008_ImpactSpeed	0.0
acc_csc_008_CollisionEver	0.0

Criteria

Name	Result
acc_csc_008 - Safe Distance Consistency	
acc_csc_008 - Time To Collision	
acc_csc_008 - Comfort Deceleration Limit	
acc_csc_008 - Emergency Deceleration Bound	
acc_csc_008 - Jerk Limit	
acc_csc_008 - No Collision Distance	
acc_csc_008 - Collision Flag	
acc_csc_008 - Impact Speed	

1.8.3

Test # 1.8.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_008 └ acc_csc_008_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_008
Description:	TestRun converted from acc_csc_008_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_008_141255.erg

Characteristics

Name	Value
acc_csc_008_ActualDist	999.0
acc_csc_008_SafeDist	45.99999924
acc_csc_008_SafeDistViolated	1.0
acc_csc_008_TTC	0.0
acc_csc_008_TTCWarnEver	0.0
acc_csc_008_TTCBadEver	0.0
acc_csc_008_ComfortAx	2.644055087e-007

Name	Value
acc_csc_008_ComfortAxOutOfBoundEver	0.0
acc_csc_008_EmergencyAx	2.644055087e-007
acc_csc_008_EmergencyAxOutOfBoundEver	0.0
acc_csc_008_Jerk	8.622214409e-006
acc_csc_008_JerkOverLimitEver	1.0
acc_csc_008_NoCollDist	999.0
acc_csc_008_NoCollDistViolatedEver	0.0
acc_csc_008_CollisionFlag	0.0
acc_csc_008_ImpactSpeed	0.0
acc_csc_008_CollisionEver	0.0

Criteria

Name	Result
acc_csc_008 - Safe Distance Consistency	
acc_csc_008 - Time To Collision	
acc_csc_008 - Comfort Deceleration Limit	
acc_csc_008 - Emergency Deceleration Bound	
acc_csc_008 - Jerk Limit	
acc_csc_008 - No Collision Distance	
acc_csc_008 - Collision Flag	
acc_csc_008 - Impact Speed	

1.8.4

Test # 1.8.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_008 └ acc_csc_008_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_008
Description:	TestRun converted from acc_csc_008_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	92
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_008_141307.erg

Characteristics

Name	Value
acc_csc_008_ActualDist	999.0
acc_csc_008_SafeDist	57.43509907
acc_csc_008_SafeDistViolated	1.0
acc_csc_008_TTC	0.0
acc_csc_008_TTCWarnEver	0.0
acc_csc_008_TTCBadEver	0.0
acc_csc_008_ComfortAx	0.02257423489

Name	Value
acc_csc_008_ComfortAxOutOfBoundEver	0.0
acc_csc_008_EmergencyAx	0.02257423489
acc_csc_008_EmergencyAxOutOfBoundEver	0.0
acc_csc_008_Jerk	9.456103669e-005
acc_csc_008_JerkOverLimitEver	1.0
acc_csc_008_NoCollDist	999.0
acc_csc_008_NoCollDistViolatedEver	0.0
acc_csc_008_CollisionFlag	0.0
acc_csc_008_ImpactSpeed	0.0
acc_csc_008_CollisionEver	0.0

Criteria

Name	Result
acc_csc_008 - Safe Distance Consistency	
acc_csc_008 - Time To Collision	
acc_csc_008 - Comfort Deceleration Limit	
acc_csc_008 - Emergency Deceleration Bound	
acc_csc_008 - Jerk Limit	
acc_csc_008 - No Collision Distance	
acc_csc_008 - Collision Flag	
acc_csc_008 - Impact Speed	

1.8.5

Test # 1.8.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_008 └ acc_csc_008_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_008
Description:	TestRun converted from acc_csc_008_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	98
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_008_141319.erg

Characteristics

Name	Value
acc_csc_008_ActualDist	999.0
acc_csc_008_SafeDist	69.00031801
acc_csc_008_SafeDistViolated	1.0
acc_csc_008_TTC	0.0
acc_csc_008_TTCWarnEver	0.0
acc_csc_008_TTCBadEver	0.0
acc_csc_008_ComfortAx	-0.0001106136442

Name	Value
acc_csc_008_ComfortAxOutOfBoundEver	1.0
acc_csc_008_EmergencyAx	-0.0001106136442
acc_csc_008_EmergencyAxOutOfBoundEver	0.0
acc_csc_008_Jerk	0.0003949897973
acc_csc_008_JerkOverLimitEver	1.0
acc_csc_008_NoCollDist	999.0
acc_csc_008_NoCollDistViolatedEver	0.0
acc_csc_008_CollisionFlag	0.0
acc_csc_008_ImpactSpeed	0.0
acc_csc_008_CollisionEver	0.0

Criteria

Name	Result
acc_csc_008 - Safe Distance Consistency	
acc_csc_008 - Time To Collision	
acc_csc_008 - Comfort Deceleration Limit	
acc_csc_008 - Emergency Deceleration Bound	
acc_csc_008 - Jerk Limit	
acc_csc_008 - No Collision Distance	
acc_csc_008 - Collision Flag	
acc_csc_008 - Impact Speed	

1.9

Test # 1.9

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_009

Characteristics

Name	Description
acc_csc_009_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_009_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_009_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_009_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_009_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_009_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_009_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_009_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_009_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_009_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_009_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_009_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_009_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_009_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_009_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_009_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_009_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_009_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_009_SafeDist	27.6029	34.5021	46	57.4351	69.0003
acc_csc_009_SafeDistViolated	0.0	1.0	1.0	1.0	1.0
acc_csc_009_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_009_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_009_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_009_ComfortAx	-0.00101509	-0.00072017 7	1.13356e- 007	0.0225754	-0.00011309 4
acc_csc_009_ComfortAxOutOfBoundEver	0.0	0.0	0.0	0.0	1.0
acc_csc_009_EmergencyAx	-0.00101509	-0.00072017	1.13356e-	0.0225754	-0.00011309

Name	# 1	# 2	# 3	# 4	# 5
		7	007		4
acc_csc_009_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_009_Jerk	0.000230458	6.65516e-007	8.18188e-006	9.89362e-005	0.000395034
acc_csc_009_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_009_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_009_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_009_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_009_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_009_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_009 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_009 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_009 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_009 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_009 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_009 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_009 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_009 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_009 - Safe Distance Consistency	✓	⚡	⚡	⚡	⚡
acc_csc_009 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_009 - Comfort Deceleration Limit	✓	✓	✓	✓	⚡
acc_csc_009 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_009 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_009 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_009 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_009 - Impact Speed	✓	✓	✓	✓	✓

1.9.1

Test # 1.9.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_009 └ acc_csc_009_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_009
Description:	TestRun converted from acc_csc_009_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	55
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_009_141332.erg

Characteristics

Name	Value
acc_csc_009_ActualDist	999.0
acc_csc_009_SafeDist	27.60291839
acc_csc_009_SafeDistViolated	0.0
acc_csc_009_TTC	0.0
acc_csc_009_TTCWarnEver	0.0
acc_csc_009_TTCBadEver	0.0
acc_csc_009_ComfortAx	-0.001015092788

Name	Value
acc_csc_009_ComfortAxOutOfBoundEver	0.0
acc_csc_009_EmergencyAx	-0.001015092788
acc_csc_009_EmergencyAxOutOfBoundEver	0.0
acc_csc_009_Jerk	0.0002304580789
acc_csc_009_JerkOverLimitEver	1.0
acc_csc_009_NoCollDist	999.0
acc_csc_009_NoCollDistViolatedEver	0.0
acc_csc_009_CollisionFlag	0.0
acc_csc_009_ImpactSpeed	0.0
acc_csc_009_CollisionEver	0.0

Criteria

Name	Result
acc_csc_009 - Safe Distance Consistency	✓
acc_csc_009 - Time To Collision	✓
acc_csc_009 - Comfort Deceleration Limit	✓
acc_csc_009 - Emergency Deceleration Bound	✓
acc_csc_009 - Jerk Limit	⚡
acc_csc_009 - No Collision Distance	✓
acc_csc_009 - Collision Flag	✓
acc_csc_009 - Impact Speed	✓

1.9.2

Test # 1.9.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_009 └ acc_csc_009_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_009
Description:	TestRun converted from acc_csc_009_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_009_141344.erg

Characteristics

Name	Value
acc_csc_009_ActualDist	999.0
acc_csc_009_SafeDist	34.50207051
acc_csc_009_SafeDistViolated	1.0
acc_csc_009_TTC	0.0
acc_csc_009_TTCWarnEver	0.0
acc_csc_009_TTCBadEver	0.0
acc_csc_009_ComfortAx	-0.0007201766932

Name	Value
acc_csc_009_ComfortAxOutOfBoundEver	0.0
acc_csc_009_EmergencyAx	-0.0007201766932
acc_csc_009_EmergencyAxOutOfBoundEver	0.0
acc_csc_009_Jerk	6.655156426e-007
acc_csc_009_JerkOverLimitEver	1.0
acc_csc_009_NoCollDist	999.0
acc_csc_009_NoCollDistViolatedEver	0.0
acc_csc_009_CollisionFlag	0.0
acc_csc_009_ImpactSpeed	0.0
acc_csc_009_CollisionEver	0.0

Criteria

Name	Result
acc_csc_009 - Safe Distance Consistency	
acc_csc_009 - Time To Collision	
acc_csc_009 - Comfort Deceleration Limit	
acc_csc_009 - Emergency Deceleration Bound	
acc_csc_009 - Jerk Limit	
acc_csc_009 - No Collision Distance	
acc_csc_009 - Collision Flag	
acc_csc_009 - Impact Speed	

1.9.3

Test # 1.9.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_009 └ acc_csc_009_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_009
Description:	TestRun converted from acc_csc_009_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_009_141356.erg

Characteristics

Name	Value
acc_csc_009_ActualDist	999.0
acc_csc_009_SafeDist	45.99999967
acc_csc_009_SafeDistViolated	1.0
acc_csc_009_TTC	0.0
acc_csc_009_TTCWarnEver	0.0
acc_csc_009_TTCBadEver	0.0
acc_csc_009_ComfortAx	1.13356333e-007

Name	Value
acc_csc_009_ComfortAxOutOfBoundEver	0.0
acc_csc_009_EmergencyAx	1.13356333e-007
acc_csc_009_EmergencyAxOutOfBoundEver	0.0
acc_csc_009_Jerk	8.181879707e-006
acc_csc_009_JerkOverLimitEver	1.0
acc_csc_009_NoCollDist	999.0
acc_csc_009_NoCollDistViolatedEver	0.0
acc_csc_009_CollisionFlag	0.0
acc_csc_009_ImpactSpeed	0.0
acc_csc_009_CollisionEver	0.0

Criteria

Name	Result
acc_csc_009 - Safe Distance Consistency	
acc_csc_009 - Time To Collision	
acc_csc_009 - Comfort Deceleration Limit	
acc_csc_009 - Emergency Deceleration Bound	
acc_csc_009 - Jerk Limit	
acc_csc_009 - No Collision Distance	
acc_csc_009 - Collision Flag	
acc_csc_009 - Impact Speed	

1.9.4

Test # 1.9.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_009 └ acc_csc_009_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_009
Description:	TestRun converted from acc_csc_009_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	92
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_009_141408.erg

Characteristics

Name	Value
acc_csc_009_ActualDist	999.0
acc_csc_009_SafeDist	57.43509567
acc_csc_009_SafeDistViolated	1.0
acc_csc_009_TTC	0.0
acc_csc_009_TTCWarnEver	0.0
acc_csc_009_TTCBadEver	0.0
acc_csc_009_ComfortAx	0.02257541848

Name	Value
acc_csc_009_ComfortAxOutOfBoundEver	0.0
acc_csc_009_EmergencyAx	0.02257541848
acc_csc_009_EmergencyAxOutOfBoundEver	0.0
acc_csc_009_Jerk	9.893618085e-005
acc_csc_009_JerkOverLimitEver	1.0
acc_csc_009_NoCollDist	999.0
acc_csc_009_NoCollDistViolatedEver	0.0
acc_csc_009_CollisionFlag	0.0
acc_csc_009_ImpactSpeed	0.0
acc_csc_009_CollisionEver	0.0

Criteria

Name	Result
acc_csc_009 - Safe Distance Consistency	
acc_csc_009 - Time To Collision	
acc_csc_009 - Comfort Deceleration Limit	
acc_csc_009 - Emergency Deceleration Bound	
acc_csc_009 - Jerk Limit	
acc_csc_009 - No Collision Distance	
acc_csc_009 - Collision Flag	
acc_csc_009 - Impact Speed	

1.9.5

Test # 1.9.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_009 └ acc_csc_009_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_009
Description:	TestRun converted from acc_csc_009_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	98
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_009_141420.erg

Characteristics

Name	Value
acc_csc_009_ActualDist	999.0
acc_csc_009_SafeDist	69.00032514
acc_csc_009_SafeDistViolated	1.0
acc_csc_009_TTC	0.0
acc_csc_009_TTCWarnEver	0.0
acc_csc_009_TTCBadEver	0.0
acc_csc_009_ComfortAx	-0.0001130935593

Name	Value
acc_csc_009_ComfortAxOutOfBoundEver	1.0
acc_csc_009_EmergencyAx	-0.0001130935593
acc_csc_009_EmergencyAxOutOfBoundEver	0.0
acc_csc_009_Jerk	0.0003950342887
acc_csc_009_JerkOverLimitEver	1.0
acc_csc_009_NoCollDist	999.0
acc_csc_009_NoCollDistViolatedEver	0.0
acc_csc_009_CollisionFlag	0.0
acc_csc_009_ImpactSpeed	0.0
acc_csc_009_CollisionEver	0.0

Criteria

Name	Result
acc_csc_009 - Safe Distance Consistency	
acc_csc_009 - Time To Collision	
acc_csc_009 - Comfort Deceleration Limit	
acc_csc_009 - Emergency Deceleration Bound	
acc_csc_009 - Jerk Limit	
acc_csc_009 - No Collision Distance	
acc_csc_009 - Collision Flag	
acc_csc_009 - Impact Speed	

1.10

Test # 1.10
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010

Characteristics

Name	Description
acc_csc_010_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_010_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_010_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_010_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_010_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_010_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_010_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_010_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_010_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_010_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_010_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_010_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_010_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_010_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_010_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_010_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_010_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_010_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_010_SafeDist	35.8553	32.4775	55.1967	64.2801	68.8492
acc_csc_010_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_010_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_010_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_010_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_010_ComfortAx	1.9286	2.8	0.00115338	0.0417077	0.0524395
acc_csc_010_ComfortAxOutOfBoundEver	0.0	0.0	0.0	1.0	1.0
acc_csc_010_EmergencyAx	1.9286	2.8	0.00115338	0.0417077	0.0524395
acc_csc_010_EmergencyAxOutOfBou	0.0	0.0	0.0	0.0	0.0

Name	# 1	# 2	# 3	# 4	# 5
ndEver					
acc_csc_010_Jerk	0.339934	0.0	0.00173932	0.00305751	0.0189642
acc_csc_010_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_010_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_010_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_010_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_010_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_010_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_010 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_010 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_010 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_010 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_010 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_010 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_010 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_010 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_010 - Safe Distance Consistency					
acc_csc_010 - Time To Collision					
acc_csc_010 - Comfort Deceleration Limit					
acc_csc_010 - Emergency Deceleration Bound					
acc_csc_010 - Jerk Limit					
acc_csc_010 - No Collision Distance					
acc_csc_010 - Collision Flag					
acc_csc_010 - Impact Speed					

1.10.1

Test # 1.10.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010 └ acc_csc_010_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_010
Description:	TestRun converted from acc_csc_010_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	18
NValue	TV1Speed	13
NValue	TV1_initPos	50
NValue	TV2Speed	13
NValue	TV2_initPos	70
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_010_141432.erg

Characteristics

Name	Value
acc_csc_010_ActualDist	999.0
acc_csc_010_SafeDist	35.8552772
acc_csc_010_SafeDistViolated	1.0
acc_csc_010_TTC	0.0
acc_csc_010_TTCWarnEver	0.0

Name	Value
acc_csc_010_TTCBadEver	0.0
acc_csc_010_ComfortAx	1.928599235
acc_csc_010_ComfortAxOutOfBoundEver	0.0
acc_csc_010_EmergencyAx	1.928599235
acc_csc_010_EmergencyAxOutOfBoundEver	0.0
acc_csc_010_Jerk	0.3399337665
acc_csc_010_JerkOverLimitEver	1.0
acc_csc_010_NoCollDist	999.0
acc_csc_010_NoCollDistViolatedEver	0.0
acc_csc_010_CollisionFlag	0.0
acc_csc_010_ImpactSpeed	0.0
acc_csc_010_CollisionEver	0.0

Criteria

Name	Result
acc_csc_010 - Safe Distance Consistency	
acc_csc_010 - Time To Collision	
acc_csc_010 - Comfort Deceleration Limit	
acc_csc_010 - Emergency Deceleration Bound	
acc_csc_010 - Jerk Limit	
acc_csc_010 - No Collision Distance	
acc_csc_010 - Collision Flag	
acc_csc_010 - Impact Speed	

1.10.2

Test # 1.10.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010 └ acc_csc_010_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_010
Description:	TestRun converted from acc_csc_010_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TV1Speed	15
NValue	TV1_initPos	55
NValue	TV2Speed	15
NValue	TV2_initPos	75
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_010_141445.erg

Characteristics

Name	Value
acc_csc_010_ActualDist	999.0
acc_csc_010_SafeDist	32.47753459
acc_csc_010_SafeDistViolated	1.0
acc_csc_010_TTC	0.0
acc_csc_010_TTCWarnEver	0.0

Name	Value
acc_csc_010_TTCBadEver	0.0
acc_csc_010_ComfortAx	2.8
acc_csc_010_ComfortAxOutOfBoundEver	0.0
acc_csc_010_EmergencyAx	2.8
acc_csc_010_EmergencyAxOutOfBoundEver	0.0
acc_csc_010_Jerk	0.0
acc_csc_010_JerkOverLimitEver	1.0
acc_csc_010_NoCollDist	999.0
acc_csc_010_NoCollDistViolatedEver	0.0
acc_csc_010_CollisionFlag	0.0
acc_csc_010_ImpactSpeed	0.0
acc_csc_010_CollisionEver	0.0

Criteria

Name	Result
acc_csc_010 - Safe Distance Consistency	
acc_csc_010 - Time To Collision	
acc_csc_010 - Comfort Deceleration Limit	
acc_csc_010 - Emergency Deceleration Bound	
acc_csc_010 - Jerk Limit	
acc_csc_010 - No Collision Distance	
acc_csc_010 - Collision Flag	
acc_csc_010 - Impact Speed	

1.10.3

Test # 1.10.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010 └ acc_csc_010_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_010
Description:	TestRun converted from acc_csc_010_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	24
NValue	TV1Speed	18
NValue	TV1_initPos	62
NValue	TV2Speed	17
NValue	TV2_initPos	90
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_010_141457.erg

Characteristics

Name	Value
acc_csc_010_ActualDist	999.0
acc_csc_010_SafeDist	55.19668402
acc_csc_010_SafeDistViolated	1.0
acc_csc_010_TTC	0.0
acc_csc_010_TTCWarnEver	0.0

Name	Value
acc_csc_010_TTCBadEver	0.0
acc_csc_010_ComfortAx	0.001153383963
acc_csc_010_ComfortAxOutOfBoundEver	0.0
acc_csc_010_EmergencyAx	0.001153383963
acc_csc_010_EmergencyAxOutOfBoundEver	0.0
acc_csc_010_Jerk	0.001739319941
acc_csc_010_JerkOverLimitEver	1.0
acc_csc_010_NoCollDist	999.0
acc_csc_010_NoCollDistViolatedEver	0.0
acc_csc_010_CollisionFlag	0.0
acc_csc_010_ImpactSpeed	0.0
acc_csc_010_CollisionEver	0.0

Criteria

Name	Result
acc_csc_010 - Safe Distance Consistency	
acc_csc_010 - Time To Collision	
acc_csc_010 - Comfort Deceleration Limit	
acc_csc_010 - Emergency Deceleration Bound	
acc_csc_010 - Jerk Limit	
acc_csc_010 - No Collision Distance	
acc_csc_010 - Collision Flag	
acc_csc_010 - Impact Speed	

1.10.4

Test # 1.10.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010 └ acc_csc_010_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_010
Description:	TestRun converted from acc_csc_010_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	28
NValue	TV1Speed	21
NValue	TV1_initPos	70
NValue	TV2Speed	20
NValue	TV2_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_010_141509.erg

Characteristics

Name	Value
acc_csc_010_ActualDist	999.0
acc_csc_010_SafeDist	64.28009039
acc_csc_010_SafeDistViolated	1.0
acc_csc_010_TTC	0.0
acc_csc_010_TTCWarnEver	0.0

Name	Value
acc_csc_010_TTCBadEver	0.0
acc_csc_010_ComfortAx	0.04170769162
acc_csc_010_ComfortAxOutOfBoundEver	1.0
acc_csc_010_EmergencyAx	0.04170769162
acc_csc_010_EmergencyAxOutOfBoundEver	0.0
acc_csc_010_Jerk	0.003057505489
acc_csc_010_JerkOverLimitEver	1.0
acc_csc_010_NoCollDist	999.0
acc_csc_010_NoCollDistViolatedEver	0.0
acc_csc_010_CollisionFlag	0.0
acc_csc_010_ImpactSpeed	0.0
acc_csc_010_CollisionEver	0.0

Criteria

Name	Result
acc_csc_010 - Safe Distance Consistency	
acc_csc_010 - Time To Collision	
acc_csc_010 - Comfort Deceleration Limit	
acc_csc_010 - Emergency Deceleration Bound	
acc_csc_010 - Jerk Limit	
acc_csc_010 - No Collision Distance	
acc_csc_010 - Collision Flag	
acc_csc_010 - Impact Speed	

1.10.5

Test # 1.10.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_010 └ acc_csc_010_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_010
Description:	TestRun converted from acc_csc_010_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TV1Speed	22
NValue	TV1_initPos	75
NValue	TV2Speed	21
NValue	TV2_initPos	105
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_010_141522.erg

Characteristics

Name	Value
acc_csc_010_ActualDist	999.0
acc_csc_010_SafeDist	68.84923648
acc_csc_010_SafeDistViolated	1.0
acc_csc_010_TTC	0.0
acc_csc_010_TTCWarnEver	0.0

Name	Value
acc_csc_010_TTCBadEver	0.0
acc_csc_010_ComfortAx	0.05243948454
acc_csc_010_ComfortAxOutOfBoundEver	1.0
acc_csc_010_EmergencyAx	0.05243948454
acc_csc_010_EmergencyAxOutOfBoundEver	0.0
acc_csc_010_Jerk	0.01896420914
acc_csc_010_JerkOverLimitEver	1.0
acc_csc_010_NoCollDist	999.0
acc_csc_010_NoCollDistViolatedEver	0.0
acc_csc_010_CollisionFlag	0.0
acc_csc_010_ImpactSpeed	0.0
acc_csc_010_CollisionEver	0.0

Criteria

Name	Result
acc_csc_010 - Safe Distance Consistency	
acc_csc_010 - Time To Collision	
acc_csc_010 - Comfort Deceleration Limit	
acc_csc_010 - Emergency Deceleration Bound	
acc_csc_010 - Jerk Limit	
acc_csc_010 - No Collision Distance	
acc_csc_010 - Collision Flag	
acc_csc_010 - Impact Speed	

1.11

Test # 1.11
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011

Characteristics

Name	Description
acc_csc_011_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_011_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_011_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_011_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_011_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_011_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_011_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_011_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_011_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_011_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_011_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_011_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_011_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_011_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_011_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_011_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_011_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_011_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_011_SafeDist	35.6514	32.2007	55.1969	64.2816	68.8511
acc_csc_011_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_011_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_011_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_011_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_011_ComfortAx	1.99952	2.8	0.00107557	0.0411746	0.05178
acc_csc_011_ComfortAxOutOfBoundEver	0.0	0.0	0.0	1.0	1.0
acc_csc_011_EmergencyAx	1.99952	2.8	0.00107557	0.0411746	0.05178
acc_csc_011_EmergencyAxOutOfBou	0.0	0.0	0.0	0.0	0.0

Name	# 1	# 2	# 3	# 4	# 5
ndEver					
acc_csc_011_Jerk	0.338154	0.0	0.0016564	0.00376575	0.0194199
acc_csc_011_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_011_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_011_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_011_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_011_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_011_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_011 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_011 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_011 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_011 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_011 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_011 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_011 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_011 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_011 - Safe Distance Consistency					
acc_csc_011 - Time To Collision					
acc_csc_011 - Comfort Deceleration Limit					
acc_csc_011 - Emergency Deceleration Bound					
acc_csc_011 - Jerk Limit					
acc_csc_011 - No Collision Distance					
acc_csc_011 - Collision Flag					
acc_csc_011 - Impact Speed					

1.11.1

Test # 1.11.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011 └ acc_csc_011_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_011
Description:	TestRun converted from acc_csc_011_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	18
NValue	TV1Speed	13
NValue	TV1_initPos	50
NValue	TV2Speed	13
NValue	TV2_initPos	70
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_011_141535.erg

Characteristics

Name	Value
acc_csc_011_ActualDist	999.0
acc_csc_011_SafeDist	35.65137054
acc_csc_011_SafeDistViolated	1.0
acc_csc_011_TTC	0.0
acc_csc_011_TTCWarnEver	0.0

Name	Value
acc_csc_011_TTCBadEver	0.0
acc_csc_011_ComfortAx	1.999523289
acc_csc_011_ComfortAxOutOfBoundEver	0.0
acc_csc_011_EmergencyAx	1.999523289
acc_csc_011_EmergencyAxOutOfBoundEver	0.0
acc_csc_011_Jerk	0.3381535177
acc_csc_011_JerkOverLimitEver	1.0
acc_csc_011_NoCollDist	999.0
acc_csc_011_NoCollDistViolatedEver	0.0
acc_csc_011_CollisionFlag	0.0
acc_csc_011_ImpactSpeed	0.0
acc_csc_011_CollisionEver	0.0

Criteria

Name	Result
acc_csc_011 - Safe Distance Consistency	
acc_csc_011 - Time To Collision	
acc_csc_011 - Comfort Deceleration Limit	
acc_csc_011 - Emergency Deceleration Bound	
acc_csc_011 - Jerk Limit	
acc_csc_011 - No Collision Distance	
acc_csc_011 - Collision Flag	
acc_csc_011 - Impact Speed	

1.11.2

Test # 1.11.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011 └ acc_csc_011_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_011
Description:	TestRun converted from acc_csc_011_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TV1Speed	15
NValue	TV1_initPos	55
NValue	TV2Speed	15
NValue	TV2_initPos	75
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_011_141547.erg

Characteristics

Name	Value
acc_csc_011_ActualDist	999.0
acc_csc_011_SafeDist	32.20073838
acc_csc_011_SafeDistViolated	1.0
acc_csc_011_TTC	0.0
acc_csc_011_TTCWarnEver	0.0

Name	Value
acc_csc_011_TTCBadEver	0.0
acc_csc_011_ComfortAx	2.8
acc_csc_011_ComfortAxOutOfBoundEver	0.0
acc_csc_011_EmergencyAx	2.8
acc_csc_011_EmergencyAxOutOfBoundEver	0.0
acc_csc_011_Jerk	0.0
acc_csc_011_JerkOverLimitEver	1.0
acc_csc_011_NoCollDist	999.0
acc_csc_011_NoCollDistViolatedEver	0.0
acc_csc_011_CollisionFlag	0.0
acc_csc_011_ImpactSpeed	0.0
acc_csc_011_CollisionEver	0.0

Criteria

Name	Result
acc_csc_011 - Safe Distance Consistency	
acc_csc_011 - Time To Collision	
acc_csc_011 - Comfort Deceleration Limit	
acc_csc_011 - Emergency Deceleration Bound	
acc_csc_011 - Jerk Limit	
acc_csc_011 - No Collision Distance	
acc_csc_011 - Collision Flag	
acc_csc_011 - Impact Speed	

1.11.3

Test # 1.11.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011 └ acc_csc_011_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_011
Description:	TestRun converted from acc_csc_011_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	24
NValue	TV1Speed	18
NValue	TV1_initPos	62
NValue	TV2Speed	17
NValue	TV2_initPos	90
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_011_141600.erg

Characteristics

Name	Value
acc_csc_011_ActualDist	999.0
acc_csc_011_SafeDist	55.19690774
acc_csc_011_SafeDistViolated	1.0
acc_csc_011_TTC	0.0
acc_csc_011_TTCWarnEver	0.0

Name	Value
acc_csc_011_TTCBadEver	0.0
acc_csc_011_ComfortAx	0.001075569824
acc_csc_011_ComfortAxOutOfBoundEver	0.0
acc_csc_011_EmergencyAx	0.001075569824
acc_csc_011_EmergencyAxOutOfBoundEver	0.0
acc_csc_011_Jerk	0.00165639934
acc_csc_011_JerkOverLimitEver	1.0
acc_csc_011_NoCollDist	999.0
acc_csc_011_NoCollDistViolatedEver	0.0
acc_csc_011_CollisionFlag	0.0
acc_csc_011_ImpactSpeed	0.0
acc_csc_011_CollisionEver	0.0

Criteria

Name	Result
acc_csc_011 - Safe Distance Consistency	
acc_csc_011 - Time To Collision	
acc_csc_011 - Comfort Deceleration Limit	
acc_csc_011 - Emergency Deceleration Bound	
acc_csc_011 - Jerk Limit	
acc_csc_011 - No Collision Distance	
acc_csc_011 - Collision Flag	
acc_csc_011 - Impact Speed	

1.11.4

Test # 1.11.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011 └ acc_csc_011_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_011
Description:	TestRun converted from acc_csc_011_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	28
NValue	TV1Speed	21
NValue	TV1_initPos	70
NValue	TV2Speed	20
NValue	TV2_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_011_141613.erg

Characteristics

Name	Value
acc_csc_011_ActualDist	999.0
acc_csc_011_SafeDist	64.28162308
acc_csc_011_SafeDistViolated	1.0
acc_csc_011_TTC	0.0
acc_csc_011_TTCWarnEver	0.0

Name	Value
acc_csc_011_TTCBadEver	0.0
acc_csc_011_ComfortAx	0.04117458119
acc_csc_011_ComfortAxOutOfBoundEver	1.0
acc_csc_011_EmergencyAx	0.04117458119
acc_csc_011_EmergencyAxOutOfBoundEver	0.0
acc_csc_011_Jerk	0.003765751583
acc_csc_011_JerkOverLimitEver	1.0
acc_csc_011_NoCollDist	999.0
acc_csc_011_NoCollDistViolatedEver	0.0
acc_csc_011_CollisionFlag	0.0
acc_csc_011_ImpactSpeed	0.0
acc_csc_011_CollisionEver	0.0

Criteria

Name	Result
acc_csc_011 - Safe Distance Consistency	
acc_csc_011 - Time To Collision	
acc_csc_011 - Comfort Deceleration Limit	
acc_csc_011 - Emergency Deceleration Bound	
acc_csc_011 - Jerk Limit	
acc_csc_011 - No Collision Distance	
acc_csc_011 - Collision Flag	
acc_csc_011 - Impact Speed	

1.11.5

Test # 1.11.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_011 └ acc_csc_011_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_011
Description:	TestRun converted from acc_csc_011_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TV1Speed	22
NValue	TV1_initPos	75
NValue	TV2Speed	21
NValue	TV2_initPos	105
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_011_141625.erg

Characteristics

Name	Value
acc_csc_011_ActualDist	999.0
acc_csc_011_SafeDist	68.85113246
acc_csc_011_SafeDistViolated	1.0
acc_csc_011_TTC	0.0
acc_csc_011_TTCWarnEver	0.0

Name	Value
acc_csc_011_TTCBadEver	0.0
acc_csc_011_ComfortAx	0.05178001508
acc_csc_011_ComfortAxOutOfBoundEver	1.0
acc_csc_011_EmergencyAx	0.05178001508
acc_csc_011_EmergencyAxOutOfBoundEver	0.0
acc_csc_011_Jerk	0.0194199185
acc_csc_011_JerkOverLimitEver	1.0
acc_csc_011_NoCollDist	999.0
acc_csc_011_NoCollDistViolatedEver	0.0
acc_csc_011_CollisionFlag	0.0
acc_csc_011_ImpactSpeed	0.0
acc_csc_011_CollisionEver	0.0

Criteria

Name	Result
acc_csc_011 - Safe Distance Consistency	
acc_csc_011 - Time To Collision	
acc_csc_011 - Comfort Deceleration Limit	
acc_csc_011 - Emergency Deceleration Bound	
acc_csc_011 - Jerk Limit	
acc_csc_011 - No Collision Distance	
acc_csc_011 - Collision Flag	
acc_csc_011 - Impact Speed	

1.12

Test # 1.12
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012

Characteristics

Name	Description
acc_csc_012_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_012_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_012_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_012_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_012_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_012_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_012_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_012_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_012_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_012_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_012_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_012_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_012_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_012_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_012_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_012_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_012_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_012_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_012_SafeDist	15.0	16.4848	23	28.4	35.0522
acc_csc_012_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_012_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_012_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_012_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_012_ComfortAx	-0.004	-0.004	-3.17982e-007	-0.004	-0.004
acc_csc_012_ComfortAxOutOfBoundEver	1.0	1.0	1.0	1.0	1.0
acc_csc_012_EmergencyAx	-0.004	-0.004	-3.17982e-	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
			007		
acc_csc_012_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_012_Jerk	0.0	0.0	4.5911e-008	0.0	0.0
acc_csc_012_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_012_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_012_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_012_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_012_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_012_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_012 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_012 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_012 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_012 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_012 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_012 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_012 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_012 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_012 - Safe Distance Consistency					
acc_csc_012 - Time To Collision					
acc_csc_012 - Comfort Deceleration Limit					
acc_csc_012 - Emergency Deceleration Bound					
acc_csc_012 - Jerk Limit					
acc_csc_012 - No Collision Distance					
acc_csc_012 - Collision Flag					
acc_csc_012 - Impact Speed					

1.12.1

Test # 1.12.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012 └ acc_csc_012_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_012
Description:	TestRun converted from acc_csc_012_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	5
NValue	TV1Speed	3
NValue	TV1_initPos	33
NValue	TV2Speed	0
NValue	TV2_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_012_141638.erg

Characteristics

Name	Value
acc_csc_012_ActualDist	999.0
acc_csc_012_SafeDist	15.0
acc_csc_012_SafeDistViolated	1.0
acc_csc_012_TTC	0.0
acc_csc_012_TTCWarnEver	0.0

Name	Value
acc_csc_012_TTCBadEver	0.0
acc_csc_012_ComfortAx	-0.004
acc_csc_012_ComfortAxOutOfBoundEver	1.0
acc_csc_012_EmergencyAx	-0.004
acc_csc_012_EmergencyAxOutOfBoundEver	0.0
acc_csc_012_Jerk	0.0
acc_csc_012_JerkOverLimitEver	1.0
acc_csc_012_NoCollDist	999.0
acc_csc_012_NoCollDistViolatedEver	0.0
acc_csc_012_CollisionFlag	0.0
acc_csc_012_ImpactSpeed	0.0
acc_csc_012_CollisionEver	0.0

Criteria

Name	Result
acc_csc_012 - Safe Distance Consistency	
acc_csc_012 - Time To Collision	
acc_csc_012 - Comfort Deceleration Limit	
acc_csc_012 - Emergency Deceleration Bound	
acc_csc_012 - Jerk Limit	
acc_csc_012 - No Collision Distance	
acc_csc_012 - Collision Flag	
acc_csc_012 - Impact Speed	

1.12.2

Test # 1.12.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012 └ acc_csc_012_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_012
Description:	TestRun converted from acc_csc_012_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	7
NValue	TV1Speed	5
NValue	TV1_initPos	40
NValue	TV2Speed	0
NValue	TV2_initPos	83
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_012_141651.erg

Characteristics

Name	Value
acc_csc_012_ActualDist	999.0
acc_csc_012_SafeDist	16.48481677
acc_csc_012_SafeDistViolated	1.0
acc_csc_012_TTC	0.0
acc_csc_012_TTCWarnEver	0.0

Name	Value
acc_csc_012_TTCBadEver	0.0
acc_csc_012_ComfortAx	-0.004
acc_csc_012_ComfortAxOutOfBoundEver	1.0
acc_csc_012_EmergencyAx	-0.004
acc_csc_012_EmergencyAxOutOfBoundEver	0.0
acc_csc_012_Jerk	0.0
acc_csc_012_JerkOverLimitEver	1.0
acc_csc_012_NoCollDist	999.0
acc_csc_012_NoCollDistViolatedEver	0.0
acc_csc_012_CollisionFlag	0.0
acc_csc_012_ImpactSpeed	0.0
acc_csc_012_CollisionEver	0.0

Criteria

Name	Result
acc_csc_012 - Safe Distance Consistency	
acc_csc_012 - Time To Collision	
acc_csc_012 - Comfort Deceleration Limit	
acc_csc_012 - Emergency Deceleration Bound	
acc_csc_012 - Jerk Limit	
acc_csc_012 - No Collision Distance	
acc_csc_012 - Collision Flag	
acc_csc_012 - Impact Speed	

1.12.3

Test # 1.12.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012 └ acc_csc_012_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_012
Description:	TestRun converted from acc_csc_012_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TV1Speed	7
NValue	TV1_initPos	47
NValue	TV2Speed	0
NValue	TV2_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_012_141703.erg

Characteristics

Name	Value
acc_csc_012_ActualDist	999.0
acc_csc_012_SafeDist	23.00000091
acc_csc_012_SafeDistViolated	1.0
acc_csc_012_TTC	0.0
acc_csc_012_TTCWarnEver	0.0

Name	Value
acc_csc_012_TTCBadEver	0.0
acc_csc_012_ComfortAx	-3.179820865e-007
acc_csc_012_ComfortAxOutOfBoundEver	1.0
acc_csc_012_EmergencyAx	-3.179820865e-007
acc_csc_012_EmergencyAxOutOfBoundEver	0.0
acc_csc_012_Jerk	4.591100833e-008
acc_csc_012_JerkOverLimitEver	1.0
acc_csc_012_NoCollDist	999.0
acc_csc_012_NoCollDistViolatedEver	0.0
acc_csc_012_CollisionFlag	0.0
acc_csc_012_ImpactSpeed	0.0
acc_csc_012_CollisionEver	0.0

Criteria

Name	Result
acc_csc_012 - Safe Distance Consistency	
acc_csc_012 - Time To Collision	
acc_csc_012 - Comfort Deceleration Limit	
acc_csc_012 - Emergency Deceleration Bound	
acc_csc_012 - Jerk Limit	
acc_csc_012 - No Collision Distance	
acc_csc_012 - Collision Flag	
acc_csc_012 - Impact Speed	

1.12.4

Test # 1.12.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012 └ acc_csc_012_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_012
Description:	TestRun converted from acc_csc_012_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TV1Speed	9
NValue	TV1_initPos	54
NValue	TV2Speed	0
NValue	TV2_initPos	115
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_012_141715.erg

Characteristics

Name	Value
acc_csc_012_ActualDist	999.0
acc_csc_012_SafeDist	28.39996974
acc_csc_012_SafeDistViolated	1.0
acc_csc_012_TTC	0.0
acc_csc_012_TTCWarnEver	0.0

Name	Value
acc_csc_012_TTCBadEver	0.0
acc_csc_012_ComfortAx	-0.004
acc_csc_012_ComfortAxOutOfBoundEver	1.0
acc_csc_012_EmergencyAx	-0.004
acc_csc_012_EmergencyAxOutOfBoundEver	0.0
acc_csc_012_Jerk	0.0
acc_csc_012_JerkOverLimitEver	1.0
acc_csc_012_NoCollDist	999.0
acc_csc_012_NoCollDistViolatedEver	0.0
acc_csc_012_CollisionFlag	0.0
acc_csc_012_ImpactSpeed	0.0
acc_csc_012_CollisionEver	0.0

Criteria

Name	Result
acc_csc_012 - Safe Distance Consistency	
acc_csc_012 - Time To Collision	
acc_csc_012 - Comfort Deceleration Limit	
acc_csc_012 - Emergency Deceleration Bound	
acc_csc_012 - Jerk Limit	
acc_csc_012 - No Collision Distance	
acc_csc_012 - Collision Flag	
acc_csc_012 - Impact Speed	

1.12.5

Test # 1.12.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_012 └ acc_csc_012_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_012
Description:	TestRun converted from acc_csc_012_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TV1Speed	11
NValue	TV1_initPos	61
NValue	TV2Speed	0
NValue	TV2_initPos	125
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_012_141728.erg

Characteristics

Name	Value
acc_csc_012_ActualDist	999.0
acc_csc_012_SafeDist	35.052161
acc_csc_012_SafeDistViolated	1.0
acc_csc_012_TTC	0.0
acc_csc_012_TTCWarnEver	0.0

Name	Value
acc_csc_012_TTCBadEver	0.0
acc_csc_012_ComfortAx	-0.004
acc_csc_012_ComfortAxOutOfBoundEver	1.0
acc_csc_012_EmergencyAx	-0.004
acc_csc_012_EmergencyAxOutOfBoundEver	0.0
acc_csc_012_Jerk	0.0
acc_csc_012_JerkOverLimitEver	1.0
acc_csc_012_NoCollDist	999.0
acc_csc_012_NoCollDistViolatedEver	0.0
acc_csc_012_CollisionFlag	0.0
acc_csc_012_ImpactSpeed	0.0
acc_csc_012_CollisionEver	0.0

Criteria

Name	Result
acc_csc_012 - Safe Distance Consistency	
acc_csc_012 - Time To Collision	
acc_csc_012 - Comfort Deceleration Limit	
acc_csc_012 - Emergency Deceleration Bound	
acc_csc_012 - Jerk Limit	
acc_csc_012 - No Collision Distance	
acc_csc_012 - Collision Flag	
acc_csc_012 - Impact Speed	

1.13

Test # 1.13

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_013

Characteristics

Name	Description
acc_csc_013_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_013_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_013_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_013_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_013_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_013_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_013_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_013_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_013_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_013_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_013_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_013_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_013_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_013_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_013_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_013_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_013_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_013_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_013_SafeDist	15.0	16.4848	23	28.4	35.0515
acc_csc_013_SafeDistViolated	1.0	1.0	1.0	1.0	1.0
acc_csc_013_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_013_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_013_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_013_ComfortAx	-0.004	-0.004	-3.17982e-007	-0.004	-0.004
acc_csc_013_ComfortAxOutOfBoundEver	1.0	1.0	1.0	1.0	1.0
acc_csc_013_EmergencyAx	-0.004	-0.004	-3.17982e-	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
			007		
acc_csc_013_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_013_Jerk	0.0	0.0	4.5911e-008	0.0	0.0
acc_csc_013_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_013_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_013_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_013_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_013_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_013_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_013 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_013 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_013 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_013 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_013 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_013 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_013 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_013 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_013 - Safe Distance Consistency	⚡	⚡	⚡	⚡	⚡
acc_csc_013 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_013 - Comfort Deceleration Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_013 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_013 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_013 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_013 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_013 - Impact Speed	✓	✓	✓	✓	✓

1.13.1

Test # 1.13.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_013 └ acc_csc_013_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_013
Description:	TestRun converted from acc_csc_013_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	5
NValue	TV1Speed	3
NValue	TV1_initPos	33
NValue	TV2Speed	0
NValue	TV2_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_013_141741.erg

Characteristics

Name	Value
acc_csc_013_ActualDist	999.0
acc_csc_013_SafeDist	15.0
acc_csc_013_SafeDistViolated	1.0
acc_csc_013_TTC	0.0
acc_csc_013_TTCWarnEver	0.0

Name	Value
acc_csc_013_TTCBadEver	0.0
acc_csc_013_ComfortAx	-0.004
acc_csc_013_ComfortAxOutOfBoundEver	1.0
acc_csc_013_EmergencyAx	-0.004
acc_csc_013_EmergencyAxOutOfBoundEver	0.0
acc_csc_013_Jerk	0.0
acc_csc_013_JerkOverLimitEver	1.0
acc_csc_013_NoCollDist	999.0
acc_csc_013_NoCollDistViolatedEver	0.0
acc_csc_013_CollisionFlag	0.0
acc_csc_013_ImpactSpeed	0.0
acc_csc_013_CollisionEver	0.0

Criteria

Name	Result
acc_csc_013 - Safe Distance Consistency	
acc_csc_013 - Time To Collision	
acc_csc_013 - Comfort Deceleration Limit	
acc_csc_013 - Emergency Deceleration Bound	
acc_csc_013 - Jerk Limit	
acc_csc_013 - No Collision Distance	
acc_csc_013 - Collision Flag	
acc_csc_013 - Impact Speed	

1.13.2

Test # 1.13.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_013 └ acc_csc_013_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_013
Description:	TestRun converted from acc_csc_013_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	7
NValue	TV1Speed	5
NValue	TV1_initPos	40
NValue	TV2Speed	0
NValue	TV2_initPos	83
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_013_141754.erg

Characteristics

Name	Value
acc_csc_013_ActualDist	999.0
acc_csc_013_SafeDist	16.48481677
acc_csc_013_SafeDistViolated	1.0
acc_csc_013_TTC	0.0
acc_csc_013_TTCWarnEver	0.0

Name	Value
acc_csc_013_TTCBadEver	0.0
acc_csc_013_ComfortAx	-0.004
acc_csc_013_ComfortAxOutOfBoundEver	1.0
acc_csc_013_EmergencyAx	-0.004
acc_csc_013_EmergencyAxOutOfBoundEver	0.0
acc_csc_013_Jerk	0.0
acc_csc_013_JerkOverLimitEver	1.0
acc_csc_013_NoCollDist	999.0
acc_csc_013_NoCollDistViolatedEver	0.0
acc_csc_013_CollisionFlag	0.0
acc_csc_013_ImpactSpeed	0.0
acc_csc_013_CollisionEver	0.0

Criteria

Name	Result
acc_csc_013 - Safe Distance Consistency	
acc_csc_013 - Time To Collision	
acc_csc_013 - Comfort Deceleration Limit	
acc_csc_013 - Emergency Deceleration Bound	
acc_csc_013 - Jerk Limit	
acc_csc_013 - No Collision Distance	
acc_csc_013 - Collision Flag	
acc_csc_013 - Impact Speed	

1.13.3

Test # 1.13.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_013 └ acc_csc_013_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_013
Description:	TestRun converted from acc_csc_013_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TV1Speed	7
NValue	TV1_initPos	47
NValue	TV2Speed	0
NValue	TV2_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_013_141806.erg

Characteristics

Name	Value
acc_csc_013_ActualDist	999.0
acc_csc_013_SafeDist	23.00000091
acc_csc_013_SafeDistViolated	1.0
acc_csc_013_TTC	0.0
acc_csc_013_TTCWarnEver	0.0

Name	Value
acc_csc_013_TTCBadEver	0.0
acc_csc_013_ComfortAx	-3.179820865e-007
acc_csc_013_ComfortAxOutOfBoundEver	1.0
acc_csc_013_EmergencyAx	-3.179820865e-007
acc_csc_013_EmergencyAxOutOfBoundEver	0.0
acc_csc_013_Jerk	4.591100833e-008
acc_csc_013_JerkOverLimitEver	1.0
acc_csc_013_NoCollDist	999.0
acc_csc_013_NoCollDistViolatedEver	0.0
acc_csc_013_CollisionFlag	0.0
acc_csc_013_ImpactSpeed	0.0
acc_csc_013_CollisionEver	0.0

Criteria

Name	Result
acc_csc_013 - Safe Distance Consistency	
acc_csc_013 - Time To Collision	
acc_csc_013 - Comfort Deceleration Limit	
acc_csc_013 - Emergency Deceleration Bound	
acc_csc_013 - Jerk Limit	
acc_csc_013 - No Collision Distance	
acc_csc_013 - Collision Flag	
acc_csc_013 - Impact Speed	

1.13.4

Test # 1.13.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_013 └ acc_csc_013_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_013
Description:	TestRun converted from acc_csc_013_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TV1Speed	9
NValue	TV1_initPos	54
NValue	TV2Speed	0
NValue	TV2_initPos	115
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_013_141819.erg

Characteristics

Name	Value
acc_csc_013_ActualDist	999.0
acc_csc_013_SafeDist	28.39997251
acc_csc_013_SafeDistViolated	1.0
acc_csc_013_TTC	0.0
acc_csc_013_TTCWarnEver	0.0

Name	Value
acc_csc_013_TTCBadEver	0.0
acc_csc_013_ComfortAx	-0.004
acc_csc_013_ComfortAxOutOfBoundEver	1.0
acc_csc_013_EmergencyAx	-0.004
acc_csc_013_EmergencyAxOutOfBoundEver	0.0
acc_csc_013_Jerk	0.0
acc_csc_013_JerkOverLimitEver	1.0
acc_csc_013_NoCollDist	999.0
acc_csc_013_NoCollDistViolatedEver	0.0
acc_csc_013_CollisionFlag	0.0
acc_csc_013_ImpactSpeed	0.0
acc_csc_013_CollisionEver	0.0

Criteria

Name	Result
acc_csc_013 - Safe Distance Consistency	
acc_csc_013 - Time To Collision	
acc_csc_013 - Comfort Deceleration Limit	
acc_csc_013 - Emergency Deceleration Bound	
acc_csc_013 - Jerk Limit	
acc_csc_013 - No Collision Distance	
acc_csc_013 - Collision Flag	
acc_csc_013 - Impact Speed	

1.13.5

Test # 1.13.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_013 └ acc_csc_013_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_013
Description:	TestRun converted from acc_csc_013_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Listed maneuver steps have not been executed necessarily

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0	0.000			

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TV1Speed	11
NValue	TV1_initPos	61
NValue	TV2Speed	0
NValue	TV2_initPos	125
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_013_141831.erg

Characteristics

Name	Value
acc_csc_013_ActualDist	999.0
acc_csc_013_SafeDist	35.05149752
acc_csc_013_SafeDistViolated	1.0
acc_csc_013_TTC	0.0
acc_csc_013_TTCWarnEver	0.0

Name	Value
acc_csc_013_TTCBadEver	0.0
acc_csc_013_ComfortAx	-0.004
acc_csc_013_ComfortAxOutOfBoundEver	1.0
acc_csc_013_EmergencyAx	-0.004
acc_csc_013_EmergencyAxOutOfBoundEver	0.0
acc_csc_013_Jerk	0.0
acc_csc_013_JerkOverLimitEver	1.0
acc_csc_013_NoCollDist	999.0
acc_csc_013_NoCollDistViolatedEver	0.0
acc_csc_013_CollisionFlag	0.0
acc_csc_013_ImpactSpeed	0.0
acc_csc_013_CollisionEver	0.0

Criteria

Name	Result
acc_csc_013 - Safe Distance Consistency	
acc_csc_013 - Time To Collision	
acc_csc_013 - Comfort Deceleration Limit	
acc_csc_013 - Emergency Deceleration Bound	
acc_csc_013 - Jerk Limit	
acc_csc_013 - No Collision Distance	
acc_csc_013 - Collision Flag	
acc_csc_013 - Impact Speed	

1.14

Test # 1.14
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014

Characteristics

Name	Description
acc_csc_014_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_014_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_014_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_014_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_014_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_014_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_014_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_014_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_014_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_014_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_014_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_014_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_014_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_014_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_014_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_014_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_014_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_014_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_014_SafeDist	34.5021	34.5021	45.4683	56.1782	66.037
acc_csc_014_SafeDistViolated	0.0	0.0	0.0	1.0	1.0
acc_csc_014_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_014_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_014_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_014_ComfortAx	-0.00074280 9	-0.00074074 3	-0.004	-0.004	-0.004
acc_csc_014_ComfortAxOutOfBoundEver	0.0	0.0	0.0	1.0	1.0
acc_csc_014_EmergencyAx	-0.00074280	-0.00074074	-0.004	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
	9	3			
acc_csc_014_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_014_Jerk	3.14237e-006	2.08017e-007	0.0	0.0	0.0
acc_csc_014_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_014_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_014_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_014_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_014_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_014_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_014 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_014 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_014 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_014 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_014 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_014 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_014 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_014 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_014 - Safe Distance Consistency	✓	✓	✓	✗	✗
acc_csc_014 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_014 - Comfort Deceleration Limit	✓	✓	✓	✗	✗
acc_csc_014 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_014 - Jerk Limit	✗	✗	✗	✗	✗
acc_csc_014 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_014 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_014 - Impact Speed	✓	✓	✓	✓	✓

1.14.1

Test # 1.14.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014 └ acc_csc_014_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_014
Description:	TestRun converted from acc_csc_014_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	67
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_014_141844.erg

Characteristics

Name	Value
acc_csc_014_ActualDist	999.0
acc_csc_014_SafeDist	34.50213557

Name	Value
acc_csc_014_SafeDistViolated	0.0
acc_csc_014_TTC	0.0
acc_csc_014_TTCWarnEver	0.0
acc_csc_014_TTCBadEver	0.0
acc_csc_014_ComfortAx	-0.0007428085417
acc_csc_014_ComfortAxOutOfBoundEver	0.0
acc_csc_014_EmergencyAx	-0.0007428085417
acc_csc_014_EmergencyAxOutOfBoundEver	0.0
acc_csc_014_Jerk	3.142368143e-006
acc_csc_014_JerkOverLimitEver	1.0
acc_csc_014_NoCollDist	999.0
acc_csc_014_NoCollDistViolatedEver	0.0
acc_csc_014_CollisionFlag	0.0
acc_csc_014_ImpactSpeed	0.0
acc_csc_014_CollisionEver	0.0

Criteria

Name	Result
acc_csc_014 - Safe Distance Consistency	✓
acc_csc_014 - Time To Collision	✓
acc_csc_014 - Comfort Deceleration Limit	✓
acc_csc_014 - Emergency Deceleration Bound	✓
acc_csc_014 - Jerk Limit	⚡
acc_csc_014 - No Collision Distance	✓
acc_csc_014 - Collision Flag	✓
acc_csc_014 - Impact Speed	✓

1.14.2

Test # 1.14.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014 └ acc_csc_014_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_014
Description:	TestRun converted from acc_csc_014_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_014_141856.erg

Characteristics

Name	Value
acc_csc_014_ActualDist	999.0
acc_csc_014_SafeDist	34.50212964

Name	Value
acc_csc_014_SafeDistViolated	0.0
acc_csc_014_TTC	0.0
acc_csc_014_TTCWarnEver	0.0
acc_csc_014_TTCBadEver	0.0
acc_csc_014_ComfortAx	-0.000740743161
acc_csc_014_ComfortAxOutOfBoundEver	0.0
acc_csc_014_EmergencyAx	-0.000740743161
acc_csc_014_EmergencyAxOutOfBoundEver	0.0
acc_csc_014_Jerk	2.080170703e-007
acc_csc_014_JerkOverLimitEver	1.0
acc_csc_014_NoCollDist	999.0
acc_csc_014_NoCollDistViolatedEver	0.0
acc_csc_014_CollisionFlag	0.0
acc_csc_014_ImpactSpeed	0.0
acc_csc_014_CollisionEver	0.0

Criteria

Name	Result
acc_csc_014 - Safe Distance Consistency	✓
acc_csc_014 - Time To Collision	✓
acc_csc_014 - Comfort Deceleration Limit	✓
acc_csc_014 - Emergency Deceleration Bound	✓
acc_csc_014 - Jerk Limit	⚡
acc_csc_014 - No Collision Distance	✓
acc_csc_014 - Collision Flag	✓
acc_csc_014 - Impact Speed	✓

1.14.3

Test # 1.14.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014 └ acc_csc_014_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_014
Description:	TestRun converted from acc_csc_014_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	93
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_014_141908.erg

Characteristics

Name	Value
acc_csc_014_ActualDist	999.0
acc_csc_014_SafeDist	45.46833214

Name	Value
acc_csc_014_SafeDistViolated	0.0
acc_csc_014_TTC	0.0
acc_csc_014_TTCWarnEver	0.0
acc_csc_014_TTCBadEver	0.0
acc_csc_014_ComfortAx	-0.004
acc_csc_014_ComfortAxOutOfBoundEver	0.0
acc_csc_014_EmergencyAx	-0.004
acc_csc_014_EmergencyAxOutOfBoundEver	0.0
acc_csc_014_Jerk	0.0
acc_csc_014_JerkOverLimitEver	1.0
acc_csc_014_NoCollDist	999.0
acc_csc_014_NoCollDistViolatedEver	0.0
acc_csc_014_CollisionFlag	0.0
acc_csc_014_ImpactSpeed	0.0
acc_csc_014_CollisionEver	0.0

Criteria

Name	Result
acc_csc_014 - Safe Distance Consistency	✓
acc_csc_014 - Time To Collision	✓
acc_csc_014 - Comfort Deceleration Limit	✓
acc_csc_014 - Emergency Deceleration Bound	✓
acc_csc_014 - Jerk Limit	⚡
acc_csc_014 - No Collision Distance	✓
acc_csc_014 - Collision Flag	✓
acc_csc_014 - Impact Speed	✓

1.14.4

Test # 1.14.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014 └ acc_csc_014_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_014
Description:	TestRun converted from acc_csc_014_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	106
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_014_141920.erg

Characteristics

Name	Value
acc_csc_014_ActualDist	999.0
acc_csc_014_SafeDist	56.17815111

Name	Value
acc_csc_014_SafeDistViolated	1.0
acc_csc_014_TTC	0.0
acc_csc_014_TTCWarnEver	0.0
acc_csc_014_TTCBadEver	0.0
acc_csc_014_ComfortAx	-0.004
acc_csc_014_ComfortAxOutOfBoundEver	1.0
acc_csc_014_EmergencyAx	-0.004
acc_csc_014_EmergencyAxOutOfBoundEver	0.0
acc_csc_014_Jerk	0.0
acc_csc_014_JerkOverLimitEver	1.0
acc_csc_014_NoCollDist	999.0
acc_csc_014_NoCollDistViolatedEver	0.0
acc_csc_014_CollisionFlag	0.0
acc_csc_014_ImpactSpeed	0.0
acc_csc_014_CollisionEver	0.0

Criteria

Name	Result
acc_csc_014 - Safe Distance Consistency	
acc_csc_014 - Time To Collision	
acc_csc_014 - Comfort Deceleration Limit	
acc_csc_014 - Emergency Deceleration Bound	
acc_csc_014 - Jerk Limit	
acc_csc_014 - No Collision Distance	
acc_csc_014 - Collision Flag	
acc_csc_014 - Impact Speed	

1.14.5

Test # 1.14.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_014 └ acc_csc_014_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_014
Description:	TestRun converted from acc_csc_014_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	119
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_014_141932.erg

Characteristics

Name	Value
acc_csc_014_ActualDist	999.0
acc_csc_014_SafeDist	66.03701742

Name	Value
acc_csc_014_SafeDistViolated	1.0
acc_csc_014_TTC	0.0
acc_csc_014_TTCWarnEver	0.0
acc_csc_014_TTCBadEver	0.0
acc_csc_014_ComfortAx	-0.004
acc_csc_014_ComfortAxOutOfBoundEver	1.0
acc_csc_014_EmergencyAx	-0.004
acc_csc_014_EmergencyAxOutOfBoundEver	0.0
acc_csc_014_Jerk	0.0
acc_csc_014_JerkOverLimitEver	1.0
acc_csc_014_NoCollDist	999.0
acc_csc_014_NoCollDistViolatedEver	0.0
acc_csc_014_CollisionFlag	0.0
acc_csc_014_ImpactSpeed	0.0
acc_csc_014_CollisionEver	0.0

Criteria

Name	Result
acc_csc_014 - Safe Distance Consistency	
acc_csc_014 - Time To Collision	
acc_csc_014 - Comfort Deceleration Limit	
acc_csc_014 - Emergency Deceleration Bound	
acc_csc_014 - Jerk Limit	
acc_csc_014 - No Collision Distance	
acc_csc_014 - Collision Flag	
acc_csc_014 - Impact Speed	

1.15

Test # 1.15
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015

Characteristics

Name	Description
acc_csc_015_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_015_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_015_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_015_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_015_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_015_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_015_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_015_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_015_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_015_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_015_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_015_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_015_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_015_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_015_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_015_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_015_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_015_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_015_SafeDist	34.502	31.5702	45.4997	56.1789	66.0006
acc_csc_015_SafeDistViolated	0.0	0.0	1.0	1.0	1.0
acc_csc_015_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_015_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_015_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_015_ComfortAx	-0.000703715	1.96	-0.004	-0.004	-0.004
acc_csc_015_ComfortAxOutOfBoundEver	0.0	0.0	0.0	1.0	1.0
acc_csc_015_EmergencyAx	-0.00070371	1.96	-0.004	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
	5				
acc_csc_015_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_015_Jerk	3.57638e-006	0.0	0.0	0.0	0.0
acc_csc_015_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_015_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_015_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_015_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_015_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_015_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_015 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_015 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_015 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_015 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_015 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_015 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_015 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_015 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_015 - Safe Distance Consistency	✓	✓	⚡	⚡	⚡
acc_csc_015 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_015 - Comfort Deceleration Limit	✓	✓	✓	⚡	⚡
acc_csc_015 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_015 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_015 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_015 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_015 - Impact Speed	✓	✓	✓	✓	✓

1.15.1

Test # 1.15.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015 └ acc_csc_015_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_015
Description:	TestRun converted from acc_csc_015_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	67
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_015_141945.erg

Characteristics

Name	Value
acc_csc_015_ActualDist	999.0
acc_csc_015_SafeDist	34.50202318

Name	Value
acc_csc_015_SafeDistViolated	0.0
acc_csc_015_TTC	0.0
acc_csc_015_TTCWarnEver	0.0
acc_csc_015_TTCBadEver	0.0
acc_csc_015_ComfortAx	-0.000703714585
acc_csc_015_ComfortAxOutOfBoundEver	0.0
acc_csc_015_EmergencyAx	-0.000703714585
acc_csc_015_EmergencyAxOutOfBoundEver	0.0
acc_csc_015_Jerk	3.5763847e-006
acc_csc_015_JerkOverLimitEver	1.0
acc_csc_015_NoCollDist	999.0
acc_csc_015_NoCollDistViolatedEver	0.0
acc_csc_015_CollisionFlag	0.0
acc_csc_015_ImpactSpeed	0.0
acc_csc_015_CollisionEver	0.0

Criteria

Name	Result
acc_csc_015 - Safe Distance Consistency	✓
acc_csc_015 - Time To Collision	✓
acc_csc_015 - Comfort Deceleration Limit	✓
acc_csc_015 - Emergency Deceleration Bound	✓
acc_csc_015 - Jerk Limit	⚡
acc_csc_015 - No Collision Distance	✓
acc_csc_015 - Collision Flag	✓
acc_csc_015 - Impact Speed	✓

1.15.2

Test # 1.15.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015 └ acc_csc_015_ds002	 Error

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_015
Description:	TestRun converted from acc_csc_015_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

TestLog
Simulation ended with errors

Resultfile
Results not saved

Characteristics

Name	Value
acc_csc_015_ActualDist	999.0
acc_csc_015_SafeDist	31.57015804
acc_csc_015_SafeDistViolated	0.0
acc_csc_015_TTC	0.0
acc_csc_015_TTCWarnEver	0.0
acc_csc_015_TTCBadEver	0.0
acc_csc_015_ComfortAx	1.96
acc_csc_015_ComfortAxOutOfBoundEver	0.0
acc_csc_015_EmergencyAx	1.96
acc_csc_015_EmergencyAxOutOfBoundEver	0.0
acc_csc_015_Jerk	0.0
acc_csc_015_JerkOverLimitEver	1.0
acc_csc_015_NoCollDist	999.0
acc_csc_015_NoCollDistViolatedEver	0.0
acc_csc_015_CollisionFlag	0.0
acc_csc_015_ImpactSpeed	0.0
acc_csc_015_CollisionEver	0.0

Criteria

Name	Result
acc_csc_015 - Safe Distance Consistency	✓
acc_csc_015 - Time To Collision	✓
acc_csc_015 - Comfort Deceleration Limit	✓
acc_csc_015 - Emergency Deceleration Bound	✓
acc_csc_015 - Jerk Limit	⚡
acc_csc_015 - No Collision Distance	✓
acc_csc_015 - Collision Flag	✓
acc_csc_015 - Impact Speed	✓

1.15.3

Test # 1.15.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015 └ acc_csc_015_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_015
Description:	TestRun converted from acc_csc_015_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	93
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_015_142005.erg

Characteristics

Name	Value
acc_csc_015_ActualDist	999.0
acc_csc_015_SafeDist	45.49968048

Name	Value
acc_csc_015_SafeDistViolated	1.0
acc_csc_015_TTC	0.0
acc_csc_015_TTCWarnEver	0.0
acc_csc_015_TTCBadEver	0.0
acc_csc_015_ComfortAx	-0.004
acc_csc_015_ComfortAxOutOfBoundEver	0.0
acc_csc_015_EmergencyAx	-0.004
acc_csc_015_EmergencyAxOutOfBoundEver	0.0
acc_csc_015_Jerk	0.0
acc_csc_015_JerkOverLimitEver	1.0
acc_csc_015_NoCollDist	999.0
acc_csc_015_NoCollDistViolatedEver	0.0
acc_csc_015_CollisionFlag	0.0
acc_csc_015_ImpactSpeed	0.0
acc_csc_015_CollisionEver	0.0

Criteria

Name	Result
acc_csc_015 - Safe Distance Consistency	
acc_csc_015 - Time To Collision	
acc_csc_015 - Comfort Deceleration Limit	
acc_csc_015 - Emergency Deceleration Bound	
acc_csc_015 - Jerk Limit	
acc_csc_015 - No Collision Distance	
acc_csc_015 - Collision Flag	
acc_csc_015 - Impact Speed	

1.15.4

Test # 1.15.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015 └ acc_csc_015_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_015
Description:	TestRun converted from acc_csc_015_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	106
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_015_142017.erg

Characteristics

Name	Value
acc_csc_015_ActualDist	999.0
acc_csc_015_SafeDist	56.1788952

Name	Value
acc_csc_015_SafeDistViolated	1.0
acc_csc_015_TTC	0.0
acc_csc_015_TTCWarnEver	0.0
acc_csc_015_TTCBadEver	0.0
acc_csc_015_ComfortAx	-0.004
acc_csc_015_ComfortAxOutOfBoundEver	1.0
acc_csc_015_EmergencyAx	-0.004
acc_csc_015_EmergencyAxOutOfBoundEver	0.0
acc_csc_015_Jerk	0.0
acc_csc_015_JerkOverLimitEver	1.0
acc_csc_015_NoCollDist	999.0
acc_csc_015_NoCollDistViolatedEver	0.0
acc_csc_015_CollisionFlag	0.0
acc_csc_015_ImpactSpeed	0.0
acc_csc_015_CollisionEver	0.0

Criteria

Name	Result
acc_csc_015 - Safe Distance Consistency	
acc_csc_015 - Time To Collision	
acc_csc_015 - Comfort Deceleration Limit	
acc_csc_015 - Emergency Deceleration Bound	
acc_csc_015 - Jerk Limit	
acc_csc_015 - No Collision Distance	
acc_csc_015 - Collision Flag	
acc_csc_015 - Impact Speed	

1.15.5

Test # 1.15.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_015 └ acc_csc_015_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_015
Description:	TestRun converted from acc_csc_015_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	15.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	119
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_015_142029.erg

Characteristics

Name	Value
acc_csc_015_ActualDist	999.0
acc_csc_015_SafeDist	66.00055922

Name	Value
acc_csc_015_SafeDistViolated	1.0
acc_csc_015_TTC	0.0
acc_csc_015_TTCWarnEver	0.0
acc_csc_015_TTCBadEver	0.0
acc_csc_015_ComfortAx	-0.004
acc_csc_015_ComfortAxOutOfBoundEver	1.0
acc_csc_015_EmergencyAx	-0.004
acc_csc_015_EmergencyAxOutOfBoundEver	0.0
acc_csc_015_Jerk	0.0
acc_csc_015_JerkOverLimitEver	1.0
acc_csc_015_NoCollDist	999.0
acc_csc_015_NoCollDistViolatedEver	0.0
acc_csc_015_CollisionFlag	0.0
acc_csc_015_ImpactSpeed	0.0
acc_csc_015_CollisionEver	0.0

Criteria

Name	Result
acc_csc_015 - Safe Distance Consistency	
acc_csc_015 - Time To Collision	
acc_csc_015 - Comfort Deceleration Limit	
acc_csc_015 - Emergency Deceleration Bound	
acc_csc_015 - Jerk Limit	
acc_csc_015 - No Collision Distance	
acc_csc_015 - Collision Flag	
acc_csc_015 - Impact Speed	

1.16

Test # 1.16
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016

Characteristics

Name	Description
acc_csc_016_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_016_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_016_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_016_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_016_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_016_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_016_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_016_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_016_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_016_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_016_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_016_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_016_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_016_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_016_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_016_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_016_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_016_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_016_SafeDist	34.5021	35.0841	35.8106	45.9021	25.008
acc_csc_016_SafeDistViolated	0.0	1.0	1.0	1.0	0.0
acc_csc_016_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_016_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_016_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_016_ComfortAx	-0.00074048 3	-0.004	-0.004	-0.004	2.10225
acc_csc_016_ComfortAxOutOfBoundEver	0.0	1.0	1.0	1.0	0.0
acc_csc_016_EmergencyAx	-0.00074048	-0.004	-0.004	-0.004	2.10225

Name	# 1	# 2	# 3	# 4	# 5
	3				
acc_csc_016_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_016_Jerk	9.21858e-007	0.0	0.0	0.0	4
acc_csc_016_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_016_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_016_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_016_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_016_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_016_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_016 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_016 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_016 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_016 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_016 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_016 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_016 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_016 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_016 - Safe Distance Consistency	✓	⚡	⚡	⚡	✓
acc_csc_016 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_016 - Comfort Deceleration Limit	✓	⚡	⚡	⚡	✓
acc_csc_016 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_016 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_016 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_016 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_016 - Impact Speed	✓	✓	✓	✓	✓

1.16.1

Test # 1.16.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016 └ acc_csc_016_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_016
Description:	TestRun converted from acc_csc_016_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	58
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_016_142041.erg

Characteristics

Name	Value
acc_csc_016_ActualDist	999.0
acc_csc_016_SafeDist	34.50212889

Name	Value
acc_csc_016_SafeDistViolated	0.0
acc_csc_016_TTC	0.0
acc_csc_016_TTCWarnEver	0.0
acc_csc_016_TTCBadEver	0.0
acc_csc_016_ComfortAx	-0.0007404829719
acc_csc_016_ComfortAxOutOfBoundEver	0.0
acc_csc_016_EmergencyAx	-0.0007404829719
acc_csc_016_EmergencyAxOutOfBoundEver	0.0
acc_csc_016_Jerk	9.218581454e-007
acc_csc_016_JerkOverLimitEver	1.0
acc_csc_016_NoCollDist	999.0
acc_csc_016_NoCollDistViolatedEver	0.0
acc_csc_016_CollisionFlag	0.0
acc_csc_016_ImpactSpeed	0.0
acc_csc_016_CollisionEver	0.0

Criteria

Name	Result
acc_csc_016 - Safe Distance Consistency	✓
acc_csc_016 - Time To Collision	✓
acc_csc_016 - Comfort Deceleration Limit	✓
acc_csc_016 - Emergency Deceleration Bound	✓
acc_csc_016 - Jerk Limit	⚡
acc_csc_016 - No Collision Distance	✓
acc_csc_016 - Collision Flag	✓
acc_csc_016 - Impact Speed	✓

1.16.2

Test # 1.16.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016 └ acc_csc_016_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_016
Description:	TestRun converted from acc_csc_016_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_016_142054.erg

Characteristics

Name	Value
acc_csc_016_ActualDist	999.0
acc_csc_016_SafeDist	35.08409447

Name	Value
acc_csc_016_SafeDistViolated	1.0
acc_csc_016_TTC	0.0
acc_csc_016_TTCWarnEver	0.0
acc_csc_016_TTCBadEver	0.0
acc_csc_016_ComfortAx	-0.004
acc_csc_016_ComfortAxOutOfBoundEver	1.0
acc_csc_016_EmergencyAx	-0.004
acc_csc_016_EmergencyAxOutOfBoundEver	0.0
acc_csc_016_Jerk	0.0
acc_csc_016_JerkOverLimitEver	1.0
acc_csc_016_NoCollDist	999.0
acc_csc_016_NoCollDistViolatedEver	0.0
acc_csc_016_CollisionFlag	0.0
acc_csc_016_ImpactSpeed	0.0
acc_csc_016_CollisionEver	0.0

Criteria

Name	Result
acc_csc_016 - Safe Distance Consistency	
acc_csc_016 - Time To Collision	
acc_csc_016 - Comfort Deceleration Limit	
acc_csc_016 - Emergency Deceleration Bound	
acc_csc_016 - Jerk Limit	
acc_csc_016 - No Collision Distance	
acc_csc_016 - Collision Flag	
acc_csc_016 - Impact Speed	

1.16.3

Test # 1.16.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016 └ acc_csc_016_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_016
Description:	TestRun converted from acc_csc_016_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_016_142106.erg

Characteristics

Name	Value
acc_csc_016_ActualDist	999.0
acc_csc_016_SafeDist	35.81056568

Name	Value
acc_csc_016_SafeDistViolated	1.0
acc_csc_016_TTC	0.0
acc_csc_016_TTCWarnEver	0.0
acc_csc_016_TTCBadEver	0.0
acc_csc_016_ComfortAx	-0.004
acc_csc_016_ComfortAxOutOfBoundEver	1.0
acc_csc_016_EmergencyAx	-0.004
acc_csc_016_EmergencyAxOutOfBoundEver	0.0
acc_csc_016_Jerk	0.0
acc_csc_016_JerkOverLimitEver	1.0
acc_csc_016_NoCollDist	999.0
acc_csc_016_NoCollDistViolatedEver	0.0
acc_csc_016_CollisionFlag	0.0
acc_csc_016_ImpactSpeed	0.0
acc_csc_016_CollisionEver	0.0

Criteria

Name	Result
acc_csc_016 - Safe Distance Consistency	
acc_csc_016 - Time To Collision	
acc_csc_016 - Comfort Deceleration Limit	
acc_csc_016 - Emergency Deceleration Bound	
acc_csc_016 - Jerk Limit	
acc_csc_016 - No Collision Distance	
acc_csc_016 - Collision Flag	
acc_csc_016 - Impact Speed	

1.16.4

Test # 1.16.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016 └ acc_csc_016_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_016
Description:	TestRun converted from acc_csc_016_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	92
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_016_142118.erg

Characteristics

Name	Value
acc_csc_016_ActualDist	999.0
acc_csc_016_SafeDist	45.90206331

Name	Value
acc_csc_016_SafeDistViolated	1.0
acc_csc_016_TTC	0.0
acc_csc_016_TTCWarnEver	0.0
acc_csc_016_TTCBadEver	0.0
acc_csc_016_ComfortAx	-0.004
acc_csc_016_ComfortAxOutOfBoundEver	1.0
acc_csc_016_EmergencyAx	-0.004
acc_csc_016_EmergencyAxOutOfBoundEver	0.0
acc_csc_016_Jerk	0.0
acc_csc_016_JerkOverLimitEver	1.0
acc_csc_016_NoCollDist	999.0
acc_csc_016_NoCollDistViolatedEver	0.0
acc_csc_016_CollisionFlag	0.0
acc_csc_016_ImpactSpeed	0.0
acc_csc_016_CollisionEver	0.0

Criteria

Name	Result
acc_csc_016 - Safe Distance Consistency	
acc_csc_016 - Time To Collision	
acc_csc_016 - Comfort Deceleration Limit	
acc_csc_016 - Emergency Deceleration Bound	
acc_csc_016 - Jerk Limit	
acc_csc_016 - No Collision Distance	
acc_csc_016 - Collision Flag	
acc_csc_016 - Impact Speed	

1.16.5

Test # 1.16.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_016 └ acc_csc_016_ds005	 Error

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_016
Description:	TestRun converted from acc_csc_016_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	103
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

TestLog
Simulation ended with errors

Resultfile
Results not saved

Characteristics

Name	Value
acc_csc_016_ActualDist	999.0
acc_csc_016_SafeDist	25.0080423
acc_csc_016_SafeDistViolated	0.0
acc_csc_016_TTC	0.0
acc_csc_016_TTCWarnEver	0.0
acc_csc_016_TTCBadEver	0.0
acc_csc_016_ComfortAx	2.102250377
acc_csc_016_ComfortAxOutOfBoundEver	0.0
acc_csc_016_EmergencyAx	2.102250377
acc_csc_016_EmergencyAxOutOfBoundEver	0.0
acc_csc_016_Jerk	4
acc_csc_016_JerkOverLimitEver	1.0
acc_csc_016_NoCollDist	999.0
acc_csc_016_NoCollDistViolatedEver	0.0
acc_csc_016_CollisionFlag	0.0
acc_csc_016_ImpactSpeed	0.0
acc_csc_016_CollisionEver	0.0

Criteria

Name	Result
acc_csc_016 - Safe Distance Consistency	✓
acc_csc_016 - Time To Collision	✓
acc_csc_016 - Comfort Deceleration Limit	✓
acc_csc_016 - Emergency Deceleration Bound	✓
acc_csc_016 - Jerk Limit	⚡
acc_csc_016 - No Collision Distance	✓
acc_csc_016 - Collision Flag	✓
acc_csc_016 - Impact Speed	✓

1.17

Test # 1.17

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_017

Characteristics

Name	Description
acc_csc_017_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_017_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_017_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_017_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_017_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_017_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_017_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_017_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_017_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_017_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_017_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_017_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_017_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_017_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_017_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_017_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_017_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_017_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_017_SafeDist	34.502	34.502	15.0	45.4442	56.2093
acc_csc_017_SafeDistViolated	0.0	0.0	0.0	1.0	1.0
acc_csc_017_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_017_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_017_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_017_ComfortAx	-0.00070088 5	-0.00070103 6	2.8	-0.004	-0.004
acc_csc_017_ComfortAxOutOfBoundEver	0.0	0.0	0.0	1.0	1.0
acc_csc_017_EmergencyAx	-0.00070088	-0.00070103	2.8	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
	5	6			
acc_csc_017_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_017_Jerk	9.40855e-007	3.79745e-007	0.0	0.0	0.0
acc_csc_017_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_017_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_017_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_017_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_017_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_017_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_017 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_017 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_017 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_017 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_017 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_017 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_017 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_017 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_017 - Safe Distance Consistency	✓	✓	✓	✗	✗
acc_csc_017 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_017 - Comfort Deceleration Limit	✓	✓	✓	✗	✗
acc_csc_017 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_017 - Jerk Limit	✗	✗	✗	✗	✗
acc_csc_017 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_017 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_017 - Impact Speed	✓	✓	✓	✓	✓

1.17.1

Test # 1.17.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_017 └ acc_csc_017_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_017
Description:	TestRun converted from acc_csc_017_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	12
NValue	TVSpeed	8
NValue	TV_initPos	58
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_017_142138.erg

Characteristics

Name	Value
acc_csc_017_ActualDist	999.0
acc_csc_017_SafeDist	34.50201504

Name	Value
acc_csc_017_SafeDistViolated	0.0
acc_csc_017_TTC	0.0
acc_csc_017_TTCWarnEver	0.0
acc_csc_017_TTCBadEver	0.0
acc_csc_017_ComfortAx	-0.0007008851217
acc_csc_017_ComfortAxOutOfBoundEver	0.0
acc_csc_017_EmergencyAx	-0.0007008851217
acc_csc_017_EmergencyAxOutOfBoundEver	0.0
acc_csc_017_Jerk	9.408552159e-007
acc_csc_017_JerkOverLimitEver	1.0
acc_csc_017_NoCollDist	999.0
acc_csc_017_NoCollDistViolatedEver	0.0
acc_csc_017_CollisionFlag	0.0
acc_csc_017_ImpactSpeed	0.0
acc_csc_017_CollisionEver	0.0

Criteria

Name	Result
acc_csc_017 - Safe Distance Consistency	✓
acc_csc_017 - Time To Collision	✓
acc_csc_017 - Comfort Deceleration Limit	✓
acc_csc_017 - Emergency Deceleration Bound	✓
acc_csc_017 - Jerk Limit	⚡
acc_csc_017 - No Collision Distance	✓
acc_csc_017 - Collision Flag	✓
acc_csc_017 - Impact Speed	✓

1.17.2

Test # 1.17.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_017 └ acc_csc_017_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_017
Description:	TestRun converted from acc_csc_017_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	10
NValue	TV_initPos	65
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_017_142150.erg

Characteristics

Name	Value
acc_csc_017_ActualDist	999.0
acc_csc_017_SafeDist	34.50201548

Name	Value
acc_csc_017_SafeDistViolated	0.0
acc_csc_017_TTC	0.0
acc_csc_017_TTCWarnEver	0.0
acc_csc_017_TTCBadEver	0.0
acc_csc_017_ComfortAx	-0.0007010358556
acc_csc_017_ComfortAxOutOfBoundEver	0.0
acc_csc_017_EmergencyAx	-0.0007010358556
acc_csc_017_EmergencyAxOutOfBoundEver	0.0
acc_csc_017_Jerk	3.797453018e-007
acc_csc_017_JerkOverLimitEver	1.0
acc_csc_017_NoCollDist	999.0
acc_csc_017_NoCollDistViolatedEver	0.0
acc_csc_017_CollisionFlag	0.0
acc_csc_017_ImpactSpeed	0.0
acc_csc_017_CollisionEver	0.0

Criteria

Name	Result
acc_csc_017 - Safe Distance Consistency	✓
acc_csc_017 - Time To Collision	✓
acc_csc_017 - Comfort Deceleration Limit	✓
acc_csc_017 - Emergency Deceleration Bound	✓
acc_csc_017 - Jerk Limit	⚡
acc_csc_017 - No Collision Distance	✓
acc_csc_017 - Collision Flag	✓
acc_csc_017 - Impact Speed	✓

1.17.3

Test # 1.17.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_017 └ acc_csc_017_ds003	 Error

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_017
Description:	TestRun converted from acc_csc_017_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	14
NValue	TV_initPos	80
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

TestLog
Simulation ended with errors

Resultfile
Results not saved

Characteristics

Name	Value
acc_csc_017_ActualDist	999.0
acc_csc_017_SafeDist	15.0
acc_csc_017_SafeDistViolated	0.0
acc_csc_017_TTC	0.0
acc_csc_017_TTCWarnEver	0.0
acc_csc_017_TTCBadEver	0.0
acc_csc_017_ComfortAx	2.8
acc_csc_017_ComfortAxOutOfBoundEver	0.0
acc_csc_017_EmergencyAx	2.8
acc_csc_017_EmergencyAxOutOfBoundEver	0.0
acc_csc_017_Jerk	0.0
acc_csc_017_JerkOverLimitEver	1.0
acc_csc_017_NoCollDist	999.0
acc_csc_017_NoCollDistViolatedEver	0.0
acc_csc_017_CollisionFlag	0.0
acc_csc_017_ImpactSpeed	0.0
acc_csc_017_CollisionEver	0.0

Criteria

Name	Result
acc_csc_017 - Safe Distance Consistency	✓
acc_csc_017 - Time To Collision	✓
acc_csc_017 - Comfort Deceleration Limit	✓
acc_csc_017 - Emergency Deceleration Bound	✓
acc_csc_017 - Jerk Limit	⚡
acc_csc_017 - No Collision Distance	✓
acc_csc_017 - Collision Flag	✓
acc_csc_017 - Impact Speed	✓

1.17.4

Test # 1.17.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_017 └ acc_csc_017_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_017
Description:	TestRun converted from acc_csc_017_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	18
NValue	TV_initPos	92
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_017_142220.erg

Characteristics

Name	Value
acc_csc_017_ActualDist	999.0
acc_csc_017_SafeDist	45.44415994

Name	Value
acc_csc_017_SafeDistViolated	1.0
acc_csc_017_TTC	0.0
acc_csc_017_TTCWarnEver	0.0
acc_csc_017_TTCBadEver	0.0
acc_csc_017_ComfortAx	-0.004
acc_csc_017_ComfortAxOutOfBoundEver	1.0
acc_csc_017_EmergencyAx	-0.004
acc_csc_017_EmergencyAxOutOfBoundEver	0.0
acc_csc_017_Jerk	0.0
acc_csc_017_JerkOverLimitEver	1.0
acc_csc_017_NoCollDist	999.0
acc_csc_017_NoCollDistViolatedEver	0.0
acc_csc_017_CollisionFlag	0.0
acc_csc_017_ImpactSpeed	0.0
acc_csc_017_CollisionEver	0.0

Criteria

Name	Result
acc_csc_017 - Safe Distance Consistency	
acc_csc_017 - Time To Collision	
acc_csc_017 - Comfort Deceleration Limit	
acc_csc_017 - Emergency Deceleration Bound	
acc_csc_017 - Jerk Limit	
acc_csc_017 - No Collision Distance	
acc_csc_017 - Collision Flag	
acc_csc_017 - Impact Speed	

1.17.5

Test # 1.17.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_017 └ acc_csc_017_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_017
Description:	TestRun converted from acc_csc_017_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	22
NValue	TV_initPos	103
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_017_142316.erg

Characteristics

Name	Value
acc_csc_017_ActualDist	999.0
acc_csc_017_SafeDist	56.20934465

Name	Value
acc_csc_017_SafeDistViolated	1.0
acc_csc_017_TTC	0.0
acc_csc_017_TTCWarnEver	0.0
acc_csc_017_TTCBadEver	0.0
acc_csc_017_ComfortAx	-0.004
acc_csc_017_ComfortAxOutOfBoundEver	1.0
acc_csc_017_EmergencyAx	-0.004
acc_csc_017_EmergencyAxOutOfBoundEver	0.0
acc_csc_017_Jerk	0.0
acc_csc_017_JerkOverLimitEver	1.0
acc_csc_017_NoCollDist	999.0
acc_csc_017_NoCollDistViolatedEver	0.0
acc_csc_017_CollisionFlag	0.0
acc_csc_017_ImpactSpeed	0.0
acc_csc_017_CollisionEver	0.0

Criteria

Name	Result
acc_csc_017 - Safe Distance Consistency	
acc_csc_017 - Time To Collision	
acc_csc_017 - Comfort Deceleration Limit	
acc_csc_017 - Emergency Deceleration Bound	
acc_csc_017 - Jerk Limit	
acc_csc_017 - No Collision Distance	
acc_csc_017 - Collision Flag	
acc_csc_017 - Impact Speed	

1.18

Test # 1.18
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018

Characteristics

Name	Description
acc_csc_018_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_018_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_018_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_018_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_018_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_018_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_018_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_018_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_018_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_018_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_018_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_018_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_018_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_018_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_018_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_018_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_018_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_018_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_018_SafeDist	34.5021	34.5021	15.0	52.9213	26.4248
acc_csc_018_SafeDistViolated	0.0	0.0	0.0	0.0	0.0
acc_csc_018_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_018_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_018_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_018_ComfortAx	-0.00074432 7	-0.00073928 3	2.8	-0.004	2.8
acc_csc_018_ComfortAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_018_EmergencyAx	-0.00074432	-0.00073928	2.8	-0.004	2.8

Name	# 1	# 2	# 3	# 4	# 5
	7	3			
acc_csc_018_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_018_Jerk	4.47717e-006	1.50979e-006	0.0	0.0	0.0
acc_csc_018_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_018_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_018_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_018_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_018_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_018_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_018 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_018 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_018 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_018 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_018 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_018 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_018 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_018 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_018 - Safe Distance Consistency	✓	✓	✓	✓	✓
acc_csc_018 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_018 - Comfort Deceleration Limit	✓	✓	✓	✓	✓
acc_csc_018 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_018 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_018 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_018 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_018 - Impact Speed	✓	✓	✓	✓	✓

1.18.1

Test # 1.18.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018 └ acc_csc_018_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_018
Description:	TestRun converted from acc_csc_018_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TVSpeed	0
NValue	TV_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_018_142413.erg

Characteristics

Name	Value
acc_csc_018_ActualDist	999.0
acc_csc_018_SafeDist	34.50213994

Name	Value
acc_csc_018_SafeDistViolated	0.0
acc_csc_018_TTC	0.0
acc_csc_018_TTCWarnEver	0.0
acc_csc_018_TTCBadEver	0.0
acc_csc_018_ComfortAx	-0.0007443274915
acc_csc_018_ComfortAxOutOfBoundEver	0.0
acc_csc_018_EmergencyAx	-0.0007443274915
acc_csc_018_EmergencyAxOutOfBoundEver	0.0
acc_csc_018_Jerk	4.477173832e-006
acc_csc_018_JerkOverLimitEver	1.0
acc_csc_018_NoCollDist	999.0
acc_csc_018_NoCollDistViolatedEver	0.0
acc_csc_018_CollisionFlag	0.0
acc_csc_018_ImpactSpeed	0.0
acc_csc_018_CollisionEver	0.0

Criteria

Name	Result
acc_csc_018 - Safe Distance Consistency	✓
acc_csc_018 - Time To Collision	✓
acc_csc_018 - Comfort Deceleration Limit	✓
acc_csc_018 - Emergency Deceleration Bound	✓
acc_csc_018 - Jerk Limit	⚡
acc_csc_018 - No Collision Distance	✓
acc_csc_018 - Collision Flag	✓
acc_csc_018 - Impact Speed	✓

1.18.2

Test # 1.18.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018 └ acc_csc_018_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_018
Description:	TestRun converted from acc_csc_018_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	0
NValue	TV_initPos	135
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_018_142432.erg

Characteristics

Name	Value
acc_csc_018_ActualDist	999.0
acc_csc_018_SafeDist	34.50212544

Name	Value
acc_csc_018_SafeDistViolated	0.0
acc_csc_018_TTC	0.0
acc_csc_018_TTCWarnEver	0.0
acc_csc_018_TTCBadEver	0.0
acc_csc_018_ComfortAx	-0.0007392827526
acc_csc_018_ComfortAxOutOfBoundEver	0.0
acc_csc_018_EmergencyAx	-0.0007392827526
acc_csc_018_EmergencyAxOutOfBoundEver	0.0
acc_csc_018_Jerk	1.509789627e-006
acc_csc_018_JerkOverLimitEver	1.0
acc_csc_018_NoCollDist	999.0
acc_csc_018_NoCollDistViolatedEver	0.0
acc_csc_018_CollisionFlag	0.0
acc_csc_018_ImpactSpeed	0.0
acc_csc_018_CollisionEver	0.0

Criteria

Name	Result
acc_csc_018 - Safe Distance Consistency	✓
acc_csc_018 - Time To Collision	✓
acc_csc_018 - Comfort Deceleration Limit	✓
acc_csc_018 - Emergency Deceleration Bound	✓
acc_csc_018 - Jerk Limit	⚡
acc_csc_018 - No Collision Distance	✓
acc_csc_018 - Collision Flag	✓
acc_csc_018 - Impact Speed	✓

1.18.3

Test # 1.18.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018 └ acc_csc_018_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_018
Description:	TestRun converted from acc_csc_018_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	0
NValue	TV_initPos	170
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_018_142444.erg

Characteristics

Name	Value
acc_csc_018_ActualDist	999.0
acc_csc_018_SafeDist	15.0

Name	Value
acc_csc_018_SafeDistViolated	0.0
acc_csc_018_TTC	0.0
acc_csc_018_TTCWarnEver	0.0
acc_csc_018_TTCBadEver	0.0
acc_csc_018_ComfortAx	2.8
acc_csc_018_ComfortAxOutOfBoundEver	0.0
acc_csc_018_EmergencyAx	2.8
acc_csc_018_EmergencyAxOutOfBoundEver	0.0
acc_csc_018_Jerk	0.0
acc_csc_018_JerkOverLimitEver	1.0
acc_csc_018_NoCollDist	999.0
acc_csc_018_NoCollDistViolatedEver	0.0
acc_csc_018_CollisionFlag	0.0
acc_csc_018_ImpactSpeed	0.0
acc_csc_018_CollisionEver	0.0

Criteria

Name	Result
acc_csc_018 - Safe Distance Consistency	✓
acc_csc_018 - Time To Collision	✓
acc_csc_018 - Comfort Deceleration Limit	✓
acc_csc_018 - Emergency Deceleration Bound	✓
acc_csc_018 - Jerk Limit	⚡
acc_csc_018 - No Collision Distance	✓
acc_csc_018 - Collision Flag	✓
acc_csc_018 - Impact Speed	✓

1.18.4

Test # 1.18.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018 └ acc_csc_018_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_018
Description:	TestRun converted from acc_csc_018_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	0
NValue	TV_initPos	215
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_018_142456.erg

Characteristics

Name	Value
acc_csc_018_ActualDist	999.0
acc_csc_018_SafeDist	52.92131365

Name	Value
acc_csc_018_SafeDistViolated	0.0
acc_csc_018_TTC	0.0
acc_csc_018_TTCWarnEver	0.0
acc_csc_018_TTCBadEver	0.0
acc_csc_018_ComfortAx	-0.004
acc_csc_018_ComfortAxOutOfBoundEver	0.0
acc_csc_018_EmergencyAx	-0.004
acc_csc_018_EmergencyAxOutOfBoundEver	0.0
acc_csc_018_Jerk	0.0
acc_csc_018_JerkOverLimitEver	1.0
acc_csc_018_NoCollDist	999.0
acc_csc_018_NoCollDistViolatedEver	0.0
acc_csc_018_CollisionFlag	0.0
acc_csc_018_ImpactSpeed	0.0
acc_csc_018_CollisionEver	0.0

Criteria

Name	Result
acc_csc_018 - Safe Distance Consistency	✓
acc_csc_018 - Time To Collision	✓
acc_csc_018 - Comfort Deceleration Limit	✓
acc_csc_018 - Emergency Deceleration Bound	✓
acc_csc_018 - Jerk Limit	⚡
acc_csc_018 - No Collision Distance	✓
acc_csc_018 - Collision Flag	✓
acc_csc_018 - Impact Speed	✓

1.18.5

Test # 1.18.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_018 └ acc_csc_018_ds005	 Error

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_018
Description:	TestRun converted from acc_csc_018_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange 1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	0
NValue	TV_initPos	245
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

TestLog
Simulation ended with errors

Resultfile
Results not saved

Characteristics

Name	Value
acc_csc_018_ActualDist	999.0
acc_csc_018_SafeDist	26.42484694
acc_csc_018_SafeDistViolated	0.0
acc_csc_018_TTC	0.0
acc_csc_018_TTCWarnEver	0.0
acc_csc_018_TTCBadEver	0.0
acc_csc_018_ComfortAx	2.8
acc_csc_018_ComfortAxOutOfBoundEver	0.0
acc_csc_018_EmergencyAx	2.8
acc_csc_018_EmergencyAxOutOfBoundEver	0.0
acc_csc_018_Jerk	0.0
acc_csc_018_JerkOverLimitEver	1.0
acc_csc_018_NoCollDist	999.0
acc_csc_018_NoCollDistViolatedEver	0.0
acc_csc_018_CollisionFlag	0.0
acc_csc_018_ImpactSpeed	0.0
acc_csc_018_CollisionEver	0.0

Criteria

Name	Result
acc_csc_018 - Safe Distance Consistency	✓
acc_csc_018 - Time To Collision	✓
acc_csc_018 - Comfort Deceleration Limit	✓
acc_csc_018 - Emergency Deceleration Bound	✓
acc_csc_018 - Jerk Limit	⚡
acc_csc_018 - No Collision Distance	✓
acc_csc_018 - Collision Flag	✓
acc_csc_018 - Impact Speed	✓

1.19

Test # 1.19

longitudinal_feature / ACC

└ OSC_Imported/longitudinal_feature/ACC/acc_csc_019

Characteristics

Name	Description
acc_csc_019_ActualDist	Actual distance to lead (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_019_SafeDist	Reference safe distance (signal=FMU.CM_ACCController_V17.Out.Debug.SafeDistance)
acc_csc_019_SafeDistViolated	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment ActualDist<SafeDist while actively following (gate==1); stays 1 for the rest of the run even if distance recovers.
acc_csc_019_TTC	Time-to-collision (signal=AccelCtrl.ACC.Time2Collision)
acc_csc_019_TTCWarnEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the warn zone [3.5,11)s.
acc_csc_019_TTCBadEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment TTC ever enters the bad zone (0,3.5)s.
acc_csc_019_ComfortAx	Comfort Deceleration Limit (signal=AccelCtrl.DesiredAx)
acc_csc_019_ComfortAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Comfort Deceleration Limit ever goes out of bound (min=-3, max=2.8).
acc_csc_019_EmergencyAx	Emergency Deceleration Bound (signal=AccelCtrl.DesiredAx)
acc_csc_019_EmergencyAxOutOfBoundEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment Emergency Deceleration Bound ever goes out of bound (min=-6).
acc_csc_019_Jerk	Jerk = d(DesiredAx)/dt , base signal=AccelCtrl.DesiredAx
acc_csc_019_JerkOverLimitEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment jerk ever exceeds 4 m/s ³ .
acc_csc_019_NoCollDist	Distance to nearest lead object (signal=FMU.CM_ACCController_V17.Out.Debug.Target.DistX)
acc_csc_019_NoCollDistViolatedEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment distance ever drops below 0m.
acc_csc_019_CollisionFlag	Collision flag derived from FMU.CM_ACCController_V17.Out.Debug.Target.DistX <= 0 (nearest lead object); instantaneous, used as the latch() trigger for ImpactSpeed below.
acc_csc_019_ImpactSpeed	Ego speed latched at moment of first collision (nearest lead object)
acc_csc_019_CollisionEver	[EVALUATED OVER ENTIRE TEST RUN DURATION] Latches to 1 the moment a collision ever occurs (nearest lead object), even if the vehicles separate again before the run ends.

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_019_ActualDist	999.0	999.0	999.0	999.0	999.0
acc_csc_019_SafeDist	34.502	34.502	15.0	52.2517	63.5211
acc_csc_019_SafeDistViolated	0.0	0.0	0.0	0.0	0.0
acc_csc_019_TTC	0.0	0.0	0.0	0.0	0.0
acc_csc_019_TTCWarnEver	0.0	0.0	0.0	0.0	0.0
acc_csc_019_TTCBadEver	0.0	0.0	0.0	0.0	0.0
acc_csc_019_ComfortAx	-0.00070334 9	-0.00070090 8	2.8	-0.004	-0.004
acc_csc_019_ComfortAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_019_EmergencyAx	-0.00070334	-0.00070090	2.8	-0.004	-0.004

Name	# 1	# 2	# 3	# 4	# 5
	9	8			
acc_csc_019_EmergencyAxOutOfBoundEver	0.0	0.0	0.0	0.0	0.0
acc_csc_019_Jerk	2.61421e-006	5.43575e-007	0.0	0.0	0.0
acc_csc_019_JerkOverLimitEver	1.0	1.0	1.0	1.0	1.0
acc_csc_019_NoCollDist	999.0	999.0	999.0	999.0	999.0
acc_csc_019_NoCollDistViolatedEver	0.0	0.0	0.0	0.0	0.0
acc_csc_019_CollisionFlag	0.0	0.0	0.0	0.0	0.0
acc_csc_019_ImpactSpeed	0.0	0.0	0.0	0.0	0.0
acc_csc_019_CollisionEver	0.0	0.0	0.0	0.0	0.0

Criteria

Name	Description
acc_csc_019 - Safe Distance Consistency	Good if SafeDist was never violated while actively following throughout the run. Bad if it was violated at any point.
acc_csc_019 - Time To Collision	Good if TTC never entered the warn/bad zone while a valid target existed throughout the run. Warn if it ever entered [3.5,11)s. Bad if it ever entered (0,3.5)s.
acc_csc_019 - Comfort Deceleration Limit	Good if Comfort Deceleration Limit never went out of bound (min=-3, max=2.8) throughout the run.
acc_csc_019 - Emergency Deceleration Bound	Good if Emergency Deceleration Bound never went out of bound (min=-6) throughout the run.
acc_csc_019 - Jerk Limit	Good if jerk never exceeded 4 m/s ³ throughout the run.
acc_csc_019 - No Collision Distance	Good if distance never dropped below 0m throughout the run.
acc_csc_019 - Collision Flag	Good if no collision ever occurred (nearest lead object) throughout the run.
acc_csc_019 - Impact Speed	Good if no collision ever occurred, or impact speed = 0; Warn (0,5) m/s; Bad >= 5 m/s

Name	# 1	# 2	# 3	# 4	# 5
acc_csc_019 - Safe Distance Consistency	✓	✓	✓	✓	✓
acc_csc_019 - Time To Collision	✓	✓	✓	✓	✓
acc_csc_019 - Comfort Deceleration Limit	✓	✓	✓	✓	✓
acc_csc_019 - Emergency Deceleration Bound	✓	✓	✓	✓	✓
acc_csc_019 - Jerk Limit	⚡	⚡	⚡	⚡	⚡
acc_csc_019 - No Collision Distance	✓	✓	✓	✓	✓
acc_csc_019 - Collision Flag	✓	✓	✓	✓	✓
acc_csc_019 - Impact Speed	✓	✓	✓	✓	✓

1.19.1

Test # 1.19.1	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_019 └ acc_csc_019_ds001	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_019
Description:	TestRun converted from acc_csc_019_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	10
NValue	TVSpeed	0
NValue	TV_initPos	100
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_019_142516.erg

Characteristics

Name	Value
acc_csc_019_ActualDist	999.0
acc_csc_019_SafeDist	34.50202213

Name	Value
acc_csc_019_SafeDistViolated	0.0
acc_csc_019_TTC	0.0
acc_csc_019_TTCWarnEver	0.0
acc_csc_019_TTCBadEver	0.0
acc_csc_019_ComfortAx	-0.0007033491083
acc_csc_019_ComfortAxOutOfBoundEver	0.0
acc_csc_019_EmergencyAx	-0.0007033491083
acc_csc_019_EmergencyAxOutOfBoundEver	0.0
acc_csc_019_Jerk	2.614213201e-006
acc_csc_019_JerkOverLimitEver	1.0
acc_csc_019_NoCollDist	999.0
acc_csc_019_NoCollDistViolatedEver	0.0
acc_csc_019_CollisionFlag	0.0
acc_csc_019_ImpactSpeed	0.0
acc_csc_019_CollisionEver	0.0

Criteria

Name	Result
acc_csc_019 - Safe Distance Consistency	✓
acc_csc_019 - Time To Collision	✓
acc_csc_019 - Comfort Deceleration Limit	✓
acc_csc_019 - Emergency Deceleration Bound	✓
acc_csc_019 - Jerk Limit	⚡
acc_csc_019 - No Collision Distance	✓
acc_csc_019 - Collision Flag	✓
acc_csc_019 - Impact Speed	✓

1.19.2

Test # 1.19.2	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_019 └ acc_csc_019_ds002	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_019
Description:	TestRun converted from acc_csc_019_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	15
NValue	TVSpeed	0
NValue	TV_initPos	135
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_019_142528.erg

Characteristics

Name	Value
acc_csc_019_ActualDist	999.0
acc_csc_019_SafeDist	34.50201511

Name	Value
acc_csc_019_SafeDistViolated	0.0
acc_csc_019_TTC	0.0
acc_csc_019_TTCWarnEver	0.0
acc_csc_019_TTCBadEver	0.0
acc_csc_019_ComfortAx	-0.0007009084933
acc_csc_019_ComfortAxOutOfBoundEver	0.0
acc_csc_019_EmergencyAx	-0.0007009084933
acc_csc_019_EmergencyAxOutOfBoundEver	0.0
acc_csc_019_Jerk	5.435751404e-007
acc_csc_019_JerkOverLimitEver	1.0
acc_csc_019_NoCollDist	999.0
acc_csc_019_NoCollDistViolatedEver	0.0
acc_csc_019_CollisionFlag	0.0
acc_csc_019_ImpactSpeed	0.0
acc_csc_019_CollisionEver	0.0

Criteria

Name	Result
acc_csc_019 - Safe Distance Consistency	✓
acc_csc_019 - Time To Collision	✓
acc_csc_019 - Comfort Deceleration Limit	✓
acc_csc_019 - Emergency Deceleration Bound	✓
acc_csc_019 - Jerk Limit	⚡
acc_csc_019 - No Collision Distance	✓
acc_csc_019 - Collision Flag	✓
acc_csc_019 - Impact Speed	✓

1.19.3

Test # 1.19.3	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_019 └ acc_csc_019_ds003	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_019
Description:	TestRun converted from acc_csc_019_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	20
NValue	TVSpeed	0
NValue	TV_initPos	170
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_019_142540.erg

Characteristics

Name	Value
acc_csc_019_ActualDist	999.0
acc_csc_019_SafeDist	15.0

Name	Value
acc_csc_019_SafeDistViolated	0.0
acc_csc_019_TTC	0.0
acc_csc_019_TTCWarnEver	0.0
acc_csc_019_TTCBadEver	0.0
acc_csc_019_ComfortAx	2.8
acc_csc_019_ComfortAxOutOfBoundEver	0.0
acc_csc_019_EmergencyAx	2.8
acc_csc_019_EmergencyAxOutOfBoundEver	0.0
acc_csc_019_Jerk	0.0
acc_csc_019_JerkOverLimitEver	1.0
acc_csc_019_NoCollDist	999.0
acc_csc_019_NoCollDistViolatedEver	0.0
acc_csc_019_CollisionFlag	0.0
acc_csc_019_ImpactSpeed	0.0
acc_csc_019_CollisionEver	0.0

Criteria

Name	Result
acc_csc_019 - Safe Distance Consistency	✓
acc_csc_019 - Time To Collision	✓
acc_csc_019 - Comfort Deceleration Limit	✓
acc_csc_019 - Emergency Deceleration Bound	✓
acc_csc_019 - Jerk Limit	⚡
acc_csc_019 - No Collision Distance	✓
acc_csc_019 - Collision Flag	✓
acc_csc_019 - Impact Speed	✓

1.19.4

Test # 1.19.4	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_019 └ acc_csc_019_ds004	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_019
Description:	TestRun converted from acc_csc_019_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	25
NValue	TVSpeed	0
NValue	TV_initPos	215
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_019_142552.erg

Characteristics

Name	Value
acc_csc_019_ActualDist	999.0
acc_csc_019_SafeDist	52.25167099

Name	Value
acc_csc_019_SafeDistViolated	0.0
acc_csc_019_TTC	0.0
acc_csc_019_TTCWarnEver	0.0
acc_csc_019_TTCBadEver	0.0
acc_csc_019_ComfortAx	-0.004
acc_csc_019_ComfortAxOutOfBoundEver	0.0
acc_csc_019_EmergencyAx	-0.004
acc_csc_019_EmergencyAxOutOfBoundEver	0.0
acc_csc_019_Jerk	0.0
acc_csc_019_JerkOverLimitEver	1.0
acc_csc_019_NoCollDist	999.0
acc_csc_019_NoCollDistViolatedEver	0.0
acc_csc_019_CollisionFlag	0.0
acc_csc_019_ImpactSpeed	0.0
acc_csc_019_CollisionEver	0.0

Criteria

Name	Result
acc_csc_019 - Safe Distance Consistency	✓
acc_csc_019 - Time To Collision	✓
acc_csc_019 - Comfort Deceleration Limit	✓
acc_csc_019 - Emergency Deceleration Bound	✓
acc_csc_019 - Jerk Limit	⚡
acc_csc_019 - No Collision Distance	✓
acc_csc_019 - Collision Flag	✓
acc_csc_019 - Impact Speed	✓

1.19.5

Test # 1.19.5	Result
longitudinal_feature / ACC └ OSC_Imported/longitudinal_feature/ACC/acc_csc_019 └ acc_csc_019_ds005	 Failed

General Information

Test Run	
Name:	OSC_Imported/longitudinal_feature/ACC/acc_csc_019
Description:	TestRun converted from acc_csc_019_001.xosc

Vehicle	
Name:	TeslaY.ADAS_ACC
Description:	Typical, unvalidated data for passenger car with Electrical Powertrain Tire: RT 255/35 R20

Tires Vehicle	
Tire 0:	Examples/IPG_195_65R15
Tire 1:	Examples/IPG_195_65R15
Tire 2:	Examples/IPG_195_65R15
Tire 3:	Examples/IPG_195_65R15

Maneuvers

Note: Only executed maneuver steps are listed

No	Start	Dur	Long	Lat	Label/Description
0:0	0.0			LaneChange -1 0 offset 0.000 linear	Ego_cutout_action
1:0	0.0	10.00 0	VelTransition 15.000 linear		Ego_maintain_speed

Active Settings

Type	Name	Value
NValue	EgoSpeed	30
NValue	TVSpeed	0
NValue	TV_initPos	245
KValue	TestRun:Tire.0	Examples/IPG_195_65R15
KValue	TestRun:Tire.1	Examples/IPG_195_65R15
KValue	TestRun:Tire.2	Examples/IPG_195_65R15
KValue	TestRun:Tire.3	Examples/IPG_195_65R15
KValue	TestRun:Vehicle	TeslaY.ADAS_ACC

Resultfile
OSC_Imported_longitudinal_feature_ACC_acc_csc_019_142604.erg

Characteristics

Name	Value
acc_csc_019_ActualDist	999.0
acc_csc_019_SafeDist	63.52111545

Name	Value
acc_csc_019_SafeDistViolated	0.0
acc_csc_019_TTC	0.0
acc_csc_019_TTCWarnEver	0.0
acc_csc_019_TTCBadEver	0.0
acc_csc_019_ComfortAx	-0.004
acc_csc_019_ComfortAxOutOfBoundEver	0.0
acc_csc_019_EmergencyAx	-0.004
acc_csc_019_EmergencyAxOutOfBoundEver	0.0
acc_csc_019_Jerk	0.0
acc_csc_019_JerkOverLimitEver	1.0
acc_csc_019_NoCollDist	999.0
acc_csc_019_NoCollDistViolatedEver	0.0
acc_csc_019_CollisionFlag	0.0
acc_csc_019_ImpactSpeed	0.0
acc_csc_019_CollisionEver	0.0

Criteria

Name	Result
acc_csc_019 - Safe Distance Consistency	✓
acc_csc_019 - Time To Collision	✓
acc_csc_019 - Comfort Deceleration Limit	✓
acc_csc_019 - Emergency Deceleration Bound	✓
acc_csc_019 - Jerk Limit	⚡
acc_csc_019 - No Collision Distance	✓
acc_csc_019 - Collision Flag	✓
acc_csc_019 - Impact Speed	✓