

VAC-U-MAX

37 Rutgers Street Belleville, NJ 07109

Tel: 973-759-4600 * 973-759-6449 E-mail: info@vac-u-max.com * www.vac-u-max.com

MDL55, Four Jet Venturi, Dry



STANDARD EQUIPMENT

- * Vacuum power head with:
 - Four venturi power unit
 - Noise muffler and guard for sound levels below 85 DBA
 - Manual high pressure air control valve
 - Twin adjustable orifice assemblies for vacuum control 8" Hg. - 16" Hg.
 - 3" Material inlet
 - Internal Dust Filter
 - Carbon steel construction with blue powder coat finish.
- * Collection Container: (Supplied separately, see Optional Equipment)
Cover unit fits any minimum 16 gauge, 55 gallon steel drum

TECHNICAL DATA

*** Four venturi power head**

- | | |
|-----------------------------|---------------------------------|
| - Maximum suction | 16" Hg. (208" H ₂ O) |
| - Maximum air flow | 400 SCFM |
| - Suction connection | 3" |
| - Air operated, requires | 140 SCFM @ 60 PSIG |
| - Compressed air connection | 1" NPT (female) |
| - Noise Level | 84 DBA @ 6" Hg. |
| - Dimension | 24" diameter |

PRICE: 55M-031

PRICE: 55M-032

Carbon Steel

Stainless Steel