

VAC-U-MAX

37 Rutgers Street Belleville, NJ 07109

Tel: 973-759-4600 Fax: 973-759-6449

E-mail: info@vac-u-max.com www.vac-u-max.com

Model TK Liquid Recovery/ Transfer Tank Kit Unit



STANDARD EQUIPMENT:

Vacuum power head with:

- Single venturi power unit
- Noise muffler and guard for sound levels below 80 DBA
- Manual HP air control valve
- Adjustable orifice assembly for vacuum control 8" Hg - 16" Hg.
- Gasketed flange for insertion in drum vent
- Material inlet elbow
- AutoVac liquid cutoff

**Unique design results in 99% filled drums.
Fewer drums = Lower shipping cost!!!**

TECHNICAL DATA:

* Single venturi power unit

- Maximum suction power 16" Hg. (208" H₂O)
- Maximum air flow 100 SCFM
- Suction connection 1 1/2" or 2.0"
- Air operated, requires 35 SCFM @ 60 PSI compressed air
- Compressed air connection 1/2" NPT (female)
- Noise Level 79 DBA @ 6" Hg.
- Weight 36 lbs.

Model #	Inlet Size	Material of Construction	Finish
TK-01	1.5"	CARBON STEEL	POWDER COAT
TK-02	2.0"	CARBON STEEL	POWDER COAT
TK-05	1.5"	STAINLESS STEEL	BEAD BLAST
TK-06	2.0"	STAINLESS STEEL	BEAD BLAST

VAC-U-MAX

37 Rutgers Street Belleville, NJ 07109

Tel: 973-759-4600 Fax: 973-759-6449

E-mail: info@vac-u-max.com www.vac-u-max.com

Model TK Liquid Recovery/ Transfer Tank Kit Unit



PERFECT FOR:

- Parts washers
- Machine tool sumps
- Drum to drum transfer
- Sludge removal from finishing tanks
- Ink wells on printing presses
- Liquid spill cleaning including flammable liquids
- Hazardous liquids
- Spill kits
- Hydraulic fluids
- Transformer oil
- Wet dust collector sumps

For use with 55 gallon (minimum 18 gauge) steel close top drums. Shown above an optional VAC-U-MAX 55 gallon close top drum.



Easily fits the .75" opening on close top drum.



Equipped with a 1.5" or 2.0" inlet designed to fit a 2"npt bung on close top drum.