

37 Rutgers Street Belleville, NJ 07109
Tel: 973-759-4600 Fax: 973-759-6449
E-mail: info@vac-u-max.com www.vac-u-max.com

Model 1041-8.5HP Central Vacuum System



- Extra-large spunbond polyester cartridge filter with 50 square feet of filter area. Media rated 99.9% @ 1micron particle size.
- Convenient manual push-button pulse-jet filter cleaning. Includes air reservoir, pressure regulator / filter / gauge package.
- Flexible design allows either drum dolly or skid under the collection container. Also allows 180-degree access for forklift or operator to remove the collection drum.
- Collection system includes a 55-gallon steel drum with heavy-duty drum dolly with (4) 4" swivel casters.
- No discharge valve or cone section! No discharge problems!
- Unique lifting frame with hydraulic jack mechanism to raise / lower filter housing to remove collection container.
- Structural steel floor-standing frame with integral mounting for vacuum producer.
- Quiet 8.5HP continuous-duty TEFC motor, 230V or 460V, 3-phase, directly-coupled to impeller on vacuum producer. No belts or gears to maintain.
- Direct-drive aluminum oil-free impeller in aluminum housing with outboard bearings for higher vacuum performance.
- Vacuum Relief Valve

Performance:

Maximum vacuum: 8" Hg (108 " waterlift)

Maximum airflow: 390 CFM

Inlet Size: 3.0" Camlock adaptor with hose coupler for 3" ID hose

Footprint: 65" long x 35" wide x 70" tall (with 55-gallon collection container)

Weight: 500 lbs

WWW.VAC-U-MAX.COM