

	VAC-U-MAX 40008 / 40012	HAFCO VAC HV-30-2010X / HV-55-2010X or HAFCO VAC HV-30-1510X / HV-55-1510X	HAFCO VAC HV-30-2060X / HV-55-2060X or HAFCO VAC HV-30-1560X / HV-55-1560X	ANNUAL Cost Benefits with VAC-U-MAX
COMPRESSED AIR (CA) SUPPLY				
Minimum air consumption (CFM @ PSIG)	35 @ 60	100 @ 90	60 @ 100	
Recommended CA hose size	1/2"	3/4"	3/4"	
Approximate Compressor HP @ 4CFM/BHP	9 BHP	25 BHP	15 BHP	
Annual Cost of CA @ 10 hours / week @ \$0.50 per 1000SCFM	\$546.00	\$1,560.00	\$936.00	\$1,014.00
GENERAL				
Inlet Size	1.5"	2010X: 2" // 1510X: 1.5"	2010X: 2" // 1510X: 1.5"	
Inlet Construction	304SS Anti-Sparking	Stat-Con Plastic	Stat-Con Plastic	
Cover weight				
Noise Level		92 dBA @ 3ft	88dBA @ 3ft	
Country of Origin / Assembly	USA / USA	China & India / USA	China & India / USA	
FILTER / FILTRATION				
Filter Media	PTFE (Teflon-coated)	HEPA cartridge with cloth bag overwrap	HEPA cartridge with cloth bag overwrap	
Static-conductive Filter	Yes	No	No	
Filter Cleaning Method (by operator)	Manual Pulse-Jet	NONE, and No instructions in O&M Manual Outer Cloth Bag only, NOT HEPA	NONE, and No instructions in O&M Manual Outer Cloth Bag only, NOT HEPA	\$500.00
Is Filter Media Washable?	Yes			
Est'd Annual Filter Costs	\$294.00 (one dust filter) or less	\$1,300 (six HEPA's) + \$24.00 per cloth bag overwrap	\$1,300.00 (six HEPA's) + \$24.00 per cloth bag overwrap	\$1,006.00 <i>MINIMUM</i>
Filter mounting	Six (6) heavy-duty captive SS lugs with wingnuts and internal support cage	Three (3) loose light-duty retaining springs	Three (3) loose light-duty retaining springs	
PERFORMANCE				
Maximum Airflow	100 CFM	120 CFM	85 CFM	
Maximum Vacuum	8" Hg (needles "in" @ 35 SCFM @ 60 PSIG)	17" Hg	16.5	
	16" Hg (needles "out" @ 70 SCFM @ 60 PSIG)			
	18" Hg (needles "out" @ 70 SCFM @ 90 PSIG)			
GROUNDING				
Filter(s)	Yes	No	No	
Cover to Drum Dolly	Yes	No	No	
DRUM DOLLY	Heavy-duty spinning with (4) 4"-diameter S/C Rubber swivel casters and (3) drum lock-down nuts, fully assembled	Bolt-together cross-members with (4) 3"- diameter steel swivel wheels. Assembly required by customer	Bolt-together cross-members with (4) 3"- diameter steel swivel wheels. Assembly required by customer	
ACCESSORIES INCLUDED				
Static-Conductive Compressed Air Hose	25ft long	20ft	20ft	
Quick-Disconnect Fittings	Brass with integral shut-off	Chicago-type w/o shut-off	Chicago-type w/o shut-off	
Vacuum Hose	Choice of 15ft or 25ft lengths, choice of Static- Dissipative PVC or S/C Neoprene	15ft static-dissipative PVC	15ft static-dissipative PVC	
Vacuum Equalizer Kit (VEK)	Yes	No	No	\$88.00
Static-conductive polybag drum liners	Yes, 10 pcs included	No	No	\$150.00
Tool Kit	Floor wand with 17"wide wet/dry wheeled floor tool, crevice tool, and bevelled rubber hand tool	Floor wand with 12"wide floor tool, crevice tool	Floor wand with 12"wide floor tool, crevice tool	
Support leg & Extended Inlet to protect filter	Yes	No	No	
LOCAL REPRESENTATION / EXPERTISE / AFTER-SALES SERVICE	Yes	No	No	20% of selling price
PURCHASE PRICE with 15FT PVC HOSE	\$4,392 / \$4,432.00	\$1,650.00	\$1,600.00	
Stainless steel construction available	Yes	No	No	