



320NA

Neoprene Automatic Door Bottom for Hollow Metal Doors

PRODUCT CUT SHEET

Material

Aluminum Alloy 6063, T6 Temper
Synthetic EPDM Rubber in Polypropylene Thermoplastic Matrix
Neoprene is Black

- BHMA Certified to ANSI/BHMA A156.22, 1,000,000 Cycle Test-Grade 1
- BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- Very Good Abrasion Resistance, Tensile Strength and Memory
- Flame-Resistant
- Moisture-Resistant
- Temperature Range -76°F to 275°F
- Good Resistance to Ozone, Sunlight and Aging
- Fits in 1 5/8" x 3/4" Channel. A "Furring Strip" May Be Used to Lower Automatic Door Bottom When a Deeper Channel is Used
- Furnished 1/2" Shorter Than Ordered to Fit Within Net Door Size. (i.e. 36" is Furnished 35 1/2") Length May Be Field Cut up to 1 1/2"
- ADB's from 12" to 18" Can be Cut Down 1/2". ADB's 20" and Over Can be Cut Down up to 1 1/2"
- Fire Ratings Apply to Metal Doors Only
- #6 x 1/2" Tek Screws Furnished
- End Caps Not Available
- Available 12" to 60" in Length
- Non-Handed

Finish

Clear Anodized Aluminum

Options

Lead Insert Available for Radiation Shield – Specify 'Lead Lined'





PROJECT:

SUBMITTED BY:

DATE:

NOTES:



NGP-GKT-320NA-PCS-0426-A

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874

Email: info@ngp.com

Quotes: quotes@ngp.com

Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH