


Exercise: HTTP Protocol

This document defines the exercises for the ["ASP.NET Fundamentals" Course @ SoftUni](#).

1. The Project for Testing: GitHub Issues API


In this exercise we shall **test the GitHub REST API**, more specifically, the **GitHub Issues API**:



The screenshot shows a Postman interface with a GET request to `https://api.github.com/repos/testnakov/test-nakov-repo/issues`. The response status is 200 OK, with a time of 879 ms and a size of 63.24 KB. The response body is a JSON object with the following fields:

```
1 {
2   "url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/3882",
3   "repository_url": "https://api.github.com/repos/testnakov/test-nakov-repo",
4   "labels_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/3882/labels{/name}",
5   "comments_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/3882/comments",
6   "events_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/3882/events",
7   "html_url": "https://github.com/testnakov/test-nakov-repo/issues/3882",
8   "id": 1348089323,
9   "node_id": "I_kwDOBGGNf85QWjXr",
10 }
```

GitHub Issues is a popular issue tracking software, coming with all GitHub repositories. It is available for free, after a free registration in GitHub. This is how **GitHub Issues** user interface looks like:



The screenshot shows the GitHub Issues user interface for the repository `testnakov/test-nakov-repo`. The interface includes a search bar, filters, and a list of issues. The issues are sorted by 'Open' status, and the first issue is titled 'alabala' with labels 'bug' and 'enhancement'.

The above user interface is publicly accessible from: <https://github.com/testnakov/test-nakov-repo/issues>.

2. API Endpoints for GitHub Issues

GitHub Issues provides the standard RESTful **API endpoints**, which you can access with Postman HTTP client from <https://api.github.com>:

- **GET endpoints** – respond with **JSON** object as result.
 - **GET /repos/{user}/{repo}/issues** – returns the **issues** in given GitHub repo.
 - **GET /repos/{user}/{repo}/issues/{num}** – returns the specified **issue**.

- GET /repos/{user}/{repo}/issues/{num}/comments – returns the **comments** for an issue.
- GET /repos/{user}/{repo}/issues/comments/{id} – returns the specified **comment**.
- POST / PATCH / DELETE endpoints – all of them need **authentication**.
 - POST /repos/{user}/{repo}/issues – creates a new **issue**.
 - PATCH /repos/{user}/{repo}/issues/{num} – modifies the specified **issue**.
 - POST /repos/{user}/{repo}/issues/{num}/comments – creates new **comments** for certain issue.
 - PATCH /repos/{user}/{repo}/issues/comments/{id} – modifies existing **comment**.
 - DELETE /repos/{user}/{repo}/issues/comments/{id} – deletes existing **comment**.

Note that in GitHub API some requests (mostly retrieval requests) identify the resources **by number**. The **issue number** is the sequential number (1, 2, 3, ...) inside the project issue tracker. The **issue id** / **comment id** is global identifier (such as 762541045, 843104478).

Authentication in GitHub API

Some GitHub API endpoints need **authentication**. In Postman, you can use **Basic authentication**, using your **GitHub username** + a **password**, created from the “**Personal Access Tokens**” section in the GitHub user profile setting.

Create new **personal access token** for the GitHub API from your profile: <https://github.com/settings/tokens/new>.

github.com/settings/tokens/new

Search or jump to... Pulls Issues Marketplace Explore

Settings / Developer settings

GitHub Apps
OAuth Apps
Personal access tokens

New personal access token

Personal access tokens function like ordinary OAuth access tokens. They can be used instead of a password for Git over HTTPS, or can be used to [authenticate to the API over Basic Authentication](#).

Note


What's this token for?

Select scopes

Scopes define the access for personal tokens. [Read more about OAuth scopes](#).

<input checked="" type="checkbox"/> repo	Full control of private repositories
<input checked="" type="checkbox"/> repo:status	Access commit status
<input checked="" type="checkbox"/> repo_deployment	Access deployment status
<input checked="" type="checkbox"/> public_repo	Access public repositories
<input checked="" type="checkbox"/> repo:invite	Access repository invitations
<input checked="" type="checkbox"/> security_events	Read and write security events

Once, a **personal access token** is created in GitHub, you can use it from **Postman** by adding a "**Basic authentication**" header for the HTTP request. An example is shown below:



In this exercise you shall use **HTTP Basic authentication** to authenticate and authorize your GitHub API requests. The **username** is your **GitHub username**. The **password** is your **personal access token**, that you have previously created from the [Developer settings] page in your GitHub profile.

GitHub API: Sample HTTP Request

This is how a typical **HTTP request to GitHub API** looks like:

```
POST /repos/testnakov/test-nakov-repo/issues/6/comments HTTP/1.1
Host: api.github.com
Content-Type: application/json
Authorization: Basic
dGVzdG5ha2920jMzYjQ3MzUzZTE2NGU4YTkxZD1mMDM2MGVjNDdkYmFmNWUzNzJhNg==
Content-Length: 25

{
  "body": "Comment"
}
```

In the above request the **username** and the **password** (the personal access token) used to authorize the request, are encoded in the **"Authorization" header**. This header holds a **base64 string**, which encodes together the **username** and the **password**, separated by **':'**. This is the decoded base64 string from the above request:

Base64 string	dGVzdG5ha2920jMzYjQ3MzUzZTE2NGU4YTkxZD1mMDM2MGVjNDdkYmFmNWUzNzJhNg==
String value	testnakov:33b47353e164e8a91d9f0360ec47dbaf5e372a6

GitHub API: Sample HTTP Response

A typical **HTTP response** from the GitHub API may look like this:

```
HTTP/1.1 201 Created
Date: Tue, 19 Jan 2021 13:20:12 GMT
Content-Type: application/json; charset=utf-8
```

Content-Length: 1453

Server: GitHub.com


...

```
{"url":"https://api.github.com/repos/testnakov/test-nakov-repo/issues/comments/762834681", "html_url":"https://github.com/testnakov/test-nakov-repo/issues/6#issuecomment-762834681", "issue_url":"https://api.github.com/repos/testnakov/test-nakov-repo/issues/6", "id":762834681,"node_id":"MDEyOk1zc3VlQ29tbWVudDc2MjgzNDY4MQ==","user":{"login":"testnakov","id":23406465,"node_id":"MDQ6VXNlcjIzNDA2NDY1","avatar_url":"https://avatars2.githubusercontent.com/u/23406465?u=b090ea0dc2d6c5cf71bcc39160cda63ab2f28714&v=4","gravatar_id":"","url":"https://api.github.com/users/testnakov","html_url":"https://github.com/testnakov","followers_url":"https://api.github.com/users/testnakov/followers","following_url":"https://api.github.com/users/testnakov/following{/other_user}", "gists_url":"https://api.github.com/users/testnakov/gists{/gist_id}", "starred_url":"https://api.github.com/users/testnakov/starred{/owner}/{repo}", "subscriptions_url":"https://api.github.com/users/testnakov/subscriptions", "organizations_url":"https://api.github.com/users/testnakov/orgs", "repos_url":"https://api.github.com/users/testnakov/repos", "events_url":"https://api.github.com/users/testnakov/events{/privacy}", "received_events_url":"https://api.github.com/users/testnakov/received_events", "type":"User", "site_admin":false}, "created_at":"2021-01-19T13:20:11Z", "updated_at":"2021-01-19T13:20:11Z", "author_association":"OWNER", "body":"This is a comment", "performed_via_github_app":null}
```

3. Create Postman Collection of Requests

Now, you should create a **Postman collection** of HTTP requests for accessing the **GitHub Issues API**. Select **Collections** in the sidebar, then select the **[+]** button and click on **Create new Collection** (see the screenshot).

The new **Postman collection** will hold the **HTTP requests for the GitHub API**, related to **issues** and **issue comments**. The Postman collection may look as shown below. It may be structured in **folders** and the requests should have appropriate names, like it is shown below:



Now it's time to **create a few HTTP requests** in the new Postman collection.

Retrieve All Issues from Repo

Retrieve all issues from repo "test-nakov-repo" in user "testnakov". Use the following **HTTP GET request** in Postman:

Request	GET https://api.github.com/repos/testnakov/test-nakov-repo/issues
Body	(empty)

This is how the above HTTP request may look in **Postman** after successful execution:

The screenshot shows the Postman interface with a GET request to the GitHub API. The response is a 200 OK status with a JSON body. The first issue object is highlighted, showing details like url, repository_url, labels_url, comments_url, events_url, html_url, id, node_id, number, and title.

The returned HTTP status code is "**200 OK**" and the HTTP **response body** holds the returned issues as **JSON array** of objects. Note that the issues in this repo could be thousands and returning all of them will be too slow and the response will be huge. To optimize the speed, the GitHub API uses **paging**. By default, the above request will return the most recent 30 issues. You can request the others by using a **request parameter "page"**:

The screenshot shows the Postman interface with a GET request to the GitHub API. The URL is https://api.github.com/repos/testnakov/test-nakov-repo/issues?page=2. The 'Query Params' section shows 'page' with a value of '2'.


Retrieve Issue by Number

Retrieve issue #1 from repo "test-nakov-repo" in user "testnakov":

Request	GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/1
----------------	---

Body	(empty)
------	---------

The returned HTTP status code is **"200 OK"** and the HTTP **response body** holds the requested issue as **JSON** object:



Get Issue #1 by Repo

Examples 0 BUILD

GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/1 Send Save

Params Authorization Headers (6) Body Pre-request Script Tests Settings Cookies Code

Body Cookies Headers (25) Test Results 200 OK 419 ms 3.56 KB Save Response

Pretty Raw Preview Visualize JSON

```


1 {
2   "url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1",
3   "repository_url": "https://api.github.com/repos/testnakov/test-nakov-repo",
4   "labels_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1/labels{/name}",
5   "comments_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1/comments",
6   "events_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1/events",
7   "html_url": "https://github.com/testnakov/test-nakov-repo/issues/1",
8   "id": 188822935,
9   "node_id": "MDU6SXNzdWUxODg4MjI5MzU=",
10  "number": 1,
11  "title": "yesbe",

```

Note that **"issue number"** (in this example **1**) and **"issue id"** (in this example **188822935**) are different identifiers of the same issue. The issue **id** is a global unique issue identifier in the GitHub issues database. The issue **number** is a local identifier within the current project's issue tracker.

You can also view the same **issue #1** from the Web in the GitHub Issues page for the above-mentioned project: <https://github.com/testnakov/test-nakov-repo/issues/1>.

If you try to retrieve a **non-existing issue** from the GitHub API (for example **issue #0**), you will get **404 Not Found**:



GitHub / Get Issue by Number

Save ...

GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/0 Send

Params Authorization Headers (6) Body Pre-request Script Tests Settings Cookies

Query Params

KEY	VALUE	DESCRIPTION	...	Bulk Edit
Body	404 Not Found	160 ms	1.16 KB	Save Response

Pretty Raw Preview Visualize JSON

```

1 {
2   "message": "Not Found",
3   "documentation_url": "https://docs.github.com/rest/reference/issues#get-an-issue"
4 }

```

Create a New Issue

Create a new issue in the repo **"test-nakov-repo"** of user **"testnakov"**. You will need a valid GitHub **access token** to authorize the request:

Request	POST https://api.github.com/repos/testnakov/test-nakov-repo/issues
Authorization	Basic (GitHub username + GitHub personal access token)
Body	<pre>{ "title": "Missing [Submit] button", "body": "I'm having a problem with this." }</pre>

In case of success, the HTTP response should have status **201 Created** and should hold in the response body a **JSON** object, holding **the number of the new issue**, together with other issue details:

```

1 {
2   "url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1130",
3   "repository_url": "https://api.github.com/repos/testnakov/test-nakov-repo",
4   "labels_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1130/labels{/name}",
5   "comments_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1130/comments",
6   "events_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/1130/events",
7   "html_url": "https://github.com/testnakov/test-nakov-repo/issues/1130",
8   "id": 788909191,
9   "node_id": "MDU6SXNzdWU3ODg5MDkxOTE=",
10  "number": 1130,

```

The issue number for the above new issue is **#1130**. Note that **"issue id"** and **"issue number"** are different things. The **issue number** is unique for certain GitHub repository. The **issue id** is globally unique at GitHub.

You can view this new issue in the GitHub Issues: <https://github.com/testnakov/test-nakov-repo/issues/1130>.

In case you don't provide valid authentication for the GitHub API for the HTTP request, you will get an error response: **401 Unauthorized** or **404 Not Found**.

Sometimes GitHub returns **404 Not Found** when you request a resource without proper authentication instead of the correct HTTP status code. This is semantically incorrect, but GitHub returns this to avoid "information disclosure". Be warned that if you get **404 Not Found** from GitHub, this may mean **"Unauthorized access"**.

Edit Existing Issue

Edit existing issue **#1119** from the repo **"test-nakov-repo"** of user **"testnakov"**:

Request	PATCH https://api.github.com/repos/testnakov/test-nakov-repo/issues/1119
Authorization	Basic (GitHub username + GitHub personal access token)
Body	<pre>{ "title": "Edited bug (new title)" }</pre>

On success, the HTTP response should have status **200 OK** and should hold **the edited issue** as response body:

PATCH ▼ <https://api.github.com/repos/testnakov/test-nakov-repo/issue> Send Save ▼

Params Auth ● Headers (11) Body ● Pre-req. Tests Settings Cookies Code

raw ▼ JSON ▼ Beautify

```

1 {
2   "title": "Edited bug"
3 }

```

Body ▼ 200 OK 471 ms 3.03 KB Save Response ▼

Pretty Raw Preview Visualize JSON ▼ ↕

```

8   "id": 747530404,
9   "node_id": "MDU6SXNzdWU3NDc1MzA0MDQ=",
10  "number": 1119,
11  "title": "Edited bug",
12  "user": {
13    "login": "Bilboking",

```

Note: you can edit only your own issues. Repo admins can edit also other user's issues. If you try to edit an issue without sufficient privileges, you will get **403 Forbidden**:

GitHub / Create an Issue Save ▼ ... ✎ 💬

PATCH ▼ <https://api.github.com/repos/testnakov/test-nakov-repo/issues/1119> Send ▼

Params Authorization ● Headers (9) Body ● Pre-request Script Tests Settings Cookies

● none ● form-data ● x-www-form-urlencoded ● raw ● binary ● GraphQL JSON ▼ Beautify

```

1 {
2   "title": "Edited bug (new title)"
3 }
4

```

Body Cookies Headers (24) Test Results 403 Forbidden 194 ms 1.3 KB Save Response ▼

Pretty Raw Preview Visualize JSON ▼ ↕

```

1 {
2   "message": "Must have admin rights to Repository.",
3   "documentation_url": "https://docs.github.com/rest/reference/issues#update-an-issue"
4 }

```

Close Existing Issue

Close issue #6 from the repo "test-nakov-repo" of user "testnakov":

Request	PATCH https://api.github.com/repos/testnakov/test-nakov-repo/issues/6
Authorization	Basic (GitHub username + GitHub personal access token)
Body	<pre>{ "state": "closed" }</pre>

The HTTP response should have status **200 OK** and should hold **the edited issue** as response body. You can see the closed issue here: <https://github.com/testnakov/test-nakov-repo/issues/6>.

Note: you can edit / close only your own issues. Repo admins can edit or close user's issues. If you try to close an issue without sufficient privileges, you will get **403 Forbidden**.

Retrieve All Labels for Issue

Retrieve all comments for existing issue #6 from the repo "test-nakov-repo" of user "testnakov":

Request	GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/6/labels
Body	(empty)

The HTTP response should have status **200 OK** and should hold **the issue labels** as response body in JSON format (array of labels):

The screenshot shows a REST client interface with the following details:

- Method: GET
- URL: https://api.github.com/repos/testnakov/test-nakov-repo/issues/6/labels
- Status: 200 OK
- Response Time: 335 ms
- Response Size: 1.45 KB
- Response Format: JSON
- Response Body (Pretty):

```
[
  {
    "id": 479839735,
    "node_id": "MDU6TGFiZWw0Nzk4Mzk3MzU=",
    "url": "https://api.github.com/repos/testnakov/test-nakov-repo/labels/bug",
    "name": "bug",
    "color": "ee0701",
    "default": true,
    "description": null
  },
  {
    "id": 479839737,
    "node_id": "MDU6TGFiZWw0Nzk4Mzk3Mzc=",
    "url": "https://api.github.com/repos/testnakov/test-nakov-repo/labels/enhancement",
    "name": "enhancement",
  }
]
```

You can see these labels here: <https://github.com/testnakov/test-nakov-repo/issues/6>. All available labels for this repos can be seen here: <https://github.com/testnakov/test-nakov-repo/labels>.

In case of **no labels** available for the specified issue, the HTTP response body will hold an **empty JSON array**: `[]`.

Create a Comment for Issue

Create a new comment for existing issue #6 from the repo "test-nakov-repo" of user "testnakov":

Request	POST https://api.github.com/repos/testnakov/test-nakov-repo/issues/6/comments
Authorization	Basic (GitHub username + GitHub personal access token)
Body	{

	<pre>"body": "This is a comment" }</pre>
--	--

The HTTP response should have status **201 Created** and should hold **the new comment** as response body in JSON format. You can see the new comment here: <https://github.com/testnakov/test-nakov-repo/issues/6>.

If you try to create a comment in a repo, where you don't have sufficient privileges, you will get **403 Forbidden**.

Retrieve All Comments for Issue

Retrieve all comments for existing issue #6 from the repo "test-nakov-repo" of user "testnakov":

Request	GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/6/comments
Body	(empty)

The HTTP response should have status **200 OK** and should hold **the issue comments** as response body in JSON format (array of comments):

The screenshot shows a REST client interface. The top bar indicates a GET request to `https://api.github.com/repos/testnakov/test-nakov-repo/issues/6/comments` with a status of 200 OK, 367 ms, and 17.74 KB. The response body is displayed in JSON format, showing an array with one comment object:

```
[
  {
    "url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/comments/762538948",
    "html_url": "https://github.com/testnakov/test-nakov-repo/issues/6#issuecomment-762538948",
    "issue_url": "https://api.github.com/repos/testnakov/test-nakov-repo/issues/6",
    "id": 762538948,
    // ... other fields
  }
]
```

You can see these comments here: <https://github.com/testnakov/test-nakov-repo/issues/6>.

In case of **no comments** available for the specified issue, the HTTP response body will hold an **empty JSON array**:

The screenshot shows a REST client interface. The top bar indicates a GET request to `https://api.github.com/repos/testnakov/test-nakov-repo/issues/61/comments` with a status of 200 OK, 379 ms, and 1.21 KB. The response body is displayed in JSON format, showing an empty array:

```
[]
```

Retrieve Comment by Id

Retrieve a comment by id. The comment **id** is global for the entire GitHub (in this example **#762538948**), but still, the **user** and **repo** for the comment are required in the request URL:

Request	GET https://api.github.com/repos/testnakov/test-nakov-repo/issues/comments/762538948
----------------	---

Body	(empty)
-------------	---------

The HTTP response should have status **200 OK** and should hold **the new issue comment** in JSON format. You can see this comment here: <https://github.com/testnakov/test-nakov-repo/issues/6#issuecomment-762538948>.

Edit Existing Comment

Edit existing comment by id. The comment **id** is global for the entire GitHub (in this example **#762541976**), but still, the **user** and **repo** for the comment are required in the request URL:

Request	PATCH https://api.github.com/repos/testnakov/test-nakov-repo/issues/comments/762541976
Body	{ "body": "Edited Comment" }

The HTTP response should have status **200 OK** and should hold **the modified issue comment** in JSON format. You can see this comment here: <https://github.com/testnakov/test-nakov-repo/issues/6#issuecomment-762541976>.

Note: you can edit only your own comments. Repo admins can edit also other user's comments. If you try to edit a comment without sufficient privileges, you will get **401 Unauthorized** or **403 Forbidden**.

Delete Existing Comment

Delete existing comment by id. The comment **id** is global for the entire GitHub. First **create a new comment** and put its **id** in the request below:

Request	DELETE https://api.github.com/repos/testnakov/test-nakov-repo/issues/comments/{id}
Body	(empty)

The HTTP response should have status **204 No Content** and should hold empty body.

In case of non-existing comment, the above request will return **404 Not Found**.

Note: you can delete only your own comments. Repo admins can delete also other user's comments. If you try to delete a comment without sufficient privileges, you will get **401 Unauthorized** or **403 Forbidden**.