

Representations in Deep Neural Networks

What they are, why we care, and how we can use them

Joseph H. Rudoler

February 20, 2025

Motivation

We talk a lot in ML/AI about "representations" but the idea is either fuzzy / circular ("something useful", "high-dim representation") or overly technical/concrete ("activations of hidden layers")

This talk will hopefully cover:


- Intuition for how representations in ANNs were developed
- Theoretical frameworks
- Survey modern use cases

Representations in Neuroscience

Individual neurons fire in an "all or nothing" manner.

- This 0-or-1 activity can be treated as a boolean primitive
- A connected network of neurons can express many complex logical functions.^a

^aMcCulloch and Pitts, 1943.





Representations in Neuroscience

Neural networks are capable of learning

- Discrete boolean logic is too rigid
- Hebbian learning^a framework explained how co-activation could strengthen connections
 - ▷ *Neurons that fire together, wire together*
- Extension to probabilistic setting produced the "perceptron"^b, with a convergence theorem in the case of linearly separable classes

^aD.o Hebb, 1949.

^bRosenblatt, 1958.




Hierarchical representations in neuroscience

Biological neurons in the visual cortex exhibit hierarchy^a

- Experiments on cats - observed neural firing when shown simple images / shapes.
- (B) circular local receptive fields \Rightarrow "simple" cells that can identify lines/boundaries
- (A) Simple cells \Rightarrow complex cells
- Information propagates through visual cortex^b

^aHubel and Wiesel, 1962.

^bGoodale and Milner, 1992.



Hierarchical representations in computer vision

Convolutional Neural Networks (CNNs) were inspired by biological NNs

- First CNN developed by Fukushima, manually-designed kernels to recreate the same feature extraction^a
- Later developed more flexible "neocognitron" using Hebbian unsupervised learning^b

^aFukushima, 1969.

^bFukushima, 1980.




Fig. 5. Sketch of the network structure. Only typical interconnections are shown. The elements in a layer (enclosed within a solid line) are connected to the element in the next layer with positive interconnecting coefficients; those enclosed within a dotted line are connected with negative interconnecting coefficients.

Hierarchical representations in Computer Vision

Backpropagation was the key to learning "useful" representations

Learning representations by back-propagating errors (Rumelhart et al., 1986)

"In perceptrons, there are "feature-analysers" between the input and output that are not true hidden units because their input connections are fixed by hand, so their states are completely determined by the input vector: they do not learn representations. The learning procedure must decide under what circumstances the hidden units should be active **in order to help achieve the desired input-output behaviour**. This amounts to deciding what these units should represent."


- Yann Lecun applied supervised learning to train CNN kernels via backpropagation (classic MNIST results)¹

¹LeCun et al., 1989.

Correspondence between visual system and CNNs

Does the brain extract the same features as CNNs?

- Yamins et al., 2014 was one of the first studies to show a correspondence between representations in brains and ANNs
- This area of research comes with *lots* of caveats



Parallel Distributed Processing (PDP)

So... why are NN representations good?

- McClelland et al., 1986 posit that there are advantages to models which compose smaller "units", processed in parallel, into larger patterns
- Computational advantages of parallelism
- Distributed representations are robust, and exhibit spontaneous generalization

Parallel Distributed Processing (PDP)

Parallelism


- No way our brains could respond quickly enough if we had to process everything in sequence.
- People get *faster*, not slower, when you add more constraints
- Huge computational advantage to processing units in parallel



Parallel Distributed Processing (PDP)

Distributed Representations

- More robust
- Content-addressable memory
- Spontaneous generalization to similar stimuli



Information theoretic perspective

Efficient coding hypothesis

Sensory relays recode messages, extracting signals of **high relative entropy** from the highly redundant inputs^a

^aBarlow, 1961; Simoncelli and Olshausen, 2001.

- "Relative entropy" not in the KL-divergence sense, but rather the ratio expressing entropy relative to channel capacity


$$H = - \sum_x p(x) \log p(x)$$

$$H_{rel} = H/C$$

- In vision, an efficient code depends on the statistics of natural images.
- Evidence that efficient neural codes emerge naturally through gradient descent learning (Benjamin et al., 2022)

Information theoretic perspective

- In vision, an efficient code depends on the statistics of natural images.
- Evidence that efficient neural codes emerge naturally through gradient descent learning (Benjamin et al., 2022)



Decoding

Another intuitive perspective is that networks learn features that are optimized for **linear decoding**.²




Figure 2: Probes being added to every layer of a model. Note that **the model parameters are not affected by the probes**. We add a little diode symbol through the arrows to indicate that the gradients will not backpropagate through those connections (implemented with `tf.stop_gradient` in tensorflow).




Figure 3: The auxiliary head, shown under the model, was observed to have a prediction error that was slightly better than the main head. This is not necessarily a condition that will hold at the end of training, but merely an observation.

²Alain and Bengio, 2017.

Decoding

Prediction, via a linear readout or otherwise, gives us a principled way to think about or compare representations.

- GULP distance³: maximum difference between best ridge regressions on each representation

GULP distance

Fix $\lambda > 0$. The GULP distance between representations $\phi(X)$ and $\psi(X)$ is given by

$$d_\lambda(\phi, \psi) := \sup_{\eta} \left(\mathbb{E} \left(\beta_\lambda^\top \phi(X) - \gamma_\lambda^\top \psi(X) \right)^2 \right)^{\frac{1}{2}},$$

where the supremum is taken over all regression functions η such that $\|\eta\|_{L^2(P_X)} \leq 1$.

- Connections between other similarity measures / distances and "predictability" or "decodable information" Harvey et al., 2024

³Boix-Adsera et al., 2022.

Interpretability

Similarity of representations


- Claim: if A and B form similar representations, this is evidence that A and B are mechanistically similar.
- Problems: identifiability issues, inconsistency across metrics

Activation patterns tell us what the model is doing mechanistically


- Similar to neuroscience studies that observe behavior claim "brain area A is involved in behavior X"
- Better than neuro studies, because we can manipulate the activations and learn causal relationships

Intervention / Steering

Identify and intervene on representations associated with behaviors of interest. Zou et al., 2023



(a) Linear Artificial Tomography



(b) Lie Detection

Summary

- DNNs have their origins in biologically-inspired feature-extractors
- There are long-standing theories about why and how representations arise
- We can use representations to better understand and control network behavior

References I



Alain, G., & Bengio, Y. (2017). Understanding intermediate layers using linear classifier probes. Retrieved February 18, 2025, from <https://openreview.net/forum?id=HJ4-rAVtl>



Barlow, H. B. (1961). Possible principles underlying the transformations of sensory messages. In W. A. Rosenblith (Ed.), *Sensory communication* (pp. 216–234). The MIT Press.
<https://doi.org/10.7551/mitpress/9780262518420.003.0013>



Benjamin, A. S., Zhang, L.-Q., Qiu, C., Stocker, A. A., & Kording, K. P. (2022). Efficient neural codes naturally emerge through gradient descent learning [Number: 1 Publisher: Nature Publishing Group]. *Nature Communications*, 13(1), 1–12.
<https://doi.org/10.1038/s41467-022-35659-7>



Boix-Adsera, E., Lawrence, H., Stepaniants, G., & Rigollet, P. (2022, October 12). GULP: A prediction-based metric between representations. <https://doi.org/10.48550/arXiv.2210.06545>

References II



D.o Hebb. (1949). *The organization of behavior*. Retrieved February 16, 2025, from <http://archive.org/details/in.ernet.dli.2015.226341>



Fukushima, K. (1969). Visual feature extraction by a multilayered network of analog threshold elements [Conference Name: IEEE Transactions on Systems Science and Cybernetics]. *IEEE Transactions on Systems Science and Cybernetics*, 5(4), 322–333. <https://doi.org/10.1109/TSSC.1969.300225>



Fukushima, K. (1980). Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biological Cybernetics*, 36(4), 193–202. <https://doi.org/10.1007/BF00344251>



Goodale, M. A., & Milner, A. D. (1992). Separate visual pathways for perception and action. *Trends in Neurosciences*, 15(1), 20–25. [https://doi.org/10.1016/0166-2236\(92\)90344-8](https://doi.org/10.1016/0166-2236(92)90344-8)



Harvey, S. E., Lipshutz, D., & Williams, A. H. (2024, November 12). What representational similarity measures imply about decodable information. <https://doi.org/10.48550/arXiv.2411.08197>

References III



Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of Physiology*, 160(1), 106–154.2. Retrieved February 13, 2025, from <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC1359523/>



LeCun, Y., Boser, B., Denker, J. S., Henderson, D., Howard, R. E., Hubbard, W., & Jackel, L. D. (1989). Backpropagation applied to handwritten zip code recognition. *Neural Computation*, 1(4), 541–551. <https://doi.org/10.1162/neco.1989.1.4.541>



McClelland, J. L., Rumelhart, D. E., & Hinton, G. E. (1986). The appeal of parallel distributed processing. <https://doi.org/10.7551/mitpress/5236.003.0004>



McCulloch, W. S., & Pitts, W. (1943). A logical calculus of the ideas immanent in nervous activity. *The bulletin of mathematical biophysics*, 5(4), 115–133. <https://doi.org/10.1007/BF02478259>

References IV



Rosenblatt, F. (1958). The perceptron: A probabilistic model for information storage and organization in the brain [Place: US Publisher: American Psychological Association]. *Psychological Review*, 65(6), 386–408. <https://doi.org/10.1037/h0042519>



Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-propagating errors [Publisher: Nature Publishing Group]. *Nature*, 323(6088), 533–536. <https://doi.org/10.1038/323533a0>



Simoncelli, E. P., & Olshausen, B. A. (2001). Natural image statistics and neural representation. *Annual Review of Neuroscience*, 24(1), 1193–1216. <https://doi.org/10.1146/annurev.neuro.24.1.1193>



Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014). Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23), 8619–8624. <https://doi.org/10.1073/pnas.1403112111>

References V



Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., Goel, S., Li, N., Byun, M. J., Wang, Z., Mallen, A., Basart, S., Koyejo, S., Song, D., Fredrikson, M., ... Hendrycks, D. (2023, October 10). Representation engineering: A top-down approach to AI transparency. <https://doi.org/10.48550/arXiv.2310.01405>