

T-Cal: An optimal test for the calibration of predictive models

Edgar Dobriban, University of Pennsylvania

based on joint work with
Donghwan Lee, Xinmeng Huang, and Hamed Hassani

March 4, 2022

Overview

Overview

Calibration

T-Cal Method

Experiments


Optimality and lower bounds

Context

- ▶ Prediction accuracy of machine learning methods is steadily increasing

Context

- ▶ Prediction accuracy of machine learning methods is steadily increasing
- ▶ Success stories: AlphaFold, cancer tissue image classification, computer vision, NLP ...




Title: United Methodists Agree to Historic Split
Subtitle: Those who oppose gay marriage will form their own denomination
Article: After two days of intense debate, the United Methodist Church has agreed to a historic split - one that is expected to end in the creation of a new denomination, one that will be "theologically and socially conservative," according to The Washington Post. The majority of delegates attending the church's annual General Conference in May voted to strengthen a ban on the ordination of LGBTQ clergy and to write new rules that will "discipline" clergy who officiate at same-sex weddings. But those who opposed these measures have a new plan: They say they will form a separate denomination by 2020, calling their church the Christian Methodist denomination.

Figure 3.14: The GPT-3 generated news article that humans had the greatest difficulty distinguishing from a human written article (accuracy: 12%).

Context

- ▶ Prediction accuracy of machine learning methods is steadily increasing
- ▶ Success stories: AlphaFold, cancer tissue image classification, computer vision, NLP ...



Title: United Methodists Agree to Historic Split
Subtitle: Those who oppose gay marriage will form their own denomination
Article: After two days of intense debate, the United Methodist Church has agreed to a historic split - one that is expected to end in the creation of a new denomination, one that will be "theologically and socially conservative," according to The Washington Post. The majority of delegates attending the church's annual General Conference in May voted to strengthen a ban on the ordination of LGBTQ clergy and to write new rules that will "discipline" clergy who officiate at same-sex weddings. But those who opposed these measures have a new plan: They say they will form a separate denomination by 2020, calling their church the Christian Methodist denomination.

Figure 3.14: The GPT-3 generated news article that humans had the greatest difficulty distinguishing from a human written article (accuracy: 12%).

- ▶ Meanwhile, growing concerns: safety, ethics, energy- and sample-efficiency, **uncertainty**

Uncertainty Quantification

- ▶ Given input x , the output y is often not uniquely determined

Uncertainty Quantification

- ▶ Given input x , the output y is often not uniquely determined
- ▶ Examples of uncertainty:
 - ▶ GPT-3: given text prompt, ...?

Uncertainty Quantification

- ▶ Given input x , the output y is often not uniquely determined
- ▶ Examples of uncertainty:
 - ▶ GPT-3: given text prompt, ...?
 - ▶ Skin cancer classification: given skin image, ...?

Uncertainty Quantification

- ▶ Given input x , the output y is often not uniquely determined
- ▶ Examples of uncertainty:
 - ▶ GPT-3: given text prompt, ...?
 - ▶ Skin cancer classification: given skin image, ...?
- ▶ Standard ML pipeline does not provide a solution

Uncertainty Quantification

- ▶ Example problems:

- ▶ Prediction Set: find mapping C of inputs to subsets of \mathcal{Y} :
 $P(y \in C(x)) \geq 1 - \alpha$, for some $\alpha \in (0, 1)$.

Uncertainty Quantification

- ▶ Example problems:


- ▶ Prediction Set: find mapping C of inputs to subsets of \mathcal{Y} :
 $P(y \in C(x)) \geq 1 - \alpha$, for some $\alpha \in (0, 1)$.
- ▶ **Calibration**: construct probability predictions that reflect true probabilities.
For binary classification, for all appropriate z ,

$$P(y = 1 | f(x) = z) \approx z$$

Uncertainty Quantification for ML - My course at Penn


← → ↻

github.com/dobriban/Topics-In-Modern-Statistical-Learning



Search or jump to...

[Pull requests](#) [Issues](#) [Marketplace](#) [Explore](#)

 [dobriban / Topics-In-Modern-Statistical-Learning](#) Public

[Code](#) [Issues](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)

STAT 991: Topics In Modern Statistical Learning (UPenn, 2022 Spring)

This class surveys advanced topics in statistical learning based on student presentations.

The core topic of the course is [uncertainty quantification for machine learning methods](#). While modern machine learning methods can have a high prediction accuracy in a variety of problems, it is still challenging to properly quantify their uncertainty. There has been a recent surge of work developing methods for this problem. It is one of the fastest developing areas in contemporary statistics. This course will survey a variety of different problems and approaches, such as calibration, prediction intervals (and sets), conformal inference, OOD detection, etc. We will discuss both empirically successful/popular methods as well as theoretically justified ones. See below for a sample of papers.

About

Materials for STAT 9911303: Topics In Modern Statistical Learning (UPenn, 2022 Spring) - focus on uncertainty quantification

[machine-learning](#) [deep-learning](#) [prediction](#) [uncertainty-quantification](#) [conformal-prediction](#) [tolerance-intervals](#)

Calibration

- ▶ Input $x \in \mathbb{R}^d$; output: one-hot encoded label $y \in \{0, 1\}^K$
- ▶ A probabilistic classifier (probability predictor) $f : \mathbb{R}^d \rightarrow \Delta_{K-1}$ (simplex of probability distributions over $1, \dots, K$) is **calibrated** if

$$P(y_k = 1 | f(x) = z) = z_k \quad \text{for any } k \in [K] = \{1, \dots, K\} \text{ and } z \in \Delta_{K-1}$$

Here $z_k = [f(x)]_k$

Calibration

- ▶ Input $x \in \mathbb{R}^d$; output: one-hot encoded label $y \in \{0, 1\}^K$
- ▶ A probabilistic classifier (probability predictor) $f : \mathbb{R}^d \rightarrow \Delta_{K-1}$ (simplex of probability distributions over $1, \dots, K$) is **calibrated** if

$$P(y_k = 1 | f(x) = z) = z_k \quad \text{for any } k \in [K] = \{1, \dots, K\} \text{ and } z \in \Delta_{K-1}$$

Here $z_k = [f(x)]_k$

- ▶ Often focus on top-1 calibration, condition on $f^+(x) = \max_k [f(x)]_k$; use

$$y^+ = I(y = y_{\hat{k}(x)}), \quad \hat{k}(x) = \arg \max_k [f(x)]_k,$$

so calibration amounts to correctly predicting accuracy

$$P(y = y_{\hat{k}(x)} | f^+(x)) = f^+(x)$$

Calibration

- Modern finding: powerful ML methods (e.g., deep CNNs) are *over-confident* and *mis-calibrated*




Figure: Guo et al, 2017

Calibration

- Modern finding: powerful ML methods (e.g., deep CNNs) are *over-confident* and *mis-calibrated*




Figure: Guo et al, 2017

- Historical context: Humans are *also over-confident*

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions
- ▶ 1962: Meteorologist Robert Miller proposes chi-squared test for testing calibration of sets of binary predictions

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions
- ▶ 1962: Meteorologist Robert Miller proposes chi-squared test for testing calibration of sets of binary predictions
- ▶ 1960s-: psychology, social science: over-confidence [Tversky & Kahneman, Lichtenstein, Fishhoff, Phillips, ...]

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions
- ▶ 1962: Meteorologist Robert Miller proposes chi-squared test for testing calibration of sets of binary predictions
- ▶ 1960s-: psychology, social science: over-confidence [Tversky & Kahneman, Lichtenstein, Fishhoff, Phillips, ...]
- ▶ 1970s-80s-: statistics: decision theory, Bayesian, re-calibration, ... [Dawid, DeGroot, Fienberg, Foster, Vohra, Gneiting, Raftery, ...]

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions
- ▶ 1962: Meteorologist Robert Miller proposes chi-squared test for testing calibration of sets of binary predictions
- ▶ 1960s-: psychology, social science: over-confidence [Tversky & Kahneman, Lichtenstein, Fishhoff, Phillips, ...]
- ▶ 1970s-80s-: statistics: decision theory, Bayesian, re-calibration, ... [Dawid, DeGroot, Fienberg, Foster, Vohra, Gneiting, Raftery, ...]
- ▶ Many other contributions from various communities: medical statistics, business analytics, etc. [Miller, Murphy, Winkler, Van Calster, ...]

Rich History of Calibration

- ▶ 1906: Meteorologist Cooke suggests to express forecasts as probabilities
- ▶ 1950: Meteorologist Brier: evaluate forecasts via quadratic scoring rule $(I(A) - p)^2$ (Brier score; widely generalized)
- ▶ 1958: Statistician David R. Cox proposes score test for testing calibration of binary predictions
- ▶ 1962: Meteorologist Robert Miller proposes chi-squared test for testing calibration of sets of binary predictions
- ▶ 1960s-: psychology, social science: over-confidence [Tversky & Kahneman, Lichtenstein, Fishhoff, Phillips, ...]
- ▶ 1970s-80s-: statistics: decision theory, Bayesian, re-calibration, ... [Dawid, DeGroot, Fienberg, Foster, Vohra, Gneiting, Raftery, ...]
- ▶ Many other contributions from various communities: medical statistics, business analytics, etc. [Miller, Murphy, Winkler, Van Calster, ...]
- ▶ Present day: ML community

Workflow for Calibration

1. Obtain probability forecaster/classifier f (possibly train for calibration as well as accuracy)

Workflow for Calibration

1. Obtain probability forecaster/classifier f (possibly train for calibration as well as accuracy)
2. Test calibration

Workflow for Calibration

1. Obtain probability forecaster/classifier f (possibly train for calibration as well as accuracy)
2. **Test calibration**
3. If it is mis-calibrated, retrain/re-calibrate

Testing Calibration

- ▶ Classical tests of calibration (Cox, Miller): Given $B_i \sim \text{Bernoulli}(q_i)$, $i = 1, \dots, n$, test $q_i = p_i$, for a given probability predictions p_i .

Testing Calibration

- ▶ Classical tests of calibration (Cox, Miller): Given $B_i \sim \text{Bernoulli}(q_i)$, $i = 1, \dots, n$, test $q_i = p_i$, for a given probability predictions p_i .
- ▶ Cox: $\log(q_i/(1 - q_i)) = \beta_0 + \beta_1 \log(p_i/(1 - p_i))$, test $\beta_0 = 0$, $\beta_1 = 1$

Testing Calibration

- ▶ Classical tests of calibration (Cox, Miller): Given $B_i \sim \text{Bernoulli}(q_i)$, $i = 1, \dots, n$, test $q_i = p_i$, for a given probability predictions p_i .
- ▶ Cox: $\log(q_i/(1 - q_i)) = \beta_0 + \beta_1 \log(p_i/(1 - p_i))$, test $\beta_0 = 0$, $\beta_1 = 1$
 - ▶ **Key limitation:** may not have power to detect certain forms of mis-calibration




Figure: Van Calster et al, 2015

Testing Calibration

- ▶ Miller: after “suitable grouping” of p_i , use chi-squared test for per-group average predicted probability vector
 - ▶ **Key limitation**: how to choose groups?

Testing Calibration

- ▶ Miller: after “suitable grouping” of p_i , use chi-squared test for per-group average predicted probability vector
 - ▶ **Key limitation**: how to choose groups?
- ▶ Further **key questions**: which test statistic? optimality?

T-Cal: An optimal test of calibration

- ▶ Our contribution: **T-Cal**: An optimal test of calibration
 - ▶ Resolves key limitations, answer key questions
 - ▶ Readily applicable to state-of-the-art deep nets

T-Cal: An optimal test of calibration

- ▶ Our contribution: **T-Cal**: An optimal test of calibration
 - ▶ Resolves key limitations, answer key questions
 - ▶ Readily applicable to state-of-the-art deep nets
- ▶ How to detect general forms of mis-calibration?
 - ▶ Non-parametric testing model, chi-squared type test



T-Cal: An optimal test of calibration

- ▶ Our contribution: **T-Cal**: An optimal test of calibration
 - ▶ Resolves key limitations, answer key questions
 - ▶ Readily applicable to state-of-the-art deep nets
- ▶ How to detect general forms of mis-calibration?
 - ▶ Non-parametric testing model, chi-squared type test
- ▶ How to choose groups?
 - ▶ **Adaptive binning scheme**

T-Cal: An optimal test of calibration

- ▶ Our contribution: **T-Cal**: An optimal test of calibration
 - ▶ Resolves key limitations, answer key questions
 - ▶ Readily applicable to state-of-the-art deep nets
- ▶ How to detect general forms of mis-calibration?
 - ▶ Non-parametric testing model, chi-squared type test
- ▶ How to choose groups?
 - ▶ **Adaptive binning scheme**
- ▶ Which test statistic? optimality?
 - ▶ **Debiased** plug-in estimator of Empirical Calibration Error (ECE)
 - ▶ Minimax optimal over Hölder smooth calibration curves

T-Cal: An optimal test of calibration





$$T_{m,n}^d = \sum_{\substack{1 \leq i \leq m \\ |\mathcal{I}_{m,i}| \geq 1}} \frac{1}{n|\mathcal{I}_{m,i}|} \sum_{j_1 \neq j_2 \in \mathcal{I}_{m,i}} [Y_{j_1} - f(X_{j_1})][Y_{j_2} - f(X_{j_2})]$$

-7.65×10^{-4} ✓ 1.60×10^{-5} ✓ ... 4.51×10^{-4} ✗ 2.67×10^{-4} ✓

✗ (f is mis-calibrated)

T-Cal: An optimal test of calibration



$$T_{m,n}^d = \sum_{\substack{1 \leq i \leq m \\ |\mathcal{I}_{m,i}| \geq 1}} \frac{1}{n|\mathcal{I}_{m,i}|} \sum_{j_1 \neq j_2 \in \mathcal{I}_{m,i}} [Y_{j_1} - f(X_{j_1})][Y_{j_2} - f(X_{j_2})]$$

-5.95×10^{-5} ✓ -1.48×10^{-4} ✓ \dots -2.33×10^{-4} ✓ -4.36×10^{-4} ✓

✓ (f is perfectly calibrated)

Overview

Overview

Calibration

T-Cal Method

Experiments

Optimality and lower bounds

Regression/Residual Function

- Recall: A classifier (probability predictor) $f : \mathbb{R}^d \rightarrow \Delta_{K-1}$ is calibrated if

$$\mathbb{E}[Y \mid f(X) = z] = z \quad \text{for any } z \in \Delta_{K-1}.$$

Regression/Residual Function

- Recall: A classifier (probability predictor) $f : \mathbb{R}^d \rightarrow \Delta_{K-1}$ is calibrated if

$$\mathbb{E}[Y \mid f(X) = z] = z \quad \text{for any } z \in \Delta_{K-1}.$$

- The calibration curve (*regression function*) $\text{reg}_f : \Delta_{K-1} \rightarrow \Delta_{K-1}$ is

$$\text{reg}_f(z) := \mathbb{E}[Y \mid f(X) = z].$$

We define the *residual function* (mis-calibration curve)

$\text{res}_f : \Delta_{K-1} \rightarrow \mathbb{R}^K$ as

$$\text{res}_f(z) := \text{reg}_f(z) - z.$$

Regression/Residual Function

- Recall: A classifier (probability predictor) $f : \mathbb{R}^d \rightarrow \Delta_{K-1}$ is calibrated if

$$\mathbb{E}[Y \mid f(X) = z] = z \quad \text{for any } z \in \Delta_{K-1}.$$

- The calibration curve (*regression function*) $\text{reg}_f : \Delta_{K-1} \rightarrow \Delta_{K-1}$ is

$$\text{reg}_f(z) := \mathbb{E}[Y \mid f(X) = z].$$

We define the *residual function* (mis-calibration curve)

$\text{res}_f : \Delta_{K-1} \rightarrow \mathbb{R}^K$ as

$$\text{res}_f(z) := \text{reg}_f(z) - z.$$

- In this language, the classifier f is calibrated if

$$\text{res}_f(Z) = 0,$$

almost surely w.r.t. the law of $Z = f(X)$.

Expected Calibration Error

- ▶ For any $p \geq 1$, the ℓ_p -ECE is

$$\begin{aligned}\ell_p\text{-ECE}_P(f) &= \mathbb{E}_{Z \sim P_Z} \left[\|\text{reg}_f(Z) - Z\|_p^p \right]^{\frac{1}{p}} \\ &= \mathbb{E}_{Z \sim P_Z} \left[\|\text{res}_f(Z)\|_p^p \right]^{\frac{1}{p}}.\end{aligned}$$

- ▶ $\ell_p\text{-ECE}_P(f) = 0$ iff f is calibrated under P

Hypothesis Testing Setup

- ▶ $\mathcal{P}_{s,L,K}$: distributions over $(f(X), Y) = (Z, Y) \in \Delta_{K-1} \times \mathcal{Y}$ under which $z \mapsto [\text{res}_{f,P}(z)]_k$ is (s, L) -Hölder continuous¹ for every $k \in \{1, \dots, K\}$.

¹for a Hölder smoothness parameter s and a Hölder constant L

Hypothesis Testing Setup

- ▶ $\mathcal{P}_{s,L,K}$: distributions over $(f(X), Y) = (Z, Y) \in \Delta_{K-1} \times \mathcal{Y}$ under which $z \mapsto [\text{res}_{f,P}(z)]_k$ is (s, L) -Hölder continuous¹ for every $k \in \{1, \dots, K\}$.
- ▶ Goal: Test the *null hypothesis* of calibration against the *alternative* of an ε -calibration error:

$$H_0 : P \in \mathcal{P}_0 \quad \text{versus} \quad H_1 : P \in \mathcal{P}_1(\varepsilon, p, s).$$

- ▶ Calibrated data distributions

$$\mathcal{P}_0 := \{P \in \mathcal{P}_{s,L,K} : \text{res}_{f,P}(Z) = 0, P_Z\text{-a.s.}\}.$$

- ▶ For separation rate $\varepsilon > 0$: $\mathcal{P}_1(\varepsilon, p, s)$, distributions P of (Z, Y) under which the ℓ_p -ECE of f is at least ε :

$$\mathcal{P}_1(\varepsilon, p, s) := \{P \in \mathcal{P}_{s,L,K} : \ell_p\text{-ECE}_P(f) \geq \varepsilon\}.$$

¹for a Hölder smoothness parameter s and a Hölder constant L

Reduction to two-sample testing: Intuition

- ▶ If a classifier is calibrated, then its probability predictions match the true class probabilities.

Reduction to two-sample testing: Intuition

- ▶ If a classifier is calibrated, then its probability predictions match the true class probabilities.
- ▶ Randomly sampling new labels according to the probability predictions yields a sample from the true distribution.

Reduction to two-sample testing: Intuition

- ▶ If a classifier is calibrated, then its probability predictions match the true class probabilities.
- ▶ Randomly sampling new labels according to the probability predictions yields a sample from the true distribution.
- ▶ After sample splitting, we can use classical two-sample tests to check if the two samples are from the same distribution.

Experiment




Figure: $s = 0.6$, $\rho = 100$

- Due to sample splitting, effective sample size is smaller than that of T-Cal.

Overview

Overview

Calibration

T-Cal Method

Experiments

Optimality and lower bounds

Plug-in Estimator

► Recall

$$\ell_2\text{-ECE}(f)^2 = \mathbb{E}_{Z \sim P_Z} [\|\text{reg}_f(Z) - Z\|_2^2]$$

► Given a partition $\mathcal{B}_m = \{B_1, \dots, B_{m^{K-1}}\}$ of Δ_{K-1} , with

$$\mathcal{I}_i := \{j \in \{1, \dots, N\} : Z_j \in B_i\},$$

the plug-in estimator for $\ell_2\text{-ECE}(f)^2$ by piecewise averaging is defined as

$$T_{m,n}^b := \sum_{\substack{i \in [m^{K-1}] \\ |\mathcal{I}_i| \geq 1}} \frac{|\mathcal{I}_i|}{n} \left\| \frac{1}{|\mathcal{I}_i|} \sum_{j \in \mathcal{I}_i} (Y_j - Z_j) \right\|^2. \quad (1)$$

Bias of the Plug-in Estimator

- Consider $K = 2$, $Z \sim P_Z = \text{Unif}[0, 1]$, $P_0 : P_Z \times \text{Ber}(Z)$ and $P_1 : P_Z \times \text{Ber}(\text{reg}_f(Z))$ depicted below (left).




Figure: Left: A graph of the calibration curve $z \mapsto \text{reg}_f(z)$ under P_1 . **Right:** Histograms of $T_{m,n}^b$ and $T_{m,n}^d$ under P_0 and P_1 are obtained from 1,000 independent observations.

Debiasing the Plug-in Estimator

- ▶ The plug-in estimator is biased, because we are estimating both $\mathbb{E}[Y \mid Z \in B_i]$ and $\mathbb{E}[Z \mid Z \in B_i]$ using the same sample $(Z_i, Y_i), i \in \{1, \dots, n\}$.

Debiasing the Plug-in Estimator

- ▶ The plug-in estimator is biased, because we are estimating both $\mathbb{E}[Y \mid Z \in B_i]$ and $\mathbb{E}[Z \mid Z \in B_i]$ using the same sample $(Z_i, Y_i), i \in \{1, \dots, n\}$.
- ▶ We define the *Debiased Plug-in Estimator* (DPE):

$$T_{m,n}^d = \sum_{\substack{i \in [m^K-1] \\ |\mathcal{I}_i| \geq 1}} \frac{1}{n|\mathcal{I}_i|} \left[\left\| \sum_{j \in \mathcal{I}_i} (Y_j - Z_j) \right\|^2 - \sum_{j \in \mathcal{I}_i} \|Y_j - Z_j\|^2 \right].$$

Debiasing the Plug-in Estimator

- ▶ The plug-in estimator is biased, because we are estimating both $\mathbb{E}[Y \mid Z \in B_i]$ and $\mathbb{E}[Z \mid Z \in B_i]$ using the same sample $(Z_i, Y_i), i \in \{1, \dots, n\}$.
- ▶ We define the *Debiased Plug-in Estimator* (DPE):

$$T_{m,n}^d = \sum_{\substack{i \in [m^K-1] \\ |\mathcal{I}_i| \geq 1}} \frac{1}{n|\mathcal{I}_i|} \left[\left\| \sum_{j \in \mathcal{I}_i} (Y_j - Z_j) \right\|^2 - \sum_{j \in \mathcal{I}_i} \|Y_j - Z_j\|^2 \right].$$

- ▶ The mean of $T_{m,n}^d$ is not exactly $\ell_2\text{-ECE}(f)^2$ under $P \in \mathcal{P}_1(\varepsilon, p, s)$, but debiasing makes it comparable to $\ell_2\text{-ECE}(f)^2$.

T-Cal: Debiased Plug-in Test

- ▶ We use $T_{m,n}^d$ as our test statistic.

$$\xi_{m,n}(\alpha) = \xi_{m,n} := \begin{cases} I \left(T_{m,n}^d \geq \sqrt{\frac{2K}{\alpha}} m^{\frac{K-1}{2}} n^{-1} \right) & \text{if } m^{K-1} \leq n, \\ I \left(T_{m,n}^d \geq \sqrt{\frac{2K}{\alpha}} m^{-\frac{K-1}{2}} \right) & \text{if } m^{K-1} > n. \end{cases}$$

T-Cal: Debiased Plug-in Test

- ▶ We use $T_{m,n}^d$ as our test statistic.

$$\xi_{m,n}(\alpha) = \xi_{m,n} := \begin{cases} I \left(T_{m,n}^d \geq \sqrt{\frac{2K}{\alpha}} m^{\frac{K-1}{2}} n^{-1} \right) & \text{if } m^{K-1} \leq n, \\ I \left(T_{m,n}^d \geq \sqrt{\frac{2K}{\alpha}} m^{-\frac{K-1}{2}} \right) & \text{if } m^{K-1} > n. \end{cases}$$

- ▶ One can choose critical values by bootstrapping (or, consistency resampling) in practice.

Main Theorem I

Theorem (T-Cal: Calibration test via debiased plug-in estimation)

Suppose $p \leq 2$. For $m^* = \lfloor n^{2/(4s+K-1)} \rfloor$, we have

1. **False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_{m^*,n} = 1) \leq \alpha$.

Main Theorem I

Theorem (T-Cal: Calibration test via debiased plug-in estimation)

Suppose $p \leq 2$. For $m^* = \lfloor n^{2/(4s+K-1)} \rfloor$, we have

- 1. False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_{m^*,n} = 1) \leq \alpha$.
- 2. True detection rate control.** There exists $c > 0$ depending on $(s, L, K, \nu_l, \nu_u, \alpha, \beta)$ such that the power (true positive rate) is bounded as $P(\xi_{m^*,n} = 1) \geq 1 - \beta$ for every $P \in \mathcal{P}_1(\varepsilon, p, s)$ —i.e., when f is mis-calibrated with an ℓ_p -ECE of at least


$$\varepsilon \geq cn^{-\frac{2s}{4s+K-1}}.$$

Combined with lower bounds we show, T-Cal is **minimax optimal** over Hölder smooth calibration curves

Adaptive T-Cal

For a number $B = \lceil \frac{2}{K-1} \log_2(n/\sqrt{\log n}) \rceil$ of tests performed, let

$$\xi_n^{\text{ad}} := \max_{b \in \{1, \dots, B\}} \xi_{2^b, n} \left(\frac{\alpha}{B} \right).$$



$$T_{m,n}^{\text{d}} = \sum_{\substack{1 \leq i \leq m \\ |\mathcal{I}_{m,i}| \geq 1}} \frac{1}{n|\mathcal{I}_{m,i}|} \sum_{j_1 \neq j_2 \in \mathcal{I}_{m,i}} [Y_{j_1} - f(X_{j_1})][Y_{j_2} - f(X_{j_2})]$$

-7.65×10^{-4} ✓ 1.60×10^{-5} ✓ \dots 4.51×10^{-4} ✗ 2.67×10^{-4} ✓

✗ (f is mis-calibrated)

Main Theorem II: Adaptive T-Cal

Theorem (Adaptive T-Cal)

Suppose $p \leq 2$. The adaptive test ξ_n^{ad} enjoys

1. **False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{ad}} = 1) \leq \alpha$.

Main Theorem II: Adaptive T-Cal

Theorem (Adaptive T-Cal)

Suppose $p \leq 2$. The adaptive test ξ_n^{ad} enjoys

1. **False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{ad}} = 1) \leq \alpha$.
2. **True detection rate control.** There exists $c_{\text{ad}} > 0$ depending on $(s, L, K, \nu_l, \nu_u, \alpha, \beta)$ such that the power (true positive rate) is lower bounded as $P(\xi_n^{\text{ad}} = 1) \geq 1 - \beta$ for every $P \in \mathcal{P}_1(\varepsilon, p, s)$ —i.e., when f is mis-calibrated with an ℓ_p -ECE of at least

$$\varepsilon \geq c_{\text{ad}}(n/\sqrt{\log n})^{-\frac{2s}{4s+K-1}}.$$

Overview

Overview

Calibration

T-Cal Method

Experiments

Optimality and lower bounds

Synthetic data

- ▶ We compare T-Cal with classical calibration tests [2, 9, 4, 10]:
 - ▶ Cox's Logistic Score test
 - ▶ test based on plug-in $\widehat{\ell_1}$ -ECE

Synthetic data

- ▶ We compare T-Cal with classical calibration tests [2, 9, 4, 10]:
 - ▶ Cox's Logistic Score test
 - ▶ test based on plug-in $\widehat{\ell_1\text{-ECE}}$
- ▶ $H_1 : (Z, Y) \sim P_{1,m}$




Figure: Calibration curve under $P_{1,m}$

Synthetic data results: T-Cal vs other tests




Figure: Comparison of calibration tests: T-Cal (with m^*) is more sample-efficient than other methods (with $n = 10,000$)

Synthetic data ablation: m^* , debiasing, ℓ_2 vs ℓ_1




Figure: Type II error comparison for $T_{m^*,n}^d$ (T-Cal), $T_{m^*,n}^b$, and $T_{m^*,n}^{\ell_1}$. Using ℓ_2 is better than ℓ_1 , and debiased ℓ_2 (T-Cal) is better than biased ℓ_2 . Standard error bars are plotted over 10 repetitions. m^* has largest effect.

Empirical data

- ▶ We test adaptive T-Cal on various deep neural networks trained on CIFAR-10/100 and ImageNet.

Empirical data

- ▶ We test adaptive T-Cal on various deep neural networks trained on CIFAR-10/100 and ImageNet.
- ▶ We test models calibrated by standard post-hoc methods (and uncalibrated ones).

Results on empirical data: CIFAR-10

	DenseNet 121		ResNet 50		VGG-19	
	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?
No Calibration	2.02%	reject	2.23%	reject	2.13%	reject
Platt Scaling	2.32%	reject	1.78%	reject	1.71%	reject
Poly. Scaling	1.71%	reject	1.29%	reject	0.90%	accept
Isot. Regression	1.16%	reject	0.62%	reject	1.13%	accept
Hist. Binning	0.97%	reject	1.12%	reject	1.28%	reject
Scal. Binning	1.94%	reject	1.21%	reject	1.67%	reject

Table 1: The values of the empirical ℓ_1 -ECE (Guo et al., 2017) and the testing results, via adaptive T-Cal and multiple binomial testing, of models trained on CIFAR-10.

Figure: Results roughly align with the magnitude of the empirical ECE.

Results on empirical data: CIFAR-100

	MobileNet-v2		ResNet 56		ShuffleNet-v2	
	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?
No Calibration	11.87%	reject	15.2%	reject	9.08%	reject
Platt Scaling	1.40%	accept	1.84%	accept	1.34%	accept
Poly. Scaling	1.69%	reject	1.91%	reject	1.81%	accept
Isot. Regression	1.76%	accept	2.33%	reject	1.38%	accept
Hist. Binning	1.66%	reject	2.44%	reject	2.77%	reject
Scal. Binning	1.85%	reject	1.57%	reject	1.65%	accept

Table 2: The values of the empirical ℓ_1 -ECE (Guo et al., 2017) and the testing results, via adaptive T-Cal and multiple binomial testing, of models trained on CIFAR-100.

Figure: Results roughly align with the magnitude of the empirical ECE. However, T-Cal *not the same as* ℓ_1 -ECE: see ResNet-56.

Results on empirical data: CIFAR-10, reliability diagrams




Figure: The reliability diagrams for VGG-19, trained on CIFAR-10, calibrated by Platt scaling (left - reject), polynomial scaling (middle - accept), and histogram binning (right - accept). Bins containing less than 10 data points, where the sample noise dominates, are omitted for clarity.

Results on empirical data: ImageNet

	DenseNet 161		ResNet 152		EfficientNet-b7	
	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?	$\widehat{\ell_1\text{-ECE}}$	Calibrated?
No Calibration	5.67%	reject	4.99%	reject	2.82%	reject
Platt Scaling	1.58%	reject	1.41%	reject	1.90%	reject
Poly. Scaling	0.62%	accept	0.64%	accept	0.71%	accept
Isot. Regression	0.63%	reject	0.80%	reject	1.06%	reject
Hist. Binning	0.46%	reject	1.26%	reject	0.88%	reject
Scal. Binning	1.55%	reject	1.40%	reject	1.97%	reject

Table 3: The values of the empirical ℓ_1 -ECE (Guo et al., 2017) and the testing results, via adaptive T-Cal and multiple binomial testing, of models trained on ImageNet.

Overview

Overview

Calibration

T-Cal Method

Experiments

Optimality and lower bounds

Impossibility for continuous mis-calibration curves

- ▶ If the mis-calibration curve can oscillate with arbitrarily high frequency, mis-calibration cannot be detected from a finite sample. (Caution when using complex models!)

Impossibility for continuous mis-calibration curves

- ▶ If the mis-calibration curve can oscillate with arbitrarily high frequency, mis-calibration cannot be detected from a finite sample. (Caution when using complex models!)
- ▶ Define minimax type II error for distributions in the alternative with continuous mis-calibration curves

$$R_n^{\text{cont}}(\varepsilon, p) := \inf_{\xi \in \Phi_n(\alpha)} \sup_{P \in \mathcal{P}_1^{\text{cont}}(\varepsilon, p)} P(\xi = 0).$$

Proposition

Let $\varepsilon_0 = 0.1$. For any level $\alpha \in (0, 1)$, the minimax type II error $R_n^{\text{cont}}(\varepsilon_0, p)$ for testing the null hypothesis of calibration at level α against the hypothesis $P \in \mathcal{P}_1^{\text{cont}}(\varepsilon_0, p)$ of continuous mis-calibration curves satisfies

$$R_n^{\text{cont}}(\varepsilon_0, p) \geq 1 - \alpha$$

for all n .

Hölder continuous calibration curves

- ▶ We consider detecting mis-calibration when the mis-calibration curves are Hölder continuous; as usual in nonparametric statistics [5, 8, 3, 6].

Hölder continuous calibration curves

- ▶ We consider detecting mis-calibration when the mis-calibration curves are Hölder continuous; as usual in nonparametric statistics [5, 8, 3, 6].
- ▶ Rich class of mis-calibration curves, including non-smooth ones.

Lower bound for Hölder continuous mis-calibration curve

- ▶ Test the calibration of the K -class probability predictor f assuming (s, L) -Hölder continuity of mis-calibration curves at a level $\alpha \in (0, 1)$.
- ▶ Minimax type II error

$$R_n(\varepsilon, p, s) := \inf_{\xi \in \Phi_n(\alpha)} \sup_{P \in \mathcal{P}_1(\varepsilon, p, s)} P(\xi = 0).$$

- ▶ Minimum separation needed for a minimax type II error of at most β

$$\varepsilon_n(p, s) = \inf\{\varepsilon' : R_n(\varepsilon', p, s) \leq \beta\}.$$

Lower bound for Hölder continuous mis-calibration curve

- ▶ Test the calibration of the K -class probability predictor f assuming (s, L) -Hölder continuity of mis-calibration curves at a level $\alpha \in (0, 1)$.
- ▶ Minimax type II error

$$R_n(\varepsilon, p, s) := \inf_{\xi \in \Phi_n(\alpha)} \sup_{P \in \mathcal{P}_1(\varepsilon, p, s)} P(\xi = 0).$$

- ▶ Minimum separation needed for a minimax type II error of at most β

$$\varepsilon_n(p, s) = \inf\{\varepsilon' : R_n(\varepsilon', p, s) \leq \beta\}.$$

Theorem

There exists $c_{\text{lower}} > 0$ depending only on $(p, s, L, K, \alpha, \beta)$ such that, for any $p > 0$, the minimum ℓ_p -ECE of f , i.e. $\varepsilon_n(p, s)$, required to have a test with a false positive rate (type I error) at most α and with a true positive rate (power) at least $1 - \beta$ satisfies

$$\varepsilon_n(p, s) \geq c_{\text{lower}} n^{-\frac{2s}{4s+K-1}}$$

for all n .

Context, continued

- ▶ Non-parametric rate $n^{-\frac{2s}{4s+K-1}}$ slower than parametric $n^{-1/2}$ rate. Slower as the number of classes K grows.

Context, continued

- ▶ Non-parametric rate $n^{-\frac{2s}{4s+K-1}}$ slower than parametric $n^{-1/2}$ rate. Slower as the number of classes K grows.
- ▶ What one expects based on nonparametric two-sample goodness-of-fit testing for densities on Δ_{K-1} [6].

Context, continued

- ▶ Non-parametric rate $n^{-\frac{2s}{4s+K-1}}$ slower than parametric $n^{-1/2}$ rate. Slower as the number of classes K grows.
- ▶ What one expects based on nonparametric two-sample goodness-of-fit testing for densities on Δ_{K-1} [6].
- ▶ T-Cal is minimax optimal.

Context, continued

- ▶ Non-parametric rate $n^{-\frac{2s}{4s+K-1}}$ slower than parametric $n^{-1/2}$ rate. Slower as the number of classes K grows.
- ▶ What one expects based on nonparametric two-sample goodness-of-fit testing for densities on Δ_{K-1} [6].
- ▶ T-Cal is minimax optimal.
- ▶ Evaluating multi-class model calibration on a small dataset can be challenging.

Summary and takeaways

- ▶ Uncertainty quantification important for ML. Calibration is a key problem with rich history.

Summary and takeaways

- ▶ Uncertainty quantification important for ML. Calibration is a key problem with rich history.
 1. **The need for statistical significance to claim calibration.**

Summary and takeaways

- ▶ Uncertainty quantification important for ML. Calibration is a key problem with rich history.
 1. **The need for statistical significance to claim calibration.**
 2. **Potential suboptimality of popular approaches.**

Summary and takeaways

- ▶ Uncertainty quantification important for ML. Calibration is a key problem with rich history.
 1. **The need for statistical significance to claim calibration.**
 2. **Potential suboptimality of popular approaches.**
- ▶ **T-Cal**: adaptive test for calibration of ML models; supported by empirical & theoretical results.
 - ▶ Available at <https://github.com/dh7401/Calibration-Test>

Reduction

- For $i \in \{\lfloor n/2 \rfloor + 1, \dots, n\}$, we generate random variables $\tilde{Y}_i \sim \text{Cat}(Z_i)$.

Reduction

- ▶ For $i \in \{\lfloor n/2 \rfloor + 1, \dots, n\}$, we generate random variables $\tilde{Y}_i \sim \text{Cat}(Z_i)$.
- ▶ For each $k \in \{1, \dots, K\}$, define

$$\mathcal{V}_k := \left\{ Z_i : [Y_i]_k = 1, 1 \leq i \leq \left\lfloor \frac{n}{2} \right\rfloor \right\},$$

$$\mathcal{W}_k := \left\{ Z_i : [\tilde{Y}_i]_k = 1, \left\lfloor \frac{n}{2} \right\rfloor + 1 \leq i \leq n \right\}.$$

Reduction

- ▶ For $i \in \{\lfloor n/2 \rfloor + 1, \dots, n\}$, we generate random variables $\tilde{Y}_i \sim \text{Cat}(Z_i)$.
- ▶ For each $k \in \{1, \dots, K\}$, define

$$\mathcal{V}_k := \left\{ Z_i : [Y_i]_k = 1, 1 \leq i \leq \left\lfloor \frac{n}{2} \right\rfloor \right\},$$

$$\mathcal{W}_k := \left\{ Z_i : [\tilde{Y}_i]_k = 1, \left\lfloor \frac{n}{2} \right\rfloor + 1 \leq i \leq n \right\}.$$

- ▶ \mathcal{V}_k and \mathcal{W}_k have densities

$$\pi_k^{\mathcal{V}}(z) := \frac{[\text{reg}_f(z)]_k}{\int_{\Delta_{K-1}} [\text{reg}_f(z)]_k dP_Z(z)} = \frac{[\text{reg}_f(z)]_k}{\mathbb{E}[Y]_k},$$

$$\pi_k^{\mathcal{W}}(z) := \frac{[z]_k}{\int_{\Delta_{K-1}} [z]_k dP_Z(z)} = \frac{[z]_k}{\mathbb{E}[Z]_k}$$

with respect to P_Z .

Reduction detail

- ▶ Let $TS_{\alpha,\beta}$ be an optimal two-sample goodness-of-fit test (e.g., due to Ingster, Arias-Castro et al., Kim et al., [5, 1, 7]).

Reduction detail

- ▶ Let $\text{TS}_{\alpha,\beta}$ be an optimal two-sample goodness-of-fit test (e.g., due to Ingster, Arias-Castro et al., Kim et al., [5, 1, 7]).
- ▶ For $k \in \{1, \dots, K\}$,

$$T_{1,k} = \frac{1}{n} \sum_{i=1}^n [Y_i - Z_i]_k,$$

$$T_{2,k} = \frac{1}{n} \sum_{i=1}^n [Z_i]_k [Y_i - Z_i]_k,$$

$$b_k = I \left(|T_{1,k}| \geq \sqrt{\frac{3K}{\alpha n}} \right) \vee I \left(|T_{2,k}| \geq \sqrt{\frac{3K}{\alpha n}} \right) \vee \text{TS}_{\frac{\alpha}{3K}, \frac{\beta}{2}}(\mathcal{V}_k, \mathcal{W}_k).$$

Reduction detail

- ▶ Let $\text{TS}_{\alpha,\beta}$ be an optimal two-sample goodness-of-fit test (e.g., due to Ingster, Arias-Castro et al., Kim et al., [5, 1, 7]).
- ▶ For $k \in \{1, \dots, K\}$,

$$T_{1,k} = \frac{1}{n} \sum_{i=1}^n [Y_i - Z_i]_k,$$

$$T_{2,k} = \frac{1}{n} \sum_{i=1}^n [Z_i]_k [Y_i - Z_i]_k,$$

$$b_k = I \left(|T_{1,k}| \geq \sqrt{\frac{3K}{\alpha n}} \right) \vee I \left(|T_{2,k}| \geq \sqrt{\frac{3K}{\alpha n}} \right) \vee \text{TS}_{\frac{\alpha}{3K}, \frac{\beta}{2}}(\mathcal{V}_k, \mathcal{W}_k).$$

- ▶ Reject H_0 if $\max\{b_1, \dots, b_K\} = 1$.

Main Result: Known smoothness

Theorem (Optimal calibration test via sample splitting)

Suppose $p \leq 2$ and let ξ_n^{split} be the test described in the previous slide. Assume the Hölder smoothness parameter s is known. We have

- 1. False detection rate control.** *For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{split}} = 1) \leq \alpha$.*

Main Result: Known smoothness

Theorem (Optimal calibration test via sample splitting)

Suppose $p \leq 2$ and let ξ_n^{split} be the test described in the previous slide. Assume the Hölder smoothness parameter s is known. We have

- False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{split}} = 1) \leq \alpha$.
- True detection rate control.** There exists $c_{\text{split}} > 0$ depending on $(s, L, K, \nu_l, \nu_u, d_c, \alpha, \beta)$ such that the power (true positive rate) is bounded as $P(\xi_n^{\text{split}} = 1) \geq 1 - \beta$ for every $P \in \mathcal{P}_1(\varepsilon, p, s)$ —i.e., when f is mis-calibrated with an ℓ_p -ECE of at least

$$\varepsilon \geq c_{\text{split}} n^{-\frac{2s}{4s+K-1}}.$$

Main Result: Adapting to smoothness

- Consider an adaptive two-sample goodness-of-fit test $\text{TS}_{\alpha,\beta}^{\text{ad}}$.

Corollary (Adaptive test via sample splitting)

Suppose $p \leq 2$ and let $\xi_n^{\text{ad-s}}$ be the test described above with TS replaced by an adaptive two-sample test TS^{ad} . We have

1. **False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{ad-s}} = 1) \leq \alpha$.

Main Result: Adapting to smoothness

- Consider an adaptive two-sample goodness-of-fit test $\text{TS}_{\alpha,\beta}^{\text{ad}}$.

Corollary (Adaptive test via sample splitting)

Suppose $p \leq 2$ and let $\xi_n^{\text{ad-s}}$ be the test described above with TS replaced by an adaptive two-sample test TS^{ad} . We have

- 1. False detection rate control.** For every P for which f is calibrated, i.e., for $P \in \mathcal{P}_0$, the probability of falsely claiming mis-calibration is at most α , i.e., $P(\xi_n^{\text{ad-s}} = 1) \leq \alpha$.
- 2. True detection rate control.** There exists $c_{\text{ad-s}} > 0$ depending on $(s, L, K, \nu_l, \nu_u, d_c, \alpha, \beta)$ such that the power (true positive rate) is bounded as $P(\xi_n^{\text{ad-s}} = 1) \geq 1 - \beta$ for every $P \in \mathcal{P}_1(\varepsilon, p, s)$ —i.e., when f is mis-calibrated with an ℓ_p -ECE of at least

$$\varepsilon \geq c_{\text{ad-s}}(n / \log \log n)^{-\frac{2s}{4s+K-1}}.$$

References I



Ery Arias-Castro, Bruno Pelletier, and Venkatesh Saligrama.

Remember the curse of dimensionality: The case of goodness-of-fit testing in arbitrary dimension.

Journal of Nonparametric Statistics, 30(2):448–471, 2018.



David R Cox.

Two further applications of a model for binary regression.

Biometrika, 45(3/4):562–565, 1958.



László Györfi, Michael Kohler, Adam Krzyżak, and Harro Walk.

A distribution-free theory of nonparametric regression, volume 1.

Springer, 2002.



Frank E Harrell.

Regression modeling strategies: with applications to linear models, logistic and ordinal regression, and survival analysis, volume 3.

Springer, 2015.

References II



Yu I Ingster.

Minimax testing of nonparametric hypotheses on a distribution density in the L_p metrics.

Theory of Probability & Its Applications, 31(2):333–337, 1987.



Yuri Ingster and Irina A Suslina.

Nonparametric goodness-of-fit testing under Gaussian models, volume 169.

Springer Science & Business Media, 2012.



Ilmun Kim, Sivaraman Balakrishnan, and Larry Wasserman.

Minimax optimality of permutation tests.

The Annals of Statistics, 50(1):225–251, 2022.



Mark G Low.

On nonparametric confidence intervals.

The Annals of Statistics, 25(6):2547–2554, 1997.

References III



Robert G Miller.

Statistical prediction by discriminant analysis.

In *Statistical Prediction by Discriminant Analysis*, pages 1–54. Springer, 1962.



Juozas Vaicenavicius, David Widmann, Carl Andersson, Fredrik Lindsten, Jacob Roll, and Thomas Schön.

Evaluating model calibration in classification.

In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3459–3467. PMLR, 2019.