

Generative Adversarial Nets and Application in Uncertainty Quantification

Yibo Yang

Department of Mechanical Engineering and Applied Mechanics, University of Pennsylvania,
Philadelphia, PA, 19104, USA

ybyang@seas.upenn.edu

April 25, 2019

Generative Adversarial Nets

GANs takes samples from a simple distribution $z \sim p(z)$, pass them through a Neural network $x = f_\theta(z)$ to approximate an unknown distribution $q(x)$ take their samples. The objective function is of the following form:

$$\mathbb{E}_{q(x)} \log(1 - \sigma(T_\psi(x))) + \mathbb{E}_{p(z)} \log \sigma(T_\psi(G_\theta(z))) \quad (1)$$

The results of the adversarial training are:

$$\begin{aligned}\hat{\psi} &= \arg \max_{\psi} \mathbb{E}_{q(x)} \log(1 - \sigma(T_\psi(x))) + \mathbb{E}_{p(z)} \log \sigma(T_\psi(G_\theta(z))) \\ \hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{p(z)} T_\psi(G_\theta(z))\end{aligned} \quad (2)$$

Here σ is the sigmoid function. ψ are the coefficients of the discriminator, θ are the coefficients for the generator.

Density ratio estimation by probabilistic classification

One may show that for fixed θ , the optimal solution for the discriminator is $T_\psi(x) = \log[\frac{p_\theta(x)}{q(x)}]$. In this case, the discriminator $T_\psi(x)$ is playing a role of estimating the log of density ratio $\frac{p_\theta(x)}{q(x)}$. Thus, the generator is playing the role that approximating of the KL divergence between $p_\theta(x)$ and $q(x)$:

$$\text{KL}[p_\theta(x) || q(x)] = \mathbb{E}_{p(z)} T_\psi(G_\theta(z)) \quad (3)$$

$$\begin{aligned} \text{KL}[p_\theta(x) || q(x)] &= \mathbb{E}_{p_\theta} \log \left[\frac{p_\theta(x)}{q(x)} \right] \\ &= -\mathbb{H}(p_\theta(x)) - \mathbb{E}_{p_\theta(x)} \log q(x) \end{aligned} \quad (4)$$

Distribution Matching and Mode Collapse in GANs




Figure: Left: Mode collapse. Right: No mode collapse.

$$\begin{aligned} \mathbb{KL}[p_\theta(x) || q(x)] &= \mathbb{E}_{p_\theta(x)} \log \left[\frac{p_\theta(x)}{q(x)} \right] \\ &= -\mathbb{H}(p_\theta(x)) - \mathbb{E}_{p_\theta(x)} \log q(x) \\ &= -\mathbb{H}(p_\theta(x)) - \int_{\mathcal{S}_{p_\theta} \cap \mathcal{S}_q^o} p_\theta(x) \log q(x) dx - \int_{\mathcal{S}_{p_\theta} \cap \mathcal{S}_q} p_\theta(x) \log q(x) dx \end{aligned} \quad (5)$$

Li, C., Li, J., Wang, G., & Carin, L. (2018). Learning to Sample with Adversarially Learned Likelihood-Ratio.

Mode Collapse in GANs

Classical GANs would not suffer the risk to explore outside the support domain of the empirical distribution $q(x)$. This is so-called mode collapse issue.


Reverse KL:

$$\text{KL}[p_\theta(x) || q(x)] = -\mathbb{H}[p_\theta(x)] - \mathbb{E}_{p_\theta(x)}[\log q(x)]$$

$$= -\mathbb{H}[p_\theta(x)]$$

$$- \int_{\mathcal{S}_{p_\theta} \cap \mathcal{S}_q} \log q(x)p_\theta(x)dx$$

$$- \int_{\mathcal{S}_{p_\theta} \cap \mathcal{S}_q^o} \log q(x)p_\theta(x)dx$$



$p_\theta(x)$: **Generative model distribution**

$q(x)$: **Empirical data distribution**

Use $-\lambda \mathbb{H}(p_\theta(x)) - \mathbb{E}_{p_\theta(x)} \log q(x)$ instead of $\text{KL}[p_\theta(x) || q(x)]$ with $\lambda > 1$.

Mitigate Mode Collapse in GANs by Entropy Regularization

Construct a computable lower bound for the entropy $\mathbb{H}(p_\theta(\mathbf{x}))$.

$$\mathbb{I}(\mathbf{x}; \mathbf{z}) = \mathbb{H}(\mathbf{x}) - \mathbb{H}(\mathbf{x}|\mathbf{z}) = \mathbb{H}(\mathbf{z}) - \mathbb{H}(\mathbf{z}|\mathbf{x}),$$

$$p_\theta(\mathbf{x}, \mathbf{z}) = p_\theta(\mathbf{x}|\mathbf{z})p(\mathbf{z}),$$

Since in our setup, samples of $p_\theta(\mathbf{x}|\mathbf{z})$ are generated by a deterministic function $f_\theta(\mathbf{z})$, it follows that $\mathbb{H}(\mathbf{x}|\mathbf{z}) = 0$. We therefore have

$$\mathbb{H}(\mathbf{x}) = \mathbb{H}(\mathbf{z}) - \mathbb{H}(\mathbf{z}|\mathbf{x}), \quad (6)$$

where $\mathbb{H}(\mathbf{z}) := -\int \log p(\mathbf{z})p(\mathbf{z})d\mathbf{z}$ does not depend on the generative model parameters θ . Now consider a general variational distribution $q_\phi(\mathbf{z}|\mathbf{x})$ parametrized by a set of parameters ϕ . Then,

$$\begin{aligned} \mathbb{H}(\mathbf{z}|\mathbf{x}) &= -\mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{z})}[\log(p_\theta(\mathbf{z}|\mathbf{x}))] \\ &= -\mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{z})}[\log(q_\phi(\mathbf{z}|\mathbf{x}))] \\ &\quad - \mathbb{E}_{p_\theta(\mathbf{x})}[\mathbb{KL}[p_\theta(\mathbf{z}|\mathbf{x})||q_\phi(\mathbf{z}|\mathbf{x})]] \\ &\leq -\mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{z})}[\log(q_\phi(\mathbf{z}|\mathbf{x}))]. \end{aligned} \quad (7)$$

Entropy Regularization

Construct a computable lower bound for the entropy $\mathbb{H}(p_\theta(\mathbf{x}, \mathbf{y}))$.

$$\mathbb{H}(p_\theta(\mathbf{x})) \geq \mathbb{H}(\mathbf{z}) + \mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{z})}[\log(q_\phi(\mathbf{z}|\mathbf{x}))]. \quad (8)$$

Then,

$$-\lambda \mathbb{H}(p_\theta(\mathbf{x})) - \mathbb{E}_{p_\theta(\mathbf{x})} \log q(\mathbf{x}) \quad (9)$$

$$= -(\lambda - 1) \mathbb{H}(p_\theta(\mathbf{x})) - \mathbb{H}(p_\theta(\mathbf{x})) - \mathbb{E}_{p_\theta(\mathbf{x})} \log q(\mathbf{x}) \quad (10)$$

$$= -(\lambda - 1) \mathbb{H}(p_\theta(\mathbf{x})) + \mathbb{KL}[p_\theta(\mathbf{x})||q(\mathbf{x})] \quad (11)$$

$$\leq (1 - \lambda) \{\mathbb{H}(\mathbf{z}) + \mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{z})}[\log(q_\phi(\mathbf{z}|\mathbf{x}))]\} + \mathbb{KL}[p_\theta(\mathbf{x})||q(\mathbf{x})] \quad (12)$$

Matching Joint Distribution

$$\mathcal{L}_{\mathcal{D}}(\psi) = \mathbb{E}_{q(x)p(z)}[\log \sigma(T_\psi(f_\theta(z)))] + \mathbb{E}_{q(x)}[\log(1 - \sigma(T_\psi(x)))] \quad (13)$$


$$\mathcal{L}_{\mathcal{G}}(\theta, \phi) = \mathbb{E}_{q(x)p(z)}[T_\psi(f_\theta(z)) + (1 - \lambda) \log(q_\phi(z|f_\theta(z)))] \quad (14)$$

the generative model can be trained by alternating between optimizing the two objectives in equations using stochastic gradient descent as

$$\max_{\psi} \mathcal{L}_{\mathcal{D}}(\psi) \quad (15)$$

$$\min_{\theta, \phi} \mathcal{L}_{\mathcal{G}}(\theta, \phi). \quad (16)$$

Distribution matching using GANs with entropy regularization



GANs for Uncertainty Quantification

We consider the uncertainty quantification for the regression task.

$$y = p_{\theta}(x, z), \quad z \sim p(z) \quad (17)$$




Figure: Linear Regression UQ.

Matching Joint Distribution Suffers Mode Collapse

Use simple GANs to do conditional generative model:

$$\begin{aligned}\mathcal{L}_{\mathcal{D}}(\psi) &= \mathbb{E}_{q(\mathbf{x})p(\mathbf{z})}[\log \sigma(T_{\psi}(\mathbf{x}, f_{\theta}(\mathbf{x}, \mathbf{z})))] + \\ &\quad \mathbb{E}_{q(\mathbf{x}, \mathbf{y})}[\log(1 - \sigma(T_{\psi}(\mathbf{x}, \mathbf{y})))]\end{aligned}\tag{18}$$

$$\mathcal{L}_{\mathcal{G}}(\theta, \phi) = \mathbb{E}_{q(\mathbf{x}, \mathbf{y})p(\mathbf{z})}[T_{\psi}(\mathbf{x}, f_{\theta}(\mathbf{x}, \mathbf{z}))]\tag{19}$$





Figure: Linear Regression Mode Collapse.

Mode Collapse in GANs

Classical GANs would not suffer the risk to explore outside the support domain of the empirical distribution $q(\mathbf{x}, \mathbf{y})$. This is so-called mode collapse issue.

$$\text{Reverse KL: } \text{KL} [p_\theta(\mathbf{x}, \mathbf{y}) || q(\mathbf{x}, \mathbf{y})] = -\mathbb{H} [p_\theta(\mathbf{x}, \mathbf{y})] - \mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{y})} [\log q(\mathbf{x}, \mathbf{y})]$$



$$= -\int_{S_{p_\theta} \cap S_q} \log q(\mathbf{x}, \mathbf{y}) p_\theta(\mathbf{x}, \mathbf{y}) d\mathbf{x} d\mathbf{y}$$
$$- \int_{S_{p_\theta} \cap S_q^o} \log q(\mathbf{x}, \mathbf{y}) p_\theta(\mathbf{x}, \mathbf{y}) d\mathbf{x} d\mathbf{y}$$

$p_\theta(\mathbf{x}, \mathbf{y})$: **Generative model distribution** $q(\mathbf{x}, \mathbf{y})$: **Empirical data distribution**

Try $-\lambda \mathbb{H}(p_\theta(\mathbf{x}, \mathbf{y})) - \mathbb{E}_{p_\theta(\mathbf{x}, \mathbf{y})} \log q(\mathbf{x}, \mathbf{y})$ instead of $\text{KL}[p_\theta(\mathbf{x}, \mathbf{y}) || q(\mathbf{x}, \mathbf{y})]$ with $\lambda > 1$.

Matching Joint Distribution

$$\mathcal{L}_{\mathcal{D}}(\psi) = \mathbb{E}_{q(\mathbf{x})p(\mathbf{z})}[\log \sigma(T_{\psi}(\mathbf{x}, f_{\theta}(\mathbf{x}, \mathbf{z})))] + \mathbb{E}_{q(\mathbf{x}, \mathbf{y})}[\log(1 - \sigma(T_{\psi}(\mathbf{x}, \mathbf{y})))] \quad (20)$$

$$\mathcal{L}_{\mathcal{G}}(\theta, \phi) = \mathbb{E}_{q(\mathbf{x}, \mathbf{y})p(\mathbf{z})}[T_{\psi}(\mathbf{x}, f_{\theta}(\mathbf{x}, \mathbf{z})) + (1 - \lambda) \log(q_{\phi}(\mathbf{z}|\mathbf{x}, f_{\theta}(\mathbf{x}, \mathbf{z})))], \quad (21)$$

the generative model can be trained by alternating between optimizing the two objectives in equations using stochastic gradient descent as

$$\max_{\psi} \mathcal{L}_{\mathcal{D}}(\psi) \quad (22)$$

$$\min_{\theta, \phi} \mathcal{L}_{\mathcal{G}}(\theta, \phi). \quad (23)$$

Comparison with Gaussian Processes and Bayesian Neural Networks on Linear Regression

We consider 3 cases:

- (i) *Gaussian homoscedastic noise:*

$$y = f(x) + \delta, \quad (24)$$


- (ii) *Gaussian heteroscedastic noise:*

$$y = f(x) + \delta(x), \quad (25)$$

- (iii) *Non-additive, non-Gaussian noise:*

$$y = f(x, \delta(x)) \quad (26)$$

Comparison with GP and BNN



Physics Informed Neural Networks

For a given differential equation: $u_t + \mathcal{N}[u] = 0$, one defines the residual function:

$$r := u_t + \mathcal{N}[u] \quad (27)$$

The function used for training remains:

$$\text{MSE} = \text{MSE}_u + \text{MSE}_r \quad (28)$$

where

$$\text{MSE}_u = \frac{1}{N_u} \sum_{i=1}^{N_u} |u(t_u^i, x_u^i) - u^i|^2, \quad (29)$$

and

$$\text{MSE}_r = \frac{1}{N_r} \sum_{i=1}^{N_r} |r(t_r^i, x_r^i)|^2, \quad (30)$$


Where, $\{t_u^i, x_u^i, u^i\}_{i=1}^{N_u}$ are training data corresponding to the initial conditions and boundary conditions. $\{t_r^i, x_r^i\}_{i=1}^{N_r}$ are the collocation points within the computational domain.

Physics Informed Neural Networks on Simple ODE

$$\frac{d^2 u(x)}{dx^2} - u(x) = f(x), \quad x \in [-1, 1] \quad (31)$$

$$u(-1) = 0, u(1) = 0$$

where $f(x) = -(\pi^2 + 1) \sin(\pi x)$. $N_u = 2$, $N_r = 100$.



Physics Informed Deep Generative Model

Satisfying the PDE constraint by simply minimizing the mean square loss on collocation points

$$\mathcal{L}_{PDE}(\theta) = \frac{1}{N_r} \sum_{i=1}^{N_r} \|r_\theta(\mathbf{x}_i, t_i)\|^2. \quad (32)$$

with

$$\begin{aligned} \mathcal{L}_{\mathcal{D}}(\psi) &= \mathbb{E}_{q(\mathbf{x}, t)p(\mathbf{z})}[\log \sigma(T_\psi(\mathbf{x}, t, f_\theta(\mathbf{x}, t, \mathbf{z})))] + \\ &\quad \mathbb{E}_{q(\mathbf{x}, t, \mathbf{u})}[\log(1 - \sigma(T_\psi(\mathbf{x}, t, \mathbf{u})))] \end{aligned} \quad (33)$$

$$\mathcal{L}_{\mathcal{G}}(\theta, \phi) = \mathbb{E}_{q(\mathbf{x}, t)p(\mathbf{z})}[T_\psi(\mathbf{x}, t, f_\theta(\mathbf{x}, t, \mathbf{z}))] \quad (34)$$

$$+ (1 - \lambda) \log(q_\phi(\mathbf{z}|\mathbf{x}, t, f_\theta(\mathbf{x}, t, \mathbf{z}))), \quad (35)$$

Then, the resulting adversarial game for training the physics-informed model:

$$\begin{aligned} &\max_{\psi} \mathcal{L}_{\mathcal{D}}(\psi) \\ &\min_{\theta, \phi} \mathcal{L}_{\mathcal{G}}(\theta, \phi) + \beta \mathcal{L}_{PDE}(\theta), \end{aligned} \quad (36)$$

Physics Informed GANs on Simple ODE

Let us illustrate the basic capabilities of the proposed methods through a simple example corresponding to the following nonlinear second-order ordinary differential equation

$$\begin{aligned} u_{xx} - u^2 u_x &= f(x), \quad x \in [-1, 1], \\ f(x) &= -\pi^2 \sin(\pi x) - \pi \cos(\pi x) \sin^2(\pi x), \end{aligned} \tag{37}$$

subject to random boundary conditions $u(-1), u(1) \sim \mathcal{N}(\mathbf{0}, \sigma_n^2 \mathbf{I})$. For this simple example, the deterministic solution corresponding to $\sigma_n^2 = 0$ can be readily obtained as $u(x) = \sin(\pi x)$. Given N_u observations of $u(x)$ corresponding to different realizations of the random boundary conditions our goal is to obtain a probabilistic representation of the solution $p_\theta(u|x, z)$ by training a physics-informed generative model of the form $u = f_\theta(x, z)$, $z \sim p(z)$ that satisfies the physics constrained.

Physics Informed GANs on Simple ODE




Figure: Predicted marginal densities against the reference Monte Carlo solution.
(a) $p_\theta(u|x = -0.5, z)$. (b) $p_\theta(u|x = +0.5, z)$.

Shock Capturing in PDEs





Figure: Shock wave in aerospace dynamics.

In the classical numerical methods of partial differential equations, it is hard to predict or capture the shock wave due to the nature of discretization.




Ami Harten 1947-1994
The developer of TVD &
ENO schemes. We'll always
miss your originality in
science and in life.
R.I.P., (2003)

Figure: Left: Stanley Osher. Middle:
Ami Harten. Right: Chi-Wang Shu.


Physics Informed GANs on Burgers Equation

We test a more challenging canonical problem involving the non-linear time-dependent Burgers equation in one spatial dimension:

$$\begin{aligned} u_t + uu_x - \nu u_{xx} &= 0, & x \in [-1, 1], t \in [0, 1], \\ u(0, x) &= -\sin(\pi x), \\ u(t, -1) &= u(t, 1) = 0, \end{aligned} \tag{38}$$



(a)



(b)

Figure: Burgers equation: (a) Exact initial condition and noise-free training data. (b) Training data corresponding to a single realization of the non-additive noise corruption process.

Physics Informed GANs on Burgers Equation




Figure: Burgers equation with noise-free data: *Top*: Mean of $p_\theta(u|x, t, z)$, along with the location of the noisy training data $\{(x_i, t_i), u_i\}$, $i = 1, \dots, N_u$. *Middle*: Prediction and predictive uncertainty at $t = 0.25$, $t = 0.5$ and $t = 0.75$. *Bottom*: Variance of $p_\theta(u|x, t, z)$.

Physics Informed GANs on Burgers Equation




Figure: Burgers equation with noisy data: *Top*: Mean of $p_\theta(u|x, t, z)$, along with the location of the training data $\{(x_i, t_i), u_i\}$, $i = 1, \dots, N_u$. *Middle*: Prediction and predictive uncertainty at $t = 0.25$, $t = 0.5$ and $t = 0.75$. *Bottom*: Variance of $p_\theta(u|x, t, z)$.

References

-  Yang, Yibo, and Paris Perdikaris. "Physics-informed deep generative model." arXiv preprint arXiv:1811.04026 (2018).
-  Yang, Yibo, and Paris Perdikaris. "Adversarial Uncertainty Quantification in Physics-Informed Neural Networks." arXiv preprint arXiv:1811.04026 (2018).
-  Yang, Yibo, and Paris Perdikaris. "Conditional deep surrogate models for stochastic, high-dimensional, and multi-fidelity systems." arXiv preprint arXiv:1901.04878 (2019).
-  Raissi, M., P. Perdikaris, and G. E. Karniadakis. "Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations." Journal of Computational Physics 378 (2019): 686-707.
-  LeCun, Yann, Yoshua Bengio, and Geoffrey Hinton. "Deep learning." nature 521, no. 7553 (2015): 436.
-  Goodfellow, Ian, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. "Generative adversarial nets." In Advances in neural information processing systems, pp. 2672-2680. 2014.
-  Li, Chunyuan, Jianqiao Li, Guoyin Wang, and Lawrence Carin. "Learning to Sample with Adversarially Learned Likelihood-Ratio." (2018).
-  Mirza, Mehdi, and Simon Osindero. "Conditional generative adversarial nets." arXiv preprint arXiv:1411.1784 (2014).

References

-  Berthelot, David, Colin Raffel, Aurko Roy, and Ian Goodfellow. "Understanding and improving interpolation in autoencoders via an adversarial regularizer." arXiv preprint arXiv:1807.07543 (2018).
-  Zhu, Yinhao, and Nicholas Zabaras. "Bayesian deep convolutional encoderdecoder networks for surrogate modeling and uncertainty quantification." Journal of Computational Physics 366 (2018): 415-447.
-  Radford, Alec, Luke Metz, and Soumith Chintala. "Unsupervised representation learning with deep convolutional generative adversarial networks." arXiv preprint arXiv:1511.06434 (2015).
-  Ma, Chao, Yingzhen Li, and Jos Miguel Hernndez-Lobato. "Variational Implicit Processes." arXiv preprint arXiv:1806.02390 (2018).
-  Makhzani, Alireza, Jonathon Shlens, Navdeep Jaity, Ian Goodfellow, and Brendan Frey. "Adversarial autoencoders." arXiv preprint arXiv:1511.05644 (2015).
-  Yang, Liu, Dongkun Zhang, and George Em Karniadakis. "Physics-informed generative adversarial networks for stochastic differential equations." arXiv preprint arXiv:1811.02033 (2018).
-  Parussini, Lucia, Daniele Venturi, Paris Perdikaris, and George E. Karniadakis. "Multi-fidelity Gaussian process regression for prediction of random fields." Journal of Computational Physics 336 (2017): 36-50.

The End