



Read on your phone



Watch our video

# Video Graph Transformer for Video Question Answering


Junbin Xiao, Pan Zhou, Tat-Seng Chua and Shuicheng Yan  
Sea AI Lab (SAIL) & National University of Singapore (NUS)



Data & Code

## Introduction:

Existing transformer-style models only demonstrate their success in answering questions that involve the coarse recognition or description of video contents. Their performances are either unknown or weak in answering questions that challenge real-world **visual relation reasoning**, especially the **causal** and **temporal** relations that feature **video dynamics at action and event level**. Cross-modal pretraining seems promising, yet it requires the handling of million-scale video-text data.



MSRVT-QA & MSVD-QA [Xu et al, MM'17]:

Who is looking at the dog? Lady.

What is the dog doing? Sitting.

NExT-QA[Xiao et al, CVPR'21]:


Why did the woman walk towards the table in the middle of the video? Clean the table.




## Method:

We propose Video Graph Transformer (VGT) to improve previous arts in answering relation-type questions from two major aspects:

- **Video Encoding:** Dynamic Graph Transformer (DGT) that explicitly encodes the visual objects, their relations and dynamics, for spatial and temporal relation reasoning.
- **Contrastive Learning:** we design *separate* video and text transformers to encode video and QA information respectively for contrastive learning, instead of cross-modal transformer for answer classification. Fine-grained vision-text information communication is done by additional lightweight cross-modal interaction modules.



### ➤ Contrastive Learning



$$\mathcal{L}_*(x, x^+, x^-) = -\mathbb{E}_i[\log(\frac{e^{\text{svgt}(x_i, x_i^+)}}{e^{\text{svgt}(x_i, x_i^+)} + \sum_{(x_i, x_j^-) \in \mathcal{N}_i} e^{\text{svgt}(x_i, x_j^-)}})]$$

### ➤ Dynamic Graph Transformer

#### • Spatial-temporal:

Consider contextual graphs to improve the graphs obtained at static frames.

#### • Compositional:

Summarize local/atomic interactions to global activities.




Illustration of the 4 stages to encode a video clip.

- Cross-modal Interaction  $x^{qv} = x^v + \sum_{m=1}^M \beta_m x_m^q$ , where  $\beta = \sigma(x^v (X^q)^\top)$
- $x^v$ : visual representations, e.g.,  $F^{\text{DGT}}$
- $x^q$ : textual representations, e.g., Outputs from BERT.

## Experiment:





### ➤ SoTA Comparison.

Methods	NExT-Val	NExT-Test	Methods	TGIF-FQA	MSRVT T-QA
VQA-T*[ICCV'21]	45.30	44.54	HCRN[CVPR'20]	55.9	35.6
HQGA[AAAI'22]	51.42	51.75	ClipBERT[CVPR'21]	60.3	37.4
VQA-T* (PT)	52.32	50.83	HQGA[AAA'22]	61.3	38.6
P3D-G[AAAI'22]	53.40	-	MERRLOT(PT)	<b>69.5</b>	<b>43.1</b>
VGT (Ours)	<u>55.02</u>	<u>53.68</u>	VGT (Ours)	<u>61.6</u>	39.7
VGT(PT)	<b>56.89</b>	<b>55.70</b>			

Methods	TGIF-QA		TGIF-QA-R*	
	Act	Trans	Act	Trans
PGAT[MM'21]	80.6	85.7	58.7	65.9
ClipBERT[CVPR'21]	82.8	87.8	-	-
MERLOT[NeurIPS'21]	94.0	96.2	-	-
VGT (Ours)	<b>95.0</b>	<b>97.6</b>	<u>59.9</u>	<u>70.5</u>
VGT(PT)	-	-	<b>60.5</b>	<b>71.5</b>

### ➤ Ablation Study

Models	TGIF-QA		NExT-QA Val			
	Action	Trans	Acc@C	Acc@T	Acc@D	Acc@All
VGT	<b>95.0</b>	<b>97.6</b>	<b>52.28</b>	<b>55.09</b>	64.09	<b>55.02</b>
w/o DGT	89.6	95.4	50.10	52.85	64.48	53.22
w/o TTrans	94.0	97.6	50.86	53.04	64.86	53.74
w/o ETrans	94.5	97.4	50.79	54.22	63.32	53.84
w/o ETrans	94.8	97.4	51.25	54.34	64.48	54.30
w/o $F_I$	93.5	97.0	50.44	53.97	63.32	53.58
Comp→CLS	70.1	79.9	42.96	46.96	53.02	45.82



## Conclusion:

- We propose **video graph transformer** to advance VideoQA from coarse recognition and description to fine-grained visual reasoning in dynamic scenarios, and we achieve **SOTA** results on related benchmarks.
- We propose **dynamic graph transformer** to encode visual graph dynamics for relation reasoning in space-time. Most importantly, we demonstrate that **contrastive learning** significantly outperforms classification for multi-choice cross-modal video reasoning.
- We are the 1<sup>st</sup> to shown that **pretraining visual graph transformer** can benefit video-language understanding towards a more data-efficient and fine-grained direction.