

## Appendix A

# A Proofs of Lemmas 1, 2 and Theorem 4.5 from Chapter 4

*All's well that ends well*

### A.1 Proof of Lemma 1

For the sake of convenience, let's repeatedly adduce the basic definition used in Lemma 1 and the formulation of this lemma.

**Definition.** Let  $B$  be an arbitrary conceptual basis,  $n \geq 1$ , for  $i = 1, \dots, n$ ,  $c_i \in D(B)$ ,  $s = c_1 \dots c_n$ ,  $1 \leq k \leq n$ . Then let the expressions  $lt_1(s, k)$  and  $lt_2(s, k)$  denote the number of the occurrences of the symbol  $'('$  and the symbol  $'<'$  respectively in the substring  $c_1 \dots c_k$  of the string  $s = c_1 \dots c_n$ .

Let the expressions  $rt_1(s, k)$  and  $rt_2(s, k)$  designate the number of the occurrences of the symbol  $')'$  and the symbol  $'>'$  into the substring  $c_1 \dots c_k$  of the string  $s$ . If the substring  $c_1 \dots c_k$  doesn't include the symbol  $'('$  or the symbol  $'<'$ , then let respectively

$$lt_1(s, k) = 0, lt_2(s, k) = 0,$$

$$rt_1(s, k) = 0, rt_2(s, k) = 0.$$

**Lemma 1.** Let  $B$  be an arbitrary conceptual basis,  $y \in Ls(B)$ ,  $n \geq 1$ , for  $i = 1, \dots, n$ ,  $c_i \in D(B)$ ,  $y = c_1 \dots c_n$ . Then

(a) if  $n > 1$ , then for every  $k = 1, \dots, n - 1$  and every  $m = 1, 2$

$$lt_m(y, k) \geq rt_m(y, k);$$

$$(b) \quad lt_m(y, n) = rt_m(y, n).$$

**Proof.** Let's agree that for arbitrary sequence  $s \in Ds^+(B)$ , the length of  $S$  ( the number of elements from  $Ds(B)$  ) will be denoted as  $l(s)$  or  $Length(s)$ .

Let  $B$  be an arbitrary conceptual basis,  $y \in Ls(B)$ ,  $n \geq 1$ , for  $I = 1, \dots, n$ ,  $c_i \in D(B)$ ,  $y = c_1 \dots c_n$ . If  $n = 1$ , then it immediately follows from the rules  $P[0], P[1], \dots, P[10]$  that  $y \in X(B) \cup V(B)$ .

According to the definition of conceptual basis, the symbols from the sets  $X(B)$  and  $V(B)$  are distinct from the symbols  $'('$ ,  $')'$ ,  $'<'$ ,  $'>'$ . That is why

$$lt_1(y, n) = rt_1(y, n) = 0,$$

$$lt_2(y, n) = rt_2(y, n) = 0.$$

If  $n > 1$ , then  $y$  has been constructed with the help of some rules from the list  $P[1], \dots, P[10]$  (in addition to the rule  $P[0]$ ). Let's prove the lemma by induction, using the number  $q$  of the applications of the rules  $P[1], \dots, P[10]$  for building  $y$  as the parameter of induction.

**Part 1.** Let's assume that  $q = 1$ .

**Case 1.1.** Let a string  $y$  be obtained by applying just one time the rule  $P[2]$  or  $P[4]$ . Then

$$y = f(u_1, \dots, u_m) \text{ or } y = r(u_1, \dots, u_m),$$

where  $m \geq 1$ ,  $f \in F(B)$ ,  $r \in R(B)$ ,

$$u_1, \dots, u_m \in X(B) \cup V(B).$$

Obviously, in this situation

$$lt_1(y, 1) = rt_1(y, 1) = 0, \quad lt_1(y, n) = rt_1(y, n) = 1,$$

for  $1 < k < n$ ,  $lt_2(y, k) = 1$ ,  $rt_2(y, k) = 0$ ,

for  $k = 1, \dots, n$   $lt_2(y, k) = rt_2(y, k) = 0$ .

**Case 1.2.** If  $y$  is obtained by applying the rule  $P[3]$ , then there are such elements  $u_1, u_2 \in X(B) \cup V(B)$ , that  $y = (u_1 \equiv u_2)$ . Then for  $k = 1, \dots, n - 1$ ,

$$lt_1(y, k) = 1, \quad rt_1(y, k) = 0,$$

$$lt_1(y, n) = rt_1(y, n) = 1,$$

for  $k = 1, \dots, n$ ,

$$lt_2(y, k) = rt_2(y, k) = 0.$$

**Case 1.3.** Let's suppose that the string  $y$  is constructed as a result of applying just one time the rule  $P[7]$ , and with this aim the binary logical connective  $bin \in \{\wedge, \vee\}$  and the elements  $d_1, \dots, d_m \in X(B) \cup V(B)$ , where  $m > 1$ , were used. Then

$$y = (d_1 \text{ bin } d_2 \text{ bin } \dots \text{ bin } d_m).$$

Therefore, for  $k = 1, \dots, n - 1$ ,

$$lt_1(y, k) = 1, \quad rt_1(y, k) = 0,$$

$$lt_1(y, n) = 1, \quad rt_1(y, n) = 1,$$

for  $k = 1, \dots, n$ ,  $lt_2(y, k) = rt_2(y, k) = 0$ .

**Case 1.4.** If  $y$  is obtained by applying just one time the rule  $P[1]$  or  $P[6]$ , then  $y$  doesn't contain the symbols  $'(, ' ', ' \langle, ' \rangle'$ . Then

$$lt_1(y, k) = rt_1(y, k) = lt_2(y, k) = rt_2(y, k) = 0$$

for  $k = 1, \dots, n$ .

**Case 1.5.** The analysis of the rule  $P[9]$  shows that the string  $y$  couldn't be constructed from the elements of the sets  $X(B)$  and  $V(B)$  by means of applying just one time the rule  $P[9]$  (and, possibly, the rule  $P[0]$ ).

Supposing that it is not true we have  $y = Qv(\text{concept})\text{descr}$ , where  $Q \in \{\forall, \text{exists}\}$ ,  $v \in V(B)$ ,  $\text{concept} \in X(B)$ ,  $\text{descr} \& P \in Ts(B)$ , where  $P$  is the sort "a meaning of proposition." But the string  $\text{des}$  is to include the variable  $v$ , where  $tp(v) = [\text{entity}]$ . That is why  $\text{descr} = v$ . This relationship contradicts the relationship  $\text{descr} \& P \in Ts(B)$ .

**Case 1.6.** If the string  $y$  was obtained by applying one time the rule  $P[10]$ ,  $y$  doesn't include the symbols  $'('$ ,  $')$ , and the first symbol of  $y$  is  $'\langle'$ . Then for  $k = 1, \dots, n$ ,

$$lt_1(y, k) = 1, rt_1(y, k) = 0,$$

for  $k = 1, \dots, n-1$ ,  $lt_2(y, k) = 1, rt_2(y, k) = 0$ ,

$$lt_2(y, n) = rt_2(y, n) = 1.$$

**Part 2.** Let such  $q \geq 1$  exist that the statements (a), (b) of Lemma 1 are valid for every string  $y$  constructed out of the elements from the sets  $X(B)$  and  $V(B)$  by applying not more than  $q$  times the rules  $P[1], \dots, P[10]$  (and, possibly, by applying arbitrarily many times the rule  $P[0]$ ).

Let's prove that in this case the statements (a), (b) are true for every string  $y$  obtained by applying  $q+1$  times the rules from the list  $P[1], \dots, P[10]$ . Consider possible cases.

**Case 2.1.**  $y = f(a_1, \dots, a_m)$  or  $y = r(a_1, \dots, a_m)$ , where  $m > 1$ . For  $a_1, \dots, a_m$  the conditions (a), (b) are satisfied. That is why, obviously,

$$lt_1(y, 1) = rt_1(y, 1) = 0,$$

$$lt_1(y, 2) = 1, rt_1(y, 2) = 0;$$

for  $i = 3, \dots, n-1$ ,

$$lt_1(y, i) > rt_1(y, i), lt_1(y, n) = rt_1(y, n).$$

**Case 2.2.** If  $y$  is the string  $(a_1 \equiv a_2)$ , then it follows from the inductive assumption that

$$lt_1(y, 1) = 1, rt_1(y, 1) = 0,$$

for  $i = 2, \dots, n-1$ ,  $lt_1(y, n) = rt_1(y, n)$ .

**Case 2.3.** Let such a binary logical connective  $b \in \{\wedge, \vee\}$ , such  $m > 1$ , and such strings  $a_1, \dots, a_m$  exist that  $y$  was obtained from  $b, a_1, \dots, a_m$  by applying just one time the rule  $P[7]$ . Then

$$y = (a_1 b a_2 b \dots b a_m).$$

Let  $Length(a_1) = n_1, \dots, Length(a_m) = n_m$ . Obviously, for  $a_1, \dots, a_m$  the statements (a), (b) of Lemma 1 are valid. Let's notice that the connective  $b$  is located in  $y$  in the positions

$$n_1 + 2, n_1 + n_2 + 3, n_1 + \dots + n_m + (m + 1);$$

then

$$lt_1(y, 1) = 1, rt_1(y, 1) = 0;$$

for  $p = n_1 + 2, n_1 + n_2 + 3, n_1 + n_2 + \dots + n_m + m + 1,$

$$rt_1(y, p) = lt_1(y, p) - 1;$$

for  $i = 1, \dots, m - 1$  and for every such  $p$  that

$$n_1 + \dots + n_i + i + 1 < p < n_1 + \dots + n_i + n_{i+1} + i + 2.$$

$$rt_1(y, p) \leq lt_1(y, p) - 1;$$

$$lt_1(y, n) = rt_1(y, n).$$

## A.2 Proof of Lemma 2

For the sake of convenience, let's repeatedly adduce the formulation of Lemma 2 from Sect. 3.8.

**Lemma 2.** Let  $B$  be an arbitrary conceptual basis,  $y \in Ls(B)$ ,  $n > 1$ ,  $y = c_1 \dots c_n$ , where for  $i = 1, \dots, n$ ,  $c_i \in D(B)$ , the string  $y$  includes the comma or any of the symbols  $\equiv, \wedge, \vee$ , and  $k$  be such arbitrary natural number that  $1 < k < n$ . Then

(a) if  $c_k$  is one of the symbols  $\equiv, \wedge, \vee$ , then

$$lt_1(y, k) > rt_1(y, k) \geq 0;$$

(b) if  $c_k$  is the comma, then at least one of the following relationships takes place:

$$lt_1(y, k) > rt_1(y, k) \geq 0,$$

$$lt_2(y, k) > rt_2(y, k) \geq 0.$$

**Proof.** Let for  $B$  and  $y$  the assumptions of Lemma 2 are true, and

$$Symb = \{\equiv, \wedge, \vee\}.$$

Since  $y$  contains at least one of the elements of the set  $Symb$ , the string  $y$  is constructed out of the elements of the set  $X(B) \cup V(B)$  and several auxiliary symbols

by applying  $r$  times, where  $r \geq 1$ , some rules from the list  $P[1], \dots, P[10]$  (and, possibly, by applying several times the rule  $P[0]$ ).

Let's prove the lemma by induction on  $r$ .

**Case 1.** If  $r = 1$ , then the truth of the goal statement for  $y$  immediately follows from the analysis of all situations considered in Part 1 of the proof of Lemma 1.

**Case 2 (inductive step).** Let such  $r \geq 1$  exist that the statement of the lemma is true for arbitrary conceptual basis and for every such  $y \in Ls(B)$  that in the process of constructing  $y$ ,  $m$  rules from the list  $P[1], \dots, P[10]$  were used, where  $1 \leq m \leq r$ . Let's prove that in this case the statement of the lemma is true and for every such  $z \in Ls(B)$  that, while constructing  $y$ ,  $r + 1$  rules from the list  $P[1], \dots, P[10]$  were used.

**Case 2.1a.** Let the rule  $P[7]$  be used on the last step of constructing the string  $z$ . Then the string  $z$  can be represented in the form

$$z = (y_1 q y_2 q \dots q y_m),$$

where  $m > 1$ ,  $q \in \{\wedge, \vee\}$ , for  $i = 1, \dots, m$ ,  $y_i \in Ls(B)$ . According to inductive assumption, for constructing every string from the strings  $y_1, \dots, y_m$ , the rules  $P[1], \dots, P[10]$  were employed not more than  $r$  times.

Let  $2 < k < l(y_1) + 1$ . Then, obviously, the symbol  $c_k$  is an inner element of the string  $y_1$ . According to inductive assumption, if  $lt_1(y_1, k - 1) > 0$ , then  $lt_1(y_1, k - 1) > rt_1(z, k - 1)$ ; if  $lt_2(y_1, k - 1) > 0$ , then  $lt_2(y_1, k - 1) > rt_2(y_1, k - 1)$ .

But  $lt_1(z, k) = lt_1(y_1, k - 1) + 1$ ,  $rt_1(z, k) = rt_1(y_1, k - 1)$ , that is why  $lt_1(z, k) > rt_1(z, k)$ .

Besides,  $lt_2(z, k) = lt_2(y_1, k - 1)$ ,  $rt_2(z, k) = rt_2(y_1, k - 1)$ .

That is why, in accordance with inductive assumption, if  $lt_2(z, k) > 0$ , then  $lt_2(z, k) > rt_2(z, k)$ .

**Case 2.1b.** Let's assume, as above, that the rule  $P[7]$  was employed at the last step of constructing the string  $z$  and that the string  $z$  can be represented in the form

$$(y_1 q y_2 q \dots q y_m),$$

where  $m > 1$ ,  $q \in \{\wedge, \vee\}$ , for  $i = 1, \dots, m$ ,  $y_i \in Ls(B)$ . Besides, let there be such  $i$ ,  $1 \leq i \leq m$ , that

$$1 + l(y_1) + 1 + \dots + l(y_i) + 2 < k < 1 + l(y_1) + 1 + \dots + l(y_i) + 1 + l(y_{i+1}),$$

where  $l(y_h) = \text{Length}(y_h)$ ,  $h = 1, \dots, i + 1$ . This means that the symbol  $c_k$  is an inner element of a certain substring  $y_{i+1} \in Ls(B)$ .

Let the  $k$ th position of the considered string  $z$  coincide with the  $p$ -th position of the string  $y_{i+1}$ . Then

$$lt_1(z, k) = 1 + lt_1(y_1, l(y_1)) + \dots + lt_1(y_i, l(y_i)) + lt_1(y_{i+1}, p),$$

$$rt_1(z, k) = rt_1(y_1, l(y_1)) + \dots + rt_1(y_i, l(y_i)) + rt_1(y_{i+1}, p).$$

In accordance with Lemma 1, for  $j = 1, \dots, i$ ,

$$\begin{aligned} lt_1(y_j, l(y_j)) &= rt_1(y_j, \\ l(y_j)), lt_2(y_j, l(y_j)) &= rt_2(y_j, l(y_j)), \\ lt_1(y_{j+1}, p) &\geq rt_1(y_{j+1}, p). \end{aligned}$$

That is why  $lt_1(z, k) > rt_1(z, k)$ .

**Case 2.1c.** Let there exist such  $m > 1$ ,  $y_1, \dots, y_m \in Ls(B)$ ,  $q \in \{\wedge, \vee\}$  that

$$z = (y_1 q y_2 q \dots q y_m),$$

and there is such  $i$ ,  $1 \leq i < m$  that

$$k = 1 + l(y_1) + 1 + \dots + l(y_i) + 1 = l(y_1) + \dots + l(y_i) + i + 1.$$

This means that  $c_k$  is an occurrence of the logical connective  $q$ , separating  $y_i$  and  $y_{i+1}$ . It follows from Lemma 1 that for  $s = 1, \dots, i$ ,

$$lt_1(y_s, l(y_s)) = rt_1(y_s, l(y_s)).$$

That is why

$$\begin{aligned} lt_1(z, k) &= 1 + lt_1(y_1, l(y_1)) + \dots + lt_1(y_i, l(y_i)), \\ rt_1(z, k) &= rt_1(y_1, l(y_1)) + \dots + rt_1(y_i, l(y_i)). \end{aligned}$$

Therefore,  $lt_1(z, k) = rt_1(z, k) + 1$ .

**Case 2.2.** During the last step of constructing the string  $z$ , the rule  $P[3]$  has been used. In this situation, there are such  $y_0, y_2 \in Ls(B)$  that  $z$  can be represented in the form  $(y_0 \equiv y_2)$ . Obviously, this situation can be considered similar to the Case 2.1 for  $m = 2$ .

**Case 2.3.** On the last step of constructing the string  $z$ , one of the rules  $P[2]$  or  $P[4]$  was applied. Then there are such  $y_1, \dots, y_n \in Ls(B)$  that  $z$  can be represented in the form  $f(y_1, \dots, y_n)$  or in the form  $r(y_1, \dots, y_n)$  respectively, where  $f$  is an  $n$ -functional symbol,  $r$  is an  $n$ -ary relational symbol. Obviously, this case is considered similar to the Case 2.1.

**Case 2.4.** During the final step of constructing the string  $z$ , one of the rules  $P[8]$  or  $[9]$  or  $[10]$  has been used. These cases are to be considered similar to the Case 2.1 too.

### A.3 Proof of Theorem 4.5

Let there be an arbitrary conceptual basis,  $z \in Ls(B) \setminus (X(B) \cup V(B))$ . Then it directly follows from the structure of the rules  $P[0]$ ,  $P[1]$ ,  $\dots$ ,  $P[10]$  and the

definition of the set  $Ls(B)$  the existence of such  $k$ , where  $1 \leq k \leq 10$ ,  $n \geq 1$ , and  $y_0, y_1, \dots, y_n \in Ls(B)$  that

$$y_0 \& y_1 \& \dots \& y_n \& z \in Ynr_{10}^k(B).$$

That is why the main attention is to be paid to proving the uniqueness of such  $n+3$ -tuple  $(k, n, y_0, \dots, y_n)$ . Remember that, in accordance with the definition from Sect. 3.8, for arbitrary conceptual basis,

$$D(B) = X(B) \cup V(B) \cup \{', '(', ')', ':', '*', '\langle', '\rangle'\},$$

$$Ds(B) = D(B) \cup \{'\&'\},$$

$D^+(B)$  and  $Ds^+(B)$  are the sets of all non empty finite sequences of the elements from  $D(B)$  and  $Ds(B)$  respectively.

Suppose that  $B$  is an arbitrary conceptual basis,  $z$  is an arbitrary formula from  $Ls(B) \setminus (X(B) \cup V(B))$ ,  $1 \leq k \leq 10$ ,  $n \geq 1$ , and  $y_0, y_1, \dots, y_n$  are such formulas from  $Ls(B)$  that

$$y_0 \& y_1 \& \dots \& y_n \& z \in Ynr_{10}^k(B).$$

Let's prove that in this case the  $n+3$ -tuple  $(k, n, y_0, \dots, y_n)$  is the only such  $n+3$ -tuple that for this tuple the above relationship takes place. For achieving this goal, it is necessary to consider rather many possible cases.

The length of arbitrary string  $s \in Ds^+(B)$  (the number of elements from  $Ds(B)$ ) will denote, as before,  $l(s)$ . With respect to our agreement, the elements of arbitrary primary informational universe  $X(B)$  and the variables from the set  $V(B)$  are considered as symbols, i.e as non structured elements. That is why the length  $l(d)$  of arbitrary  $d \in (X(B) \cup V(B))$  is equal to 1. The number 0 will be considered as the length of empty string  $e$ .

**Case 1.** The first symbol of the string  $z$ , denoted as  $z[1]$ , is the left parenthesis “(”. Then, obviously,  $k = 3$  or  $k = 7$ . If  $k = 3$ , then  $n = 2$ , and  $z$  is the string of the form  $(y_0 \equiv y_2)$ , and  $y_1$  is the symbol  $\equiv$ .

If  $k = 7$ , then  $n \geq 2$ ,  $y_0$  is the logical connective  $\vee$  or  $\wedge$ , and  $z$  is the string of the form

$$(y_1 y_0 y_2 y_0 \dots y_0 y_n).$$

That is,  $z$  is the string of the form  $(y_1 \wedge y_2 \wedge \dots \wedge y_n)$  in case  $y_0 = \wedge$  and the string of the form  $(y_1 \vee y_2 \vee \dots \vee y_n)$  in case  $y_0 = \vee$ .

Suppose that  $z$  is the string of the form  $(y_0 \equiv y_2)$ ,  $y_0, y_2 \in D^+(B)$  and prove that it is impossible to present  $z$  in a different way. It will be a proof by contradiction.

**Case 1a.** Suppose that there are such  $w_1, w_2 \in Ls(B)$  that  $l(y_1) > l(w_1)$ , and  $z$  can be represented in the form  $(w_1 \equiv w_2)$ . Then the string  $w_1 \equiv$  is the beginning of the string  $y_0$ . Let there be such  $k, m$  that

$$1 \leq k < m, y_1 = c_1 \dots c_m,$$

$$w_1 = c_1 \dots c_k,$$

where  $c_1 \dots c_m \in D(B)$ . Then  $c_{k+1} = ' \equiv '$ , and, since no one string from  $Ls(B)$  has no ending being the symbol  $' \equiv '$ , the inequality  $k+1 < m$  is valid.

Since  $y_0$  includes the symbol  $' \equiv '$ , then the string  $y_1$  includes the left parenthesis  $'('$  in a certain position  $j < k+1$ . That is why

$lt_1(y_1, k+1) > 0$ . But it follows from the relationship  $c_{k+1} = ' \equiv '$  (in accordance with Lemma 2) that

$$lt_1(y_0, k+1) > rt_1(y_0, k+1).$$

Obviously,

$$lt_1(y_0, k+1) = lt_1(w_1, k),$$

$$rt_1(y_0, k+1) = rt_1(w_1, k).$$

That is why  $lt_1(w_1, k) > rt_1(w_1, k)$ . However, with respect to Lemma 1, it follows from  $w_1 \in Ls(B)$  and  $k = l(w_1)$  that

$$lt_1(w_1, k) = rt_1(w_1, k).$$

Therefore, a contradiction has been obtained.

Similar speculations can be fulfilled in case of the assumption about the existence of such  $w_1, w_2 \in Ls(B)$  that

$$l(w_1) > l(y_0),$$

$$l(w_2) < l(y_2),$$

$$z = (w_1 \equiv w_2).$$

That is why such  $w_1$  and  $w_2$  don't exist.

**Case 1b.** Let's assume, as before, that the string  $z$  can be presented in the form  $(y_0 \equiv y_2)$ , where  $y_0, y_2 \in D^+(B)$ . Suppose also that there are such  $q \in \{\wedge, \vee\}$ ,  $m > 1$ , and  $w_1, \dots, w_m \in Ls(B)$  that

$$z = (w_1 q w_2 q \dots q w_m).$$

Obviously,  $l(w_1) \neq l(y_2)$ . Let  $l(y_0) < l(w_1)$ . Then the string  $y_0 \equiv$  is a beginning of the string  $w_1 \in Ls(B)$ . Taking this into account, we easily receive a contradiction, repeating the speculations of the Case 1a.

If  $l(w_1) < l(y_0)$ , the string  $w_1 q$  is a beginning of the string  $y_0 \in Ls(B)$ . In this case we again apply the Lemma 2 and the way of reasoning used in the process of considering Case 1a.

Therefore, if  $z \in Ls(B)$  and for some  $y_0, y_2 \in Ls(B)$ ,  $z$  is a string of the form  $(y_0 \equiv y_2)$ , where  $y_0, y_2 \in D^+(B)$ , then the string  $z$  can't be obtained with the help of any rule (on the final step of inference) being different from the rule [3], and only from the "blocks"  $y_0, y_2$ .

**Case 1c.** Let there be such  $q \in \{\wedge, \vee\}$ ,  $m > 1$ , and  $y_1, \dots, y_m \in Ls(B)$  that

$$z = (y_1 q y_2 q \dots q y_m).$$



Then it is necessary to consider two situations:

1. there are such  $u_1, u_2 \in Ls(B)$  that  $z$  is the string of the form  $(u_1 \equiv u_2)$ ;
2. there are such  $p > 1, w_1, \dots, w_p \in Ls(B), d \in \{\wedge, \vee\}$  that

$$z = (w_1 d w_2 d \dots d w_p),$$

besides, the  $m+1$ -tuple  $(q, y_1, \dots, y_m)$  is distinct from the  $m+1$ -tuple  $(d, w_1, \dots, w_p)$ .

Consider the situation (1). Let  $l(u_1) < l(y_1)$ , then  $u_1, y_1 \in Ls(B)$ , and the string  $u_1 \equiv$  is a beginning of the string  $y_1$ . This situation was analyzed in Case 1, where we obtained a contradiction.

If  $l(y_1) < l(u_1)$ , then  $u_1, y_1 \in Ls(B)$ , and the string  $y_1 q$  is a beginning of the string  $u_1$ ; that is why, obviously,  $l(y_1 q) < l(u_1)$ .

Let's use the Lemma 2. Suppose that

$$y_1 q = c_1 \dots c_r c_{r+1},$$

where for  $i = 1, \dots, r+1, c_i \in D(B), c_{r+1} = q$ .

Since  $c_{r+1}$  is the symbol  $' \equiv '$ , it follows from Lemma 2 that

$$lt_1(u_1, r+1) > rt_1(u_1, r+1).$$

But we have the relationships

$$lt_1(u_1, r+1) = lt_1(u_1, r) = lt_1(y_1, r),$$

$$rt_1(u_1, r+1) = rt_1(u_1, r) = rt_1(y_1, r).$$

But, since  $y_1 \in Ls(B)$ , it follows from Lemma 1 that

$$lt_1(y_1, r) = rt_1(y_1, r).$$

We have obtained a contradiction.

Let's analyze the situation (2). Suppose that  $l(w_1) < l(y_1)$ . Then  $w_1, y_1 \in Ls(B)$ , and the string  $w_1 d$  is a beginning of  $y_1$ , where  $d$  is one of the symbols  $\wedge, \vee$ . But in this case we are able to obtain a contradiction exactly in the same way as while analyzing the situation (1).

Obviously, the case  $l(y_1) < l(w_1)$  is symmetric to the just considered case. Let's assume that  $q = d$ , and there is such  $j, 1 \leq j < m$  that

$$y_1 = w_1, \dots, y_j = w_j,$$

but  $w_{j+1} \neq y_{j+1}$ . Then either the string  $w_{j+1} d$  is a beginning of the string  $y_{j+1}$  or  $y_{j+1} d$  is a beginning of  $w_{j+1}$ . That is why we are in the situation considered above.

Thus, the analysis of the Case 1 has been finished. We have proved the following intermediary statement:

Let  $B$  be an arbitrary conceptual basis,  $z \in Ls(B)$   
:  $(X(B)) \cap V(B)$ , and the first symbol of the string  $z$  is the left parenthesis  $'('$ .

Then there is such unique  $n + 3$ -tuple  $(k, n, y_0, \dots, y_n)$ , where  $1 \leq k \leq 10$ ,  $n \geq 1$ ,  $y_0, y_1, \dots, y_n \in Ls(B)$  that

$$y_0 \& y_1 \& \dots \& y_n \& z \in Lnr_{10}^k(B);$$

in this case,  $k = 3$  or  $k = 7$ .

**Case 2.** Let  $B$  be an arbitrary conceptual basis,  $z$  be an arbitrary formula from  $Ls(B)$  :  $(X(B) \cup V(B))$ ,  $1 \leq k \leq 10$ , and  $y_0, y_1, \dots, y_n$  are such formulas from  $Ls(B)$  that the relationship above takes place.

Suppose that  $z$  has a beginning being a functional symbol, i.e.,  $z[1] \in F(B)$ , and that the second before the end symbol  $z$  is distinct from the symbol  $' : '$ . Then it immediately follows from the structure of the rules  $P[0], P[1], \dots, P[10]$  that the string  $z$  is obtained as a result of applying the rule  $P[2]$  at the last step of inference. That is why  $z = f(y_1, \dots, y_n)$ , where  $n \geq 1$ ,  $y_1, \dots, y_n \in Ls(B)$ .

If  $f \in F_1(B)$ , i.e.,  $f$  is an unary functional symbol, then  $n = 1$ , and  $y_1$  is unambiguously determined by  $z$ . Suppose that  $n > 1$ ,  $f \in F_n(B)$ , and there is such a sequence  $u_1, \dots, u_n$  being distinct from the sequence  $y_1, \dots, y_n$  that  $u_1, \dots, u_n \in Ls(B)$ , and string  $(y_1, \dots, y_n)$  coincides with the string  $(u_1, \dots, u_n)$ .

Applying Lemma 2 similarly to the way of reasoning used while considering Case 1c, it is easy to show that the existence of two different representations  $(y_1, \dots, y_n)$  and  $(u_1, \dots, u_n)$  of the string  $z \in Ls(B)$  is impossible due to the same reason as two different representations

$(y_1 d y_2 d \dots d y_n)$  and  $(u_1 d u_2 d \dots d u_n)$ , where  $d \in \{\wedge, \vee\}$ , are impossible.

**Case 3.** Let the assumptions of the formulation of the Theorem 4.5 be true for the conceptual basis  $B$  and the string  $z$ ; this string  $z$  has the beginning  $z[1]$  being a relational symbol, and  $z[1]$  is not a functional symbol (that is,  $z[1] \in R(B) \setminus F(B)$ ), and the second from the end symbol of the string  $z$  is distinct from the symbol  $' : '$ . This situation is similar to the Case 2, only  $z$  is constructed as a result of employing the rule  $P[4]$  at the last step of inference.

That is why there exists the only (for  $z$ ) such sequence  $(k, n, y_0, \dots, y_n)$  that  $1 \leq k \leq 10$ ,  $n \geq 1$ ,

$$y_0, y_1, \dots, y_n \in Ls(B),$$

$$y_0 \& y_1 \& \dots \& y_n \& z \in Ynr_{10}^k(B),$$

where  $k = 4$ .

**Case 4.** Let  $B$  be an arbitrary conceptual basis,  $z \in Ls(B)$  setminus  $(X(B) \cup V(B))$ , for  $i = 1, \dots, l(z)$ ,  $z[i]$  the  $i$ -th symbol of the string  $z$ ,  $z[1] \in X(B)$ ,  $z[2] = ' * '$ , the next to last symbol  $z$  is distinct from the symbol  $' : '$ . Then it directly follows from the rules  $P[0], P[1], \dots, P[10]$  that for constructing the string  $z$ , the rule  $P[8]$  has been employed during the last step of inference. That is why there are such  $p \geq 1$  and a sequence  $(r_1, b_1, \dots, r_p, b_p)$ , where for  $i = 1, \dots, p$ ,  $r_i \in R_2(B)$ ,  $b_i \in Ls(B)$ , that if  $a = z[1]$ , then

$$z = a * (r_1, b_1) \dots (r_p, b_p).$$

We must now prove that for every  $n + 3$ -tuple  $(k, n, y_0, \dots, y_n)$ , such that  $1 \leq k \leq 10$ ,  $n \geq 1$ , for  $i = 0, \dots, n$ ,  $y_i \in Ls(B)$ , it follows from the relationship

$$y_0 \& y_1 \& \dots \& y_n \& z \in Ynr_{10}^k(B)$$

that the  $n + 3$ -tuple  $(k, n, y_0, \dots, y_n)$  coincides with the tuple

$$(8, 2p + 1, a, r_1, b_1, \dots, r_p, b_p).$$

The relationship  $z = a * (r_1, b_1) \dots (r_p, b_p)$  implies that it is necessary to consider only the following situation: there are such

$$m \geq 1, h_1, \dots, h_m \in R_2(B), d_1, \dots, d_m \in Ls(B)$$

that

$$Z = a * (h_1, d_1) \dots (h_m, d_m),$$

and this representation is distinct from the representation

$$z = a * (r_1, b_1) \dots (r_p, b_p).$$

The elements  $a, r_1, \dots, r_p, h_1, \dots, h_m$  are interpreted as symbols. That is why, obviously,  $r_1 = h_1$ .

Let  $d_1 \neq b_1$  and  $l(b_1) < l(d_1)$ . Then the string  $b_1$  is a beginning of the string  $d_1$ . Using the Lemma 2 and Lemma 1 similar to the way of reasoning in the course of considering the Cases 1a and 1c, we obtain a contradiction. Therefore,  $b_1 = d_1$ .

Let there be such  $i$  that  $1 \leq i \leq \min p, m$  and for  $j = 1, \dots, I$ ,

$$r_j = h_j, b_j = d_j,$$

$$r_{j+1} = h_{j+1}, b_{j+1} \neq d_{j+1}.$$

Then it follows from  $l(b_{j+1}) < l(d_{j+1})$  that the string  $b_{j+1}$  is a beginning of the string  $d_{j+1}$ , but we've just analyzed a similar situation.

If  $l(b_{j+1}) < l(d_{j+1})$ , the string  $(d_{j+1})$  is a beginning of the string  $b_{j+1}$ , and we encounter, in essence, the same situation. Therefore, the representations

$$z = a * (r_1, b_1) \dots (r_p, b_p),$$

$$Z = a * (h_1, d_1) \dots (h_m, d_m),$$

coincide.

**Case 5.** Suppose that for the conceptual basis  $B$  and the string  $z$ , the assumptions of the formulation of the Theorem 3.5 are true,  $z[1]$  is the quantifier  $\forall$  or  $\exists$ , the symbol  $z[n - 1] \neq '!$ , where  $n = \text{Length}(z)$ . Then, obviously, the rule  $P[9]$  was applied at the last step of building the string  $Z$ . That is why  $z$  is the string of the form

$$Q \text{ var}(\text{conc}) A,$$

where  $Q = z[1]$ ,  $var \in V(B)$ ,  $conc, A \in Ls(B)$ ,  $conc \in X(B)$  or  $conc$  is such a string that for constructing it, the rule  $P[8]$  was applied at the last step of inference, and  $A \& P \in Ts(B)$ , where  $P$  is the sort “a meaning of proposition” of the basis  $B$ .

Let  $l(z) = m$  (that is,  $m$  is the length of  $z$ ). If  $conc \in X(B)$ , then the uniqueness of the representation of  $z$  is obvious:

$$Q = z[1], v = z[2], '( = z[3],$$

$$conc = z[4], ') = z[5], A = z[6] \dots z[m].$$

If  $conc \in Ls(B) \setminus (X(B) \cup V(B))$ , then let's use the Lemma 1.

Let  $l(conc) = p$ , where  $p > 1$  then for  $i = 1, \dots, p$ ,

$$lt_1(conc, i) \geq rt_1(conc, i);$$

$$lt_1(conc, p) = rt_1(conc, p).$$

That is why for  $q = 1, \dots, p+3$ ,

$$lt_1(z, q) > rt_1(z, q),$$

$$lt_1(z, p+4) = rt_1(z, p+4).$$

Therefore, the position of the right parenthesis  $' )'$  immediately after the string  $conc$  can be defined as such minimal integer  $s$  *leq* 1 that

$$lt_1(z, s) > rt_1(z, s),$$

$$lt_1(z, s) = rt_1(z, s).$$

That is why, if  $z \in Ls(B)$  and  $z[1]$  is the quantifier  $Q$ , where  $Q = \forall$  or  $Q = \exists$ , then there exists the only such  $n+3$ -tuple  $(k, n, y_0, \dots, y_n)$ , where  $1 \leq k \leq 10$ ,  $n \geq 1$ ,  $y_0, y_1, \dots, y_n \in Ls(B)$ , that

$$y_0 \& y_1 \& \dots \& y_n \& z \in Ynr_{10}^k(B);$$

besides,  $k = 9$ ,  $n = 4$ ,  $y_0 = Q$ ,  $y_1 = v$ ,  $y_3 = conc$ ,  $y_4 = A$  (with respect to the relationship  $z = Q var(conc) A$ ).

**Case 6.** Suppose that the assumptions of the formulation of the Theorem 3.5 are true for the conceptual basis  $B$  and the string  $z$ ,  $z[1] = '($ , and the next to last symbol  $z$  is distinct from  $':$  (colon). Then, obviously, the rule  $P[10]$  was used at the last step of constructing  $z$ . Assume that there exists such sequence  $m, u_1, \dots, u_m$  and a different sequence  $n, y_1, \dots, y_n$ , where  $m, n \geq 1$ ,  $u_1, \dots, u_m, y_1, \dots, y_n \in Ls(B)$ , that  $z$  can be represented in two forms

$$\langle u_1, \dots, u_m \rangle,$$

$$\langle langle y_1, \dots, y_n \rangle.$$

Applying Lemma 2 similar to the way of reasoning in Case 2, we conclude that two different representations of  $z$  are impossible due to the same reason as the impossibility of two different representations  $f(u_1, \dots, u_m)$  and  $f(y_1, \dots, y_n)$  of the same string from  $Ls(B)$ .

**Case 7.** Let the assumptions of the Theorem 4.5 be true for the conceptual basis  $B$  and the string  $z$ ,  $z[1]$  be an intensional quantifier from  $Int(B)$ ,  $z$  has no ending of the form  $:v$ , where  $v \in V(B)$ ,  $m = l(z)$ . Then, obviously,  $z$  can be obtained with the help of the rule with the number  $k = 1$  out of the “blocks”  $y_1 = z[1]$  and  $y_2 = z[2] \in z[m]$ .

**Case 8.** Let  $B$  be an arbitrary conceptual basis,  $z \in Ls(B) \setminus (X(B) \setminus V(B))$ ,  $z[1] = \neg$ . Then there is such string  $y \in Ls(B)$  that  $z = \neg y$ . The analysis of the structure of the rules  $P[0], P[1], \dots, P[10]$  shows that only two situations are possible: (1)  $y$  has no ending  $:v$ , where  $v \in V(B)$ , that is why  $z$  was constructed out of the pair  $(\neg, y)$  as a result of employing the rule  $P[6]$ ; (2)  $y = w : v$ , where  $v \in V(B)$ ; in this case,  $z$  was built out of the pair of operands  $(\neg w, v)$  by applying one time the rule  $P[5]$ .

Let's pay attention to the fact that the situation when  $z$  was constructed out of the pair of operands  $(\neg, w : v)$  by means of applying the rule  $P[6]$ , is impossible; the reason is that the rule  $P[6]$  allows for constructing the expressions of the form  $\neg a$  only in case when either  $a \in X(B)$  or no one of the rules  $P[2], P[5], P[10]$  was employed at the last step of constructing the string  $a$ .

**Case 9.** Let  $B$  be an arbitrary conceptual basis,  $z \in Ls(B) \setminus (X(B) \cup V(B))$ ,  $z$  has an ending being the substring of the form  $:var$ , where  $var \in V(B)$ , and  $z$  has no beginning  $'\neg'$ . Let's show that in this case the rule  $P[5]$  was applied at the last step of obtaining the string  $a$ .

Assume that it is not true, and the rule  $P_m$ , where  $1 \leq m \leq 10$ ,  $m \neq 5$ ,  $m \neq 6$ , was used at the last step of constructing the string  $a$ . If  $m = 1$ , then  $z = qtrdes$ , where  $q$  is an intensional quantifier from  $Int(B)$ ,  $des \in X(B)$  or

$$des = cpt * (r_1, b_1) \dots (r_p, b_p),$$

where  $p \geq 1$ ,  $a \in X(B)$ ,  $r_1, \dots, r_n \in R(B)$ ,  $b_1, \dots, b_p \in Ls(B)$ .

Since  $z$  has an ending being the substring of the form  $:var$ , where  $var \in V(B)$ , then the situation  $z = qtrdes$ , where  $q \in Int(B)$ ,  $des \in X(B)$ , is excluded. But  $v \neq '\neg'$ ; therefore, we obtain a contradiction, and the situation  $m = 1$  is impossible. If  $m$  is one of the integers 2, 3, 4, 7, 8, the last symbol of  $z$  is the right parenthesis  $'\neg'$ . That is why each of these situations is impossible. If  $m = 10$ , the last symbol of  $z$  is  $'\neg'$ , and it is impossible too.

Suppose that the rule  $P[9]$  was applied at the last step of inference. Then there are such

$$qex \in \{\exists, \forall\}, var \in V(B), des \in Ls(B), A \in Ls(B),$$

that  $z = qexvar(des)A$ .

According to the definition of the rule  $P[9]$ , the string  $A$  has no ending of the form  $:z$ , where  $z$  is an arbitrary variable from  $V(B)$ . That is why in Case 9, the rule  $P[5]$  was applied at the last step of constructing  $z$ . Thus, we've considered all possible cases, and Theorem 4.5 is proved.

# Glossary

**c.b.** conceptual basis

**CIA** Computer Intelligent Agent

**CMR** Component-Morphological Representation of an NL-text

**DRT** Discourse Representation Theory

**e-Commerce** Electronic Commerce

**e-Contracting** Electronic Contracting

**e-Negotiations** Electronic Negotiations

**e-Science** Electronic Science

**EL** Episodic Logic

**FIPA** Foundation for Intelligent Physical Agents

**IFS** Integral Formal Semantics of Natural Language

**K-calculus** Knowledge Calculus

**KCL-theory** Theory of K-calculuses and K-languages

**l.b.** linguistic basis

**LP** Linguistic Processor

**MAS** Multi-Agent System (or Systems)

**m.c.b.** marked-up conceptual basis

**MR** Morphological Representation of an NL-text

**MSSR** Matrix Semantic-Syntactic Representation of an NL-text

**NL** Natural Language

**NLPS** Natural Language Processing System

**NLPSs** Natural Language Processing Systems

**OWL** Ontology Web Language

**SCL-theory** Theory of S-calculuses and S-languages

**SK-language** Standard Knowledge Language

**SR** Semantic Representation of an NL-text

**TCG** Theory of Conceptual Graphs

**UNL** Universal Networking Language

**USR** Underspecified Semantic Representation of an NL-text

# References

1. Abrahams, A. S., Eyers, D. M., Kimbrough, S. O.: On defining and capturing events in business communication systems. In: IDT brownbag (2006) <http://opim-sky.wharton.upenn.edu/sok/sokpapers/2007/flbc-implementation-foils-20060422.pdf>. Cited 22 Apr 2006
2. Aczel, P., Israel, D., Katagiri, Y., Peters, S.: Situation Theory and Its Applications. CSLI Publications, Stanford (1993)
3. Ahrenberg, L.: On the integration and scope of segment-based models of discourse. the Third Nordic Conf. on Text Comprehension in Man and Machine, Linköping Univ., 1–16 (1992)
4. Allen, J.F. , Schubert, L.K., Ferguson, G. M., Heeman, P. A., Hwang, C. H., Kato, T., Light, M., Martin, N. G., Miller, B. W., Poesio, M., Traum, D.R.: The TRAINS project: A case study in building a conversational planning agent. *Journal Experimental and Theoretical Artificial Intelligence*. **7**, 7–48 (1995)
5. Alshawi, H., van Eijck, J.: Logical forms in the core language engine. 27th Ann. Meeting of the ACL, Vancouver, Canada., 25–32 (1989)
6. Alshawi, H.: Resolving quasi logical forms. *Computational Linguistics*. **16**, 133–144 (1990)
7. Alshawi, H.: The Core Language Engine. MIT Press, Cambridge, MA (1992)
8. Alshawi, H., Crouch, R.: Monotonic semantic interpretation. In: Proceedings of the 30th Annual Meeting of the Association for Computational Linguistics, University of Delaware, pp. 32–39 (1992)
9. Alshawi, H., van Eijck, J.: Logical forms in the core language engine. 27th Ann. Meeting of the ACL, Vancouver, Canada., 25–32 (1989)
10. Angelova, G.: Language technology meet ontology acquisition. In: Dau, F., Mugnier, M.-L., Stumme, G. (eds.) *International Conference on Conceptual Structures 2005*. LNCS 3596, pp. 367–380. Springer, Heidelberg (2005)
11. Apresyan, Yu. D.: *Lexical Semantics. Synonymic Means of Language*. Nauka Publ., Moscow, (in Russian) (1974)
12. Baclawski, K., Niu, T.: *Ontologies for Bioinformatics*. MIT Press, Cambridge, MA (2005)
13. Baldwin, T.: Making sense of Japanese relative clause constructions. In: Hirst, G., Nirenburg, S. (eds.) *Proceedings of the Second Workshop on Text Meaning and Interpretation held in cooperation with ACL-2004*, 25–26 July 2004, Barcelona, Spain, pp. 49–56 (2004)
14. Barwise, J., Cooper, R.: Generalized quantifiers and natural language. *Linguistics & Philosophy*. **4**, 159–219 (1981)
15. Barwise, J., Cooper, R.: Extended karp notation: a graphical notation for situation theory. Aczel, Israel, Katagiri, fc Peters., 29–53 (1993)
16. Barwise, J., Perry, J.: *Situations and Attitudes*. The MIT Press, Cambridge, MA (1983)
17. Beale, S., Lavoie, B., McShane, M., Nirenburg, S., Korelsky, T.: Question answering using ontological semantics. In: Hirst, G., Nirenburg, S. (eds.) *Proceedings of the Second Work-*



- shop on Text Meaning and Interpretation held in cooperation with ACL-2004, 25–26 July 2004, Barcelona, Spain, pp. 41–48 (2004)
18. Berners-Lee, T., Hendler, J., Lassila, O.: The semantic web. *Scientific American*, 34–43 (2001)
  19. Cannataro, M., Talia, D.: Semantics and knowledge grids: building the next-generation grid. *IEEE Intelligent Systems* (Jan/Feb 2004), Special issue on E-Science (2004)
  20. Caron, J.: *Precis de Psycholinguistique*. Presses Universitaires de France, Paris, (1989)
  21. Carpenter B., Penn G.: Attribute logic engine (ALE), Version 3.2 <http://www.cs.toronto.edu/gpenn/ale.html>.
  22. Chafe, W. L.: *Meaning and the Structure of Language*. The University of Chicago Press Chicago and London, (1971)
  23. Chai, J., Lin, J., Zadrozny, W., Ye, Y., Budzikowska, M., Horvath, V., Kambhatla, N., Wolf, C.: The role of a natural language conversational interface in online sales: A case study. *International Journal of Speech Technology*. **4**, 285–295 (2001)
  24. Chai, J., Horvath, V., Nicolov, N., Stys, M., Kambhatla, N., Zadrozny, W., Melville, P.: Natural language assistant – a dialog system for online product recommendation. *Artificial Intelligence Magazine (AI Magazine)*. **23**, 63–76 (2002)
  25. Chen, H., Wang, Y., Wu, Z.: Introduction to semantic e-Science in biomedicine (2007)
  26. Chierchia, G.: Structured meanings, thematic roles and control. In Chierchia, G., Partee, B. H., Turner, R. (eds.) *Properties, Types and Meaning, Semantic Issues.*, pp. 131–166. Kluwer, Dordrecht (1989)
  27. Clifford, J.: QE-III : a formal approach to natural language querying. In William K. (ed.) *Proceedings of the National Conference on Artificial Intelligence (AAAI-83)*, pp. 79–83. AAAI, Los Altos, California (1983)
  28. Clifford, J.: Language querying of historical data bases. *Computational Linguistics*. **14**, 10–34 (1988)
  29. Cresswell, M. J.: *Structured Meanings: The Semantics of Prepositional Attitudes*. MIT Press, Cambridge, MA (1985)
  30. Cooper, R.: Three lectures on situation theoretic grammar. In Filgueiras, M. (eds.) *Natural Language Processing*, pp. 102–140. Springer-Verlag, Berlin (1991)
  31. CrossFlow Project. Insurance Requirements. CrossFlow Consortium (1999) <http://www.crossflow/public/pubdel/D1b.pdf>. Cited 1999
  32. Reference description of the DAML + OIL ontology markup language. In DAML plus OIL (2001) <http://www.daml.org/2001/03/daml+oil>. Cited March 2001
  33. Delmonte, R.: Text understanding with GETARUNS for Q/A and summarization. In: Hirst, G., Nirenburg, S. (eds.), *Proceedings of the Second Workshop on Text Meaning and Interpretation held in cooperation with ACL-2004*, 25–26 July 2004, Barcelona, Spain, pp. 97–104 (2004)
  34. Dekker, P.: The scope of negation in discourse: towards a flexible dynamic Montague grammar. In *Quantification and Anaphora 1. DYANA. Deliverable R2.2.A*. July 1990. Edinburgh, 79–134 (1990)
  35. De Roure, D., Hendler, J. A.: E-science: the grid and the semantic web. *IEEE Intelligent Systems* (Jan/Feb 2004), Special issue on E-Science (2004)
  36. van Eijck, D. J. N., Kamp, H.: *Representing Discourse in Context*. The University of Amsterdam, Amsterdam (1996)
  37. Eklund, P. W., Ellis, G., Mann, G.: Conceptual structures; knowledge representation as Interlingua. In Eklund, P. W., Ellis, G., Mann, G. (eds.) *Proceedings of the 4th Intern. Conf. on Conceptual Structures*, p. 321. ICCS'96, Sydney, Australia, Springer-Verlag, Berlin, Heidelberg, New York (1996)
  38. Ershov, A. P.: Machine Fund of Russian Language: An External Task Statement. In Karaulov, Yu. N. (ed.), *Machine Fund of Russian Language: Ideas and Opinions*. Nauka Publ. Moscow, pp. 7–12, in Russian (1986)
  39. Fauconnier, G.: *Mental Spaces: Aspects of Meaning Construction in Natural Language*. Cambridge University Press, Cambridge (1985)

40. Fellbaum, C., Hahn, U., Smith, B.: Towards new information resources for public health – From WordNet to MedicalWordNet. *Journal of Biomedical Informatics* **39**, 321–332 (2006)
41. Fensel, D.: OIL in a Nutshell. Knowledge acquisition, modeling, and management, *Proceedings of the European Knowledge Acquisition Conference (EKAW-2000)*. In Dieng, R. (ed.) *Lecture Notes in Artificial Intelligence (LNAI)*. Springer-Verlag, Berlin (2000)
42. Fenstad, J.E., Halvorsen, P. K., Langholm, T. , Van Benthem, J.: *Situations, Language and Logic*. D. Reidel, Dordrecht (1987)
43. Fenstad, J.E., Langholm, T., Vestre, E.: Representations and interpretations. In Rosner, M., Johnson, R. (eds.) *Computational Linguistics and Formal Semantics*, Cambridge University Press, Cambridge, MA 31–95 (1992)
44. Fenstad, J. E., Lonning, J. T.: Computational semantics: steps towards “Intelligent” Text Processing. In Studer, R. (ed.) *Natural Language and Logic*. Springer-Verlag, Berlin, 70–93 (1990)
45. Fillmore, C.: Frames and the semantics of understanding. *Quaderni di Semantica*, **6**, 222–253 (1985)
46. Finin, T., Weber, J., Wiederhold, G., Genesereth, M., Fritzson, R., McKay, D., Mc Guire, J., Pelavin, R., Shapiro, S., Beck, C.: Specification of the KQML. Agent-Communication Language. The DARPA Knowledge Sharing Initiative, External Interfaces Working Group (1993)
47. FIPA SL Content Language Specification. In: FIPA SL CL (2002) <http://www.fipa.org/specs/fipa00008/SC000081.htm>. Cited 2002
48. Fisher, C., Gleitman, H., Gleitman, L. R.: On the semantic content of subcategory frames. *Cognitive Psychology*, **23**, 331–392 (1991)
49. Fodor, J. A.: *The Language of Thought*. Crowell New York, (1975)
50. Fodor, J. A.: *Psychosemantics: The Problem of Meaning in the Philosophy of Mind*. 2nd print. The MIT Press Cambridge, MA, London, (1988)
51. Fomichov, V. A. (1980). Some principles of mathematical describing natural language’s subsets. In Ailamazyan, A. K. (ed.) *Proceedings of the 1st and 2nd sc.-techn. conf. of young specialists. Informational Processes and Their Automation*. Moscow, VNTITSentr, 125–136, in Russian (1980)
52. Fomichov, V. A.: To the theory of logic-algebraic modelling the speech-forming mechanisms of conceptual level. 1. Task statement and the idea of an approach to its resolving. Moscow Institute of Electronic Engineering, 85 pp. – The paper deposited in the All-Union Institute of Scientific and Technical Information; in Russian – Vsesoyuzny Institut Nauchnoy i Tekhnicheskoy Informatsii, or VINITI (27/10/81, No. 4939-81 Dep. – The abstract 2B1386DEP in the Abstracts Journal “Mathematika” of VINITI), 1982, No. 2; in Russian (1981)
53. Fomichov, V.A.: About elaboration and application of the theory of logic-algebraic modeling of some natural language’s text-forming mechanisms of conceptual level. IX All-Union Symposium on Cybernetics (Theses of symposium. Sukhumi, 10–15 Nov. 1981), Vol. 1, Moscow: Sc, Council on complex problem “Cybernetics” of As. Sc USSR, 186–188 (1981)
54. Fomichov, V. A.: Development and application of methods of logic-algebraic modeling the mechanisms of speech-formation semantics. Ph.D. dissertation. Moscow: Moscow Inst. of Electronic Eng. (1982)
55. Fomitchov, V. A. (1983). Formal systems for natural language man-machine interaction modelling. In *International Symposium on Artificial Intelligence IFAC*, Vol. 1. Leningrad: Ac. Sc. USSR, 223–243 (in two variants – in Russian and in English). Paper presented at the First Symposium of the Int. Federation of Automatic Control on Artificial Intelligence (1983)
56. Fomitchov, V.: Formal systems for natural language man-machine interaction modeling. In Ponomaryov, V. M. (ed.) *Artificial Intelligence. Proc. of the IFAC Symposium*, Leningrad, USSR (1983), IFAC Proc. Series, pp. 203–209. Oxford, UK; New York (1984)
57. Fomichov, V.A.: *Calculuses for modeling the processes of treating the conceptual information*. Moscow, 83pp. Unpublished manuscript (1985)
58. Fomichov, V.A.: A mathematical model of linguistic processor and its application to the design of training complexes. In Y. A. Ryazanov (ed.) *Automatic Regulation and Control*.

- Mathematical Modeling of the Non-stationary Processes of Automatic Control Systems, Moscow: All-Union Machine-Building Institute for Tuition by Correspondence, pp. 110–114 (1986)
59. Fomichov, V. A.: About synthesis of tasks formal specifications in the dialogue system TEMP-1. In: Markov, V.N. (ed.) *Mathematical Provision and Programming for Calculating and Control Systems*, pp. 10–13. Moscow Institute of Electronic Engineering Publishing House, Moscow (1986)
  60. Fomichov, V.A.: The experience of mathematical designing a system of communication with the database of a flexible manufacturing system. In: *Problems of creating flexible manufacturing systems in machine-building. Theses of papers of the Republican sc.-techn. Conf. 1–2 October 1987, Kaunas. Vilnius : Lithuanian Sc. -Res. Inst. of Sc. -Techn. Information and Technical-Economical Studies, Kaunas Polytechnic Inst., Sc. Council Ac. Sc. USSR on Problems of Machine-Building and Technological Processes*, 90–91 (1987)
  61. Fomichov, V.A.: K-calculuses and K-languages as instruments for investigation of some key questions of the fifth generation computer systems theory. In: *Informatics-87, II All-Union conf. on actual problems of informatics and computer technics. Theses of papers, Yerevan, 20–22 October 1987, Yerevan: Ac. Sc. Armyan. SSR Publ. House*, pp. 182–183 (1987)
  62. Fomichov, V. A.: *Representing Information by Means of K-calculuses: Textbook. The Moscow Institute of Electronic Engineering (MIEE) Press, Moscow, in Russian* (1988)
  63. Fomichov, V. A.: About the means of constructing natural-language-communication mathematical theory. In Markov, V. N. (ed.); *Mathematical Provision of Calculating, Informational, and Control Systems. The MIEE Press, Moscow*; pp. 21–25. in Russian (1988)
  64. Fomichov, V.A.: About mathematical models for designing analyzers of discourses. In: Petrov, A.E. (ed.) *Scientific-Technical Means of Informatization, Automatization and Intellectualization in National Economy. Materials of a seminar. Moscow: Central Russian Knowledge House Press*, pp. 62–70; in Russian (1991)
  65. Fomichov, V.: Mathematical models of natural-language-processing systems as cybernetic models of a new kind. *Cybernetica (Belgium)*. **35**, 63–91 (1992)
  66. Fomichov, V. A.: Towards a mathematical theory of natural-language communication. *Informatica. An International Journal of Computing and Informatics (Slovenia)*. **17**, 21–34 (1993)
  67. Fomichov, V. A.: K-calculuses and K-languages as powerful formal means to design intelligent systems processing medical texts. *Cybernetica (Belgium)*. **36**, 161–182 (1993)
  68. Fomichov, V. A.: Integral formal semantics and the design of legal full-text databases. *Cybernetica (Belgium)*. **37**, 145–17 (1994)
  69. Fomichov, V. A.: A variant of a universal metagrammar of conceptual structures. Algebraic systems of conceptual syntax (Invited talk). In Nijholt, A., Scollo, G., Steetskamp, R. (eds.) *Algebraic Methods in Language Processing. Proceedings of the Tenth Twente Workshop on Language Technology joint with First AMAST Workshop on Language Processing*, pp. 195–210. University of Twente, Enschede, The Netherlands, December 6–8, 1995 (1995)
  70. Fomichov, V. A.: A mathematical model for describing structured items of conceptual level. *Informatica (Slovenia)*. **20**, 5–32 (1996)
  71. Fomichov, V. A.: An outline of a formal metagrammar for describing structured meanings of complicated discourses. In II Intern. Conf. on Mathematical Linguistics (ICML'96), Abstracts, Tarragona, Grup de Recerca en Linguística Matemàtica i Enginyeria del Llenguatge (GRLMC), Report 7/96, pp. 31–32. Universitat Rovira i Virgili (1996).
  72. Fomichov, V. A.: K-calculuses and the problem of conceptual information retrieval in textual data bases. *Knowledge Transfer (Volume II)*. In Behrooz, A. (ed.) *International Conference "Knowledge Transfer – 1997 (KT97)", Symposium "Information Technology"*, pp. 52–58. London, University of London (1997)
  73. Fomichov, V. A.: Formal studies of anticipative systems as a basis of effective humanitarian and computer applications. In Lasker, G. E., Dubois, D., Teiling, B. (eds.) *Modelling of Anticipative Systems, Vol. II*, pp. 73–77. University of Windsor, Canada (1997)
  74. Fomichov, V. A.: K-calculuses and matrix grammars as powerful tools for designing natural language processing systems// Abstracts of Papers, Interdisciplinary Symposium "Artificial

- Intelligence, Cognitive Science, and Philosophy for Social Progress" (President – Chairperson: Mr. Vladimir Fomichov, Russia), 15th International Congress on Cybernetics, Namur, Belgium, August 24–28. Namur, International Association for Cybernetics (1998)
75. Fomichov, V. A.: A comprehensive mathematical framework for designing agent communication languages. Proceedings of the International Conference "Information Society (IS'98)", pp. 81–84. Ljubljana, Slovenia, 6–7 October (1998)
  76. Fomichov, V. A.: Theory of restricted K-calculuses as a comprehensive framework for constructing agent communication languages; Special Issue on NLP and Multi-Agent Systems. In Fomichov, V. A., Zeleznikar, A.P. (eds.). *Informatica. An International Journal of Computing and Informatics (Slovenia)*. **22(4)**, 451–463 (1998)
  77. Fomichov, V. A.: Theory of restricted K-calculuses as a universal informational framework for electronic commerce. Database, Web and Cooperative Systems. The Proceedings of 1999 International Symposium on Database, Web and Cooperative Systems, August 3–4, 1999 in Baden-Baden, Germany – DWACOS'99 / In: Lasker, G. E. (ed.). University of Windsor and Yanchun Zhang, University of Southern Queensland. The International Institute for Advanced Studies in Systems Research and Cybernetics, University of Windsor, Windsor, Ontario, Canada. **1**, pp. 41–46 (1999)
  78. Fomichov, V. A.: A universal resources and agents framework for electronic commerce and other applications of multi-agent systems; 7th International Workshop on Computer Aided Systems Theory and Technology 1999 – EUROCAST'99. In: Kopacek, P. (ed.). September 29th – October 2nd, 1999, Vienna, Austria, Vienna University of Technology. pp. 99–102 (1999)
  79. Fomichov, V. A.: An ontological mathematical framework for electronic commerce and semantically-structured web. In Zhang, Y., Fomichov, V.A., Zeleznikar, A.P. (eds.) Special Issue on Database, Web, and Cooperative Systems. *Informatica. An International Journal of Computing and Informatics (Slovenia, Europe)*, **24(1)**, 39–49 (2000)
  80. Fomichov, V. A.: New content languages for electronic commerce and digital libraries. In Binder, Z. (ed.), *Management and Control of Production and Logistics 2000 (MCPL 2000)*. A Proceedings volume from the 2nd IFAC/IFIP/IEEE Conference, Grenoble, France, 5–8 July 2000. Pergamon, An Imprint of Elsevier Science, Oxford, UK., New York, Tokyo. **2**, pp. 503–508 (2001)
  81. Fomichov, V.A.: The method of constructing the linguistic processor of the animation system AVIAROBOT. Preconference Proceedings "Collaborative Decision-Support Systems" (Focus Symposium in conjunction with the 14th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2002, July 29 – August 3, 2002, Germany). Focus Symposia Chair: Jens Pohl – CAD Research Center, Cal Poly, San Luis Obispo, CA, USA, pp. 91–102 (2002)
  82. Fomichov, V. A.: Theory of K-calculuses as a powerful and flexible mathematical framework for building ontologies and designing natural language processing systems. In Andreassen, T., Motro, A., Christiansen, H., Larsen, H.L. (eds.) *Flexible Query Answering Systems. 5th International Conference, FQAS 2002, Copenhagen, Denmark, October 27–29, 2002. Proceedings; LNAI 2522 (Lecture Notes in Artificial Intelligence, 2522)*, Springer: Berlin, Heidelberg, New York, Barcelona, Hong Kong, London, Milan, Paris, Tokyo. pp. 183–196 (2002)
  83. Fomichov, V.A.: Mathematical foundations of representing texts' meanings for the development of linguistic informational technologies. Part 1. A model of the system of primary units of conceptual level. Part 2. A system of the rules for constructing semantic representations of phrases and complex discourses. *Informational Technologies (Moscow)* **2002/10–11**, 16–25, 34–45 (2002)
  84. Fomichov, V.A.: Theory of standard K-languages as a model of a universal semantic networking language. Preconference Proceedings "Intelligent Software Systems for the New Infostructure" (Focus Symposium in conjunction with the 16th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2004, July 29 – August 5, 2004,

- Germany). Focus Symposia Chair: Jens Pohl – CAD Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 51–61 (2004)
85. Fomichov, V.A.: The Formalization of Designing Natural Language Processing Systems. MAX Press, Moscow; in Russian (2005)
  86. Fomichov, V.A.: A new method of transforming natural language texts into semantic representations. *Informational Technologies (Moscow)* **2005/10**, 25–35 (2005)
  87. Fomichov, V.A.: Standard K-languages as a powerful and flexible tool for building contracts and representing contents of arbitrary E-negotiations. In Bauknecht, K., Proell, B., Werthner, H. (eds.) *The 6th Intern. Conf. on Electronic Commerce and Web Technologies “EC-Web 2005”*, Copenhagen, Denmark, Aug. 23–26, Proceedings. *Lecture Notes in Computer Science*. **3590**. Springer Verlag. pp. 138–147 (2005)
  88. Fomichov, V.A.: A class of formal languages and an algorithm for constructing semantic annotations of Web-documents. *Vestnik of N.E. Bauman State Technical University. Series “Instrument-Making”*. **60**, 73–86 (2005)
  89. Fomichov, V.A.: The theory of SK-languages as a powerful framework for constructing formal languages for electronic business communication. Preconference Proceedings “Advances in Intelligent Software Systems” (Focus Symposium in conjunction with the 18th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2006, August 7–12, 2006, Germany). Focus Symposia Chair: Jens Pohl – CAD Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 123–130 (2006)
  90. Fomichov, V.A.: Theory of K-representations as a framework for constructing a semantic networking language of a new generation. Preconference proceedings “Representation of Context in Software: Data  $\Rightarrow$  Information  $\Rightarrow$  Knowledge” (Focus Symposium in conjunction with the 19th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2007, July 30 – August 4, 2007, Germany). Focus Symposia Chair: Jens Pohl – CAD Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 61–70 (2007)
  91. Fomichov, V. A.: Mathematical Foundations of representing the Content of Messages Sent by Computer Intelligent Agents. The Publishing House “TEIS”, Moscow (2007)
  92. Fomichov, V.A.: The approach of the theory of K-representations to reflecting in a formal way the content of contracts and records of negotiations in the field of electronic commerce. *Business-informatics (Moscow)*, **2007/2**, 34–38 (2007)
  93. Fomichov, V. A.: Theory of K-representations as a powerful framework for eliminating the language barrier between the users of internet. Robert Trappl (ed.) *Cybernetics and Systems 2008. Proceedings of the Ninetieth European Meeting on Cybernetics and Systems Research*, held at the University of Vienna, Austria, 25–28 March 2008. The Austrian Cybernetic Society for Cybernetic Studies, Vienna. 2008. Vol. 2. pp. 537–542 (2008)
  94. Fomichov, V. A.: A comprehensive mathematical framework for bridging a gap between two approaches to creating a meaning-understanding Web. *International Journal of Intelligent Computing and Cybernetics (Emerald Group Publishing Limited, UK)*. 2008. **1**(1), 143–163. (2008)
  95. Fomichov, V. A.: Towards Joining Systems Science and Engineering of Semantics-Oriented Natural Language Processing Systems. – Preconference Proceedings “Intelligent Software Tools and Services” (Focus Symposium in conjunction with the 20th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2008, July 24–30, 2008, Germany). Focus Symposia Chair: Jens Pohl. CAD Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 55–66. (2008)
  96. Fomichov, V. A., Akhromov, Ya. V.: Standard K-languages as a Powerful and Flexible Tool for Constructing Ontological Intelligent Agents. Preconference Proceedings “Collaborative Decision-Support Systems” (Focus Symposium in conjunction with the 15th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2003, July 28–August 01, 2003, Germany). Focus Symposia Chair: Jens Pohl – CAD Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 167–176 (2003)
  97. Fomichov, V. A., Chuykov, A. V.: An intelligent agent with linguistic skills for the Web-search of production manufacturers. *InterSymp-2000, 12th International Conference on*

- Systems research, Informatics and Cybernetics (July 31–August 4, 2000, Germany). Pre-conference Proceedings “Advances in Computer-Based and Web-Based Collaborative Systems (Focus Symposia, August 1 and 2, 2000)”, Focus Symposia Chairs Jens Pohl and Thomas Fowler, IV. – Collaborative Agent Design (CAD) Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 137–147. (2000)
98. Fomichov, V. A., Kochanov, A. A.: Principles of Semantic Search for Information on the Web by the Intelligent Agent LingSearch-1. Preconference Proceedings “Advances in Computer-Based and Web-Based Collaborative Systems” (Focus Symposia in conjunction with the 13th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2001, July 31–August 1, 2001, Germany). Focus Symposia Chairs: Jens Pohl and Thomas Fowler, IV. – Collaborative Agent Design (CAD) Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 121–131 (2001)
  99. Fomichov, V. A., Lustig, I. V.: A Computer Intelligent Agent for Semantic Classification of E-mail Messages. Preconference Proceedings “Advances in Computer-Based and Web-Based Collaborative Systems” (Focus Symposia in conjunction with the 13th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2001, July 31 – August 1, 2001, Germany). Focus Symposia Chairs: Jens Pohl and Thomas Fowler, IV. – Collaborative Agent Design (CAD) Research Center, Cal Poly, San Luis Obispo, CA, USA. pp. 29–37. (2001)
  100. Fomichova O. S., Fomichov, V. A.: (2004). A new approach to designing children-oriented web-sites of art museums. In *Cybernetics and Systems 2004. 2. Proceedings of the Seventeenth European Meeting on Cybernetics and Systems Research* (University of Vienna, Austria, 13–16 April 2004). In Trappl, R. (ed.) University of Vienna and Austrian Society for Cybernetic Studies. pp. 757–762 (2004)
  101. Gaerdenfors, P. (ed): *Generalised Quantifiers. Linguistic and Logical Approaches*. Reidel, Dordrecht (1987)
  102. Gazdar, G., Klein, E., Pullum, G., Sag, I.: *Generalized Phrase Structure Grammar*. Blackwell, Oxford, (1985)
  103. Geeraerts, D.: Editorial Statement. *Cognitive Linguistics*. **1** (1), 1–3 (1990)
  104. Genesereth, M. R., Fikes, R. E.: *Knowledge Interchange Format Version 3 Reference Manual*. Technical Report Logic-92-1, Computer Science Department, Stanford University (1992)
  105. Grishman, R.: *Computational Linguistics : An Introduction*. Cambridge University Press Cambridge, (1986)
  106. Groenendijk, J., Stokhof, M.: Dynamic montague grammar. In Kalman, L. Polos L. (eds.) *Papers from the Second Symposium on Logic and Language*. Akademiai Kiado Budapest, – 1990. – pp. 3–48. (1990)
  107. Groenendijk, J., Stokhof, M.: Two theories of dynamic semantics. In J. van Eijck (ed.) *Logics in Artificial Intelligence*. Springer-Verlag, Berlin, 55–64 (1991)
  108. Groenendijk, J., Stokhof, M.: Dynamic predicate logic. *Linguistics and Philosophy*, **14**(1), pp. 39–101. (1991)
  109. Gruber, T. R.: A translation approach to portable ontology specifications. *Knowledge Acquisition Journal*. **5** 199–220 (1993)
  110. Guarino, N.: Formal ontology and information systems. In: *Proceedings of FOIS’98, Trento, Italy*, pp. 3–15. IOS Press, Amsterdam (1998)
  111. An accommodation recommender system based on associative networks (2003) Available online: [http://ispaces.ec3.at/papers/DITTENBACH.EA\\\_2003\\\_a-natural-language.pdf](http://ispaces.ec3.at/papers/DITTENBACH.EA\_2003\_a-natural-language.pdf)
  112. How to analyze free text descriptions for recommending TV programmes (2006) Available online. [http://www8.informatik.uni-erlangen.de/IMMD8/Lectures/EINFKI/ecai\\\_2006.pdf](http://www8.informatik.uni-erlangen.de/IMMD8/Lectures/EINFKI/ecai\_2006.pdf)
  113. Habel: *Kognitionswissenschaft als Grundlage der Computerlinguistik*. In *Computerlinguistik und ihre theoretischen Grundlagen*. Berlin etc.: Springer-Verlag, 204–209 (1988)
  114. Hahn, U.: Making understands out of parsers: semantically driven parsing as a key concept for realistic text understanding applications. *International Journal of Intelligent Systems*. **4** (3), 345–385 (1989)

115. Hahn, U., Schulz, S.: Ontological foundations for biomedical sciences. *Artificial Intelligence in Medicine*. **39**, 179–182 (2007)
116. Hahn, U., Valencia, A.: Semantic Mining in Biomedicine (Introduction to the papers selected from the SMBM 2005 Symposium, Hinxton, U.K., April 2005). *Bioinformatics*. **22**, 643–644 (2005)
117. Hunter, J., Drennan, J., Little, S.: Realizing the hydrogen economy through semantic web technologies. *IEEE Intelligent Systems* (Jan/Feb 2004), Special issue on E-Science (2004)
118. Hasselbring, W., Weigand, H.: Languages for electronic business communication: state of the art. *Industrial Management and Data Systems*. **1001**, 217–226 (2001)
119. Hausser, R.: Database semantics for natural language. *Artificial Intelligence (AIJ)*. **130**, (1), Elsevier, Dordrecht (2001)
120. Hausser, R.: Foundations of Computational Linguistics, Human-Computer Communication in Natural Language. 2nd Edition. Springer, Berlin, New York (2001)
121. Hausser, R.: A Computational Model of Natural Language Communication; Interpretation, Inference, and Production in Database Semantics. Springer, Berlin, Heidelberg, New York (2006)
122. Heim, I.: E-Type pronouns and donkey anaphora. *Linguistics & Philosophy*. **13**(2), 137–177 (1990)
123. Hendler, J., Shadbolt, N., Hall, W., Berners-Lee, T., Weitzner, D.: Web Science: an interdisciplinary approach to understanding the web. *Communications of the ACM*. **51**, 60–69 (2008)
124. Herzog, O. Rollinger, C.-R. (eds.): Text Understanding in LILOG. Integrating Computational Linguistics and Artificial Intelligence. Final Report on the IBM Germany LILOG-Project. Springer-Verlag Berlin, (1991)
125. Hirst, G.: Semantic Interpretation and Ambiguity. *Artificial Intelligence*. **34**, 131–177 (1988)
126. Hobbs, J.R., Stickel, M.E., Appelt, D.E., Martin, P.: Interpretation as abduction. *Artificial Intelligence*. **63**, 69–142 (1993)
127. Horrocks, I.: A denotational semantics for Standart OIL and Instance OIL. Department of Computer Science, University of Manchester, UK, (2000) <http://www.ontoknowledge.org/oil/download/semantics.pdf>
128. Horrocks, I, van Harmelen, F., Patel-Schneider, P. DAML + OIL Release (March 2001) <http://www.daml.org/2001/03/daml+oil+index>.
129. Hwang, C.H. A Logical Approach to Narrative Understanding. Ph.D. Dissertation, U. of Alberta, Edmonton, Canada. (1992)
130. Hwang, C. H., Schubert, L.K.: Meeting the interlocking needs of LF-computation, deindexing, and inference: An organic approach to general NLU. // Proc. 13th Int. Joint Conf. on AI (IJCAI'93). Chambéry, France, 28 August–3 September (1993)
131. Hwang, C. H., Schubert, L.K. Episodic Logic: a situational logic for natural language processing. In Aczel, P., Israel, D., Katagiri, Y., Peters, S. (eds.) *Situation Theory and Its Application*, CSLT Publication, Stanford, 303–338 (1993)
132. Hwang, C.H., Schubert, L.K.: Episodic Logic: a comprehensive, natural representation for language understanding. *Minds and Machines*. 1993b, **3**, 381–419 (1993)
133. Hwang, C. H., Schubert, L.K.: Tense trees as the 'fine structure' of discourse. In: *Proceedings of the 30th Annual Meeting of the ACL*, Newark, DE, pp. 232–240 (1992)
134. Hwang, C. H., Schubert, L.K.: Interpreting tense, aspect, and time adverbials: a compositional, unified approach. In: Gabbay, D.M., Ohlbach, H.J. (eds.) *Proceedings of the 1st Int. Conf. on Temporal Logic*, July 11–14, Bonn, Germany, pp. 238–264. Springer, Heidelberg (1994)
135. Jackendoff, R.S.: *Semantic Structures*. MIT Press, Cambridge, MA (1990)
136. Java, A., Finin, T., Nirenburg, S.: Text Understanding Agents and the Semantic Web. In: *Proceedings of the 39th Hawaii International Conference on System Sciences*, (2006) [http://ebiquity.umbc.edu/file\\_directory/papers/205.pdf](http://ebiquity.umbc.edu/file_directory/papers/205.pdf).

137. Johnson, M.: *The Body in the Mind: The Bodily Basis of Meaning, Imagination, and Reason*. The University of Chicago Press Chicago, (1987)
138. Johnson, M.: *Attribute-Value Logic and the Theory of Grammar*. CSLI, Stanford (1988)
139. Johnson-Laird, P.: *Mental Models*. Harvard University Press Cambridge, MA (1983)
140. Johnsonbaugh, R.: *Discrete Mathematics*. Fifth edition. Prentic Hall, Upper Saddle River, NJ 621–621 (2001)
141. Jowsey, E. *Montague Grammar and First Order Logic*. Edinburgh Working Papers in Cognitive Science., **1**, Univ. of Edinburgh (1987)
142. Kamp, H.: A theory of truth and semantic representation. In Groenendijk, J., Janssen, T., Stokhof, M. (eds.) *Formal Methods in the Study of Natural Language. Part 1. Mathematical Centre, Amsterdam*, 227–322. (1981)
143. Kamp, H., Reyle, U.: *Introduction to Modeltheoretic Semantics of Natural Language, Formal Logic and Discourse Representation Theory*. Kluwer Academic Publishers, Dordrecht (1993)
144. Kamp, H., Reyle, U. A calculus for first order discourse representation structures. *Journal for Logic, Language and Information (JOLLI)*, **5**, 297–348 (1996)
145. Kimbrough, S.O. A Note on Getting Started with FLBC: Towards a User Guide for FLBC. August 25, (2001) <http://grace.wharton.upenn.edu/sok/sokpapers/2001-2/lap/lap-acm-questions-flbc-20010825.pdf>.
146. Kimbrough, S.O.: A Note on the FLBC Treatment of an Example X12 Purchase Order (2001) <http://opim-sun.wharton.upenn.edu/sok/flbcinfo/span-fullEDI-sok-sam.pdf>.
147. Kimbrough, S.O.: Reasoning about the Objects of Attitudes and Operators: Towards a Disquotation Theory for Representation of Propositional Content //Proceedings of the Tenth International Conference on Artificial Intelligence and Law- ICAIL'2001, (2001) <http://grace.wharton.upenn.edu/sok/sokpapers/2000-1/icail/sok-icail01.pdf>.
148. Kimbrough, S.O., Moore, S.A.: On automated message processing in electronic commerce and work support systems: speech act theory and expressive felicity. *ACM Transactions on Information Systems*, **15(4)**, 321–367. (1997)
149. Lakoff, G.: *Women, Fire and Dangerous Things: What Categories Reveal about the Mind*. The University of Chicago Press, Chicago (1987)
150. Lakoff, G., Johnson, M.: *Metaphors We Live By*. The University of Chicago Press, Chicago (1980)
151. Langacker, R. W.: *Foundations of Cognitive Grammar. Vol. 1. Theoretical Prerequisites*. Stanford University Press, Stanford (1987)
152. Langacker, R. W.: *Concept, Image, and Symbol. The Cognitive Basis of Grammar*. Mouton de Gruyter, Berlin, New York (1990)
153. Lee, C.H., Na, J.C., Khoo C.: (Singapore), In: ICADL 2003, LNCS 2911 (2003)
154. McShane, M., Zabłudowski, M., Nirenburg, S., Beale, S.: OntoSem and SIMPLE: Two multilingual world views. In: Hirst, G., Nirenburg, S. (eds.) *Proceedings of the Second Workshop on Text Meaning and Interpretation held in cooperation with ACL-2004*, 25–26 July 2004, Barcelona, Spain, pp. 25–32 (2004)
155. Mel'cuk, I., Zolkovskij, A.: Towards a functioning meaning-text model of language. *Linguistics*, **57**, 10–47 (1970)
156. Minsky, M.: Framework for representing knowledge. In Winston, P. H. (ed.), *The Psychology of Computer Vision*, Mc Graw-Hill book comp., New York (1975)
157. Meyer, R.: Probleme von Zwei-Ebenen-Semantiken. *Kognitionswissenschaft*, **4**, 32–46 (1994)
158. Montague, R.: *Universal Grammar*. *Theoria*, **36**, 373–398 (1970)
159. Montague, R.: English as a formal language. In Thompson, R.H. (ed.) *Formal Philosophy. Selected papers of Richard Montague*. Yale University Press, New Haven and London 188–221 (1974)
160. Montague, R.: The proper treatment of quantification in ordinary english. In Thompson, R.H. (ed.) *Formal Philosophy*, Yale University Press, London, 247–270. (1974)



161. Navigli, R., Velardi, P.: Through automatic semantic annotation of on-line glossaries. In *Proc. of European Knowledge Acquisition Workshop (EKAW)-2006*, LNAI 4248, pp. 126–140 (2006)
162. OWL Web Ontology Language Semantics and Abstract Syntax, Patel-Schneider, P. F., Hayes, P., Horrocks, I. (eds.) W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-owl-semantics-20040210/>. Latest version available at <http://www.w3.org/TR/owl-semantics/>
163. OWL Web Ontology Language Overview, Deborah L. McGuinness and Frank van Harmelen, Editors. W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-owl-features-20040210/>. Latest version available at <http://www.w3.org/TR/owl-features/>
164. OWL Web Ontology Language Reference, Mike Dean and Guus Schreiber, Editors. W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-owl-ref-20040210/>. Latest version available at <http://www.w3.org/TR/owl-ref/>
165. Panedes-Frigolett, H.: Interpretation in a cognitive architecture. In: Hirst, G., Nirenburg, S. (eds.) *Proceedings of the Second Workshop on Text Meaning and Interpretation held in co-operation with ACL-2004*, 25–26 July 2004, Barcelona, Spain, pp. 1–8 (2004)
166. Partee, B. H. (ed.) *Montague Grammar*. Academia Press, New York (1976)
167. Partee, B. H., ter Meulen, A., Wall, R.: *Mathematical Methods in Linguistics*. Kluwer, Dordrecht (1990)
168. Peregrin, J.: On a logical formalization of natural language. *Kybernetika*. **26**, 327–341 (1990)
169. Pohl, J.: Adapting to the information age. In: *Preconference Proceedings “Advances in Computer-Based and Web-Based Collaborative Systems (Focus Symposia, August 1 and 2, 2000)”*, Focus Symposia Chairs Jens Pohl and Thomas Fowler, IV. 12th International Conference on Systems Research, Informatics and Cybernetics – InterSymp-2000 (July 31–August 4, 2000, Baden-Baden, Germany), pp. 9–25. Collaborative Agent Design (CAD) Research Center, Cal Poly, San Luis Obispo, CA, USA (2000)
170. Putnam, H.: *Reason, Truth, and History*. Cambridge University Press, Cambridge (1981)
171. Resource Description Framework (RDF) Model and Syntax Specification, Ora Lasila, Ralph R. Swick, Editors. World Wide Web Consortium Recommendation, (1999) <http://www.w3.org/TR/1999/REC-rdf-syntax-19990222/>. Latest version available at <http://www.w3.org/TR/REC-rdf-syntax/>.
172. RDF/XML Syntax Specification (Revised), Dave Beckett, Editor. W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-rdf-syntax-grammar-20040210/>. Latest version available at <http://www.w3.org/TR/rdf-syntax-grammar>
173. Resource Description Framework (RDF): Concepts and Abstract Syntax, Graham Klyne and Jeremy J. Carroll, Editors. W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-rdf-concepts-20040210/>. Latest version available at <http://www.w3.org/TR/rdf-concepts/>
174. Resource Description Framework (RDF) Schema Specification. W3C Recommendation, March 1999 (1999) <http://www.w3.org/TR/WD-rdf-schema>. Cited 1999
175. RDF Vocabulary Description Language 1.0: RDF Schema, Dan Brickley and R.V. Guha, Editors. W3C Recommendation, 10 February 2004 (2004) <http://www.w3.org/TR/2004/REC-rdf-schema-20040210/>. Latest version available at <http://www.w3.org/TR/rdf-schema/>. Cited 2004
176. Reeve, L., Han, H.: Survey of semantic annotation platforms. *Proc. of the 20th Annual ACM Symposium on Applied Computing and Web Technologies* (2005)
177. Saint-Dizier, P.: An approach to natural-language semantics in Logic Programming. *Journal of Logic Programming*. **3** (4), 329–356 (1986)
178. Schank, R.C.: Conceptual dependency: a theory of natural language understanding. *Cognitive Psychology*. 1972. **3**(4), 552–631 (1972)

179. Schank, R.C., Goldman, N.M., Rieger, C.J., Riesbeck, C.K.: *Conceptual Information Processing*. North-Holland Publ. Company; Amsterdam, Oxford American Elsevier Publ. Comp., Inc., New York (1975)
180. Schank, R., Birnbaum, L., Mey, J.: *Integrating semantics and pragmatics*. *Quaderni di Semantica*. VI(2) (1985)
181. Schubert, L.K.: *Dynamic skolemization*. In Bunt, H. Muskens, R. (eds.) *Computing Meaning*, vol. 1, *Studies in Linguistics and Philosophy Series*, Kluwer Academic Press, Dordrecht (also Boston, London), 219–253 (1999)
182. Schubert, L.K.: *The situations we talk about*. In Minker, J. (ed.) *Logic-Based Artificial Intelligence*. Kluwer, Dordrecht, 407–439 (2000)
183. Schubert, L. K., Hwang, C. H.: *An episodic knowledge representation for narrative texts*. *Proceedings of the First Int. Conf. on Principles of Knowledge Representation and Reasoning (KR'89)*, Toronto, Canada. pp. 444–458. (1989)
184. Schubert, L.K., Hwang, C.H.: *Episodic logic meets little red riding hood: a comprehensive, natural representation for language understanding*. In Iwanska, L. Shapiro, S.C. (eds.) *Natural Language Processing and Knowledge Representation: Language for Knowledge and Knowledge for Language*, MIT/AAAI Press, Menlo Park, CA, and Cambridge, MA, 2000, 111–174 (2000)
185. Sembock, T.M.T., Van Rijsbergen, C.J.: *SILOL : A Simple Logical-linguistic Document Retrieval System*. *Information Processing and Management*, **26**(1), 111–134 (1990)
186. *Semantic Web Activity Statement*. W3C, (2001) <http://www.w3.org/2001/sw/activity>
187. Seuren, P. A. M.: *Discourse Semantics*. Basil Blackwell, Oxford (1985)
188. Saint-Dizier, P.: *An approach to natural-language semantics in Logic Programming*. *Journal of Logic Programming*. **3**, 329–356 (1986)
189. Sgall, P., Hajicova, E., Panevova, J.: *The Meaning of the Sentence in Its Semantic and Pragmatic Aspects*. Academia and D. Reidel, Prague and Dordrecht (1986)
190. Sgall, P.: *The tasks of semantics and the perspectives of computers*. *Computers and Artificial Intelligence*. **8** (5), 403–421 (1989)
191. Shadbolt, N., Hall, W., Berners-Lee, T.: *The Semantic Web Revisited*. *IEEE Intelligent Systems*. **21**, 96–101 (2006)
192. Shapiro S.C.: *Formalizing English*. *International Journal of Expert Systems*. **9** (1), 151–171. (1996)
193. Shapiro, S.C.: *SnepPS: a logic for natural language understanding and commonsense reasoning*. In: Iwanska, L.M., Shapiro, S.C. (eds.) *Natural Language Processing and Knowledge Representation: Language for Knowledge and Knowledge for Language*, pp. 175–195. AAAI Press/The MIT Press, Menlo Park, CA (2000)
194. Shoenfield, J.L.: *Mathematical Logic*. Addison-Wesley Publ. Co., Reading, MA (1967)
195. Sowa, J.F.: *Conceptual Structures: Information Processing in Mind and Machine*. Addison-Wesley Publ. Comp. Reading (1984)
196. Sowa, J.F.: *Toward the expressive power of natural language*. In Sowa, J.F. (ed.) *Principles of Semantic Networks. Explorations in the Representation of Knowledge*. Morgan Kaufman Publ., Inc. San Mateo pp. 157–189. (1991)
197. Sowa, J.F.: *Knowledge Representation: Logical, Philosophical, and Computational Foundations*. Brooks/Cole, Pacific Grove, CA (2000)
198. Thibadeau, R., Just, M. A., Carpenter, P. A.: *A model of the time course and content of reading*. *Cognitive Science*. **6**, 157–203 (1982)
199. Uchida, H., Zhu, M., Della Senta T.: *A Gift for a Millennium*, A book published by the United Nations University, (1999) <http://www.unl.ias.unu.edu/publications/gm/index.htm>. Cited 1999
200. *Universal Networking Language (UNL) Specifications, Version 2005* (2005) [www.unl.org/unlsys/unl/unl2005](http://www.unl.org/unlsys/unl/unl2005). Cited 2005
201. *Universal Networking Language (UNL) Specifications, Version 2005, Edition 2006*, 30 August 2006, UNL Center of UNDL Foundation (2005) <http://www.unl.org/unlsys/unl/unl2005-e2006>. Cited 2006

202. Wermter, J., Hahn, U.: Massive Biomedical Term Discovery. *Discovery Science*, 281–293 (2005)
203. Wierzbicka, A.: *Lingua Mentalis. The Semantics of Natural Language*. Academic Press, Sydney, (1980)
204. “Voice Browser” Activity – Voice enabling the Web! W3C paper. (2001) <http://www.w3.org/Voice/>. Cited 2001
205. Wilks, Y.: An artificial intelligence approach to machine translation. In *Computer Models of Thought and Language*. Schank, R. Colby, K. (eds.) Freeman, San Francisco pp. 114–151. (1973)
206. Wilks, Y.: Form and content in semantics. *Synthese*, **82**(3), 329–351 (1990)
207. Winograd, T.: *Understanding Natural Language*. Academic Press, New York, Edinburgh Univ. Press Edinburgh (1972)
208. Wolska, M., Kruijff-Korabayova, I., Horacek, H.: Lexical-semantic interpretation of language input in mathematical dialogs. In: Hirst, G., Nirenburg, S. (eds.) *Proceedings of the Second Workshop on Text Meaning and Interpretation held in cooperation with ACL-2004*, 25–26 July 2004, Barcelona, Spain, pp. 81–88 (2004)
209. Wroe, C., Goble, C., Greenwood, M., Lord, P., Miles, S., Papay, J., Payne, T., Moreau, L.: Automating Experiments Using Semantic Data on a Bioinformatics Grid. *IEEE Intelligent Systems* (Jan/Feb 2004), Special issue on E-Science (2004)
210. Xu, L., Jeusfeld, M.A.: A concept for monitoring of electronic contracts. Tilburg University, The Netherlands (2003) <http://infolab.uvt.nl/pub/itrs010.pdf>. 19 p. Cited 2003
211. Zhu, M., Uchida, H.: Universal Word and UNL Knowledge Base. In: *Proceedings of the International Conference on Universal Knowledge Language (ICUKL-2002)*, 25–29 November 2002, Goa of India (1999) <http://www.unl.ias.edu/publications/UW%20and%20UNLKB.htm>. Cited 1999
212. Zhuge, H.: China’s E-Science Knowledge Grid Environment. *IEEE Intelligent Systems* (Jan/Feb 2004), Special issue on E-Science (2004)
213. Yasukawa, H., Suzuki, H., Noguchi, N.: Knowledge representation language based on situation theory. In: Fuehi, K., Kott, L. (eds.) *Programming of Future Generation Computers II: Proceedings of the 2nd Franco-Japanese Symp.* Amsterdam: North-Holland, pp. 431–460 (1988)

# Index

- e-science, 138
- formal system, 30
- Integral Formal Semantics of Natural Language, 27
- linguistic processors, 165
- metagrammar, 30
- restricted S-language, 34
- semantic annotation, 140
  
- algorithm of semantic assembly, 195
- algorithm of semantic-syntactic analysis, ix
- alphabet, 48
- antireflexive relation, 50
- antisymmetric relation, 50
  
- binary relation on a set, 49
- Broadly-Applicable Conceptual Metagrammar, 29
  
- calculus, 30
- classifying representation of a NL-text, 188
- component-morphological representation of a NL-text, 189
- concept-object system (c.o.s.), 64
- conceptual basis (c.b.), 70
- concretization of a type, 62
- concretization relation on a set of types, 58
- constructors, 171
  
- dictionary of the role interrogative word combinations, 181
- dictionary of verbal-prepositional frames, 176
- discourse, ix
  
- elementary compound type, 60
- elementary type, 60
- Episodic Logic, 24
  
- extensional quantifiers, 69
  
- formal language in an alphabet, 49
- function length(t), 49
- functional symbol, 64
  
- generalization of a type, 62
  
- intensional quantifier, 69
  
- K-calculus, 108
- K-representation (KR) of a NL-expression, 113
- K-representation of a NL-expression, 42
- K-string, 42
  
- l-formulas, 108
- lexico-semantic dictionary, 173
- linguistic basis, 182
- linguistic database, xi
  
- M-determinant, 167
- main types, 57
- marked-up conceptual basis (m.c.b.), 130
- markers, 171
- mathematical linguocybernetics, viii
- matrix semantic-syntactic representation (MSSR) of a NL-text, 192
- morphological determinant, 167
- morphological representation of a NL-text, 186
- morphological space, 168
  
- n-ary functional symbol, 93
- n-ary relation on a set, 49
- n-ary relational symbol, 93
- natural language, vii
- non-empty strings, 49

- partial order on a set, 50
- primary informational universe, 64
- principle of stability, 166
- principle of succession, 166
- projection of a dictionary of prepositional frames on the input text, 190
- projection of a dictionary of verb-prepositional frames on the input text, 190
- projection of a lexico-semantic dictionary on the input text, 190
- referential quantifier, 69
- referential structure of an NL-text, 125
- refinement of a sort, 61
- reflexive relation, 49
- role interrogative word combination, 213
- S-calculus, 34
- semantic dimension, 173
- semantic e-science, 138
- semantic representation (SR), ix
- semantic technologies, x
- semantics of natural language, ix
- semantics-oriented natural language processing systems (NLPs), vii
- SK-language, 108
- sort a meaning of proposition, 50
- sorts, 50
- spectrum of a type, 60
- strings in an alphabet, 49
- structured meaning of a NL-expression, ix
- symmetric relation, 50
- system of quantifiers and logical connectives, 69
- t-formulas, 108
- thematic role, 175
- Theory of Conceptual Graphs, 24
- theory of K-representations, xii, 32
- tolerance relation, 51
- transitive relation, 50
- type of a primary informational unit, 64
- types of a sort system, 55
- unary relation on a set, 49
- underspecified semantic representation, 23
- Universal Conceptual Metagrammar, 30
- universe of formal study, 78
- variable, 64
- y-formulas, 108