Senzing Demo MacBook Checklist

Provision a factory-reset MacBook Pro for Senzing Bootcamp demos. Tick one column per machine.

Machines	`Senzing-demo-01` · `Senzing-demo-02`
Accounts	`senzing` (administrator) · `demo` (standard; all sign-ins and demos)
Repository	`~/senzing-demos-for-mac`, linked from `~/Desktop/Senzing Demos`
Install pages	hub.senzing.com/bootcamp · hub.dockter.com/senzing-bootcamp-copilot-plugin-development/site

A. Before you start

01	02	As	Step
☐	☐	you	Have the demo GitHub account ready, with read access to `Senzing/senzing-bootcamp-copilot-plugin`.
☐	☐	you	Have sign-ins and plans ready: Claude (Max 5x or higher), ChatGPT (Pro), GitHub Copilot, Kiro (2000 credits or more).
☐	☐	you	Choose passwords for `senzing` and `demo`. Do not use the same `demo` password on both machines.

B. macOS setup assistant

01	02	As	Step
☐	☐	—	Create the administrator account `senzing`. Skip Apple ID / iCloud, or at least turn **off** iCloud Desktop & Documents.
☐	☐	senzing	System Settings › General › Software Update: install all updates and restart.

C. Provision (administrator)

01	02	As	Step

☐	☐	senzing	In Terminal, download and run the provisioning script with this machine's name:
			`curl -fsSLO https://raw.githubusercontent.com/docktermj/senzing-demos-for-mac/main/scripts/provision.sh`
			`bash provision.sh --name Senzing-demo-01   # or Senzing-demo-02`
			Names the Mac; installs Homebrew, git, gh, Python, Java, Maven, jq, the Senzing SDK (answer **y** to the EULA) and the apps it can; keeps the Mac awake on power.

☐	☐	senzing	When the script asks, enter the `demo` password you chose in section A. The script creates the standard user `demo`.
☐	☐	senzing	Install by hand any app the script lists at the end (Codex, GitHub Copilot, …). Drag each to `/Applications`.
☐	☐	senzing	Re-run `bash provision.sh`. It should finish with nothing left to install by hand.

D. Demo user

01	02	As	Step

☐	☐	demo	Log out, log in as `demo`, then in Terminal:
			`git clone https://github.com/docktermj/senzing-demos-for-mac.git ~/senzing-demos-for-mac`
			`bash ~/senzing-demos-for-mac/scripts/setup-user.sh`
			Adds `Senzing Demos` to the Desktop, checks the app links, sets the Senzing environment in `~/.zshrc` and the Codex network setting.

☐	☐	demo	Open `Senzing Demos` on the Desktop and double-click each app: Claude, ChatGPT, Codex, GitHub Copilot, Kiro. Each one opens.
☐	☐	demo	Turn on Do Not Disturb. Turn off screen lock and screen saver (System Settings › Lock Screen).

E. Sign in and install the bootcamp plugin (as `demo`)

01	02	As	Step
☐	☐	demo	**Claude:** sign in. Code › New, then + › Plugins › Manage plugins › Yours › Add › Add Marketplace: `https://github.com/Senzing/senzing-bootcamp-claude-plugin` › Sync › install for project (personal). Mode auto, model Sonnet 5.5, effort medium.
☐	☐	demo	**Codex (ChatGPT):** sign in. Plugins › Add › Add a marketplace: `https://github.com/Senzing/senzing-bootcamp-chatgpt-plugin` › Personal › Senzing Bootcamp › Install plugin. Model GPT-5.6 Terra, effort Medium.
☐	☐	demo	**GitHub Copilot:** sign in with the demo GitHub account. Customize › + Add › Manage marketplaces: `https://github.com/Senzing/senzing-bootcamp-copilot-plugin` › Browse › All types › “bootcamp” › senzing-bootcamp › Install. Mode Interactive, Copilot Fusion, effort Standard.
☐	☐	demo	**Kiro:** sign in. Powers › Add Custom Power › Import power from GitHub: `https://github.com/Senzing/senzing-bootcamp-kiro-power/tree/main/senzing-bootcamp` (paste the full URL).
☐	☐	demo	Write down each app's version and the plugin version that you tested: _____

F. Check the prepared demos (on both machines)

01	02	As	Step
☐	☐	demo	Each folder in `Desktop/demos/bootcamp/` is a finished, packaged bootcamp. For each one, open it in Claude and follow `docs/REVISIT_BOOTCAMP.md` to restore its database and state.
☐	☐	demo	**Banking** KYC/KYB and AML (`bootcamp-truthset-banking-kyc-kyb-aml`): restores; `docs/bootcamp_recap.pdf` opens.
☐	☐	demo	**Insurance** P&C claims fraud (`bootcamp-truthset-pc-insurance-claims-fraud`): restores; `docs/bootcamp_recap.pdf` opens.
☐	☐	demo	**Retail** customer deduplication (`demo-01`): restores; `docs/bootcamp_recap.pdf` opens.
☐	☐	demo	Run `reset.sh` afterwards so section G starts clean.
☐	☐	demo	If the bootcamp needs software that is not installed, install it as `senzing` without logging out, then add it to `provision.sh`: `su - senzing -c 'brew install <package>'` Always run the bootcamp as `demo`. Homebrew belongs to `senzing`, so typing its password at an install prompt does not help.

G. Test the canned bootcamps

01	02	As	Step
☐	☐	demo	**Claude:** open a prepared demo; it resumes and shows results.
☐	☐	demo	**Codex (ChatGPT):** open a canned demo; it resumes and shows results.
☐	☐	demo	**GitHub Copilot:** open a canned demo and follow its `OPEN_ME_FIRST.md`; it resumes and shows results.
☐	☐	demo	**Kiro:** open a canned demo; it resumes and shows results.
☐	☐	demo	Repeat one demo on poor or no Wi-Fi. Note what fails: _____

H. Before each event

01	02	As	Step
☐	☐	demo	Run `bash ~/senzing-demos-for-mac/scripts/reset.sh`.
☐	☐	demo	Check app and plugin versions against section E. If anything updated, re-run one test from section G.
☐	☐	demo	Charger, Do Not Disturb on, Wi-Fi details for the venue.

I. After each demo

01	02	As	Step
☐	☐	demo	Quit the AI apps, then run `bash ~/senzing-demos-for-mac/scripts/reset.sh` and answer **y**. This restores the repository exactly; it does not clear the apps' chat history.