

Demo document with computer code

HPL

Jun 22, 2021

1 Data file

Suppose we have some data in a file. The final result of including this file with `@@@CODE mydat.txt` (which implies a code environment starting with `!bc dat`) looks like this:

```
1  #      A      B      C      D      E
2      -0.5253   -0.9315   -0.3427   -0.1613   -0.8472
3      -0.9740   -0.2558   -0.5622   -0.7635   -0.0914
4      0.9216    0.7702   -0.4818    0.2155    0.2967
```

2 Complete program and terminal output

The following program (which breaks a page) reads the data in the file and performs analysis (typeset with `!bc pypro`):

```
1  from __future__ import print_function
2  import numpy as np
3
4  def readfile(filename):
5      """Read tabular data from file and return as numpy array."""
6      f = open(filename, 'r')
7      data = [] # list of rows in table
8      for line in f:
9          if line.startswith('#'):
10             continue # drop comment lines
11             numbers = [float(w) for w in line.split()]
12             data.append(numbers)
13     return np.array(data)
```

```

14
15 def analyze(data):
16     """Return statistical measures of an array data."""
17     return np.mean(data), \
18            np.std(data), \
19            np.corrcoef(data)
20
21 if __name__ == '__main__':
22     data = readfile('mydat.txt')
23     # Treat each column as a variable
24     m, s, c = analyze(data.transpose())
25     print("""
26     mean=%f
27     st.dev=%f
28     correlation matrix:
29     %s
30     """ % (m, s, c))

```

The output becomes (typeset with !bc sys):

```

1  Terminal> python fileread.py
2
3  mean=-0.006005
4  st.dev=0.583542
5  correlation matrix:
6  [[ 1.          0.0509676  0.52406366  0.20964645  0.1574504 ]
7   [ 0.0509676   1.         -0.30920845 -0.12129049  0.7611538 ]
8   [ 0.52406366 -0.30920845  1.         0.49355806 -0.42263817]
9   [ 0.20964645 -0.12129049  0.49355806  1.         -0.38286589]
10  [ 0.1574504   0.7611538  -0.42263817 -0.38286589  1.         ]]

```

3 Code snippet

Fortran 77 is also sometimes handy. Snippets in that language are typeset inside !bc fcod environments.

Fortran code box.

$$r_i = ca_i, \quad i = 1, \dots, n$$

```
1      subroutine process(a, n, c, r)
2  C    This subroutine returns array r = c*a
3      integer n
4      real*8 a(n), c, r(n)
5      integer i
6      do i = 1,n
7          r(i) = c*a(i)
8      end do
9      return
0      end
```