DocOps.io AsciiDoctorJ Architecture Decision Record(ARD)

Steve D Roach

Table of Contents

1. What is it?	1
2. How to use?	1
2.1. ADR Format	
2.2. First Example	1
2.3. Resulting ADR	2
3. ADR Summary Example	4
3.1. ADR Summary Source	5

1. What is it?

An Architectural Decision (AD) is a software design choice that addresses a functional or non-functional requirement that is architecturally significant. ADR

2. How to use?

```
[adr,test2,border=false] ① ② ③
----
include::123.adr[] ④
----
```

- 1 adr—name of the extension
- 2 test2—name of the generated file
- 3 border-use shadowed border or not
- 4 file that contains the adr format

2.1. ADR Format

• Using colons as separators for the file layout.

```
Title:Arch decision Title ①
Date: November 24th, 2010 ②
Status: Proposed ③
Context: Setting the context here ④
Consequences: What are the consequences of the decision ⑤
Participants: Architect, Engineer ⑥
```

- 1 Title for the record
- 2 Date for the record
- ③ Status can be 1 of (Proposed, Accepted, Superseded, Deprecated, Rejected)
- 4 Context
- **5** Consequences
- 6 Participants (optional)

2.2. First Example

• Contents of 123.adr

```
Title:Use Solr for Structured Data Search
Date: November 24th, 2010
Status: Proposed
```

Context: There is a need of having an API exposed which can be used to search structured data.

The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment.

There are options like [[https://www.elastic.co ElasticSearch]] and Solr where data can be replicated.

These solutions provide out of the box capabilities that can be leveraged by developers without needed to build RESTful or GraphQL type APIs.

Decision:Use [[https://solr.apache.org/ Solr]] for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences: Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr Cloud environment.

Participants:Roach,Rose,Duffy

2.3. Resulting ADR

Use Solr for Structured Data Search

Status: Proposed

Date: November 24th, 2010

Context

There is a need of having an API exposed which can be used to search structured data. The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment. There are options like and Solr where data can be replicated.

These solutions provide out of the box capabilities that can be leveraged by developers without needed to build RESTful or GraphQL type APIs.

<u>Decision</u>

Use for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences

Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr Cloud environment

Participants

Roach,Rose,Duffy

2.3.1. New Window Test

Use Solr for Structured Data Search

Status: Accepted **Date:** November 24th, 2010

Context

There is a need of having an API exposed which can be used to search structured data. The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment. There are options like and Solr where data can be replicated. These solutions provide out of the box capabilities

that can be leveraged by developers without needed to build RESTful or GraphQL type APIs.

Decision

Use for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences

Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr

Participants

Roach,Rose,Duffy

Source for Non New Window

```
[adr,test4,border=true, width="70%",role="center", newWin=false,
boxWidthIncrease="20"]
```

include::456.adr[] ①

Use Solr for Structured Data Search

Status: Superseded Date: November 24th, 2010

Context

There is a need of having an API exposed which can be used to search structured data. The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment. There are options like and Solr where data can be replicated. These solutions provide out of the box capabilities

that can be leveraged by developers without needed to build RESTful or GraphQL type APIs. $\label{eq:can} % \begin{center} \$

Decision

Use for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences

Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr Cloud environment.

Participants

Roach,Rose,Duffy

Use Solr for Structured Data Search

Status: Deprecated Date: November 24th, 2010

Context

There is a need of having an API exposed which can be used to search structured data. The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment. There are options like and Solr where data can be replicated. These solutions provide out of the box capabilities

that can be leveraged by developers without needed to build RESTful or GraphQL type APIs.

Decision

Use for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences

Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr

Participants

Roach,Rose,Duffy

Use Solr for Structured Data Search

Status: Rejected Date: November 24th, 2010

Context

There is a need of having an API exposed which can be used to search structured data. The Data currently resides in RDBMS, it is difficult to expose micro-service directly querying out of RDBMS databases since the application runs out of the same environment. There are options like and Solr where data can be replicated. These solutions provide out of the box capabilities that can be leveraged by developers without needed to build RESTful or GraphQL type APIs.

Decision

Use for data indexing. This use is because Solr has high performance throughput with large volume of data.

Unstructured data can also be supported.

If this decision does not meet the need then additional PoC will be created.

Consequences

Data Needs to be replicated across the solr cloud instances.

This Solr cloud needs maintenance.

Near realtime data replication is required Additional Cost of maintaining the Solr Cloud environment.

Participants

Roach,Rose,Duffy

1 Included adr file

3. ADR Summary Example

Title	Status	Participants	Date
Use Solr for Structured	Proposed	Roach,Rose,Duffy	November 24th, 2010
Data Search			

Title	Status	Participants	Date		
Use Solr for Structured Data Search	Accepted	Roach,Rose,Duffy	November 24th, 2010		
Use Solr for Structured Data Search	Rejected	Roach,Rose,Duffy	November 24th, 2010		
Use Solr for Structured Data Search	Superseded	Roach,Rose,Duffy	November 24th, 2010		
Use Solr for Structured Data Search	Deprecated	Roach,Rose,Duffy	November 24th, 2010		
server for http://127.0.0.1:8000/src/main/docs/456.adr does not exist. null					
server for http://127.0.0.1:8000/src/main/docs/123.adr does not exist. null					

3.1. ADR Summary Source

WARNING

Only adr files can be processes. Recommend using adr files and include as you can version control this file.

```
[adrsummary]
----
123.adr ①
http://127.0.0.1:8000/src/main/docs/456.adr ②
http://127.0.0.1:8000/src/main/docs/123.adr
----
```

- ① Relative path to current document
- 2 Full URL to adr