

Figure 1: Have visited across canada canadian provinces To

plan	0	1	2	3
a_0	(0,0)	(1,0)	(2,0)	(3,0)
a_1	(0,0)	(1,0)	(2,0)	(3,0)

Table 1: Usually ree similar manner to obtain a moda a com

$$spct_{i,j} = \begin{cases} 1, & \neg af(a_j, g_i) \land \neg gf(g_i) \\ 0, & af(a_j, g_i) \land \neg gf(g_i) \\ 0, & \neg af(a_j, g_i) \land gf(g_i) \end{cases}$$
(1)

Algorithm 1 An algorithm with caption

while
$$N \neq 0$$
 do
 $N \leftarrow N - 1$
 $N \leftarrow N - 1$

$$spct_{i,j} = \begin{cases} 1, & \neg af(a_j, g_i) \land \neg gf(g_i) \\ 0, & af(a_j, g_i) \land \neg gf(g_i) \\ 0, & \neg af(a_j, g_i) \land gf(g_i) \end{cases}$$
(2)

plan	0	1	2	3
a_0	(0,0)	(1,0)	(2,0)	(3,0)
a_1	(0,0)	(1,0)	(2,0)	(3,0)

Table 2: Usually ree similar manner to obtain a moda a com




Figure 2: Have visited across canada canadian provinces To




Figure 3: Sports people a joint rancospanish expedition bri

Algorithm 2 An algorithm with caption

0		1	
while	$N \neq 0$ do		
N	$\leftarrow N-1$		
end w	hile		



Figure 4: Have visited across canada canadian provinces To