

DigiPPPiP: Digital Partner Pen Play in Parallel

A Cyberphysical, Temporal, Active-Inference, and Place-Based Successor to PPPiP (2018)

Siddhant Shrivastava

PhD Student (AI and Robotics), Singapore University of Technology and Design, Singapore

`siddhant_shrivastava@mymail.sutd.edu.sg`

ORCID: 0000-0002-9688-4730

and Evelyn C. Goh

PhD Student, Biomedical Engineering, National University of Singapore College of Design and Engineering

National University of Singapore Saw Swee Hock School of Public Health

`e0983111@u.nus.edu`

ORCID: 0000-0001-7182-3950

and Alexandra Mikhailova

Active Inference Institute

`alexandra@activeinference.institute`

and Daniel Ari Friedman

Active Inference Institute

`daniel@activeinference.institute`

ORCID: 0000-0001-6232-9096

August 1, 2026

Contents

1 Abstract	2
2 Introduction: From Shared Marks to Study-Ready Infrastructure	3
3 Cyberphysical Substrate: Canvas, Body, Archive	5
4 Temporal Coordination: Turns, Overlap, and Persistence	7
5 Modeling Lens: Active Inference Without Mechanism Claims	10
6 Neuroergonomic Burden and Shared Attention	12
7 Cyber-Phenomenology: Presence, Embodiment, and Mediation	13
8 Accessible Shared Drawing: Capability Before Claim	14
9 Relational Aesthetics: Coauthored Marks and Social Form	15
10 Place-Based Micropractice and Digital Placemaking	17
11 Temporal-Spatial Taxonomy for Study Design	19
12 Dyadic Digital Health: Consent, Relationship Boundaries, and AI Separation	21
13 Methods Protocol: Governance, Provenance, and Validation	23
13.1 Event Logging and Participant-Facing Governance	23
13.2 Source and Claim Governance	24
13.3 Systems Boundary and Feedback Governance	27
13.4 Evidence Scope and Non-Claims	28
13.5 Reproducible Figure Methods	28
13.6 Study Package, Access, Place, and Outcomes	31
13.7 Falsification and Claim Boundaries	32
14 Research Agenda: From Feasibility to Evidence	35
15 Integrative Model: The Human-Human DigiPPPiP Kernel	37
16 Discussion: Limits, Failure Modes, and Future Replacement	38
17 Case Studies: Dementia Care as a Stress Test	40
17.1 Dementia Care: Asymmetric Dyads, Biographical Scaffolding, and Fluctuating Consent	40
18 Conclusions: Study-Ready Without Overclaiming	42
19 Appendix: Free-Energy and Active-Inference Formalisms	43
19.1 Event-to-Model Mapping	43
19.2 Minimal Free-Energy Primitive	43
19.3 Hyperscanning and Network Geometry	44
19.4 Narrative Information and Aesthetic Discovery	45
20 References	48

1 Abstract

DigiPPPiP extends Partner Pen Play in Parallel (PPPiP) from a co-present paper practice into a reproducible framework for cyberphysical, remote, semisynchronous, asynchronous, accessible, and place-responsive dyadic drawing [Mikhailova and Friedman, 2018]. The framework is positioned within collaborative-work studies of shared drawing surfaces [Tang, 1991], cyber-physical-social systems [Sobb et al., 2023], mediated embodiment and presence [Biocca, 1997, Lee, 2004], digital intimacy technologies [Hassenzahl et al., 2012, Neustaedter and Greenberg, 2012], and cautious hyperscanning methodology [Czeszumski et al., 2020, Hamilton, 2021].

The manuscript translates the project brief into a modular research artifact: 9 temporal-spatial modalities, 13 evidence dimensions, 6 planned outcome measures, and 35 conceptual figures are generated or registered by the project code rather than hand-maintained prose. The computational layer is explicitly illustrative, not empirical: the active-inference, inter-brain-synchrony, Forman-Ricci, narrative-information, source-quality, accessibility, and neuroergonomic outputs are deterministic conceptual models designed to make theoretical commitments inspectable. Formal equations are consolidated in sec. 19 so the main line can state evidence boundaries before presenting mathematical detail.

The argument is that DigiPPPiP should be treated as human-human relational technology. Its irreducible design kernel is modest: two partners, a shared mark field, perceptible traces of agency, a temporal relation among contributions, and consentful control over persistence. Digital infrastructure expands the substrate of shared mark-making without replacing the second-person, embodied, narrative, and affective conditions that make the practice relationally meaningful [Schilbach et al., 2013, Lehmann et al., 2024, Vaisvaser et al., 2024]. The manuscript explicitly avoids claims that DigiPPPiP is clinically therapeutic, universally accessible, or causally validated by neural synchrony; those remain empirical questions for controlled studies. Cross-references use Pandoc labels, so sections, equations, figures, and tables remain automatically numbered across PDF and web render targets.

2 Introduction: From Shared Marks to Study-Ready Infrastructure

The original PPPiP paper defined a simple dyadic practice: two partners draw simultaneously on one shared sheet, treating improvised mark-making as a non-clinical, low-cost, relational exercise [Mikhailova and Friedman, 2018]. Couple joint-drawing research also gives the manuscript a more direct arts-therapy precedent for reading connectedness and individuality through shared image-making [Snir and Wiseman, 2013]. Its theoretical value came from the convergence of art therapy, partner improvisation, controlled novelty, interpersonal neural synchrony, and the Free Energy Principle [Friston, 2010]. DigiPPPiP keeps that foundation but asks what changes when the shared surface becomes a tablet, networked canvas, augmented paper, persistent whiteboard, or place-responsive archive.

The CSCW lineage matters because shared drawing surfaces have long been more than image-output devices. Observational work on collaborative drawing showed that gestures, spatial orientation, drawing process, and the common workspace all carry information that the finished drawing alone does not capture [Tang, 1991]. ClearBoard made the same point technologically by integrating interpersonal space with a shared drawing workspace, using gaze and gesture as part of the collaborative medium rather than as side channels [Ishii et al., 1993]. Social translucence and workspace-awareness research then name the design obligation: a system should make relevant partner activity visible enough to support awareness and accountability while avoiding indiscriminate exposure [Erickson and Kellogg, 2000, Gutwin and Greenberg, 2002]. DigiPPPiP therefore treats the canvas as an interaction scene: marks, pauses, attention shifts, access controls, and return visits are part of the relational event. This positioning prevents a novelty overclaim. The contribution is not that digital co-drawing exists, but that PPPiP can be reframed as a reproducible, partner-centered research program for studying how shared marks mediate relational attention.

From first principles, the framework has fewer hard requirements than a typical app description implies. It requires participating agents who can affect a shared surface; a trace that both partners can perceive, interpret, or revisit; enough temporal structure to distinguish simultaneous, alternating, and delayed action; and governance over who can save, replay, export, or erase the artifact. Tablets, AR overlays, machine-learning prompts, physiological sensors, and cloud archives are optional implementations, not constitutive requirements. This distinction matters because DigiPPPiP should not optimize for digital sophistication when the function to preserve is reciprocal attention through marks.

The project brief motivates a successor framework with cyberphysical, temporal, active-inference, neuroergonomic, cyber-phenomenological, accessibility, relational-aesthetic, place-based, and dyadic digital-health dimensions. The evidence graph in fig. 1 formalizes those dimensions as a lineage from the original PPPiP domains into the present framework. The graph currently covers 5 source domains and 13 DigiPPPiP dimensions with 100 percent citation coverage.

DigiPPPiP is therefore a framework for designing and studying intentional shared drawing across substrates. It is not a claim that every digital canvas is therapeutic, nor that any synthetic model here measures a real couple. A weak implementation would merely connect users to drawing software; a stronger implementation would preserve agency, mutual visibility, access, privacy, and interpretive openness. The manuscript uses computational primitives to keep conceptual claims explicit and testable: fig. 2 shows the conceptual expansion, fig. 3 maps the actors and artifacts, sec. 11 defines the design space, sec. 5 states the modeling lens, sec. 19 keeps the formal primitives inspectable, sec. 13 specifies what future studies must log and govern, and sec. 14 names the empirical work required before intervention claims would be justified.

Reader route map: substrate, temporal coordination, and taxonomy sections define what counts as a DigiPPPiP condition; the modeling, neuroergonomic, phenomenological, accessibility, aesthetic, and place sections explain how the condition can be interpreted without treating interpretation as evidence; the digital-health section sets the dyadic ethics boundary; the methods protocol specifies source verification, figure provenance, participant-facing controls, and validation gates; the agenda and discussion sections state what evidence would strengthen or falsify the framework. The route is intentionally ordered from theory to protocol to limits, with the formal appendix separated so equations and diagnostic figures do not outrun the human-human claim.




Figure 1: Bipartite evidence graph linking original PPPiP evidence domains to DigiPPiP dimensions. This conceptual synthesis is generated by `generate_evidence_synthesis_plot()` from the citation-bearing graph in `src/evidence.py`; read left nodes as source domains, right nodes as framework dimensions, node numbers as citekey counts, and link weight as lineage density supporting the introduction’s scope argument. It is conceptual rather than empirical, and stronger claims would require direct comparative studies within each dimension.




Figure 2: Timeline of the conceptual expansion from paper PPPiP into a cyberphysical research program. The figure is generated by `generate_evolution_timeline()`; read the connected markers as staged additions of substrate, hybrid interaction, neural measurement, narrative analysis, and place responsiveness. It supports the introduction’s claim that DigiPPiP is an organized expansion, not an adoption history or outcome trend; empirical chronology would require archival or deployment data.




Figure 3: Conceptual ecology of DigiPPiP as a dyadic system of actors, devices, shared canvas artifacts, event logs, and situated contexts. The visual grammar is generated by `generate_conceptual_ecology()`; blue actor boxes, green artifact boxes, orange signal boxes, and purple context boxes show how partner agency flows through the shared surface. It supports the introduction’s design-kernel argument and remains conceptual until instrumented sessions test these dependencies.

3 Cyberphysical Substrate: Canvas, Body, Archive

Cyberphysical DigiPPiP treats the “paper” in PPPiP as a variable substrate rather than a fixed object. Pen-and-paper remains the haptic baseline, but shared tablets, web canvases, AR overlays, VR drawing spaces, smart paper, and persistent whiteboards all create different couplings among gesture, mark, archive, and partner response. Cyberphysical-social systems research is useful because it keeps physical, cyber, and social layers in one analytic frame rather than reducing the system to a device or app [Sobb et al., 2023]. Collaborative-work studies add a second discipline: the drawing surface must preserve the interactional value of gestures, spatial relations, and work-in-progress marks, not only the final image [Tang, 1991, Ishii et al., 1993].

That design discipline is stronger when the canvas is treated as a shared-workspace system rather than as a drawing file with two accounts. Workspace awareness asks what each partner can know about the other’s location, action, intention, and change history in the shared field [Gutwin and Greenberg, 2002]. Social translucence asks whether that visibility supports social coordination and accountability without becoming total visibility [Erickson and Kellogg, 2000]. Collaborative tabletop research adds a spatial constraint: people create personal, group, and storage territories even when the work surface is shared, so the canvas should support mutual access without erasing ownership, reach, and turn structure [Scott et al., 2004]. DigiPPiP should therefore expose partner activity at the granularity needed for response: live strokes, recent changes, viewport differences, consent state, and replay availability. It should not expose hidden drafts, every hesitation, device telemetry, or physiological streams by default.

Digital drawing should therefore be evaluated by affordance fit rather than by whether it perfectly imitates paper. Context-sensitive pen-tablet systems show that drawing can become more natural when software is aware of the relation among hand, pen, and surface [Sun et al., 2011]. Remote co-design work likewise shows that shared digital sketching can support collaborative understanding even when the expressive qualities of paper remain distinctive [Close et al., 2024]. Creativity-support and collaborative-visual-analytics scholarship adds a methods lesson: tools should support exploration, annotation, provenance, shared context, and recoverable interpretation rather than only faster production [Shneiderman, 2007, Heer and Agrawala, 2008]. Co-creative drawing workflow research adds an important boundary for AI-assisted extensions: computational systems can observe, model, and prompt creative processes, but they should be evaluated by how they support human authorship and shared interpretation [Jansen and Sklar, 2021]. DigiPPiP extends these design lessons into intimate and domestic contexts where low friction, privacy, ambiguity, and ritual may

matter as much as precision.

fig. 4 maps DigiPPPiP as a cyber-physical-social system with explicit architecture lanes rather than a generic app stack. The default lane is the human-human drawing loop: one partner acts, the shared surface changes, the other partner responds, and both partners retain archive-control agency. Instrumentation, modeling, optional AI support, and publication governance are adjacent branches. They can make the practice more study-ready, but they are not allowed to become the practice itself. This diagram is therefore also a non-claim statement: it describes boundaries, data movement, and stop conditions; it does not claim that the architecture improves relationships, reduces distress, or identifies a cognitive mechanism.




Figure 4: DigiPPPiP system architecture with a human-human default lane, instrumentation support, computed modeling layer, optional AI branch, and publication-governance boundary. The figure is generated by `generate_cpss_architecture()` from `src/systems_governance.py`; read the left badges as boundary status, the middle blocks as components, and the right boxes as governance gates or non-claims. It supports the cyberphysical argument that system boundaries must be explicit before features are interpreted. The diagram is conceptual, and validation would require observing how real interface changes affect partner behavior, consent, access, and archive control.

fig. 5 positions the modes as affordance trade-offs rather than replacements. Physical-only PPPiP preserves haptic richness and place grounding. Remote digital modes extend geographic reach and accessibility. Hybrid modes are especially important because they let one partner keep a material surface while the shared artifact remains digitally visible, versioned, and transportable.

The minimum viable substrate is not “a digital drawing app.” It is any arrangement that lets partner action become visible as a shared mark while preserving enough timing, authorship, and consent context for the other partner to respond. A high-resolution tablet can fail that test if notifications, menus, opaque storage policies, or AI prompts pull attention away from the dyad. A photographed paper exchange can satisfy it if the image, timing, and response loop remain clear. This is the first-principles reason the framework treats cyberphysical modes as affordance configurations rather than a progress ladder.

This substrate shift changes the research problem. The central question is no longer whether digital drawing is equivalent to paper drawing. A more useful question is which relational affordance a pair needs in a given context: immediacy, haptics, accessibility, distance, persistence, privacy, or place anchoring. The taxonomy in sec. 11 gives those choices a stable vocabulary, and the protocol in sec. 13 defines what must be logged before such affordances can be compared.




Figure 5: Cyberphysical affordance spectrum for physical, digital, hybrid, AR, VR, and asynchronous drawing modes. Scores are conceptual design variables generated by `generate_cyberphysical_spectrum()`; read the green and purple lines as contrasting affordances for haptic richness and geographic reach, with the filled area marking trade-off space. The plot supports modality selection, not superiority claims; measured user outcomes would be needed to calibrate the scores.

4 Temporal Coordination: Turns, Overlap, and Persistence

The original PPPiP form is synchronous: both partners mark the surface at the same time. DigiPPPiP separates synchrony from relationality. Synchronous sessions still matter because joint action requires partners to coordinate bodies, intentions, and timing, and because active interaction is a strong candidate context for inter-brain synchrony in cooperative and naturalistic tasks [Sebanz et al., 2006, Czeszumski et al., 2020, 2022]. Emerging work on online group interaction suggests that neural alignment can also appear under virtual conditions when participants remain actively engaged [Azhari et al., 2025]. Yet synchrony is not the only temporal form that can support intimacy, play, or shared meaning.

Remote and delayed modes should not be described as if distance has been solved. Distance changes the cost of coordination, common ground, informal repair, and collaboration readiness [Olson and Olson, 2000]. Grounding theory adds a finer vocabulary: partners need evidence that a mark, gesture, or prompt has been perceived and understood well enough for the next contribution [Clark and Brennan, 1991]. Recent video-mediated collaborative-drawing work makes that requirement concrete: proposal sequences depend on verbal, embodied, and screen-based actions, and the person controlling the drawing tool can become pivotal in coordinating joint decisions [Oittinen and Räisänen, 2025]. DigiPPPiP’s temporal design should therefore measure not only whether users were online together, but how the canvas supported acknowledgement, repair, turn completion, tool-control transfer, and later re-entry into the same shared artifact.

Semisynchronous DigiPPPiP introduces alternation. Partners are present in the same session but take turns or contribute in bursts. That mode preserves mutual responsiveness while creating short prediction intervals: each mark becomes a cue for anticipating the partner’s next action. It also makes repair visible: an undo, hesitation, or spoken clarification can become part of the event stream rather than an invisible failure. This is a natural bridge between the modeling lens in sec. 5 and the formal narrative account in sec. 19.

Asynchronous DigiPPPiP changes the practice more radically. Partners contribute at separate times, making the canvas a persistent relational object. Asynchronous mental-health technologies show that clinical or supportive exchange need not always be real-time to be meaningful [Lagera et al., 2023]. For DigiPPPiP, absence becomes part of the form: waiting, revisiting, and responding create a slower temporal arc of curiosity and resolution. Digital-intimacy research is relevant here because many strong-tie technologies rely on awareness, traces, rituals, and low-pressure presence rather than continuous conversation [Hassenzahl et al., 2012, Vetere et al., 2005].

The temporal primitives are overlap, order, delay, persistence, and repair. Overlap supports co-action; order supports

anticipation; delay supports reflection; persistence supports return; repair supports trust after confusion. These primitives are more fundamental than labels such as live, remote, or asynchronous because the same interface can instantiate them differently for different dyads. A study that logs only a session label loses the very structure that may explain relational meaning.

fig. 6 translates these distinctions into a staged study matrix. The matrix separates peer, mentor, and AI-assisted roles from co-located, remote, turn-taking, and persistent temporal-spatial conditions. It is a protocol-planning figure, not a claim that any one condition is universally superior.




Figure 6: Dyadic task matrix for staged DigiPPPiP studies. Values generated by `generate_dyadic_task_matrix()` encode conceptual mutual-responsiveness demand across role structures and temporal-spatial conditions; read rows as partner-role arrangements, columns as session modes, numeric labels as planning scores, and patterned cells as high-coordination conditions. The matrix supports the temporal architecture’s sampling argument rather than ranking modes as universally better. Empirical calibration would require observed timing logs, participant reports, and matched-condition comparisons.

fig. 7 shows how the temporal distinction becomes measurable. Strokes, utterances, repairs, and synchrony windows occupy separate tracks so future studies can distinguish overlap, alternation, latency, and delayed response without collapsing all of them into a single session label.

fig. 8 complements the timeline with three canonical event patterns. The point is design clarity: parallel marks, turn-taking marks, and long-delay marks invite different hypotheses about attention, anticipation, and narrative continuity.

fig. 9 gives a conceptual phase model for synchronous sessions. It should not be read as empirical fNIRS output. Its role is to make explicit the hypothesis that initiation, elaboration, convergence, and completion may differ in inter-brain-synchrony profiles and should be tested directly.




Figure 9: Conceptual inter-brain-synchrony phase profile across initiation, elaboration, convergence, and completion. Values are generated by `generate_ibs_phase_plot()` from `src/hyperscanning.py`; read the line as an illustrative synchrony proxy and shaded bands as session phases. The figure supports hypothesis formation for synchronous sessions, not neural evidence. Real fNIRS or EEG analyses would need artifact correction, controls, and preregistered phase definitions.

5 Modeling Lens: Active Inference Without Mechanism Claims

Active inference gives DigiPPPiP a disciplined modeling vocabulary for dyadic mark-making. Each partner can be described as maintaining expectations about the shared canvas, the other partner’s likely contribution, and the evolving meaning of the artifact. The shared drawing is therefore a sensory sample, a prediction target, and an action channel [Friston, 2010, Friston et al., 2017, Ramstead et al., 2020]. Active-inference accounts of human communication support this interactional reading only when the model stays tied to observable communicative events rather than becoming a generic metaphor [Vasil et al., 2020]. In second-person terms, the partner is not a stimulus to observe from outside but an agent whose responses shape one’s own policy choices [Schilbach et al., 2013, Redcay and Schilbach, 2019, Lehmann et al., 2024].

The main claim is intentionally narrow. DigiPPPiP does not claim that participants literally compute free-energy equations, nor that the current simulations measure a real couple. The claim is that a useful formal account must specify states, observations, policies, update rules, and observable consequences. If a study cannot map interface events to observations, define partner-relevant policies, or distinguish reciprocal updating from shared-stimulus effects, then active inference is not doing explanatory work for that study.

The formal appendix consolidates the mathematical primitives, model figures, and toy diagnostics in one place sec. 19. That appendix maps DigiPPPiP events to active-inference variables, gives the Gaussian point-belief model used by `src/active_inference.py`, shows the coupled-versus-decoupled toy run, and places narrative entropy, epistemic arcs, and geometric hyperscanning under the same evidence boundary. Keeping those details out of the main line makes the argument easier to inspect: the manuscript first states why the model is useful, then the appendix shows exactly what the model assumes.

This separation also protects the empirical agenda. Hyperscanning, narrative information, and free-energy trajectories are candidate measurement languages, not outcome evidence. Synchrony can be inflated by shared stimulus timing, motion artifacts, physiology, preprocessing decisions, and analytic windows [Tachtsidis and Scholkmann, 2016, Hamilton, 2021, Zimmermann et al., 2024]. Narrative entropy can identify symbolic structure without proving shared meaning. A conceptual free-energy curve can expose a coupling assumption without showing that partners improved. The framework is strongest when each formalism names the future comparison that could reject it.

The practical upshot is a modeling checklist. A DigiPPPiP study should log the visible mark, the timing of the response, the partner-facing cue, the repair or withdrawal option, and the artifact-governance state. It should then ask whether the model explains something beyond simpler alternatives such as ordinary shared drawing, video conversation, or solo art-making. Active inference remains in the manuscript because it forces those commitments into the open, not because

it upgrades conceptual simulations into evidence.

6 Neuroergonomic Burden and Shared Attention

Neuroergonomics studies brain and behavior in real-world tasks rather than only laboratory tasks [Ayaz and Dehais, 2019]. DigiPPPiP needs this framing because the desired practice happens in homes, cafes, studios, hospitals, classrooms, and long-distance relationships. Mobile fNIRS and related field methods make it increasingly plausible to study social and cognitive workload in naturalistic environments [Dehais et al., 2020, Moffat et al., 2024]. The same literature also cautions that naturalism raises measurement risk: motion, lighting, posture, fatigue, device familiarity, and partner relationship history can all change what a signal means.

The core design rule is restraint. The original paper-based practice worked partly because the interface was nearly invisible: pen, paper, partner, mark [Mikhailova and Friedman, 2018]. Digital implementations should add capabilities only where they support the dyad: shared visibility, accessibility, persistence, consensual replay, or place anchoring. Tool palettes, notifications, social feeds, and AI suggestions can easily become technofence if they compete with partner attention, a risk already documented in couple-relationship technology research [McDaniel and Coyne, 2016].

Attention is the scarce resource in DigiPPPiP. The first-principles question for any interface feature is whether it increases partner-directed perception, action, repair, or reflection. A feature that increases expressivity while fragmenting attention is not automatically an improvement. A slower or plainer interface may be neuroergonomically superior when it keeps the dyad inside the shared act rather than inside the tool.

fig. 10 operationalizes three design constraints. The flow surface represents challenge-skill balance, drawing on flow research while remaining a conceptual interface diagnostic rather than an experience sample [Csikszentmihalyi and LeFevre, 1989]. The technofence curve models the cost of interruptions. The attention simplex asserts that attention must be allocated among the partner’s marks, one’s own marks, and the shared canvas. These are design diagnostics, not biomarkers. Their purpose is to make interface burden visible before a digital feature is treated as relationally helpful.




Figure 10: Conceptual neuroergonomic diagnostics: flow channel, technofence cost, intentional-enclosure gain, and attention allocation. The figure is generated by `generate_neuroergonomics_flow_plot()` from `src/neuroergonomics.py`; read the panels as challenge-skill fit, interruption cost versus enclosure gain, and distribution of attention across partner, self, and canvas. It supports interface-burden reasoning. The values are design primitives, not measured workload or flow-state evidence.

BCI and neurofeedback extensions should remain secondary to the human-human practice. Digital art-therapy research suggests that technology can support creative expression and research instrumentation while creating ethical, material, and access constraints [Zubala et al., 2021, Reitere et al., 2024], but DigiPPPiP should not make neural instrumentation a prerequisite. The strongest design path is progressive enhancement: the practice works with pen and paper, improves with a shared digital canvas, and may later support optional biofeedback for research contexts.

7 Cyber-Phenomenology: Presence, Embodiment, and Mediation

DigiPPPiP changes the phenomenology of shared drawing. In co-present PPPiP, the partner’s mark arrives with posture, breath, hesitation, and ambient bodily cues. In remote DigiPPPiP, the mark arrives through a mediated surface. This does not make the practice unreal; it changes how embodiment is distributed across body, tool, screen, and archive. Phenomenology of embodiment gives the theoretical background for treating tools and media as extensions of bodily agency [Merleau-Ponty, 2012], while presence research distinguishes social richness, mediated immediacy, and shared-space illusions as design variables rather than guarantees of togetherness [Lombard and Ditton, 1997, Biocca, 1997, Lee, 2004].

Telepresence and re-embodiment are central. A remote shared canvas carries traces of the partner’s motor act, while video, voice, latency, cursor trails, stroke halos, and replay create additional layers of presence and absence [Lombard and Ditton, 1997, Biocca, 1997, Lee, 2004]. The concept of digitally mediated or marbled embodiment helps avoid a simplistic hierarchy in which physical co-presence is always authentic and remote connection is always degraded [Atuk and Cole, 2024]. Video-mediated collaborative drawing also shows that screen action is not merely a visual output; it is part of how participants make proposals, invite co-participation, and coordinate who has practical control of the emerging drawing [Oittinen and Räisänen, 2025]. A DigiPPPiP system can support social presence without photorealistic avatars by using lightweight, privacy-preserving cues: labeled cursors, delayed traces, visible turn-taking, and explicit tool-control state.

The same cues can fail phenomenologically. A cursor trail can feel intimate when it makes hesitation visible, but invasive when it makes every micro-movement inspectable. A replay can help partners revisit a moment, but it can also convert a fragile exchange into evidence to be judged later. DigiPPPiP therefore needs a phenomenology of control as much as a phenomenology of presence: partners should know when they are visible, when traces persist, and when a mark can be withdrawn.

Privacy is not just a settings panel in this account. Contextual-integrity theory treats privacy as appropriate information flow within a social context, while networked-privacy work treats privacy as a dynamic boundary-management process rather than a simple public/private switch [Nissenbaum, 2011, Palen and Dourish, 2003]. Communication Privacy Management theory is especially relevant for partner drawing because the artifact can become co-owned: one partner’s expressive mark may disclose something about both partners, and later sharing may require negotiated rules rather than unilateral export [Petronio and Child, 2020]. A DigiPPPiP archive is therefore phenomenologically legitimate only when persistence, replay, and deletion preserve the dyad’s felt control over the trace.

This matters most for asynchronous practice. The gap between contributions becomes part of the event structure: the absence after a mark creates expectation; the next mark answers it. The formal appendix describes this as curiosity, epistemic action, and co-discovery under an expected-information-gain arc sec. 19. The phenomenological hypothesis is that waiting can intensify, not merely interrupt, dyadic meaning when the shared artifact remains stable and intentional. That claim should be tested with presence measures and qualitative accounts; it should not be generalized from theory alone.

8 Accessible Shared Drawing: Capability Before Claim

The original PPPiP emphasized low cost, but DigiPPPiP must treat disability access as a first-order constraint rather than an accommodation afterthought. Digital art therapy and telehealth arts-therapy research show that online and digital modalities can expand participation for people whose access needs make conventional studio or clinic settings difficult, while also introducing pragmatic and ethical constraints [Zubala et al., 2021, Reitere et al., 2024, Potash et al., 2020]. Online art-therapy work with learning-disabled young adults also shows why the platform, group norms, and communication channel are part of access rather than neutral delivery infrastructure [Datlen and Pandolfi, 2020]. Reframing digital art therapy for digitally mediated practice adds the same structural warning: technology changes the therapeutic and relational triangle rather than simply transporting a studio session online [Haywood and Grant, 2022]. Accessibility here is not merely compliance; it changes what kinds of relational drawing become possible. Ability-based design and W3C accessibility guidance support this shift from generic interface polish toward capability-specific accommodation [Wobbrock et al., 2011, World Wide Web Consortium, 2023, 2021]. Participatory design work with children with special needs shows why access claims should be made with the people affected rather than inferred from designer intent [Frauenberger et al., 2011]. Social accessibility research on assistive technology also shows that access is shaped by self-presentation, confidence, stigma, and the social meaning of visible supports [Shinohara and Wobbrock, 2016].

Inclusive DigiPPPiP should support multiple input channels: stylus, touch, mouse, eye gaze, switch control, voice, assisted drawing, and partner-mediated contribution. It should support multiple feedback channels: visual stroke changes, haptic cues, audio descriptions, high-contrast modes, and replayable action histories. Accessible-visualization research adds an implementation lesson for the figures and the drawing interface: nonvisual access needs navigable structure, multimodal input, semantic rendering, and customizable text tokens rather than a static image label [Elavsky et al., 2024, Jones et al., 2024]. Plain-language controls matter because the original practice made artistic skill non-essential; the digital successor should also make technical skill non-essential. The audit protocol in sec. 13 keeps these claims bounded to visible capabilities instead of claiming universal access.

In protocol terms, access should be documented before the session, during the session, and after the session. Before drawing, participants should be able to state preferred input methods, perceptual feedback, pacing, break needs, plain-language prompts, and partner-assistance boundaries without having to disclose a diagnosis. During drawing, the interface should log which accommodations were available and which were actually used, because a capability advertised but unavailable in the session cannot support an access claim. After drawing, participants should be able to review whether the accommodation preserved agency, privacy, and relational comfort rather than merely allowing task completion.

The access requirement is deeper than device compatibility. A participant must be able to initiate a mark, perceive the partner’s contribution, understand the session state, control persistence, and remain socially comfortable with the accommodation used. Image-heavy social systems can exclude blind users when visual content is not made semantically available [Morris et al., 2016]. At the same time, accessibility is often co-produced among disabled and nondisabled companions in concrete settings rather than solved by a single feature [Branham and Kane, 2015]. If any of those conditions fails, the system may be technically accessible while relationally exclusionary. This is why the manuscript treats social accessibility as part of the design problem rather than a secondary usability issue.

fig. 11 translates those domains into implementation-facing commitments. The central point is not that the current framework is accessible for every user; it is that each access feature should be traceable to a partner need, a logged capability, and a participatory validation plan.

Accessibility also includes relational safety. Partners need control over saving, sharing, replaying, exporting, deleting, and annotating a canvas. The persistent archive that makes asynchronous DigiPPPiP powerful can become invasive if consent and privacy are weak. The research agenda in sec. 14 therefore treats participatory design with disabled partners as a core empirical priority rather than a platform feature request.




Figure 11: Accessibility feature map linking input flexibility, perceptual feedback, cognitive-load control, and privacy agency to participatory validation. The figure is generated by `generate_accessibility_features_overview()`; read each box as an implementation commitment that must point toward the central validation requirement with disabled partners, with accessible visualization scholarship motivating structured descriptions and customizable reading order. It supports the accessibility section’s distinction between capability documentation and access claims. The diagram is conceptual and does not certify compliance or universal usability.

9 Relational Aesthetics: Coauthored Marks and Social Form

Relational aesthetics frames art as a production of human relations rather than only objects for contemplation [Bourriaud, 2002]. Bishop’s critique is equally important because it warns against treating every engineered encounter as automatically emancipatory or socially meaningful [Bishop, 2004]. PPPiP already had a relational structure: the drawing mattered because it enacted the relationship. The couple joint drawing method gives this point a nearby arts-therapy precedent by treating shared drawing as an expression of connectedness and individuality rather than a finished-image score [Snir and Wiseman, 2013]. DigiPPPiP makes that ontology explicit in digital form. The artifact is a trace of mutual attention, negotiation, and improvisation; the canvas is a social scene.

Digital-intimacy research sharpens the claim. Technologies for strong-tie relationships often work through awareness, expressivity, physicalness, gift giving, joint action, and memory rather than through high-volume information transfer [Hassenzahl et al., 2012, Vetere et al., 2005]. DigiPPPiP sits closest to joint action and memory: the partners do something together, and the resulting artifact can remain available as a trace. That makes the practice more specific than generic messaging and more cautious than therapeutic promise.

The first-principles relational test is whether the artifact still points back to the other person as an agent. A canvas full of marks is not relational if one partner dominates, if the other cannot perceive or alter the shared field, or if the system substitutes automated novelty for reciprocal response. Relational aesthetics therefore functions as a constraint on design: the scene must leave room for mutual recognition, refusal, repair, and surprise.

Creative arts therapy research offers a neurodynamic vocabulary for this claim. Aesthetic engagement can externalize affect, support co-regulation, and create intersubjective resonance [Vaisvaser et al., 2024]. Close-relationship co-regulation scholarship narrows the term: it should mean bidirectional linkage across partners’ emotional channels, not a vague feeling of harmony [Butler and Randall, 2012]. Physiological-linkage reviews make the boundary even more conservative because linkage can be helpful, neutral, or risky depending on task, affective context, and overload [Timmons et al., 2015]. Family-level coregulation models add a useful multi-timescale warning: dyadic regulation can be nested inside broader relational systems, so a drawing trace alone cannot prove well-being [Paley and Hajal, 2022]. Art-making studies also suggest plausible stress and reflection constructs for future measurement [Kaimal et al., 2016], while pandemic

art-therapy discussions show why remote creative practices need careful ethical framing [Potash et al., 2020]. Phygital art-therapy theory is useful here because it treats digital and physical media as an integrated practice ecology rather than as rival channels [Yoon et al., 2025]. DigiPPPiP does not become therapy by declaration, but related mechanisms help explain why shared drawing may be relationally meaningful: partners make affect visible, modulate each other’s timing, and jointly discover an image neither would have made alone.

The important boundary is that DigiPPPiP remains human-human unless a study or design explicitly examines AI mediation. Generative AI can assist accessibility, prompts, or reflection, but it can also displace the mutual recognition that makes partner drawing relational. AI co-drawing belongs in a separate experimental branch, not as the default form of the practice.

10 Place-Based Micropractice and Digital Placemaking

Place-based DigiPPPiP treats the drawing context as part of the relational artifact. A shared canvas can carry marks from a kitchen table, a hospital room, a train, a park, or two distant cities. CSCW place theory distinguishes lived place from abstract space, which matters because a canvas becomes place-like only through situated practice and shared interpretation [Dourish, 2006]. Place-attachment research and networked-locality and digital-placemaking scholarship show that digital media can intensify rather than dissolve place attachment when it is designed to connect people, memory, and environment [Lewicka, 2011, Gordon and de Souza e Silva, 2011, Foth et al., 2015, Canelas and Hoehnk, 2025]. The relevant unit is small: a canvas can become a relational micro-place even if it never becomes a public platform or civic interface.

Place-responsive DigiPPPiP asks each partner to draw from their immediate environment. One partner may contribute a window view; another may respond with a local sound, map trace, color palette, or remembered path. The result is neither a private diary nor a generic online whiteboard. It is a relational place object: two embodied situations negotiated on one shared surface. Place claims should remain qualitative until participants describe particular canvases as meaningful places.

The minimum place claim requires recurrence, situated reference, and shared uptake. A one-time location tag is only metadata; a repeated drawing practice can become place-responsive when partners return to recognizable cues and use them to coordinate memory, mood, or care. This boundary keeps placemaking from becoming a decorative label for any geolocated canvas.

A place-responsive protocol should therefore ask what place cue is being shared, who chose it, how precise it needs to be, and whether either partner wants it excluded from storage or export. The cue can be coarse: room type, local weather, a remembered path, an object on the table, a hospital routine, or a neighborhood sound. Precise GPS coordinates are not required for the framework claim and may be inappropriate when the canvas is intimate, health-adjacent, or used by a vulnerable participant. The research record should preserve the prompt category and consent state without turning place into surveillance.

fig. 12 maps this scale. The figure treats kitchens, studios, hospital rooms, trains, and two-city routines as contexts that can feed a persistent canvas. The point is not that a digital artifact automatically creates place attachment; it is that repeated return, situated prompts, and shared memory can make a canvas function like a small relational place.




Figure 12: Digital placemaking map for recurring DigiPPPiP relational micro-places. The figure is generated by `generate_relational_microplaces()`; read the peripheral place boxes as situated contexts and the central artifact as a persistent canvas that can be revisited. It supports the place-based claim that recurrence and shared uptake matter more than geolocation alone. The diagram is conceptual and does not imply surveillance, community-scale impact, or universal place attachment.

This place dimension is especially useful for long-distance partners and communities. A remote digital mode can support geographic reach, but place-responsive prompts keep the practice situated. The taxonomy in fig. 13 captures this as a trade-off between geographic reach and place grounding rather than a binary opposition between online and offline.

11 Temporal-Spatial Taxonomy for Study Design

DigiPPPiP is organized by two primary axes: temporal structure and spatial configuration. The configured project has 3 temporal modes, 3 spatial configurations, and 9 total modality cells. fig. 13 is the central map of that design space. The axes intentionally separate relation from infrastructure: two partners can be relationally engaged while co-present, remote, delayed, or hybrid, but each cell changes what can be perceived, logged, repaired, and revisited.




Figure 13: Three-by-three temporal-spatial taxonomy for DigiPPPiP. The matrix is generated by `generate_taxonomy_matrix()` from `src/taxonomy.py`; read rows as temporal structures, columns as spatial configurations, cell labels as modality names, numeric labels as conceptual neural-synchrony affordance scores, and hatching as high-affordance cells. It supports decision-making about study conditions rather than product ranking. The scores are design variables, and measured synchrony would require participant physiology and controls.

The taxonomy is not a typology for naming products. It is a decision procedure for matching relational need to temporal-spatial form. A study should first identify the hard constraint: co-presence, distance, disability access, uneven schedules, privacy risk, or place memory. It should then choose the simplest cell that satisfies that constraint while preserving agency and mutual interpretability. This prevents the framework from treating the most instrumented cell as the most advanced one.

Table 1: Temporal-spatial DigiPPPiP modality grid. The renderer numbers this table from the label rather than from prose.

Temporal structure	Co-located physical	Remote digital	Cyberphysical hybrid
Synchronous	Original PPPiP	Video-call plus shared canvas	AR overlay on paper
Semisynchronous	Turn-taking in the same room	Turn-taking shared canvas	Smart paper plus live mirror
Asynchronous	Sequential physical artifact	Persistent shared canvas	Photographed or printed exchange

tbl. 1 should be read as a decision aid. A couple seeking immediate mutual attunement may choose synchronous co-presence. A long-distance couple with uneven schedules may choose asynchronous remote drawing. A pair interested in place memory may choose a cyberphysical hybrid that links physical marks with a persistent digital archive. The

highest conceptual neural-synchrony score in the configured taxonomy is 0.95, but no single cell is universally best. The appropriate cell depends on access needs, privacy constraints, device availability, emotional goals, and the amount of persistence a dyad actually wants.

12 Dyadic Digital Health: Consent, Relationship Boundaries, and AI Separation

Dyadic digital health research is important because DigiPPPiP addresses two interdependent people rather than an isolated user. Scoping work on dyadic digital health interventions shows that digital systems can be designed around partner interdependence, shared goals, and reciprocal support [Shaffer et al., 2022]. Dyadic health science also sets a stronger methodological bar: high-quality work should include both dyad members, focus on a meaningful relationship, and ground the dyadic rationale in theory rather than convenience sampling [Wilson et al., 2024]. Recent dyadic digital-health design work shows how shared-care modules can expose live reports, care roles, messaging, timelines, and resources for patient-caregiver pairs [Benmessaoud et al., 2023]. Digital interventions for relationship quality show why low-barrier formats matter: cost, stigma, geography, and scheduling can prevent couples from accessing formal services [Kernová et al., 2025]. Qualitative work on remote Dyadic Developmental Psychotherapy sharpens the remote-care boundary: online delivery can widen access, but families differ in engagement, nonverbal communication, decompression, and preference, so remote format must be tailored rather than presumed equivalent [Blair et al., 2024]. At the same time, DigiPPPiP should not borrow clinical authority from adjacent literatures without clinical evidence of its own.

DigiPPPiP should be positioned as a non-clinical relational practice unless tested otherwise. It may support intimacy, novelty, communication, and emotional co-regulation, but the manuscript does not claim clinical efficacy. That distinction matters for ethics and study design. Art-making, digital-art-therapy, tele-art-therapy, phygital art-therapy, and remote dyadic-therapy sources motivate plausible constructs such as reflection, stress change, expressive engagement, remote delivery constraints, and therapeutic-relationship cautions [Kaimal et al., 2016, Zubala et al., 2021, Potash et al., 2020, Miller and McDonald, 2020, Datlen and Pandolfi, 2020, Haywood and Grant, 2022, Yoon et al., 2025, Blair et al., 2024], but they do not show that DigiPPPiP treats distress or improves relationships. The appropriate next step is to compare DigiPPPiP against matched shared activities, not to assume it outperforms them. The planned outcome structure in fig. 25 is included to make that comparison explicit.

The boundary condition is equally important. DigiPPPiP should not be used as a substitute for crisis support, couple therapy, medical treatment, or safeguarding procedures. A digital canvas can invite disclosure, conflict, dependency, or unwanted archiving; any study or deployment must define escalation paths, deletion rights, and exclusion criteria before recruiting participants. The health framing is legitimate only when it makes risk and referral responsibilities clearer.

The minimum health-adjacent protocol should include a plain-language non-treatment statement, eligibility and stop rules, contact paths for discomfort or conflict, referral information appropriate to the study setting, and a distinction between facilitator, researcher, therapist, and platform roles. It should also specify whether any clinical, physiological, or mental-health data are collected; if not, the protocol should say so explicitly. If those data are collected, they belong under separate consent, retention, access, and analysis rules rather than under the ordinary shared-canvas archive.

The privacy boundary is dyadic, not individual. Contextual privacy and communication-privacy scholarship make clear that sharing depends on actors, purposes, transmission rules, and negotiated ownership of disclosed information [Nissenbaum, 2011, Petronio and Child, 2020]. HCI privacy research sharpens that point by treating privacy and security as social and cultural practices rather than only policy toggles [Dourish and Anderson, 2006]. Values-in-design work adds a method requirement: privacy, consent, access, and authorship need design levers that bring tensions into the design process before deployment [Shilton, 2012]. Digital-health consent reviews add a practical constraint: people often want transparency about who accesses health information, for what purpose, and under what oversight [Kassam et al., 2023]. Consent-forward digital mental-health scholarship pushes the same issue toward design practice by arguing that users should have meaningful choices over how sensitive data are collected, shared, and reused [Pendse et al., 2024]. For DigiPPPiP this means a study cannot treat export consent as a one-person checkbox when the artifact records a joint interaction. The minimum safeguard is pair-level governance: consent before saving, visible persistence state during drawing, mutually understandable deletion and redaction paths, and separate rules for research logs, personal keepsakes, therapist access, and public exhibition.

The difficult cases should be written into the protocol before recruitment. Deletion, export, replay, redaction, withdrawal, adverse-event reporting, data retention, and one-partner-disagrees scenarios are not edge decorations; they define whether a persistent dyadic archive is consentful. When partners disagree about saving, replay, export, exhibition, or secondary analysis, DigiPPPiP should default to the less-disclosing option unless both partners explicitly approve the more disclosing one. That rule protects the human-human default claim: the shared artifact is valuable only while both partners retain agency over how it persists.

The digital intimacy and relationship-technology literature supports a broader claim: online relational practices can be meaningful when they are intentional, reciprocal, and norm-governed [Kernová et al., 2025, Hassenzahl et al., 2012, Vetere et al., 2005]. Studies of long-distance video chat show that mediated presence can become part of everyday

relationship maintenance [Neustaedter and Greenberg, 2012], and minimal-communication work shows that small signals can carry relational meaning when they are embedded in a strong-tie routine [Kaye, 2006]. Qualitative work on the Couple app is especially close to DigiPPPiP because partners used a pair-bounded platform with asynchronous posts, live sketching, and lightweight haptic signaling while inventing their own relational norms [McVeigh-Schultz and Baym, 2015]. Recent relatedness-technology reviews and long-distance textile prototypes sharpen the evidence boundary: the design space is rich, but empirical effects, theory grounding, and ethics often remain underdeveloped, so DigiPPPiP should compare against simpler relational technologies rather than assume superiority [Wenhardt et al., 2025, Jiang et al., 2025]. Companion-AI scholarship adds the negative boundary: if automation is designed or received as a relationship substitute, it may alter social motivation, expectations, or human relationship investment, so DigiPPPiP’s optional AI branch must be governed as mediation rather than companionship [Malfacini, 2025]. DigiPPPiP adds a distinctive visual and gestural channel to that landscape. It is not just messaging with pictures; it is a shared surface where each partner sees the other’s decisions become part of a common artifact.

13 Methods Protocol: Governance, Provenance, and Validation

13.1 Event Logging and Participant-Facing Governance

DigiPPPiP is presented as a framework manuscript, so its method layer is a protocol specification rather than a participant dataset. The protocol requires timestamped events with actor, action, and channel fields; the example trace in fig. 14 has 6 summary fields, a mean interval of 4 seconds, and a turn-balance score of 1. This makes the distinction among synchronous, semisynchronous, and asynchronous sessions auditable instead of rhetorical. The same event stream supports replay, accessibility auditing, outcome modeling, and synchronization with optional physiological channels, but those uses must stay visibly downstream from the partner-facing mark.

Digital pen and paper research in observational settings gives a practical precedent for treating pen traces as analyzable field records rather than merely as drawings [Weibel et al., 2012]. DigiPPPiP extends that idea to a dyadic protocol: the stroke is simultaneously a mark for the partner, an event for replay, and a data row for later audit. That dual role is why the manuscript separates the visible canvas from the event log, source ledger, and generated figure registry.

fig. 14 now treats the method layer as an end-to-end data-flow contract. Raw partner actions are captured as consented event rows, separated from the visible canvas and replay record, transformed into summaries, optionally modeled, rendered as figures and variables, governed by claim/source/readiness audits, and finally published through the template pipeline. The important architectural rule is separation: human-authored marks, optional AI outputs, computed diagnostics, and publication artifacts should remain distinguishable in both the protocol and the figures.




Figure 14: Event schema, data-flow path, and example DigiPPPiP session trace. The figure is generated by `generate_event_logging_schema()` from `src/session_events.py` and `src/systems_governance.py`; read the top row as the capture-to-publication path, the lower-left list as minimum event-row fields, and the timeline as an illustrative actor/action sequence with temporal summary metrics. It supports the protocol claim that synchrony categories, model diagnostics, generated figures, and publication artifacts must remain auditable. The trace is illustrative, and participant studies would replace it with consented logs while keeping optional AI and physiology logs separable.

Before human-subjects work, the protocol needs a participant-facing layer as well as an analysis layer. The Common Rule and the Declaration of Helsinki require consent, review, privacy, protocol clarity, withdrawal, and risk handling to be explicit rather than inferred from good intentions [U.S. Department of Health and Human Services, Office for Human Research Protections, 2025, World Medical Association, 2024]. Digital-health consent scholarship adds that participant understanding depends on concrete information about access, purpose, privacy protection, and oversight [Kassam et al., 2023]. The plain-language brief should say that two partners are invited to draw on a shared surface; that the study records timing, tool, archive-control, and optional replay events; that the activity is not treatment or a relationship test; and that participants can pause, stop, withdraw, ask questions, report discomfort, request redaction, and ask about save, replay, export, and delete options before analysis lock. If one partner wants more sharing and the other wants less, the stricter privacy choice governs. This participant-facing appendix is generated as a protocol artifact by `src/study_readiness.py` rather than left as informal prose.

fig. 15 converts that ethics prose into a protocol matrix. The rows are not optional decorations: they make dyadic consent, deletion, export, replay, redaction, withdrawal, adverse-event reporting, retention, disagreement handling, intervention description, and optional AI-branch governance visible before recruitment. Consent-forward digital mental-health work supports this placement because archive controls need to be designed as user-facing choices rather than hidden back-office data policy [Pendse et al., 2024].




Figure 15: Study-readiness governance matrix for DigiPPPiP. The figure is generated by `generate_study_readiness_matrix()` from `src/study_readiness.py`; read rows as protocol edge cases, green cells as text-labelled readiness commitments, source counts as anchor depth, blue outlines as shared-archive controls, purple hatching as optional AI governance, and the right panel as routing for deletion, export, replay, disagreement, and optional AI separation. It supports participant-facing readiness rather than study results. Empty cells mark controls that are not applicable to a given row, not missing duties.

13.2 Source and Claim Governance

The study protocol separates source quality from claim strength. Peer-reviewed empirical and review articles can support scoped design and measurement claims; books support theoretical framing; preprints and reports are treated as provisional. fig. 16 encodes those rules so speculative additions, including geometric hyperscanning and narrative-information proposals, are not used as settled evidence. This is why DOI verification matters: a search-result citation is not added unless title, authors, venue, and DOI or stable URL match the intended claim. The stricter rule is claim-domain specific: therapy, neural synchrony, active inference, accessibility, placemaking, digital intimacy, AI mediation, and privacy persistence each have a different maximum defensible claim strength before new evidence is collected.

fig. 17 makes that red-team layer explicit across 14 recurring claim domains. The point is not to prohibit ambitious studies; it is to keep the manuscript from borrowing strength across domains. A valid shared-workspace source can motivate the interface, but it cannot establish relationship improvement. A hyperscanning method source can motivate instrumentation, but it cannot establish causality or therapeutic benefit. A digital-art-therapy review can motivate caution and study design, but it cannot turn DigiPPPiP into treatment without direct evidence.

The boundary matrix is paired with a claim ledger rather than left as an abstract warning. `src/claim_ledger.py` records recurring manuscript claim families, their section, citekeys, present maximum strength, and the evidence needed to upgrade them. fig. 18 makes the ledger visible. This also documents the role of Perplexity and web search in the workflow: discovery tools may nominate sources, but a citekey enters the ledger only after the title, venue, year, and DOI or stable URL have been checked against Crossref, a publisher page, an official standard, or an archival record.




Figure 16: Source-quality map for DigiPPPiP claim discipline. The figure is generated by `generate_source_quality_map()` from `src/source_quality.py`; read the horizontal bars as conservative maximum claim strength by source class, the embedded labels as source-tier roles, and the right-hand text as warnings for manuscript use. It supports the protocol rule that bibliography type constrains prose strength. The map is an audit device, not a judgment of individual papers, and claims can strengthen only with domain-appropriate empirical evidence.




Figure 17: Claim-strength and evidence-boundary matrix for DigiPPPiP. The matrix is generated by `generate_claim_boundary_matrix()` from `src/source_quality.py`; read rows as reviewer-risk domains, labelled green cells and blue rule marks as currently defensible claim levels, and the right panel as the evidence gate required for stronger language. It supports adversarial validity checking. The matrix is conceptual, and a domain can move only after direct study evidence is added.



Figure 18: Claim-ledger matrix linking manuscript claim families to evidence ceilings and upgrade gates. The figure is generated by `generate_claim_ledger_matrix()` from `src/claim_ledger.py`; read each row as a stable claim family, each bar as the current maximum claim strength, the blue numbered marker as evidence-key count, and the right-hand text as the next evidence gate. It supports source-to-claim governance rather than an empirical result. A stronger bar requires direct study evidence, not a more adjacent citation.

`src/source_verification.py` makes that rule executable. Each governed citekey receives a locator, verification URL, checked-as-of date, source tier, claim family, manuscript location, and recheck trigger. The audit prioritizes 2024–2026 sources, preprints, AI claims, digital-health claims, governance sources, and reporting standards for refresh before submission. fig. 19 renders the current source-verification state from the same governed citekey surfaces used by tests: claim ledger, evidence graph, figure-method source bridge, and study-readiness cases. The ledger is intentionally stricter than a bibliography because it asks what claim family a source is allowed to support and when it must be rechecked.




Figure 19: Source-verification readiness profile for governed DigiPPPiP citekeys. The figure is generated by `generate_source_verification_readiness()` from `src/source_verification.py`; read the left panel as labelled citekey coverage and priority-refresh pressure, and the right panel as source-tier and recheck-trigger counts in audit cards. It supports provenance auditing rather than literature synthesis. A zero missing-record count means the ledger has locators and metadata, not that every source independently validates DigiPPPiP.

13.3 Systems Boundary and Feedback Governance

A first-principles pass reduces DigiPPPiP to a small hard kernel: two human partners, perceivable marks, temporal structure, response opportunity, and accountable persistence. `src/systems_governance.py` makes the rest explicit as governed branches rather than implicit scope creep. The current systems layer records 6 boundary elements, 5 feedback loops, 5 causal assumptions, and 5 ethics gates, with a completeness score of 1. Active-inference and enactive accounts support the action-perception framing and Markov-blanket caution, while contextual privacy, values-in-design, and human-subjects governance anchor the participant-facing side of the boundary [Ramstead et al., 2020, Nissenbaum, 2011, Shilton, 2012, U.S. Department of Health and Human Services, Office for Human Research Protections, 2025, World Medical Association, 2024].

The boundary table keeps the human-human drawing loop inside the kernel and marks event logs, place context, physiology, AI assistance, and clinical translation as support structures or optional branches. Each branch has a reversal gate: place prompts can be declined or coarsened; physiology requires separate consent and artifact controls; AI suggestions must be labelled, rejectable, undoable, and separable from partner authorship; clinical translation stays out of scope until a reviewed intervention protocol exists. This is a systems-governance claim, not an efficacy claim. It says that the framework can name its boundaries and stop conditions before it asks participants or reviewers to trust them.

The feedback layer is deliberately adversarial. Action-perception loops should preserve mutual agency; privacy loops should default to the stricter dyadic archive choice; access loops should respond to fatigue, sensory mismatch, and assistance needs; AI loops should detect authorship confusion or partner substitution; evidence-escalation loops should downgrade language when controls or participant reports do not support a stronger claim. This makes falsification operational: if matched controls explain the same relatedness reports, if place prompts do not change situated memory, if replay feels like surveillance, if AI reduces co-authorship, or if physiological linkage disappears after artifact correction, the corresponding claim boundary narrows rather than hardens.

13.4 Evidence Scope and Non-Claims

The present manuscript implements a design and governance architecture, not a completed empirical evaluation. It demonstrates that DigiPPPiP concepts can be expressed as manuscript sections, tested primitives, generated figures, source ledgers, claim boundaries, protocol gates, and render artifacts. It does not demonstrate therapeutic efficacy, relationship improvement, neural coupling, universal accessibility, or AI benefit. Active inference, geometric hyperscanning, narrative information, and outcome modeling are used as modeling and measurement lenses; they become mechanisms only if future studies fit them to observed sessions, compare them with plausible alternatives, and survive the falsifiers named in the protocol.

This scope statement also governs visual interpretation. Architecture figures show boundaries, not deployed software. Data-flow figures show what a study should record, not what participants have already produced. Simulation plots show toy diagnostics, not human behavior. Audit figures show that the manuscript has local governance machinery, not that DigiPPPiP is externally validated. Those distinctions are intentionally repetitive because they are the main defense against attractive diagrams becoming overclaims.

13.5 Reproducible Figure Methods

The figure-generation method is also part of the research protocol rather than a cosmetic afterthought. Visualization grammars clarify how data, marks, scales, and layers compose [Wilkinson, 2005, Wickham, 2010, Bostock et al., 2011, Satyanarayan et al., 2017], while graphical-perception, color-use, and validation work shows that scientific figures need perceptual, task, and design justification rather than merely attractive styling [Cleveland and McGill, 1984, Munzner, 2009, Crameri et al., 2020]. DigiPPPiP therefore treats each generated figure as a small reproducible claim object: a scoped argument, a method-lineage warrant, a tested primitive or explicitly conceptual source, a visual encoding grammar, an aesthetic/accessibility rule, a deterministic render, a registry entry, a caption contract, an accessibility description, and a render validation gate. fig. 20 encodes that artifact chain. The implemented method has 9 generation stages, 7 semantic encoding roles, 5 source-method families, 13 audit criteria, 8 required caption elements, and a method-contract score of 1. The relevant scholarship supports this restraint: effective figures need explicit design choices and accessible description, visualization provenance should preserve why analytic artifacts were produced, remote-health-monitoring visualization studies should account for clinician comprehension and stakeholder-specific granularity, interactive visual systems need inspectable operations, accessible visualizations need navigable structure and custom reading sequences, image-alt decisions need context-specific text alternatives, and reproducible computational work needs organized, regenerable artifacts [Kelleher and Wagener, 2011, Rougier et al., 2014, Ragan et al., 2016, LeBaron et al., 2025, Heer and Shneiderman, 2012, Elavsky et al., 2024, Jones et al., 2024, w3c, 2024, Wilson et al., 2017, Rule et al., 2019, Stodden et al., 2014, Lundgard and Satyanarayan, 2022].

Research-through-design scholarship explains why this workflow is not merely a publishing convenience. HCI research-through-design treats artifact making as a legitimate way to produce interaction-design knowledge when the artifact, process, and contribution are made legible [Zimmerman et al., 2007, Gaver, 2012]. Annotated portfolios and reflective design documentation make the same requirement more concrete: design artifacts need comparative framing, annotations, and traces of decision-making if they are to function as research outputs rather than illustrations [Gaver and Bowers, 2012, Dalsgaard and Halskov, 2012]. DigiPPPiP applies that discipline to generated figures. fig. 21 renders the source-to-method bridge. A diagram is allowed to contribute conceptual structure only when its method lineage, code path, registry row, caption, and claim boundary are visible.

fig. 22 makes the visual grammar explicit. Actors, artifacts, signals, contexts, evidence, models, and caveats are assigned stable palette keys, non-color channels, hierarchy rules, and accessibility constraints so that repeated figures can be interpreted as a family without depending on hue alone. The grammar is intentionally conservative: it separates human actors from software assistance, shared artifacts from outcomes, signal traces from interpretation, and placemaking contexts from universal community-scale claims. This makes captions more auditable because the reader can compare the figure’s visual roles with the claim boundary that the prose asserts.

fig. 23 then turns the caption and rendering expectations into a checklist. The audit is not a guarantee that every reader will understand every figure in the same way. It is a reproducibility guard: a figure must name what it encodes, identify the source or generator, state its method lineage and manuscript role, explain how to read marks or axes, declare whether it is conceptual, protocol, audit, analytic simulation, or empirical placeholder material, preserve the caveat that limits interpretation, and identify what future evidence would upgrade the claim. That requirement also improves accessibility because natural-language descriptions can convey marks, statistics, perceptual relations, and domain meaning for readers who cannot rely on the image alone [Lundgard and Satyanarayan, 2022]. Current accessible-visualization work extends the requirement from alt text toward navigable structure, customizable token order, and reader-controlled verbosity [Elavsky et al., 2024, Jones et al., 2024]. The code now writes long-description sidecars for every generated figure




Figure 20: Reproducible figure-generation method for DigiPPPiP. The pipeline is generated by `generate_figure_generation_pipeline()` from `src/figure_methods.py`; read the upper row as artifacts, the lower row as quality gates, and the colored lanes as the governed movement from scoped claim through accessibility description and render validation. It supports the methods argument that figures are reproducible claim objects. The pipeline is analytic, and future empirical figures should inherit the same gates.

Source-to-method bridge for generated figures

DigiPPPiP governed visual grammar

method family	composition archetype	verified citekeys	figure gate
shared workspace	relational field: place partners, shared surface, and awareness cues in one spatial field	5 sources: tang1991collaborativework, ishii1993clearboard, gutwin2002workspaceawareness, scott2004territoriality, oittinen2025videodrawing	canvas figures must distinguish final marks from process and awareness cues
research through design	annotated artifact chain: show artifact, warrant, caveat, and claim status as a traceable chain	4 sources: zimmerman2007rtd, gaver2012expectrtd, gaver2012annotated, dalgaard2012documentation	each figure states its conceptual contribution and its documentation trail
visual reproducibility	provenance pipeline: connect deterministic input, transformation, artifact, and validation gate	8 sources: bostock2011d3, satyanarayan2017vegalite, ragan2016provenance, heer2012interactive, cramen2020colour, rule2019jupyter, stoddan2014reproducible, lebaron2025remoteviz	registry rows, render artifacts, and captions must be regenerable and traceable
accessible visual media	description-first audit surface: foreground what is encoded and how nonvisual reading remains possible	6 sources: morris2016pictures, brainham2015collaborativeaccess, w3c2024a11decisiontree, lundgard2022accessible, elavsky2024datanavigator, jones2024customization	captions, long descriptions, and navigable labels must expose visual structure and sequence
privacy and values	governance matrix: pair participant control, conflict rule, and evidence boundary in the same view	6 sources: nissenbaum2011contextualprivacy, dourish2006collectiveprivacy, petronis2020gpm, shilton2012values, lassam2023digitalconsent, pendse2024consentforward	figures with archives, logs, or replay must surface consent and governance caveats

Perplexity can nominate sources, but this bridge uses only verified DOI, publisher, standard, or archival metadata.

AUDIT generate_method_source_bridge | Deterministic project-code figure; not participant outcome data unless stated.

Figure 21: Source-to-method bridge for generated DigiPPPiP figures. The figure is generated by `generate_method_source_bridge()` from `src/figure_methods.py`; read each row as a verified scholarly family, its composition archetype, the citekeys used by the project, source-count badges, and the gate it imposes on generated figures. It supports the methods claim that diagrams are research artifacts only when their warrant is traceable. The bridge is an audit device and does not turn conceptual figures into empirical evidence.

Visual encoding matrix for DigiPPPiP figures			
DigiPPPiP governed visual grammar			
role	semantic target	palette + non-color channel	hierarchy + guardrail
actors	partners, dyads, facilitators, and AI assistants	blue: blue outlined role boxes, A/B labels, and left-right position; non-color: role labels, left/right placement, and outlined nodes	high intensity: human actors occupy primary nodes before tools or agents; guardrail: never imply equivalence between humans and software agents
artifacts	canvas, archive, event log, and generated output	green: green centered boxes, solid fills, and archive glyph labels; non-color: solid central panels and artifact nouns	high intensity: shared artifacts sit at the compositional center when they mediate the relation; guardrail: distinguish shared artifacts from measured outcomes
signals	strokes, pauses, voice, physiological channels, and awareness cues	orange: orange arrows, tick marks, timelines, and directional labels; non-color: arrows, event ticks, and temporal ordering	medium intensity: signals connect actors to artifacts and should not dominate outcome claims; guardrail: mark signal processing requirements before interpretation
contexts	place, schedule, access setting, and privacy boundary	purple: purple peripheral layers, boundary bands, and location labels; non-color: peripheral bands, boundary outlines, and place labels	medium intensity: contexts frame the drawing event without becoming untested outcomes; guardrail: keep placemaking claims at micro-place scale unless directly studied
evidence	claim strength, study gate, source class, and lineage	sky: sky matrices, bars, ranks, and bipartite links; non-color: rank, bar length, matrix cell text, and link topology	high intensity: evidence figures foreground claim ceiling, source tier, or upgrade gate; guardrail: separate conceptual support from empirical validation
models	active inference, information theory, and multilevel outcomes	violet: green or violet model lines, equations, and labelled components; non-color: line style, equations, and named latent components	medium intensity: model figures place variables and caveats before visual drama; guardrail: state when the model is illustrative rather than fitted
caveats	risk boundaries, exclusions, and interpretation limits	red: red callouts, warning outlines, bottom notes, and status badges; non-color: warning badges, lower-third notes, and outline weight	high intensity: caveats stay visible whenever they limit interpretation; guardrail: place limits inside the figure when they constrain interpretation
The matrix is a design grammar: visual force must remain label-backed, contrast-aware, and claim-bounded.			

AUDIT

generate_visual_encoding_matrix | Deterministic project-code figure; not participant outcome data unless stated.

Figure 22: Visual encoding matrix for generated DigiPPPiP figures. The matrix is generated by `generate_visual_encoding_matrix()` from `src/figure_methods.py`; read each row as a semantic role with its target, palette key, non-color channel, hierarchy rule, contrast cue, and interpretation guardrail. It supports the methods argument that repeated colors, labels, positions, marks, and text equivalents form a reusable grammar. The matrix is conceptual, and empirical data would add measured scales without removing the guardrails.

and emits `../figures/figure_artifact_audit.json`, an artifact-level audit that checks registry uniqueness, orphan PNGs, dimensions, nonblank pixels, manuscript references, caption/prose parity, claim-status validity, long-description presence, readability metadata, long-description reading guidance, and section alignment after the figure set is rendered.




Figure 23: Figure-method audit for DigiPPPiP generated figures. Bars are generated by `generate_figure_method_audit()` from `src/figure_methods.py`; read each row as a required gate covering deterministic inputs, registry metadata, captions, claim boundaries, source alignment, accessibility text, legend/axis integrity, render resolution, auto-numbered references, and visible claim status. It supports workflow verification, not participant inference. Failed gates would require code or caption repair.

13.6 Study Package, Access, Place, and Outcomes

The minimum reproducibility package for a DigiPPPiP study should include the protocol version, temporal-spatial condition, interface capabilities, event schema, exclusion windows, consent and persistence settings, accessibility accommodations, outcome measures, and analysis code. Without that package, readers cannot tell whether an observed result belongs to the dyad, the task, the technology, the access arrangement, or the analysis pipeline. This is a first-principles requirement: if the causal candidates cannot be separated, the interpretation cannot be audited.

The protocol appendix should also separate three participant-facing surfaces that are easy to collapse. The access surface records supported input channels, feedback channels, partner-mediated assistance, cognitive-load settings, communication preferences, and accommodation changes during the session. The place surface records only the situated cues that participants consent to share, such as room type, local prompt, mobility context, or remembered place, and it should not require precise geolocation for a place-responsive claim. The health surface states that DigiPPPiP is non-clinical unless a reviewed intervention protocol says otherwise, names stop and referral procedures, and separates personal keepsakes from research logs before any export or replay.

Reporting guidance supplies the study-readiness bridge. TIDieR requires enough intervention detail for replication, and CONSORT-EHEALTH names web and mobile health reporting elements that are easy to miss when an online intervention feels self-explanatory [Hoffmann et al., 2014, Eysenbach and Group, 2011]. For DigiPPPiP that means the protocol must define session dose, materials, platform settings, tailoring, fidelity, archive-control states, and changes made during the study. PRISMA is not activated here because the evidence graph is a bounded narrative synthesis rather than a systematic review claim; it should be added only if the review question, search strategy, screening, extraction, and flow diagram become systematic.

Accessibility is handled as a protocol requirement. The current audit has 5 criteria and an illustrative implementation score of 1. The radar in fig. 24 is not a compliance certificate; it is a reproducible way to document which input, feedback,

privacy, cognitive-load, and partner-mediation capabilities a study or tool actually supports.




Figure 24: Accessibility audit radar generated from explicit implementation capabilities. The figure is generated by `generate_accessibility_audit_radar()` from `src/accessibility.py`; read each spoke as a capability domain and radial distance as documented support in the illustrative configuration. It supports reproducible access auditing, not compliance certification. Empirical accessibility claims would require participatory validation with disabled users and accommodation logs.

Outcomes are organized as a multilevel design rather than a single success metric. The project defines 6 measures across 6 domains, with a default design-strength score of 4 for a randomized longitudinal study. fig. 25 shows how temporal mode, spatial configuration, phase, and access condition can be modeled with dyad and participant random effects. This structure separates implementation outcomes, such as latency and logging completeness, from relational outcomes, such as perceived connection and shared meaning.

13.7 Falsification and Claim Boundaries

Falsification should be designed in. The framework would be weakened if matched controls produce the same relational outcomes, if accessibility accommodations reduce rather than expand agency, if synchrony measures vanish after artifact correction, if AI suggestions displace rather than support human agency, or if participants describe persistent archives as surveillance rather than shared memory. Those outcomes would not invalidate shared drawing as a practice; they would delimit which mechanisms, contexts, or claims the framework can support.

fig. 26 expresses this as 5 staged gates. Feasibility and relational meaning come before access claims, matched outcome comparisons, and optional physiology. This ordering is adversarial by design: neural or computational sophistication cannot rescue a practice that is not understood, consensual, accessible to the stated population, or meaningfully different from simpler shared activities.

This protocol prevents the main evidentiary errors. Active inference is used as a modeling language, not proof of mechanism. Hyperscanning synchrony is treated as a correlate until causal designs justify more [Cui et al., 2012, Czeszumski et al., 2020, Hamilton, 2021, Zimmermann et al., 2024]. Art-therapy and digital-health literatures motivate




Figure 25: Multilevel outcome model for DigiPPPiP studies. The figure is generated by `generate_multilevel_outcome_model()` from `src/outcomes.py`; read left components as fixed effects, the center as the dyad-level mixed model, and the right component as outcome domains. It supports planned-analysis specification rather than reporting results. Validation would require real dyadic observations, random effects diagnostics, and matched shared-activity controls.




Figure 26: Staged empirical validation ladder for DigiPPPiP. The figure is generated by `generate_validation_ladder()` from `src/source_quality.py`; read the left column as claims unlocked by each stage and the right column as minimum controls before escalation. It supports the protocol's adversarial ordering from feasibility and meaning through access, matched outcomes, and optional physiology. The ladder is conceptual, and stronger claims require completed studies at the relevant stage.

possible applications and cautions, but DigiPPPiP is not described as treatment without controlled clinical evidence [Zubala et al., 2021]. Accessibility and placemaking claims stay bounded to the capabilities and populations actually tested.

14 Research Agenda: From Feasibility to Evidence

The framework identifies a large research program. fig. 27 condenses it into priorities that can be run as staged studies rather than as a single overbroad claim. The first priority is modality comparison: co-present paper PPPiP, synchronous remote DigiPPPiP, semisynchronous drawing, and asynchronous persistent-canvas practice should be compared on relational, phenomenological, behavioral, accessibility, and narrative outcomes. The comparison should include matched controls such as ordinary shared drawing, video chat, shared games, and solo art-making so DigiPPPiP is not credited for effects that any pleasant shared activity would produce.




Figure 27: Conceptual research-priority map for DigiPPPiP. The figure is generated by `generate_research_agenda_plot()`; read paired bars as relative feasibility and research value assigned by the framework design for each agenda item. It supports staged prioritization rather than external funding or outcome claims. The values are conceptual planning scores, and future versions should replace them with feasibility data, stakeholder priorities, and study results.

The staged path should begin with feasibility and meaning before physiology, following the validation ladder in fig. 26. Early studies should ask whether partners understand the task, preserve consent, use the canvas intentionally, and describe the artifacts as relationally meaningful. Only after those conditions hold should instrumentation-heavy studies test neural, narrative, or active-inference hypotheses. This ordering follows from the design kernel: no signal-processing result can rescue a practice that participants do not experience as shared agency.

The systems-governance agenda should be tested alongside the outcome agenda. A pilot should record whether partners use save, replay, redaction, deletion, and export controls; whether place prompts are accepted, declined, or coarsened; whether accessibility accommodations change during the session; and whether optional AI suggestions are ignored, rejected, revised, or treated as partner-like. These are not secondary usability details. They are the feedback signals that decide whether the framework's branches remain reversible and ethically bounded.

Hyperscanning studies should test whether the phase structure in fig. 9 appears in real dyads. Geometric-hyperscanning studies should evaluate whether the appendix's curvature proxy tracks rupture, repair, or co-regulation events after the artifact and alignment limits are addressed sec. 19. Narrative-information studies should test whether the appendix's entropy and surprisal primitives predict partners' reports of novelty, coherence, or shared meaning [Schulz et al., 2024].

Accessibility research should be participatory from the start. Disabled partners should help define input modes, feedback channels, consent controls, and successful participation. Place-based studies should test whether place-responsive prompts increase place attachment or relational memory compared with non-place prompts [Lewicka, 2011].

AI-assisted studies need a separate preregistered logic. Mixed-initiative interfaces can join automated suggestions with direct manipulation, but that does not make automation harmless or relationship-preserving [Horvitz, 1999, Deterding et al., 2017]. AI-mediated communication scholarship is especially relevant because it treats AI as modifying, augmenting, or generating interpersonal messages on behalf of a communicator, with consequences for agency, trust, relationship interpretation, and ethics [Hancock et al., 2020]. Companion-AI scholarship adds a distinct replacement and social-deskilling concern, so AI-supported DigiPPPiP should be measured against whether it strengthens human-human attention rather than satisfying a user through the system itself [Malfacini, 2025]. Human-AI interaction guidelines

imply concrete requirements for DigiPPPiP: disclose what the model can and cannot do, let partners accept, reject, revise, or undo suggestions, support efficient dismissal, and recover gracefully from wrong or intrusive prompts [Amershi et al., 2019]. If the AI branch becomes a clinical or health-intervention trial, CONSORT-AI and SPIRIT-AI require AI-specific descriptions of the intervention, input and output data, human-AI interaction, errors, and use setting [Liu et al., 2020, Cruz Rivera et al., 2020]. Even outside a trial, the optional branch should maintain a risk log using NIST AI RMF concepts and check whether any deployed system would fall within EU AI Act obligations [Tabassi, 2023, European Parliament and Council of the European Union, 2024]. Empirical medical-AI ethics reviews add a further caution: high-level ethical principles often fail to match stakeholder experience unless patients, clinicians, developers, and ethics expertise are involved in the design and evaluation process [Tang et al., 2023]. The outcome question is not whether AI makes drawings more polished. It is whether AI helps partners notice each other, preserve co-authorship, and discuss uncertainty without outsourcing imagination, authorship, or emotional interpretation.

Longitudinal studies should compare DigiPPPiP with matched shared activities such as video calls, shared games, text messaging, relatedness-technology prototypes, or shared media consumption [Wenhart et al., 2025]. The comparison set should include at least one lightweight routine and one richer sensory or gestural system, because affective textile systems for long-distance partners show how non-visual gesture channels can address needs that a drawing canvas may not meet [Jiang et al., 2025]. No single method can validate the framework; the research agenda has to triangulate logs, interviews, accessibility audits, relational outcomes, privacy acceptability, and optional physiology.

15 Integrative Model: The Human-Human DigiPPPiP Kernel

DigiPPPiP can be summarized as a cyberphysical relational practice. Its first layer is a coupled modeling lens: partners can be described as updating expectations about each other’s intentions through shared marks, with the formal primitive isolated in sec. 19. Its second layer is cyber-phenomenological co-presence: marks carry embodied gesture across physical, digital, and hybrid surfaces. Its third layer is narrative information architecture: sessions become symbolic trajectories with entropy, surprise, and convergence.

The fourth layer is neuroergonomic design: the interface should preserve attention, reduce technofence, and support flow. The fifth layer is place-relational grounding: sessions can bind two bodies, two environments, and one artifact. The sixth layer is accessibility: input and feedback should adapt to participants rather than forcing participants to adapt to one canonical interface. The word “accessibility” is used here as a design and validation program, not as a universal guarantee.

The seventh layer is temporal flexibility. Synchronous, semisynchronous, and asynchronous modes are not rank-ordered; they answer different relational constraints. The eighth layer is measurement. Active-inference, narrative-information, event-log, accessibility, outcome-model, and geometric-hyperscanning tools give the framework empirical handles without letting the manuscript pretend that conceptual simulations are evidence.

The model can also be collapsed to a minimum viable DigiPPPiP loop: partner acts, mark persists, other partner perceives, response changes the shared field, and both partners retain agency over what remains. Every larger layer should be justified by how it strengthens that loop. If a feature does not improve perception, action, persistence, interpretation, access, or consent, it is outside the core framework even if it is technically impressive. The architecture in fig. 4 operationalizes that rule by separating the kernel from instrumentation, modeling, optional AI support, and publication governance.

The systems-governance layer makes that collapse enforceable. `src/systems_governance.py` treats the human-human mark loop as the kernel and places event logs, place context, optional physiology, AI assistance, and clinical translation in named boundary positions. This matters because a system boundary is a design decision, not a discovered fact: moving physiology, AI, or clinical translation into the kernel would change the participant contract and the evidence burden. The integrative model therefore remains reversible. Branches can be removed, disabled, coarsened, or downgraded without losing the core practice.

fig. 28 summarizes the reusable visual grammar that holds these layers together. Actors, artifacts, signals, contexts, diagnostics, and evidence maps are styled consistently so captions can identify what is encoded, which generator produced it, what claim strength it supports, and what caveat remains. The grammar now has a stronger architecture role: human actions, optional AI branches, computed diagnostics, and publication artifacts should be visually separable even when they appear in one system figure.




Figure 28: Reusable DigiPPiP figure grammar for actors, artifacts, signals, contexts, architecture maps, protocol timelines, diagnostic plots, and evidence maps. The figure is generated by `generate_framework_template()`; read the upper row as semantic roles, the small labels as non-color channels, the middle row as reusable figure forms, and the lower box as the caption and long-description rule applied throughout the manuscript. It supports integrative consistency, not empirical validation, and future data figures should keep the same claim-boundary discipline.

16 Discussion: Limits, Failure Modes, and Future Replacement

DigiPPiP belongs to the broader landscape of relational technology, but it takes a specific position within it. Many contemporary systems replace, simulate, or optimize social contact. DigiPPiP instead uses technology to give two human partners another surface for mutual attention. That difference matters ethically: the goal is not frictionless engagement, retention, or automated companionship, but a bounded practice in which each partner can see and respond to the other's agency.

The strongest scholarship added by the digital turn is not a single theory but a triangulation. CSCW explains why the shared drawing space is an interactional resource, with social translucence and workspace awareness providing sharper design constraints for what partner activity should become visible [Tang, 1991, Erickson and Kellogg, 2000, Gutwin and Greenberg, 2002]. Distance and grounding research explain why remote drawing needs evidence of understanding, repair, and re-entry rather than only a persistent file [Olson and Olson, 2000, Clark and Brennan, 1991]. Presence and embodiment research explain why lightweight traces can carry felt co-presence without recreating the whole body [Lombard and Ditton, 1997, Biocca, 1997, Lee, 2004]. Digital-intimacy and relatedness-technology research explains why rituals, minimal signals, traces, and joint action matter for strong-tie relationships while also warning that many prototypes lack robust effect evidence [Kaye, 2006, Hassenzuhl et al., 2012, Neustaedter and Greenberg, 2012, Vetere et al., 2005, McVeigh-Schultz and Baym, 2015, Wenhart et al., 2025].

The same triangulation clarifies the risks. Persistent canvases can support shared memory only when contextual privacy, collective information practice, values-in-design, and dyadic boundary rules are explicit [Nissenbaum, 2011, Palen and Dourish, 2003, Dourish and Anderson, 2006, Petronio and Child, 2020, Shilton, 2012]. Emerging work on AI-mediated collaborative drawing in romantic relationships is relevant only if AI remains a reflective mediator rather than the relationship partner or the author of the shared gesture [Won et al., 2026]. Companion-AI scholarship makes that boundary stronger: systems designed to satisfy companionship needs can raise replacement, social motivation, and social-skill concerns for human relationships, even when some users experience benefits [Malfacini, 2025]. Mixed-initiative and human-AI interaction scholarship therefore set a high bar: optionality, control, reversibility, disclosure, and recovery from wrong suggestions are not interface polish but conditions for preserving partner agency [Horvitz, 1999, Deterding et al., 2017, Amershi et al., 2019]. Hyperscanning and active inference supply testable measurement and modeling languages, but not automatic causal proof [Friston et al., 2017, Hamilton, 2021].

The most important revision to the project brief is evidentiary discipline. The framework draws from hyperscanning, active inference, digital art therapy, neuroergonomics, phenomenology, relational aesthetics, and digital placemaking, but those literatures do not yet prove DigiPPPiP’s outcomes. The manuscript therefore phrases claims as design rationales and empirical hypotheses unless a cited source directly supports the narrower statement. The source-quality map in fig. 16 makes this discipline visible in the artifact itself.

The computational model also changes the manuscript’s posture. Rather than leaving abstract phrases such as “dyadic generative model” or “narrative entropy” as metaphors, the project implements small deterministic primitives and keeps them in sec. 19. Those primitives are intentionally modest. Their value is that they expose assumptions, make figures reproducible, and prevent quantitative claims from being invented in prose.

The first-principles review leaves only a small set of hard constraints: two people, a shared field of marks, perceivable agency, temporal structure, and accountable persistence. Most other elements are soft constraints or hypotheses. Digital capture, neural measurement, AI assistance, place tagging, and clinical translation are optional branches that must justify themselves against that small core. This makes the framework easier to test and harder to inflate.

The systems review adds a second discipline: every optional branch needs a feedback loop, a causal assumption, an ethics gate, and a reversal path. Without those pieces, the branch is not mature enough to carry manuscript claims. This is especially important for long-distance use, because a persistent surface can become useful, irrelevant, burdensome, or intrusive depending on the dyad’s actual uptake. It is also important for AI assistance, where reversibility and authorship clarity matter more than novelty.

The same restraint applies to health, intimacy, and accessibility. DigiPPPiP may become useful in dyadic digital-health or creative-arts contexts, but the current evidence supports only a research agenda and design rationale. Claims about treatment, relationship improvement, universal access, AI-supported insight, privacy-safe archives, or community-scale placemaking require study designs that directly measure those outcomes. The manuscript should therefore remain hospitable to future empirical replacement: the conceptual figures can be swapped for real data, but the claim-strength rules should stay.

The textosexual insight from PPPiP remains useful: relationships can be strengthened through shared marks, shared texts, and shared visual artifacts [Mikhailova and Friedman, 2018]. DigiPPPiP updates that insight for networked surfaces. The mark can now be simultaneous or delayed, local or remote, physical or digital, private or archived. The relational requirement is unchanged: partners must attend, respond, and co-author. If future studies show that ordinary shared drawing, video chat, or another low-friction activity produces the same outcomes with less complexity, DigiPPPiP should narrow to the contexts where its persistence, accessibility, place responsiveness, or event logging add specific value.

17 Case Studies: Dementia Care as a Stress Test

We illustrate the framework with one worked case study in dementia care. It is presented not as evidence of efficacy but as a boundary test: a setting chosen because it strains several of DigiPPPiP’s core assumptions rather than confirming them. Other applications (early-childhood dyads, long-distance couples, stroke rehabilitation) belong to the empirical program in sec. 14; here we develop the single case that most sharply exposes what the kernel does and does not guarantee.

17.1 Dementia Care: Asymmetric Dyads, Biographical Scaffolding, and Fluctuating Consent

DigiPPPiP’s minimum viable kernel (two partners, a shared mark field, perceptible traces of agency, and consentful control over persistence) maps onto dementia care dyads in ways that productively stress-test several of the framework’s core assumptions. The most important asymmetry is cognitive: where the framework presupposes two agents with roughly stable capacity to govern the shared archive, dementia introduces radical temporal asymmetry. The adult child experiences each session as one point in a longitudinal caregiving relationship; the parent may experience each session as the first. This does not invalidate the practice. There is substantial evidence that creative engagement can produce genuine moments of co-presence and recognition even when sustained narrative continuity is lost; however, it requires the consent and governance model to be substantially extended. Archive control cannot rest symmetrically with both partners when one partner’s capacity fluctuates within and across sessions. The framework’s default rule (when partners disagree, the less-disclosing option governs) is a useful starting point, but dementia care contexts require an explicit supported decision-making layer, drawing on bioethics literature on fluctuating consent capacity, that specifies who holds proxy governance, under what conditions, and with what reversibility.

The cyberphysical substrate takes on new meaning in this context. Rather than treating the shared canvas as a blank field for improvised mark-making, a dementia-oriented implementation can draw on biographical materials (family photographs, familiar places, recurring objects, handwriting samples) as persistent prompts embedded in the canvas. This is not merely an accessibility feature but a theoretically motivated reframing of what the shared surface is. Long-term autobiographical memory is often more intact than short-term memory in dementia, which means that a canvas seeded with recognizable materials from the parent’s past can function as a bridge between the child’s present and the parent’s accessible memory. The place-based micropractice framing is especially relevant here: the canvas becomes a relational micro-place constructed from biographical geography. A kitchen from forty years ago, a recurring holiday destination, or a childhood home can all serve as orienting triggers. Recurrence and shared uptake remain the minimum place claim; in this context they are satisfied when a familiar image, prompt, or outline reliably orients the parent toward a recognizable relational moment.

The temporal taxonomy requires reinterpretation rather than extension. Synchronous co-present sessions remain possible and valuable, particularly in early-stage dementia, but the semisynchronous and asynchronous modes acquire specific clinical relevance. An asynchronous canvas that the child adds to between visits, and that the parent encounters during a session with a care facilitator, preserves relational continuity across the gaps that dementia and caregiving schedules impose. The canvas in this mode functions less as a real-time communication channel and more as a persistent relational object that accumulates meaning across time. This is closer to a shared memory book than a messaging platform, but with the agency and mark-making properties that distinguish DigiPPPiP from passive reminiscence materials. The temporal primitive of repair acquires particular weight: moments where the parent reorients toward the shared surface after confusion, or where the child responds to an unexpected mark, carry relational significance that the event logging schema should be designed to capture without pathologizing disorientation as failure.

The neuroergonomic design constraint is sharpened considerably. The original principle that the interface should be nearly invisible becomes a clinical requirement in dementia contexts where cognitive load management is not a design preference but a condition of participation. Tool palettes, notifications, and navigational complexity are contraindicated. The minimum viable interface is a single shared surface with one input mode, familiar visual prompts, and no decisions required beyond the mark itself. Accessibility here is not only about motor input flexibility but about cognitive accessibility: plain-language prompts, low-distraction environments, and session structures short enough to remain within the participant’s attention window. The care facilitator becomes a legitimate third role in this context, supporting participation without substituting for it, and the governance model should specify the facilitator’s access to the canvas and event log separately from both partners.

The relational aesthetics claim that the artifact points back to the other person as an agent is both the most fragile and the most important aspect of this application. A canvas full of marks is not relational if one partner is merely producing output without awareness of the other’s presence. The honest boundary condition is that DigiPPPiP in dementia care

settings cannot guarantee sustained mutual recognition, and should not be positioned as doing so. What it can offer is a structured occasion for moments of recognition: brief, genuine, and worth creating. Within a practice that asks very little in return, that is a modest claim. In the context of a condition that progressively forecloses relational possibility, it is not a small one.

18 Conclusions: Study-Ready Without Overclaiming

DigiPPPiP is a faithful extension of PPPiP and a substantive transformation of it. It preserves the central practice of making meaning together on a shared surface while expanding the possible substrates, timings, bodies, places, access needs, and measurement strategies. The framework is strongest when stated as a research program: a set of grounded hypotheses about how shared drawing can support human-human relational practice across cyberphysical conditions.

The project now expresses that program as a render-ready manuscript and reproducible conceptual codebase. The paper uses automatic section, figure, equation, and table references; the bibliography is centralized in `references.bib`; the numbers that enter the manuscript are generated through tested primitives and token hydration. Future empirical work can replace the conceptual outputs with participant data without changing the manuscript's reference architecture, figure registry, or source-quality discipline.

The result is intentionally bounded. DigiPPPiP is not presented as clinical treatment, proof of neural coupling, a universal accessibility solution, or an argument that AI improves intimate drawing. It is a structured way to design, log, visualize, and test a dyadic drawing practice whose core requirement remains simple: two partners attend to a shared surface and let the other's mark matter. The most important future contribution will not be a more elaborate interface; it will be evidence that identifies when digital persistence, temporal flexibility, accessibility support, or place responsiveness actually strengthens that core relation.

19 Appendix: Free-Energy and Active-Inference Formalisms

This appendix holds the mathematical and diagnostic primitives used by the main manuscript. The consolidation is deliberate: active inference remains a modeling lens in the main line, while the formal details sit here where readers can inspect assumptions, generators, labels, and evidence boundaries together. The appendix draws on established active-inference and free-energy treatments [Friston, 2010, Friston et al., 2017, Parr et al., 2022, Friston et al., 2023], discrete-state synthesis work [Da Costa et al., 2020], and interactional accounts of communication and second-person modeling [Vasil et al., 2020, Schilbach et al., 2013, Redcay and Schilbach, 2019, Lehmann et al., 2024].

19.1 Event-to-Model Mapping

fig. 29 maps DigiPPPiP’s theoretical terms to observable design elements. Latent states are partner intentions, narrative states, and shared affect. Observations are strokes, pauses, utterances, and interface events. Policies are drawing, waiting, responding, and revising. The figure is included to prevent active inference from becoming decorative terminology: every model term has to be tied to a protocol event or dropped.




Figure 29: Mapping from DigiPPPiP events to active-inference model components. The figure is generated by `generate_active_inference_mapping()`; read the columns as latent states, observations, and policies, with arrows showing how partner-conditioned beliefs can update through visible marks. It supports the active-inference appendix by tying terms to measurable protocol events. The mapping is conceptual; fitted parameters and failed-baseline checks would be needed for mechanism claims.

19.2 Minimal Free-Energy Primitive

The project uses a Gaussian point-belief model as a minimal conceptual primitive. Variational free energy is:

$$F(\mu) = \frac{1}{2}\pi_p(\mu - \mu_p)^2 + \frac{1}{2}\pi_l(o - \mu)^2 - \frac{1}{2}\log \pi_p - \frac{1}{2}\log \pi_l \quad (1)$$

The expression in eq. 1 defines μ as the current belief, μ_p as the prior mean, o as the canvas observation, and π_p, π_l as the prior and likelihood precisions. The analytic posterior mean used by `src/active_inference.py` is:

$$\mu^* = \frac{\pi_p \mu_p + \pi_l o}{\pi_p + \pi_l} \quad (2)$$

In a coupled dyad, each partner’s previous posterior becomes part of the other’s next prior. fig. 30 contrasts that coupled case with a decoupled baseline. The terminal free-energy values from the deterministic conceptual run are -0.693147 and 0.061153, respectively; the absolute reduction is 0.7543. These are model outputs, not human-subject measurements.




Figure 30: Coupled and decoupled conceptual free-energy trajectories generated by `generate_active_inference_loop()` from `simulate_dyadic_session()`. Read the solid and dashed lines as toy-model baselines for reciprocal versus non-reciprocal prior updating across mark steps. The plot supports the modeling argument that coupling can be formalized, not that couples improve. Empirical validation would require observed behavior and model-comparison evidence.

19.3 Hyperscanning and Network Geometry

Geometric hyperscanning is a candidate measurement vocabulary for empirical studies, not a shortcut to interpreting synchrony. NIRS-based cooperation studies and hyperscanning reviews motivate dyadic measurement [Cui et al., 2012, Czeszumski et al., 2020, 2022, Nam et al., 2020], yet shared stimulus timing, motion artifacts, physiology, task structure, preprocessing choices, and analytic windows can all inflate apparent coupling. Methodological cautions in fNIRS and hyperscanning warn against interpreting cross-brain coherence as direct evidence of shared minds, empathy, or relationship improvement [Tachtsidis and Scholkmann, 2016, Hamilton, 2021, Zimmermann et al., 2024]. Translational hyperscanning arguments are valuable only when they remain close to applied contexts and family or dyadic care questions rather than treating synchrony as a generic marker of social quality [Provenzi et al., 2022]. fig. 31 therefore separates acquisition, cleaning, windowing, synchrony estimation, graph construction, and curvature analysis before interpretation.




Figure 31: Reproducible pipeline from raw dyadic signals to interaction-network diagnostics. The figure is generated by `generate_network_analysis_pipeline()`; read the boxes left to right as acquisition, cleaning, windowing, synchrony estimation, graph construction, and curvature analysis. It supports the methods guardrail that signal processing precedes interpretation. The pipeline is analytic scaffolding; actual studies must report exclusion windows, preprocessing choices, and permutation controls.

fig. 32 makes the alignment problem more concrete. Behavioral events, physiological channels, and exclusion windows

must be synchronized before a study can ask whether a neural measure tracks co-drawing, repair, rupture, or co-regulation. The figure deliberately includes a shared artifact window to show how apparent coupling can arise from non-social signal contamination.




Figure 32: Alignment schematic for behavior, physiology, artifact rejection, and cautious interpretation. The three tracks generated by `generate_hyperscanning_alignment()` should be read vertically: behavioral event windows, raw physiological channels with shared artifacts, and cleaned channels after exclusion. It supports the caution that synchrony claims require co-registration and artifact handling. The signals are simulated; measured analyses would need device-specific quality metrics and null models.

For a simple unweighted inter-brain graph, the Forman-Ricci curvature used here is:

$$\text{Fr}(uv) = 4 - \deg(u) - \deg(v) \quad (3)$$

The implementation uses Forman’s cell-complex curvature vocabulary and dynamic-network change-detection applications as method antecedents [Forman, 2003, Weber et al., 2016]. The curvature-entropy diagnostic in fig. 33 follows recent proposals to treat topological reconfiguration in inter-brain networks as a marker of affective phase transitions [Hinrichs et al., 2025]. The conceptual run has maximum curvature entropy 2.4087 and detects 48 transition events under the configured threshold.

19.4 Narrative Information and Aesthetic Discovery

Narrative also fits the active-inference vocabulary. Narratives guide event segmentation, identity coherence, and policy selection [Bouzegarene et al., 2024, Veissière et al., 2020]. In DigiPPPiP, a mark sequence can be treated as a symbolic trajectory with Shannon entropy and surprisal [Shannon, 1948]:

$$H(X) = - \sum_i p(x_i) \log_2 p(x_i) \quad (4)$$

The expected-information-gain arc used for aesthetic co-discovery is:




Figure 33: Conceptual curvature entropy over a modeled inter-brain network sequence. The plot is generated by `generate_geometric_hyperscanning_plot()` from synthetic network snapshots; read the red curve as curvature entropy and blue points as candidate transitions. It supports the proposal that graph diagnostics could mark rupture or repair windows. The figure is not participant hyperscanning, and empirical use would require artifact-robust network estimation.

$$\text{EIG}(t) = c t e^{-\lambda t} \quad (5)$$

fig. 34 and fig. 35 translate those commitments into inspectable conceptual plots. The configured alphabet supports a maximum entropy of 2.585 bits, and the epistemic arc peaks at model step 2.

Together, these equations function as a falsifiable grammar for future studies. They succeed only if they help specify what should be measured, what comparison would matter, and what result would count against the interpretation. A free-energy curve that improves only because of parameter choices, a synchrony measure that disappears after artifact controls, or an entropy score unrelated to participant reports would all narrow the framework rather than embarrass it.




Figure 34: Narrative-information diagnostics for a conceptual stroke sequence. The figure is generated by `generate_narrative_information_plot()` from `src/narrative.py`; read the upper panel as surprisal with pivotal-moment markers and the lower panel as convergence toward a repeated motif. It supports the narrative-information appendix by making the entropy primitive inspectable. The sequence is synthetic, and participant claims would require coded stroke alphabets and inter-rater checks.




Figure 35: Expected-information-gain and order-change balance in a conceptual DigiPPPiP session. The figure is generated by `generate_epistemic_arc_plot()` from `src/aesthetics.py`; read the normalized curves as an illustrative relation between curiosity, order, change, and the marked “aha” peak. It supports the appendix’s modeling vocabulary. The plot is conceptual, and validation would require event-aligned experience reports or behavioral measures.

20 References

- Bibliography lives in `manuscript/references.bib` and is resolved by Pandoc during rendering. All manuscript citations use bracketed Pandoc syntax so the renderer, not the prose, controls bibliography formatting and numbering.
- Search tools and Perplexity are discovery aids only. A citekey should enter the manuscript only after the title, authors, year, venue, and DOI or stable URL have been checked against a DOI resolver, publisher page, PubMed, arXiv, Crossref, DataCite, official government page, official standards page, or archival record.
- An alt decision tree, 2024. URL <https://www.w3.org/WAI/tutorials/images/decision-tree/>.
- Saleema Amershi, Dan Weld, Mihaela Vorvoreanu, Adam Fourney, Besmira Nushi, Penny Collisson, Jina Suh, Shamsi Iqbal, Paul N. Bennett, Kori Inkpen, Jaime Teevan, Ruth Kikin-Gil, and Eric Horvitz. Guidelines for human-AI interaction. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*, pages 1–13, 2019. doi: 10.1145/3290605.3300233.
- Sumru Atuk and Alyson Cole. Bodies on the line vs. bodies online: A feminist phenomenology of digitally mediated political action. *Women’s Studies in Communication*, 47(1):63–86, 2024. doi: 10.1080/07491409.2023.2297288.
- Hasan Ayaz and Frédéric Dehais, editors. *Neuroergonomics: The Brain at Work and in Everyday Life*. Academic Press, 2019. URL <https://www.elsevier.com/books/neuroergonomics/ayaz/978-0-12-811926-6>.
- Atiqah Azhari, Ashvina Rai, Han Sheng Ho, Ajevan Jegathisan, Shafeeqah Gill, Noelle Norfor, and Zan Chen. Inter-brain synchrony between undergraduate students during a naturalistic online seminar predicted greater relational satisfaction and task performance. *Frontiers in Neuroscience*, 19:1705767, 2025. doi: 10.3389/fnins.2025.1705767.
- Camila Benmessaoud, Kaylen J. Pfisterer, Anjelica De Leon, Ashish Saragadam, Noor El-Dassouki, Karen G. M. Young, Raima Lohani, Ting Xiong, and Quynh Pham. Design of a dyadic digital health module for chronic disease shared care: Development study. *JMIR Human Factors*, 10:e45035, 2023. doi: 10.2196/45035.
- Frank Biocca. The cyborg’s dilemma: Progressive embodiment in virtual environments. *Journal of Computer-Mediated Communication*, 3(2), 1997. doi: 10.1111/j.1083-6101.1997.tb00070.x.
- Claire Bishop. Antagonism and relational aesthetics. *October*, 110:51–79, 2004. doi: 10.1162/0162287042379810.
- Monica Blair, Leigh Tweedlie, Helen Minnis, Irene Cronin, and Fiona Turner. Online therapy with families: What can families tell us about how to do this well? a qualitative study assessing families’ experience of remote dyadic developmental psychotherapy compared to face-to-face therapy. *PLOS ONE*, 19(4):e0301640, 2024. doi: 10.1371/journal.pone.0301640.
- Michael Bostock, Vadim Ogievetsky, and Jeffrey Heer. D3 data-driven documents. *IEEE Transactions on Visualization and Computer Graphics*, 17(12):2301–2309, 2011. doi: 10.1109/TVCG.2011.185.
- Nabil Bouizegarene, Maxwell J. D. Ramstead, Axel Constant, Karl J. Friston, and Laurence J. Kirmayer. Narrative as active inference: An integrative account of cognitive and social functions in adaptation. *Frontiers in Psychology*, 15: 1345480, 2024. doi: 10.3389/fpsyg.2024.1345480.
- Nicolas Bourriaud. *Relational Aesthetics*. Les Presses du Réel, 2002. URL <https://www.lespressesdureel.com/EN/ouvrage.php?id=5>.
- Stacy M. Branham and Shaun K. Kane. Collaborative accessibility: How blind and sighted companions co-create accessible home spaces. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems*, pages 2373–2382, 2015. doi: 10.1145/2702123.2702511.
- Emily A. Butler and Ashley K. Randall. Emotional coregulation in close relationships. *Emotion Review*, 5(2):202–210, 2012. doi: 10.1177/1754073912451630.
- Patricia Canelas and Jan Hoehnk. Practices of digital placemaking: Accelerating place attachment. *Urban Research & Practice*, 18(3):378–396, 2025. doi: 10.1080/17535069.2025.2494997.
- Herbert H. Clark and Susan E. Brennan. Grounding in communication. In Lauren B. Resnick, John M. Levine, and Stephanie D. Teasley, editors, *Perspectives on Socially Shared Cognition*, pages 127–149. American Psychological Association, 1991. doi: 10.1037/10096-006.
- William S. Cleveland and Robert McGill. Graphical perception: Theory, experimentation, and application to the development of graphical methods. *Journal of the American Statistical Association*, 79(387):531–554, 1984. doi: 10.1080/01621459.1984.10478080.

- Alex Close, Stephen Field, and Robert Teather. Visual thinking in virtual environments: Evaluating multidisciplinary interaction through drawing ideation in real-time remote co-design. *Frontiers in Virtual Reality*, 4:1304795, 2024. doi: 10.3389/frvir.2023.1304795.
- Fabio Cramer, Grace E. Shephard, and Philip J. Heron. The misuse of colour in science communication. *Nature Communications*, 11(1):5444, 2020. doi: 10.1038/s41467-020-19160-7.
- Samantha Cruz Rivera, Xiaoxuan Liu, An-Wen Chan, Alastair K. Denniston, Melanie J. Calvert, SPIRIT-AI, and CONSORT-AI Working Group. Guidelines for clinical trial protocols for interventions involving artificial intelligence: The SPIRIT-AI extension. *BMJ*, 370:m3210, 2020. doi: 10.1136/bmj.m3210.
- Mihaly Csikszentmihalyi and Judith LeFevre. Optimal experience in work and leisure. *Journal of Personality and Social Psychology*, 56(5):815–822, 1989. doi: 10.1037/0022-3514.56.5.815.
- Xue Cui, Daniel M. Bryant, and Allan L. Reiss. Nirs-based hyperscanning reveals increased interpersonal coherence in superior frontal cortex during cooperation. *NeuroImage*, 59(3):2430–2437, 2012. doi: 10.1016/j.neuroimage.2011.09.003.
- Artur Czeszumski, Sara Eustergerling, Anne Lang, David Menrath, Michael Gerstenberger, Susanne Schuberth, Felix Schreiber, Zadkiel Zuluaga Rendon, and Peter König. Hyperscanning: A valid method to study neural inter-brain underpinnings of social interaction. *Frontiers in Human Neuroscience*, 14:39, 2020. doi: 10.3389/fnhum.2020.00039.
- Artur Czeszumski, Sophie Hsin-Yi Liang, Suzanne Dikker, Peter König, Chin-Pang Lee, Sander L. Koole, and Brent Kelsen. Cooperative behavior evokes interbrain synchrony in the prefrontal and temporoparietal cortex: A systematic review and meta-analysis of fnirs hyperscanning studies. *eNeuro*, 9(2), 2022. doi: 10.1523/ENEURO.0268-21.2022.
- Lancelot Da Costa, Thomas Parr, Noor Sajid, Sebastijan Veselic, Victorita Neacsu, and Karl Friston. Active inference on discrete state-spaces: A synthesis. *Journal of Mathematical Psychology*, 99:102447, 2020. doi: 10.1016/j.jmp.2020.102447.
- Peter Dalsgaard and Kim Halskov. Reflective design documentation. In *Proceedings of the Designing Interactive Systems Conference*, pages 428–437, 2012. doi: 10.1145/2317956.2318020.
- Gillian W. Datlen and Chiara Pandolfi. Developing an online art therapy group for learning disabled young adults using whatsapp. *International Journal of Art Therapy*, 25(4):192–201, 2020. doi: 10.1080/17454832.2020.1845758.
- Frédéric Dehais, Waldemar Karwowski, and Hasan Ayaz. Brain at work and in everyday life as the next frontier: Grand field challenges for neuroergonomics. *Frontiers in Neuroergonomics*, 1:583733, 2020. doi: 10.3389/fnrgo.2020.583733.
- Sebastian Deterding, Jonathan Hook, Rebecca Fiebrink, Marco Gillies, Jeremy Gow, Memo Akten, Gillian Smith, Antonios Liapis, and Kate Compton. Mixed-initiative creative interfaces. In *Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems*, pages 628–635, 2017. doi: 10.1145/3027063.3027072.
- Paul Dourish. Re-space-ing place. In *Proceedings of the 2006 20th Anniversary Conference on Computer Supported Cooperative Work*, 2006. doi: 10.1145/1180875.1180921.
- Paul Dourish and Ken Anderson. Collective information practice: Exploring privacy and security as social and cultural phenomena. *Human-Computer Interaction*, 21(3):319–342, 2006. doi: 10.1207/s15327051hci2103_2.
- Frank Elavsky, Lucas Nadolskis, and Dominik Moritz. Data navigator: An accessibility-centered data navigation toolkit. *IEEE Transactions on Visualization and Computer Graphics*, 30(1):803–813, 2024. doi: 10.1109/TVCG.2023.3327393.
- Thomas Erickson and Wendy A. Kellogg. Social translucence: An approach to designing systems that support social processes. *ACM Transactions on Computer-Human Interaction*, 7(1):59–83, 2000. doi: 10.1145/344949.345004.
- European Parliament and Council of the European Union. Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act), 2024. URL <https://eur-lex.europa.eu/eli/reg/2024/1689/oj/eng>.
- Gunther Eysenbach and CONSORT-EHEALTH Group. CONSORT-EHEALTH: Improving and standardizing evaluation reports of web-based and mobile health interventions. *Journal of Medical Internet Research*, 13(4):e126, 2011. doi: 10.2196/jmir.1923.
- Robin Forman. Bochner’s method for cell complexes and combinatorial ricci curvature. *Discrete and Computational Geometry*, 29:323–374, 2003. doi: 10.1007/s00454-002-0743-x.
- Marcus Foth, Martin Brynskov, and Timo Ojala, editors. *Citizen’s Right to the Digital City: Urban Interfaces, Activism, and Placemaking*. Springer, 2015. doi: 10.1007/978-981-287-919-6.

- Christopher Frauenberger, Judith Good, and Wendy Keay-Bright. Designing technology for children with special needs: Bridging perspectives through participatory design. *CoDesign*, 7(1):1–28, 2011. doi: 10.1080/15710882.2011.587013.
- Karl Friston. The free-energy principle: A unified brain theory? *Nature Reviews Neuroscience*, 11(2):127–138, 2010. doi: 10.1038/nrn2787.
- Karl Friston, Thomas FitzGerald, Francesco Rigoli, Philipp Schwartenbeck, and Giovanni Pezzulo. Active inference: A process theory. *Neural Computation*, 29(1):1–49, 2017. doi: 10.1162/NECO_a_00912.
- Karl Friston, Lancelot Da Costa, Noor Sajid, Conor Heins, Kai Ueltzhöffer, Grigorios A. Pavliotis, and Thomas Parr. The free energy principle made simpler but not too simple. *Physics Reports*, 1024:1–29, 2023. doi: 10.1016/j.physrep.2023.07.001.
- Bill Gaver and John Bowers. Annotated portfolios. *Interactions*, 19(4):40–49, 2012. doi: 10.1145/2212877.2212889.
- William Gaver. What should we expect from research through design? In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 937–946, 2012. doi: 10.1145/2207676.2208538.
- Eric Gordon and Adriana de Souza e Silva. *Net Locality: Why Location Matters in a Networked World*. Wiley-Blackwell, 2011. doi: 10.1002/9781444340679.
- Carl Gutwin and Saul Greenberg. A descriptive framework of workspace awareness for real-time groupware. *Computer Supported Cooperative Work*, 11(3–4):411–446, 2002. doi: 10.1023/A:1021271517844.
- Antonia F. de C. Hamilton. Hyperscanning: Beyond the hype. *Neuron*, 109(3):404–407, 2021. doi: 10.1016/j.neuron.2020.11.008.
- Jeffrey T. Hancock, Mor Naaman, and Karen Levy. AI-mediated communication: Definition, research agenda, and ethical considerations. *Journal of Computer-Mediated Communication*, 25(1):89–100, 2020. doi: 10.1093/jcmc/zmz022.
- Marc Hassenzahl, Stephanie Heidecker, Kai Eckoldt, Sarah Diefenbach, and Uwe Hillmann. All you need is love: Current strategies of mediating intimate relationships through technology. *ACM Transactions on Computer-Human Interaction*, 19(4):30:1–30:19, 2012. doi: 10.1145/2395131.2395137.
- Sarah Haywood and Bridget Grant. Reimagining art therapy for the digitally-mediated world: A hexagonal relationship. *International Journal of Art Therapy*, 27(3):143–150, 2022. doi: 10.1080/17454832.2022.2084124.
- Jeffrey Heer and Maneesh Agrawala. Design considerations for collaborative visual analytics. *Information Visualization*, 7(1):49–62, 2008. doi: 10.1057/palgrave.ivs.9500167.
- Jeffrey Heer and Ben Shneiderman. Interactive dynamics for visual analysis. *Communications of the ACM*, 55(4):45–54, 2012. doi: 10.1145/2133806.2133821.
- Nicolas Hinrichs, Mahault Albarracin, Dimitris Bolis, Yuyue Jiang, Leonardo Christov-Moore, and Leonhard Schilbach. Geometric hyperscanning of affect under active inference. *arXiv preprint arXiv:2506.08599*, 2025. doi: 10.48550/arXiv.2506.08599. URL <https://arxiv.org/abs/2506.08599>.
- Tammy C. Hoffmann, Paul P. Glasziou, Isabelle Boutron, Ruairidh Milne, Rafael Perera, David Moher, Douglas G. Altman, Virginia Barbour, Helen Macdonald, Marie Johnston, Sarah E. Lamb, Mary Dixon-Woods, Peter McCulloch, Jeremy C. Wyatt, An-Wen Chan, and Susan Michie. Better reporting of interventions: Template for intervention description and replication (TIDieR) checklist and guide. *BMJ*, 348:g1687, 2014. doi: 10.1136/bmj.g1687.
- Eric Horvitz. Principles of mixed-initiative user interfaces. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 159–166, 1999. doi: 10.1145/302979.303030.
- Hiroshi Ishii, Minoru Kobayashi, and Jonathan Grudin. Integration of interpersonal space and shared workspace: Clearboard design and experiments. *ACM Transactions on Information Systems*, 11(4):349–375, 1993. doi: 10.1145/159764.159762.
- Chipp Jansen and Elizabeth Sklar. Exploring co-creative drawing workflows. *Frontiers in Robotics and AI*, 8:577770, 2021. doi: 10.3389/frobt.2021.577770.
- Mengqi Jiang, Vijayakumar Nanjappan, Ziming Li, Zhen Wu, Ziqian Bai, and Hai-Ning Liang. ipillowpal: Exploring affective gesture-based interactive textile design for long-distance relationship couples. *International Journal of Human-Computer Studies*, 199:103466, 2025. doi: 10.1016/j.ijhcs.2025.103466.
- Shuli Jones, Isabella Pedraza Pineros, Daniel Hajas, Jonathan Zong, and Arvind Satyanarayan. “customization is key”: Reconfigurable textual tokens for accessible data visualizations. In *Proceedings of the CHI Conference on Human*

- Factors in Computing Systems*, pages 1–14, 2024. doi: 10.1145/3613904.3641970. URL <https://vis.csail.mit.edu/pubs/customization>.
- Girija Kaimal, Kendra Ray, and Juan Muniz. Reduction of cortisol levels and participants’ responses following art making. *Art Therapy*, 33(2):74–80, 2016. doi: 10.1080/07421656.2016.1166832.
- Iman Kassam, Daria Ilkina, Jessica Kemp, Heba Roble, Abigail Carter-Langford, and Nelson Shen. Patient perspectives and preferences for consent in the digital health context: State-of-the-art literature review. *Journal of Medical Internet Research*, 25:e42507, 2023. doi: 10.2196/42507.
- Joseph Jofish Kaye. I just clicked to say i love you. In *CHI ’06 Extended Abstracts on Human Factors in Computing Systems*, pages 363–368, 2006. doi: 10.1145/1125451.1125530.
- Christa Kelleher and Thorsten Wagener. Ten guidelines for effective data visualization in scientific publications. *Environmental Modelling & Software*, 26(6):822–827, 2011. doi: 10.1016/j.envsoft.2010.12.006.
- Livia Kernová, Júlia Halamová, and Denis Deriglazov. Effectiveness of digital interventions on relationship satisfaction among couples: A systematic review and meta-analysis. *BMC Psychology*, 13:1069, 2025. doi: 10.1186/s40359-025-03444-y.
- Pamela Gail D. Lagera, Steven R. Chan, and Peter M. Yellowlees. Asynchronous technologies in mental health care and education. *Current Treatment Options in Psychiatry*, 2023. doi: 10.1007/s40501-023-00286-6.
- Virginia LeBaron, Natalie Crimp, Nutta Homdee, Kelly Reed, Victoria Petermann, William Ashe, Leslie Blackhall, and Bryan Lewis. “less words, more pictures”: Creating and sharing data visualizations from a remote health monitoring system with clinicians to improve cancer pain management. *Frontiers in Digital Health*, 7:1520990, 2025. doi: 10.3389/fdgth.2025.1520990.
- Kwan Min Lee. Presence, explicated. *Communication Theory*, 14(1):27–50, 2004. doi: 10.1111/j.1468-2885.2004.tb00302.x.
- Konrad Lehmann, Dimitris Bolis, Karl J. Friston, Leonhard Schilbach, Maxwell J. D. Ramstead, and Philipp Kanske. An active-inference approach to second-person neuroscience. *Perspectives on Psychological Science*, 2024. doi: 10.1177/17456916231188000.
- Maria Lewicka. Place attachment: How far have we come in the last 40 years? *Journal of Environmental Psychology*, 31(3):207–230, 2011. doi: 10.1016/j.jenvp.2010.10.001.
- Xiaoxuan Liu, Samantha Cruz Rivera, David Moher, Melanie J. Calvert, Alastair K. Denniston, SPIRIT-AI, and CONSORT-AI Working Group. Reporting guidelines for clinical trial reports for interventions involving artificial intelligence: The CONSORT-AI extension. *BMJ*, 370:m3164, 2020. doi: 10.1136/bmj.m3164.
- Matthew Lombard and Theresa Ditton. At the heart of it all: The concept of presence. *Journal of Computer-Mediated Communication*, 3(2):JCMC321, 1997. doi: 10.1111/j.1083-6101.1997.tb00072.x.
- Alan Lundgard and Arvind Satyanarayan. Accessible visualization via natural language descriptions: A four-level model of semantic content. *IEEE Transactions on Visualization and Computer Graphics*, 28(1):1073–1083, 2022. doi: 10.1109/TVCG.2021.3114770.
- Kim Malfacini. The impacts of companion AI on human relationships: Risks, benefits, and design considerations. *AI & Society*, 40(7):5527–5540, 2025. doi: 10.1007/s00146-025-02318-6.
- Brandon T. McDaniel and Sarah M. Coyne. “technoference”: The interference of technology in couple relationships and implications for women’s personal and relational well-being. *Psychology of Popular Media Culture*, 5(1):85–98, 2016. doi: 10.1037/ppm0000065.
- Joshua McVeigh-Schultz and Nancy K. Baym. Thinking of you: Vernacular affordance in the context of the microsocial relationship app, couple. *Social Media + Society*, 1(2), 2015. doi: 10.1177/2056305115604649.
- Maurice Merleau-Ponty. *Phenomenology of Perception*. Routledge, 2012. doi: 10.4324/9780203720714.
- Alexandra Mikhailova and Daniel A. Friedman. Partner pen play in parallel (pppip): A new pppiparadigm for relationship improvement. *Arts*, 7(3):39, 2018. doi: 10.3390/arts7030039.
- Gretchen Miller and Alex McDonald. Online art therapy during the covid-19 pandemic. *International Journal of Art Therapy*, 25(4):159–160, 2020. doi: 10.1080/17454832.2020.1846383.

- Ryssa Moffat, Courtney E. Casale, and Emily S. Cross. Mobile fnirs for exploring inter-brain synchrony across generations and time. *Frontiers in Neuroergonomics*, 4:1260738, 2024. doi: 10.3389/fnrgo.2023.1260738.
- Meredith Ringel Morris, Annuska Zolyomi, Catherine Yao, Sina Bahram, Jeffrey P. Bigham, and Shaun K. Kane. With most of it being pictures now, i rarely use it: Understanding twitter’s evolving accessibility to blind users. In *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems*, pages 5506–5516, 2016. doi: 10.1145/2858036.2858116.
- Tamara Munzner. A nested model for visualization design and validation. *IEEE Transactions on Visualization and Computer Graphics*, 15(6):921–928, 2009. doi: 10.1109/TVCG.2009.111.
- Chang S. Nam, Sanghyun Choo, Jiali Huang, and Jiyoung Park. Brain-to-brain neural synchrony during social interactions: A systematic review on hyperscanning studies. *Applied Sciences*, 10(19):6669, 2020. doi: 10.3390/app10196669.
- Carman Neustaedter and Saul Greenberg. Intimacy in long-distance relationships over video chat. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 753–762, 2012. doi: 10.1145/2207676.2207785.
- Helen Nissenbaum. A contextual approach to privacy online. *Daedalus*, 140(4):32–48, 2011. doi: 10.1162/DAED_a_00113.
- Tuire Oittinen and Tiina Räisänen. Coordinating multimodal and screen-based actions in proposal sequences of video-mediated collaborative drawing. *Language & Communication*, 104:210–227, 2025. doi: 10.1016/j.langcom.2025.08.001.
- Gary M. Olson and Judith S. Olson. Distance matters. *Human-Computer Interaction*, 15(2–3):139–178, 2000. doi: 10.1207/S15327051HCI1523_4.
- Leysia Palen and Paul Dourish. Unpacking privacy for a networked world. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 129–136, 2003. doi: 10.1145/642611.642635.
- Blair Paley and Nastassia J. Hajal. Conceptualizing emotion regulation and coregulation as family-level phenomena. *Clinical Child and Family Psychology Review*, 25(1):19–43, 2022. doi: 10.1007/s10567-022-00378-4.
- Thomas Parr, Giovanni Pezzulo, and Karl J. Friston. *Active Inference: The Free Energy Principle in Mind, Brain, and Behavior*. The MIT Press, 2022. doi: 10.7551/mitpress/12441.001.0001.
- Sachin R. Pendse, Logan Stapleton, Neha Kumar, Munmun De Choudhury, and Stevie Chancellor. Advancing a consent-forward paradigm for digital mental health data, 2024. URL <https://arxiv.org/abs/2404.14548>. arXiv preprint.
- Sandra Petronio and Jeffrey T. Child. Conceptualization and operationalization: Utility of communication privacy management theory. *Current Opinion in Psychology*, 31:76–82, 2020. doi: 10.1016/j.copsyc.2019.08.009.
- Jordan S. Potash, Debra Kalmanowitz, Isaac Fung, Swasti A. Anand, and Gretchen M. Miller. Art therapy in pandemics: Lessons for covid-19. *Art Therapy*, 37(2):105–107, 2020. doi: 10.1080/07421656.2020.1754047.
- Livio Provenzi, Elisa Roberti, and Elena Capelli. Envisioning translational hyperscanning: How applied neuroscience might improve family-centered care. *Social Cognitive and Affective Neuroscience*, 18(1), 2022. doi: 10.1093/scan/nsa0061.
- Eric D. Ragan, Alex Endert, Jibonananda Sanyal, and Jian Chen. Characterizing provenance in visualization and data analysis: An organizational framework of provenance types and purposes. *IEEE Transactions on Visualization and Computer Graphics*, 22(1):31–40, 2016. doi: 10.1109/TVCG.2015.2467551.
- Maxwell J. D. Ramstead, Michael D. Kirchhoff, and Karl J. Friston. A tale of two densities: Active inference is enactive inference. *Adaptive Behavior*, 28(4):225–239, 2020. doi: 10.1177/1059712319862774.
- Elizabeth Redcay and Leonhard Schilbach. Using second-person neuroscience to elucidate the mechanisms of social interaction. *Nature Reviews Neuroscience*, 20(8):495–505, 2019. doi: 10.1038/s41583-019-0179-4.
- Ērika Reitere, Jana Duhovska, Vicky Karkou, and Kristīne Mārtinsons. Telehealth in arts therapies for neurodevelopmental and neurological disorders: A scoping review. *Frontiers in Psychology*, 15:1484726, 2024. doi: 10.3389/fpsyg.2024.1484726.
- Nicolas P. Rougier, Michael Droettboom, and Philip E. Bourne. Ten simple rules for better figures. *PLOS Computational Biology*, 10(9):e1003833, 2014. doi: 10.1371/journal.pcbi.1003833.
- Adam Rule, Amanda Birmingham, Cristal Zuniga, Ilkay Altintas, Shih-Cheng Huang, Rob Knight, Niema Moshiri, Mai H. Nguyen, Sara Brin Rosenthal, Fernando Perez, and Peter W. Rose. Ten simple rules for writing and sharing

- computational analyses in jupyter notebooks. *PLOS Computational Biology*, 15(7):e1007007, 2019. doi: 10.1371/journal.pcbi.1007007.
- Arvind Satyanarayan, Dominik Moritz, Kanit Wongsuphasawat, and Jeffrey Heer. Vega-lite: A grammar of interactive graphics. *IEEE Transactions on Visualization and Computer Graphics*, 23(1):341–350, 2017. doi: 10.1109/TVCG.2016.2599030.
- Leonhard Schilbach, Bert Timmermans, Vasudevi Reddy, Alan Costall, Gary Bente, Tobias Schlicht, and Kai Vogeley. Toward a second-person neuroscience. *Behavioral and Brain Sciences*, 36(4):393–414, 2013. doi: 10.1017/S0140525X12000660.
- Lion Schulz, Miguel Patrício, and Daan Odijk. Narrative information theory. *arXiv preprint arXiv:2411.12907*, 2024. doi: 10.48550/arXiv.2411.12907. URL <https://arxiv.org/abs/2411.12907>.
- Stacey D. Scott, M. Sheelagh T. Carpendale, and Kori M. Inkpen. Territoriality in collaborative tabletop workspaces. In *Proceedings of the 2004 ACM Conference on Computer Supported Cooperative Work*, pages 294–303, 2004. doi: 10.1145/1031607.1031655.
- Natalie Sebanz, Harold Bekkering, and Günther Knoblich. Joint action: Bodies and minds moving together. *Trends in Cognitive Sciences*, 10(2):70–76, 2006. doi: 10.1016/j.tics.2005.12.009.
- Kelly M. Shaffer, Lindsay S. Mayberry, Emily Georgia Salivar, Brian D. Doss, Amanda M. Lewis, and Kimberly Canter. Dyadic digital health interventions: Their rationale and implementation. *Procedia Computer Science*, 206:183–194, 2022. doi: 10.1016/j.procs.2022.09.097.
- Claude E. Shannon. A mathematical theory of communication. *Bell System Technical Journal*, 27(3):379–423, 1948. doi: 10.1002/j.1538-7305.1948.tb00917.x.
- Katie Shilton. Values levers: Building ethics into design. *Science, Technology, & Human Values*, 38(3):374–397, 2012. doi: 10.1177/0162243912436985.
- Kristen Shinohara and Jacob O. Wobbrock. Self-conscious or self-confident? a diary study conceptualizing the social accessibility of assistive technology. *ACM Transactions on Accessible Computing*, 8(2):5:1–5:31, 2016. doi: 10.1145/2827857.
- Ben Shneiderman. Creativity support tools: Accelerating discovery and innovation. *Communications of the ACM*, 50(12):20–32, 2007. doi: 10.1145/1323688.1323689.
- Sharon Snir and Hadas Wiseman. Relationship patterns of connectedness and individuality in couples as expressed in the couple joint drawing method. *The Arts in Psychotherapy*, 40(5):441–450, 2013. doi: 10.1016/j.aip.2013.07.005.
- Theresa Sobb, Benjamin P. Turnbull, and Nour Moustafa. A holistic review of cyber-physical-social systems: New directions and opportunities. *Sensors*, 23(17):7391, 2023. doi: 10.3390/s23177391.
- Victoria Stodden, Friedrich Leisch, and Roger D. Peng, editors. *Implementing Reproducible Research*. Chapman and Hall/CRC, 2014. doi: 10.1201/b16868.
- Ming Sun, Xiang Cao, Hyunyoung Song, Shahram Izadi, Hrvoje Benko, François Guimbretière, Xiangshi Ren, and Ken Hinckley. Enhancing naturalness of pen-and-tablet drawing through context sensing. In *Proceedings of the ACM International Conference on Interactive Tabletops and Surfaces*, 2011. doi: 10.1145/2076354.2076371.
- Elham Tabassi. Artificial intelligence risk management framework (AI RMF 1.0). Technical Report NIST AI 100-1, National Institute of Standards and Technology, 2023. URL <https://www.nist.gov/publications/artificial-intelligence-risk-management-framework-ai-rmf-10>.
- Ilias Tachtsidis and Felix Scholkmann. False positives and false negatives in functional near-infrared spectroscopy: Issues, challenges, and the way forward. *Neurophotonics*, 3(3):031405, 2016. doi: 10.1117/1.NPh.3.3.031405.
- John C. Tang. Findings from observational studies of collaborative work. *International Journal of Man-Machine Studies*, 34(2):143–160, 1991. doi: 10.1016/0020-7373(91)90039-A.
- Lu Tang, Jinxu Li, and Sophia Fantus. Medical artificial intelligence ethics: A systematic review of empirical studies. *Digital Health*, 9:20552076231186064, 2023. doi: 10.1177/20552076231186064.
- Adela C. Timmons, Gayla Margolin, and Darby E. Saxbe. Physiological linkage in couples and its implications for individual and interpersonal functioning: A literature review. *Journal of Family Psychology*, 29(5):720–731, 2015. doi: 10.1037/fam0000115.

- U.S. Department of Health and Human Services, Office for Human Research Protections. 45 CFR 46: Protection of human subjects, 2025. URL <https://www.hhs.gov/ohrp/regulations-and-policy/regulations/45-cfr-46/index.html>. Content last reviewed February 11, 2025.
- Sharon Vaisvaser, Juliet L. King, Hod Orkibi, and Hassan Aleem. Neurodynamics of relational aesthetic engagement in creative arts therapies. *Review of General Psychology*, 28(3), 2024. doi: 10.1177/10892680241260840.
- Joshua Vasil, Paul B. Badcock, Axel Constant, Karl Friston, and Maxwell J. D. Ramstead. A world unto itself: Human communication as active inference. *Frontiers in Psychology*, 11:417, 2020. doi: 10.3389/fpsyg.2020.00417.
- Samuel P. L. Veissière, Axel Constant, Maxwell J. D. Ramstead, Karl J. Friston, and Laurence J. Kirmayer. Thinking through other minds: A variational approach to cognition and culture. *Behavioral and Brain Sciences*, 43:e90, 2020. doi: 10.1017/S0140525X19001213.
- Frank Vetere, Martin R. Gibbs, Jesper Kjeldskov, Steve Howard, Florian Mueller, Sonja Pedell, Karen Mecoless, and Marcus Bunyan. Mediating intimacy: Designing technologies to support strong-tie relationships. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 471–480, 2005. doi: 10.1145/1054972.1055038.
- Melanie Weber, Jürgen Jost, and Emil Saucan. Forman-ricci flow for change detection in large dynamic data sets. *Axioms*, 5(4):26, 2016. doi: 10.3390/axioms5040026.
- Nadir Weibel, Adam Fouse, Colleen Emmenegger, Whitney Friedman, Edwin Hutchins, and James Hollan. Digital pen and paper practices in observational research. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 1331–1340, 2012. doi: 10.1145/2207676.2208590.
- Christiane Wenhart, Ronda Ringfort-Felner, Torben Wallbaum, Maryam Amidi, Ruben Albers, and Marc Hassenzahl. Relatedness technologies: An online compendium and systematic review. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–48, 2025. doi: 10.1145/3706598.3714260.
- Hadley Wickham. A layered grammar of graphics. *Journal of Computational and Graphical Statistics*, 19(1):3–28, 2010. doi: 10.1198/jcgs.2009.07098.
- Leland Wilkinson. *The Grammar of Graphics*. Springer, 2 edition, 2005. doi: 10.1007/0-387-28695-0.
- Greg Wilson, Jennifer Bryan, Karen Cranston, Justin Kitzes, Lex Nederbragt, and Tracy K. Teal. Good enough practices in scientific computing. *PLOS Computational Biology*, 13(6):e1005510, 2017. doi: 10.1371/journal.pcbi.1005510.
- Stephanie J. Wilson, Joshua R. Novak, Jeremy B. Yorgason, Lynn M. Martire, and Karen S. Lyons. New opportunities for advancing dyadic health science in gerontology. *The Gerontologist*, 64(1):gnac187, 2024. doi: 10.1093/geront/gnac187.
- Jacob O. Wobbrock, Shaun K. Kane, Krzysztof Z. Gajos, Susumu Harada, and Jon Froehlich. Ability-based design. *ACM Transactions on Accessible Computing*, 3(3):1–27, 2011. doi: 10.1145/1952383.1952384.
- Hyunseon Won, JongHan Kim, Jihyun Kim, Taeun Kim, and Jinyoung Han. Venus and mars on canvas: Ai-mediated collaborative drawing for romantic relationship insight. In *Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems*, pages 1–23, 2026. doi: 10.1145/3772318.3791153.
- World Medical Association. World medical association declaration of helsinki: Ethical principles for medical research involving human participants. *JAMA*, 2024. doi: 10.1001/jama.2024.21972. URL <https://jamanetwork.com/article.aspx?doi=10.1001/jama.2024.21972>.
- World Wide Web Consortium. Making content usable for people with cognitive and learning disabilities, 2021. URL <https://www.w3.org/TR/coga-usable/>.
- World Wide Web Consortium. Web content accessibility guidelines (wcag) 2.2, 2023. URL <https://www.w3.org/TR/WCAG22/>.
- Rami Yoon, Hye-Won Hong, and Yun-Mi Park. Phyigital art therapy: A theoretical model integrating digital and physical media in psychotherapeutic practice. *The Arts in Psychotherapy*, 96:102381, 2025. doi: 10.1016/j.aip.2025.102381.
- John Zimmerman, Jodi Forlizzi, and Shelley Evenson. Research through design as a method for interaction design research in hci. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 493–502, 2007. doi: 10.1145/1240624.1240704.
- Marius Zimmermann, Kathrine Schultz-Nielsen, Guillaume Dumas, and Ivana Konvalinka. Arbitrary methodological decisions skew inter-brain synchronization estimates in hyperscanning-eeG studies. *Imaging Neuroscience*, 2:imag-2-00350, 2024. doi: 10.1162/imag_a_00350.

Ania Zubala, Nicola Kennell, and Simon Hackett. Art therapy in the digital world: An integrative review of current practice and future directions. *Frontiers in Psychology*, 12:600070, 2021. doi: 10.3389/fpsyg.2021.600070.