Editorial Quality at Scale: A Reproducible Prose-Review Pipeline

Daniel Ari Friedman
Active Inference Institute
daniel@activeinference.institute
ORCID: 0000-0001-6232-9096
DOI: 10.5281/zenodo.20417104

October 30, 2026

BEGINNING OF TRANSMISSION

State: unpublished / pending pairing
Pairing: pending — unresolved: - GitHub release URL: `pending` - PDF SHA-256: `pending`

Release metadata

Field	Value
Title	Editorial Quality at Scale: A Reproducible Prose-Review Pipeline
Version	0.5.0
Concept DOI	10.5281/zenodo.20417104
GitHub	docxology/template_prose_project
Zenodo	https://zenodo.org/records/20417104
SHA-256	pending
SHA-512	pending

How to verify

- Scan **Integrity** QR and compare the embedded SHA-256 prefix to the table above.
- Scan **Zenodo** / **GitHub** QR codes and confirm they resolve to this release pairing.
- Full hashes and structured fields: `../data/transmission_manifest.json`.



Figure 1: Integrity QR strip

Structured manifest: `../data/transmission_manifest.json`
Stego: off | overlays text | barcodes on | XMP on | manifest on → `./secure_run.sh`




Figure 2: Publication pairing flow

Contents

1 Abstract **3**

2 Introduction **4**

3 Methodology **5**
3.1 Read . . . 5
3.2 Analyse . . . 5
3.3 Cross-check . . . 5
3.4 Evaluate . . . 5
3.5 Render . . . 5

4 Results **7**

5 Conclusion **8**

6 Pipeline Internals **9**
6.1 Data structures . . . 9

7 Reproducibility **10**
7.1 Verifying reproducibility locally . . . 10
7.2 Determinism guarantees . . . 10

8 References **11**

1 Abstract

This paper documents `template_prose_project`, the prose-focused exemplar of the Research Project Template. It pairs the template's two-layer architecture with the prose analysis infrastructure (readability metrics, structural outline, editorial quality flags) and the reference validation infrastructure (BibTeX validation), demonstrating that **rigorous editorial review can be expressed as a configurable, deterministic pipeline** with no novel domain algorithm of its own.

A single `manuscript/config.yaml` defines target grade-level bands, citation-density floors, structural rules (every section has an H1, no heading levels skipped), and bibliography-consistency policy. The pipeline reads the manuscript, runs the prose analysers, cross-checks every `[@key]` citation against `manuscript/references.bib`, evaluates the configured checks, and writes a deterministic markdown review report alongside three figures (per-file word counts, readability metrics, citation density) and a JSON `manuscript_report.json` suitable for CI artefacts.

Run snapshot. The current configuration analyses 8 file(s) totalling 1843 words across 90 sentence(s) and 65 paragraph(s). Average Flesch-Kincaid grade level is 15.68; average Gunning Fog index is 16.38; the manuscript references 6 unique citation key(s); the longest section is 484 words and the shortest is 17. These numbers are auto-substituted by `scripts/z_generate_manuscript_variables.py` after every run, so the abstract tracks the JSON outputs in `output/`.

The contribution is methodological and architectural: a *generic, reusable* prose-quality module (`infrastructure/prose/`) that any project in the template can opt into, plus a *minimal, configurable* exemplar (`projects/templates/template_prose_project/`) that wires it to the bibliography and the manuscript pipeline.

Keywords: prose analysis, readability, editorial review, reproducible manuscript review, scientific infrastructure

2 Introduction

Editorial review is one of the longest-lived bottlenecks in scientific writing — and an obvious target for the kind of *reproducible computational workflow* advocated by [Peng, 2011]. A working draft accumulates structural drift (skipped heading levels, sections that have grown to 2,000 words while their siblings sit at 200), readability drift (a once-clean introduction now reads at the Gunning Fog level of a legal contract [Gunning, 1952]), and citation drift (`[@key]` references that no longer exist in `references.bib`, or bibliography entries that nobody actually cites). The traditional remedy — a senior co-author re-reading the manuscript with [Strunk and White, 2000] in hand — is slow, non-reproducible, and impossible to apply continuously.

`template_prose_project` exists to demonstrate that the editorial-review pass can be expressed as a **deterministic, configurable, infrastructure-backed pipeline**. This project carries no novel research contribution of its own; its purpose is to show how to compose existing template infrastructure into a complete, reproducible editorial workflow.

The architecture is simple. `manuscript/config.yaml` defines policy: target grade-level band, citation-density floor, heading-structure rules, bibliography-consistency policy. The orchestrator script `scripts/run_prose_pipeline.py` reads the manuscript directory and calls `infrastructure.prose.analyze_manuscript` to produce a `ManuscriptReport`; `src/pipeline/__init__.py::run_prose_pipeline` then cross-checks the cited keys against the `references.bib` (via the project-owned `src.pipeline.prose_facade.parse_bib_keys` helper), evaluates each configured check, and writes the JSON artefacts, while `src/manuscript/report.py::write_review_report` assembles the markdown review and three diagnostic figures are rendered from the report. None of this is project-specific: a different project can re-use the same infrastructure with a different `config.yaml` and a different manuscript directory.

The remainder of this paper documents the methodology (sec. 3), the run-time results on the bundled manuscript (sec. 4), and the architectural lessons drawn from wiring prose analysis through the template pipeline (sec. 5).

3 Methodology

The pipeline runs in five stages, each a pure function in the project's `src/` modules; the orchestrator script in `scripts/` does only argument parsing and filesystem I/O.

3.1 Read

`infrastructure.prose.read_manuscript_dir` walks the configured manuscript directory and returns a sorted `{filename: text}` mapping. Scaffolding files (`preamble.md`, `config.yaml.example`, `AGENTS.md`, `README.md`, `SYNTAX.md`) are excluded by default — they hold infrastructure documentation rather than manuscript prose.

3.2 Analyse

For each file, three analysers run in parallel:

- **Metrics** (`infrastructure.prose.analysis.metrics`) — word, sentence, paragraph, syllable counts; average words per sentence; average syllables per word; complex-word fraction; Flesch Reading Ease [Flesch, 1948]; Flesch-Kincaid Grade Level [Kincaid et al., 1975]; Gunning Fog Index [Gunning, 1952]. The implementations are textbook formulae over a vowel-group syllable heuristic; they're good enough for a writer-facing signal, not for linguistic research.
- **Structure** (`infrastructure.prose.analysis.structure`) — heading outline, per-section word counts, max heading depth, presence of an H1, detection of skipped heading levels (e.g. an H1 followed directly by an H3).
- **Quality** (`infrastructure.prose.analysis.quality`) — passive-voice candidates (heuristic: "be" form + past participle), hedge-word density, citation density (Pandoc-style `[@key]` extraction), long-sentence flagging.

The results are aggregated into a `ManuscriptReport` whose JSON form is small, greppable, and diff-friendly.

3.3 Cross-check

Every cited key is matched against the BibTeX file at `bibliography.references_path`. The check has four tunable behaviours via `config.yaml`:

Setting	Effect
`fail_on_missing: true`	Any cited `[@key]` that does not exist in the bib fails the check.
`fail_on_missing: false`	Missing citations are warned but do not fail the run.
`fail_on_unused: true`	Bib entries that are never cited fail the check.
`fail_on_unused: false`	Unused entries are warned but do not fail.

The check compares the cited keys from the `ManuscriptReport` against the BibTeX keys returned by `src.pipeline.prose_facade.parse_bib_keys` — a deliberately minimal regex that skips `@comment` blocks. (Forks that need dialect-complete BibTeX parsing can swap in `infrastructure.reference.citation.parse_bibfile` at the script layer; the exemplar's own gate does not require it.)

3.4 Evaluate

The report runs through a set of pure check functions:

- `_check_grade_level` — the manuscript-wide weighted average FKGL falls within [`target_grade_level_min`, `target_grade_level_max`].
- `_check_citation_density` — citations per 1000 words >= `citation_density_min_per_1000`.
- `_check_no_skipped_levels` — no file uses a skipped heading level (when `prose.forbid_skipped_levels: true`).
- `_check_h1_per_file` — every file has an H1 (when `prose.require_h1_per_section: true`).
- `_check_bibliography` — citation/bib consistency per the `bibliography:` policy block.

Each check produces a `CheckResult(passed, message, details)`; the run's `all_passed` flag is the conjunction.
The thresholds each check applies come from `manuscript/config.yaml`. A `prose.preset` key (`lenient` for the bundled exemplar; `strict` in `config.yaml.example`) seeds the defaults for any knob the YAML does not set explicitly, so a fork can adopt a named editorial profile in one line and override individual knobs afterwards.

3.5 Render

`src/manuscript/report.py::write_review_report` writes a markdown file with:

- Top-line counts (files, words, sentences, paragraphs, averages).
- A pass/fail table for every check.
- Per-file metrics table (word count, sentence count, FRE, FKGL, Fog, citations, hedges, passives).

- Heading outline per file.
- Quality-flag callouts (long sentences, passive candidates, hedges) per file.

Three orchestrators run in lexicographic order (so the figure and variable stages always see a fresh review):

- `scripts/run_prose_pipeline.py` writes `output/manuscript_report.json` (the raw `ManuscriptReport`), `output/checks.json` (the list of check results), `output/review_report.md` (the human-readable review report), `output/evidence_summary.json` (versioned diagnostic-only evidence), and `output/run_summary.json` (one-line metadata).
- `scripts/y_generate_prose_figures.py` reads `manuscript_report.json` and writes `../figures/section_word_counts.png`, `../figures/readability_metrics.png`, and `../figures/citation_density.png`.
- `scripts/z_generate_manuscript_variables.py` reads `manuscript_report.json`
  - `config.yaml` and writes `output/data/manuscript_variables.json` along with a resolved manuscript tree under `output/manuscript/`.
- `manuscript/references.bib` is **not** modified by this pipeline — the prose project does not generate citations, only validates them.

4 Results

After running `scripts/run_prose_pipeline.py` with the bundled `manuscript/config.yaml` and the manuscript described in this paper, the project produces the following on-disk artefacts:

- `output/manuscript_report.json` — the raw `ManuscriptReport` JSON.
- `output/checks.json` — one `CheckResult` per configured check.
- `output/review_report.md` — the assembled markdown review report.
- `../figures/section_word_counts.png` — per-file word counts.
- `../figures/readability_metrics.png` — Flesch / Flesch-Kincaid / Gunning Fog per file.
- `../figures/citation_density.png` — citations per 1000 words per file.
- `output/data/manuscript_variables.json` — substitution variables for the abstract.

By design the three figures are **standalone CI/diagnostic artefacts**, not embedded manuscript images: this is a prose-review template, so its own rendered PDF deliberately contains no figure floats and runs cleanly through the very prose gate it documents. A fork that wants figures inside the manuscript should add real markdown image references to one of the produced figures (for example `../figures/section_word_counts.png`, `../figures/readability_metrics.png`, or `../figures/citation_density.png`) after those files exist.

Because the pipeline does not consult any external service, every artefact is reproducible from the manuscript text + `config.yaml` alone. A second run on the same inputs produces byte-identical JSON (modulo timestamp metadata in any caches the project later adds).

The pass/fail status of each configured check is recorded in `output/checks.json`. With the bundled configuration:

- **`grade_level_in_band`** — the weighted average FKGL across this manuscript is reported in the `output/checks.json` `details.value` field. The default band `10.0-18.0` is intentionally generous; tighten it for editorial review of public-facing material.
- **`citation_density_above_floor`** — citations per 1000 words must meet `prose.citation_density_min_per_1000`. The bundled config sets the floor to `0.0` (disabled) so the run is green out of the box; researchers should raise it to match the publication target.
- **`no_skipped_heading_levels`** — every file in this manuscript uses contiguous heading levels.
- **`every_file_has_h1`** — every prose file starts with an H1.
- **`bibliography_consistency`** — every `[@key]` in the prose resolves against `manuscript/references.bib`.

The figures in `../figures/` are colour-blind-safe (Wong 2011 palette) [Wong, 2011], 300 dpi, and PNG-only for archival stability. They are referenced in sec. 6 where we walk through the on-disk artefact set in full.

The full pass/fail summary lands in `output/review_report.md`, which is itself a Markdown file rendered alongside the manuscript by Pandoc — i.e. the project reports on itself in the same compilation step that produces the manuscript PDF.

5 Conclusion

`template_prose_project` packages a complete, configurable, reproducible editorial-review workflow into the Research Project Template's two-layer architecture. By keeping prose analysis, structural validation, and bibliography cross-checking in two orthogonal infrastructure modules — `infrastructure/prose/` and `infrastructure/reference/` — the project demonstrates that *editorial discipline* is expressible as a configurable, deterministic pipeline.

This exemplar follows a single house style:

- `manuscript/config.yaml` is the only place run policy lives.
- `src/` is deliberately `infrastructure`-free: the report Protocols and the `parse_bib_keys`/`render_outline` helpers in `src/pipeline/prose_facade.py` are the decoupling seam.
- Scripts in `scripts/` do only filesystem I/O, CLI argument handling, and the `infrastructure/` calls (e.g. `infrastructure.prose.analyze_manuscript`) on `src/`'s behalf.
- Every artefact in `output/` is regeneratable; `manuscript/references.bib` is curated and validated read-only by this project.

The contribution of this exemplar is architectural: a *generic, reusable* prose-quality module that any project in the template can opt into, and a *minimal, configurable* exemplar wiring it to the bibliography and the manuscript pipeline.

Three concrete extensions follow naturally:

1. **Style-guide enforcement** — extend `analyze_quality` with project-specific style rules (e.g. forbidden phrases, required terminology) read from `config.yaml`.
2. **Diff-aware review** — restrict the report to files modified since a given git ref so editorial review can run on every PR.
3. **LLM-assisted rewriting** — pipe long sentences and passive candidates into `infrastructure.llm` for suggested rewrites, using the same `seed=42, temperature=0.0` reproducibility contract as optional LLM stages in the template pipeline.

6 Pipeline Internals

This section documents the artefacts produced by the prose-review run.




Figure 3: Mermaid diagram

6.1 Data structures




Figure 4: Mermaid diagram

7 Reproducibility

The bundled `manuscript/config.yaml` is configured for the **strict reproducibility** discipline advocated for computational science by [Peng, 2011]:

1. **No network calls.** All analysis is local: prose metrics, structure, quality flags, and bibliography validation are computed from in-repo files only.
2. **Deterministic outputs.** `compute_metrics`, `analyze_structure`, and `analyze_quality` are pure functions over their input strings. The same manuscript text + the same `config.yaml` produces byte-identical JSON artefacts (modulo timestamp metadata in any caches the project later adds).
3. **Threshold transparency.** Every pass/fail decision is recorded in `output/checks.json` along with the numeric value that triggered it, so a reviewer can audit the gate without re-running the pipeline.
4. **No hidden state.** The pipeline does not mutate `manuscript/`; it reads and reports. `manuscript/references.bib` is read-only here (in contrast with the public search exemplar, where it is auto-populated).
5. **Same code, different config.** A reviewer who wants stricter standards edits `manuscript/config.yaml` (`prose.target_grade_level_max: 14.0`, say); no code changes are required.

7.1 Verifying reproducibility locally

```
# Run twice; check there are no diffs in the JSON artefacts.
uv run python projects/templates/template_prose_project/scripts/run_prose_pipeline.py
mv projects/templates/template_prose_project/output projects/templates/template_prose_project/output_first
uv run python projects/templates/template_prose_project/scripts/run_prose_pipeline.py
diff -ru \
    projects/templates/template_prose_project/output_first/manuscript_report.json \
    projects/templates/template_prose_project/output/manuscript_report.json
```

The diff should be empty. If it is not, the pipeline has acquired non-determinism — file an issue.

7.2 Determinism guarantees

Stage	Deterministic?	Mechanism
Prose analysis	yes	pure functions over text
Bibliography parse	yes	byte-stable round-trip in `infrastructure.reference.citation`
Check evaluation	yes	pure comparisons
Markdown report assembly	yes	sorted file list, fixed output template
Figure generation	yes (within Matplotlib version)	fixed palette, no random subsampling
Manuscript variables	yes	derived from the deterministic JSON report

8 References

Bibliography lives in manuscript/references.bib and is read by Pandoc during PDF render. The build pipeline invokes Pandoc with `--natbib`, so every `[@key]` citation in the manuscript is rewritten to the appropriate `\cite{}`/`\citep{}`/`\citet{}` LaTeX command and resolved against the bib file.

This project does not auto-generate the bibliography — it **validates** that every `[@key]` cited in the prose has a matching entry, via the project's own `src.pipeline.prose_facade.parse_bib_keys` helper (a lightweight BibTeX-key regex that skips `@comment` blocks). The check policy is configured under `bibliography:` in config.yaml.

To validate that `references.bib` is syntactically clean:

```
uv run python -m infrastructure.reference.citation.cli validate \
    projects/templates/template_prose_project/manuscript/references.bib --strict
```

Rudolf Flesch. A new readability yardstick. *Journal of Applied Psychology*, 32(3):221–233, 1948. doi: 10.1037/h0057532.

Robert Gunning. *The Technique of Clear Writing*. McGraw-Hill, 1952.

J Peter Kincaid, Robert P Fishburne, Richard L Rogers, and Brad S Chissom. Derivation of new readability formulas (automated readability index, fog count and flesch reading ease formula) for navy enlisted personnel. *Naval Technical Training Command Research Branch Report*, (8-75), 1975.

Roger D Peng. Reproducible research in computational science. *Science*, 334(6060):1226–1227, 2011. doi: 10.1126/science.1213847.

William Strunk and E. B. White. *The Elements of Style*. Allyn & Bacon, 4th edition, 2000. ISBN 978-0-205-30902-3.

Bang Wong. Points of view: Color blindness. *Nature Methods*, 8(6):441, 2011. doi: 10.1038/nmeth.1618.

END OF TRANSMISSION

Release: v0.5.0 · DOI 10.5281/zenodo.20417104 · SHA-256 pending… · pairing pending



Figure 5: Integrity QR strip

Prior: v0.4.2 · 10.5281/zenodo.20932047 · 290d21b1…