Appendix: Exemplar Project Summary I

Appendix: Exemplar Project Summary I

Table 1: Three representative workspaces under `projects/templates/` illustrating heterogeneous domains while sharing Layer 1. This is a hand-picked sample, not the full roster: the complete public exemplar set is enumerated dynamically from `PUBLIC_PROJECT_NAMES` and listed below.

Appendix: Exemplar Project Summary I

The full public exemplar roster is: templates/template_active_inference, templates/template_advanced_literature_review, templates/template_autopoiesis, templates/template_autoresearch_project, templates/template_autoscientists, templates/template_code_project, templates/template_data_descriptor, templates/template_eda_notebook, templates/template_experiment_tree, templates/template_formal, templates/template_gold_refinement, templates/template_literature_meta_analysis, templates/template_madlib, templates/template_methods_paper, templates/template_newspaper, templates/template_pitch_deck, templates/template_pools_rules_tools, templates/template_prose_project, templates/template_redacted_report,

Appendix: Exemplar Project Summary I

templates/template_registered_report, templates/template_search_project, templates/template_sia, templates/template_storybook, templates/template_template, templates/template_textbook. The three rows below are a representative sample; a future exemplar_summary_table token in build_manuscript_metrics_dict would let this table cover every exemplar without hand-editing.

Appendix: Exemplar Project Summary I

Project slug	Purpose	Highlights	Tests	Figures (Stage 02 hint)
`template_code_project`	Optimization tutorial	Convex demo figures, scripted tables	263 discovered tests; 90% declared gate	Controlled matplotlib exports
`template_prose_project`	Prose-heavy workflow	Validates narrative-only repos	165	Lightweight / optional plots
`template_autoresearch_project`	AutoResearch readiness	Planner + validation CLI	318	Readiness reports from Stage 02

Meta manuscript location: introspective study lives in `projects/templates/template_template/` beside the public exemplar set. Discovery now follows the typed `projects/` layout—`projects/templates/**` and `projects/active/**` are discovered/rendered, while `projects/working/**`, `projects/ongoing/**`, and `projects/archive/**` remain non-rendered—see root `CLAUDE.md` for invocation patterns (`resolve_project_root`).