

Rules: Soft and Strong Governance

The Role of Governance Rules I

Research software projects make dozens of implicit governance decisions: what test-coverage threshold is acceptable, how manuscript sections should be ordered, which citation fields are mandatory. Left implicit, these decisions drift silently across projects in a monorepo, eroding the consistency that makes the repository valuable as a public exemplar. The rules layer makes governance explicit, versioned, and machine-enforceable.

A **rule set** in the template repository is a directory under `rules/<scope>/<name>/` containing a typed manifest (`rules.yaml`) and two subdirectories of rule files:

```
<name>/  
  rules.yaml      -  
manifest (type, scope, version, rule_kinds)  
  soft/          -  
Markdown guideline files (human-readable, prompt-like)
```

The Role of Governance Rules II

strong/ -

YAML constraint schemas (machine-enforceable)

This two-tier architecture reflects the distinction between *guidance* (which humans follow approximately) and *constraints* (which pipelines enforce precisely) — a distinction also recognised in enterprise application architecture [Fowler2002patterns].

Soft Rules: Style and Process Guidelines I

Soft rules are Markdown files in `soft/`. They encode preferences and conventions that cannot easily be expressed as boolean constraints but that human reviewers and AI agents can apply contextually. Examples include:

- ▶ **Style preferences:** “Prefer active voice in manuscript sections.” “Use `\module{}` macros for all code identifiers.”
- ▶ **Process guidelines:** “Tag pull requests with a review-stage label before requesting review.” “Update `TODO.md` before closing an issue.”
- ▶ **Citation conventions:** “Cite primary sources rather than textbooks where possible.”

Soft rules are treated as guidance: deviations surface as suggestions in code review and manuscript audit reports, not as pipeline blockers. This makes the soft layer suitable for evolving preferences that should not break automated checks.

Strong Rules: Hard Constraints I

Strong rules are YAML files in `strong/`. Each file defines one named constraint:

```
rule:
```

```
  name: coverage-gate
```

```
  kind: strong
```

```
  description: "Minimum test coverage threshold for src/ mo
```

```
  applies_to: "projects/*/src/"
```

```
  enforcement: fail_on_violation
```

```
  constraints:
```

```
    minimum_line_coverage: 90
```

```
    minimum_branch_coverage: 80
```

Strong Rules: Hard Constraints II

The enforcement: `fail_on_violation` field signals that a pipeline must halt and report when this rule is violated. Strong rules are suitable for invariants that, if broken, indicate a genuine defect rather than a style preference: coverage below 90% means tests are missing; a manuscript section without an abstract means the document is incomplete.

The Two Template Rule Sets I

template_project_rules

This rule set governs software projects throughout the template repository. Its strong rules currently comprise:

File	Constraint
strong/coverage-gate.yaml	Minimum line coverage 90%, branch coverage 80% for src/
strong/module-structure.yaml	Required directory layout: src/, tests/, scripts/, manuscript/

Its soft rules provide guidance on code style, commit message conventions, and pull-request labelling.

The Two Template Rule Sets II

template_manuscript_rules

This rule set governs research manuscripts. Its strong rules comprise:

File	Constraint
strong/reference-schema.yaml	Required BibTeX fields and cite-key format constraints
strong/section-schema.yaml	Required manuscript sections, ordering, and minimum word counts

In the current pipeline run, **{{integration.rules_sets_ok}}** of **2 rule sets** validated successfully (@fig:counts).

The rules_applier Module I

The src/rules_applier.py module exposes three functions:

```
from src.rules_applier import (
    load_soft_rules,
    load_strong_rules,
    validate_against_rules,
)

soft    = load_soft_rules("template_project_rules")    # list of soft rules
strong = load_strong_rules("template_project_rules")  # list of strong rules
result = validate_against_rules("template_project_rules")
# → {"status": "ok" / "partial" / "missing", "soft_count": ...}
```

The rules_applier Module II

`validate_against_rules()` performs two checks: (1) the `rules.yaml` manifest is parseable YAML; (2) every rule file in `soft/` and `strong/` is parseable YAML. It returns a status of "ok" when both checks pass, "partial" when the manifest exists but some rule files are missing or malformed, and "missing" when the rule set directory is absent entirely. This graduated status enables the integration pipeline to distinguish between a rule set that has not yet been created (acceptable during active development) and one that is present but broken (actionable defect).

Rules and Manuscript Variables I

Strong rule validation counts are injected into the manuscript through the token system. The token `{{integration.rules_sets_ok}}` expands to the count of rule sets that returned `status="ok"` during the integration run. This creates a verifiable link between the pipeline's actual behaviour and the manuscript's claims — the manuscript cannot assert successful validation without the pipeline having actually succeeded.