Methodology

Methodology I

Two distinct workflows run on top of `infrastructure/search/literature` and `infrastructure/reference/citation`:

Methodology I

- **Standard pipeline** (`scripts/run_search_pipeline.py` → `src/pipeline/pipeline.py::run_literature_pipeline`) — single `SearchQuery`. Four pure-orchestration stages with no LLM dependency: (1) search via `LiteratureClient`, (2) enrichment via `AbstractFetcher` and (optional) `FulltextFetcher`, (3) collision-free citation-key generation in `_build_citation_keys`, (4) writing `output/corpus.json` + `manuscript/references.bib` + `output/enrichment_log.json`. The orchestrator script then optionally calls `src/pipeline/synthesis.py` for per-paper and corpus LLM synthesis and `src/analysis/report.py` for the final reading report.
- **Deep search** (`scripts/run_deep_search.py` → `src/search/deep_search.py::run_deep_search`) — multi-keyword fan-out: each keyword runs its own `SearchQuery` capped at `max_results_per_keyword` (100 by default), every paper is fully enriched (abstract + PDF fulltext when available), and an LLM-driven multi-section deep summary (CONTRIBUTION / METHOD / EVIDENCE / LIMITATIONS / CONNECTIONS / SIGNIFICANCE / TAGS) is written for each paper as a standalone markdown reading note. Output lands under `output/deep_search/<keyword_slug>/` plus aggregate `aggregate.json`, `aggregate_report.md`, and a unified, deduplicated `manuscript/references_deep.bib` with collision-free citation keys.

The standard pipeline is described first in this section; the deep-search workflow is documented in sec. 8. Diagnostic figures for the latest pipeline run appear at the end of this section.

The search stage is intentionally faithful to the standard literature-search pattern documented in foundational optimisation textbooks (Boyd and Vandenberghe 2004; Nocedal and Wright 2006) — a deterministic query, capped result count, and explicit failure isolation between sources — so reviewers familiar with those references can reason about the workflow without learning new abstractions.

A `SearchQuery` is constructed from `config.search`:

```
SearchQuery(
    text=config.search.query,
    max_results=config.search.max_results,
    year_min=config.search.year_min,
    year_max=config.search.year_max,
)
```

A `LiteratureClient` is constructed with the configured backends. Each backend produces a normalised `Paper` record; the aggregator deduplicates by DOI $\rightarrow$ arXiv id $\rightarrow$ normalised (title, year), keeping the highest-scored copy and filling missing fields from the loser.

Per-backend errors are recorded into `SearchResult.errors` rather than raised. A network outage in one backend never breaks the workflow; partial coverage is reported by the final stage.

Cache I

`SearchCache` writes one JSON file per query, named by a 16-character SHA-256 prefix of the canonical query identity. Identical queries (modulo whitespace and case) share a cache entry. Cache files are pretty-printed JSON, version-control-friendly, and contain a `_cached_at` timestamp for optional TTL enforcement.

Enrichment I

Two fetchers populate fields the search backends did not supply:

Enrichment I

- `AbstractFetcher` — currently fetches arXiv abstracts via the export API, writes them to `<safe_id>.txt` under the configured cache directory, and re-uses them on subsequent runs.
- `FulltextFetcher` — downloads PDFs (arXiv URL, `paper.pdf_url`, or a caller-supplied override), writes the bytes verbatim to `<safe_id>.pdf`, and extracts text via `pypdf` to `<safe_id>.txt`. Without `pypdf` the PDF is still cached, and the fetcher returns `status="error"` with an informative message; the rest of the pipeline continues.

Enrichment I

Both fetchers stamp `paper.abstract` / `paper.fulltext` in place, so downstream stages see enriched records without re-loading.

Export I

For every `paper`, `paper_to_bibentry()` produces a `BibEntry` whose:

Export I

- citation key follows the exemplar's `<author><year><title-word>` convention with stop-word filtering and unicode folding;
- entry type is routed by `venue_type` (journal $\rightarrow$ `@article`, conference $\rightarrow$ `@inproceedings`, book $\rightarrow$ `@book`, preprint $\rightarrow$ `@article`, etc.);
- fields are emitted in the order observed in `references.bib`: title, author, journal/booktitle, year, volume, number, pages, publisher, edition, isbn, doi, url, abstract, keywords.

Export I

A `BibDatabase` collects these entries and `write_bibfile` renders them in the project's house format: 2-space indent, trailing-comma rule, `pages={N--M}`, verbatim DOIs/years, bare unicode.

Synthesis I

Two LLM passes produce the reading report (see `src/pipeline/synthesis.py`):

Synthesis I

- **Per-paper synthesis** — `build_paper_block(paper, citation_key, max_fulltext=4000)` renders the paper as a markdown block; `synthesise_per_paper` formats `PROMPT_PER_PAPER` and calls the injected `llm` callable. The prompt requests five sections: CONTRIBUTION, METHOD, EVIDENCE, LIMITATION, TAGS, plus a citation-key reference.
- **Corpus synthesis** — `build_corpus_block` concatenates every paper into a single citation-keyed block; `synthesise_corpus` formats `PROMPT_CORPUS`, which asks for 3–7 thematic clusters, methodological agreements / disagreements (≥ 2 papers each), and three open questions that the corpus does not answer.

Both functions return a `SynthesisResult(kind, prompt, text, paper_id)` record so the prompt is recoverable for reproducibility. The synthesis layer takes a callable `llm: (str) -> str` so tests pass a deterministic local function (no Ollama dependency) and runtime callers pass a thin adapter around `infrastructure.llm.LLMClient`. Determinism in production runs is enforced by `OllamaClientConfig(seed=42, temperature=0.0)`.

The deep-search workflow uses a richer prompt (`src/search/deep_search.py::DEEP_PROMPT`) with seven sections (CONTRIBUTION / METHOD / EVIDENCE / LIMITATIONS / CONNECTIONS / SIGNIFICANCE / TAGS) and a much larger `max_fulltext` budget (400000 characters by default).

Report I

`src/analysis/report.py::write_reading_report` assembles a markdown file with:

Report I

- Topic, result count, year filter, and any backend errors at the top.
- A per-source count table.
- One-line summaries for every paper.
- The corpus synthesis (if present).
- All per-paper notes (if present).

Citation keys appear in `[brackets]` so a downstream tool — for example a Pandoc filter or a manual search — can resolve them against the auto-generated `references.bib`.

Diagnostic figures I

`scripts/y_generate_search_figures.py` (a thin orchestrator over `src/publish/figures.py`) writes three diagnostic plots into `output/figures/` from `output/search/results.json`. Each figure uses Matplotlib's `Agg` backend so the pipeline runs headlessly in CI; the colour palette is colourblind-safe (Wong, *Nature Methods* 2011).

fig. 1 reports the per-backend contribution counts before deduplication, surfacing which sources actually returned coverage for the configured query. The bar values are read directly from `SearchResult.per_source_counts` (set by `LiteratureClient` *before* the DOI / arXiv-id / title merge step), so a backend that returned five papers all duplicating arXiv hits still scores five here.

Diagnostic figures I




Figure 1: Per-source paper counts read from `SearchResult.per_source_counts` (pre-deduplication contribution per backend). The numeric label above each bar reports the raw count; the y-axis spans `[0, max + headroom]`. Bar order follows `project_config.search.sources`. Empty runs render `(no results)` centred. Generated by `src/publish/figures.py::plot_papers_per_source`.

Diagnostic figures I

fig. 2 shows the publication-year distribution *after* the merge step (one bar per unique paper, not per backend hit) — useful for spotting backend coverage gaps in older / newer literature. Papers with no `year` field are dropped silently from the histogram (they remain in the corpus).

Diagnostic figures I




Figure 2: Publication-year histogram of the deduplicated paper roster. One bin per year (no smoothing); the x-axis spans the observed `[min(year), max(year)]` from `result.papers`. Papers with `year is None` are dropped; the y-axis is per-year paper count. Generated by `src/publish/figures.py::plot_year_histogram`.

fig. 3 shows the per-paper relevance scores returned by the backends, ranked descending. The offline `LocalBackend` sets `Paper.score` to the fraction of query terms found in a paper's searchable title, abstract, keywords, or author text. This is a lexical match score, not a calibrated relevance probability. A backend that leaves `Paper.score` at its default `0.0` produces a zero-length bar while retaining the paper's y-axis tick.

Diagnostic figures I




Figure 3: Per-paper backend-reported relevance scores ranked descending (highest at top). Each horizontal bar is one `Paper.score`; long y-tick titles are truncated with an ellipsis. `LocalBackend` scores are query-term match fractions; an unspecified score defaults to `0.0` and yields a zero-length bar. Generated by `src/publish/figures.py::plot_score_distribution`.