Experimental Setup

Experimental Setup I

This section details the controlled vocabulary, worked examples, and software environment used to produce the results.

Controlled vocabulary I

The DSL's vocabulary is declared once in code and consulted by every gate and the compiler — never re-declared per method:

Controlled vocabulary I

Module	Declares	Cardinality
`src/template_methods_paper/methods_dsl/vocabulary.py`	`StepKind`, `Target`, `target_accepts`	9 step kinds, 3 targets
`src/template_methods_paper/methods_dsl/units.py`	`Dimension`, `Quantity`, the unit table	18 controlled units across 8 dimensions
`src/template_methods_paper/methods_dsl/validation.py`	The four staged gates	4 gates, fixed order

Worked examples I

`all_example_methods()` (`src/template_methods_paper/methods_dsl/examples_methods.py`) returns 2 methods:

Worked examples I

Method	Domain	Target	Notable structure
`PBSPreparation`	Wet-lab bench preparation (BPL's own domain; an original example)	`HUMAN`	A strict 5-step linear chain with a final `VALIDATE` step
`SensorCalibrationSweep`	Instrument calibration (a non-biology controlled procedure)	`AUTOMATED`	Mixed automated `MEASURE`/`COMPUTE` steps and a `HUMAN ANNOTATE` sign-off step

Worked examples I

The second example exists specifically to demonstrate that the controlled vocabulary generalizes beyond wet-lab protocols, as sec. 2 claims.

Pipeline conditions I

The experiment overlay (`experiment_plan.yaml`) declares three conditions:

Pipeline conditions I

- **declared_method** (reference) — a method constructed directly as Python objects, before any validation gate has run.
- **validated_method** (proposed) — the same method after passing all four staged gates and deterministic compilation to a scheduled `Plan`.
- **automated_target_variant** (variant) — `PBSPreparation`'s steps recompiled against an `AUTOMATED` execution target, ablating the target-compatibility gate's `HUMAN`/`AUTOMATED` step boundary (a `HUMAN` method's steps must all be `HUMAN`-compatible; an `AUTOMATED` method's steps may be either).

Pipeline conditions I

The primary metric is gate pass rate: the fraction of staged-gate evaluations a method's steps satisfy.

Computational environment I

- **Language**: Python 3.14.10 on Linux x86_64 (see root `pyproject.toml` for the supported version range).
- **Core dependencies**: `pyyaml`, `matplotlib` (declared in `domain_profile.yaml::required_packages`); the DSL library itself (`src/template_methods_paper/methods_dsl/`) has zero third-party dependencies beyond the standard library, with one declared `infrastructure` logging exception (`_logging.py`).
- **Headless plotting**: the analysis script sets `MPLBACKEND=Agg` before importing matplotlib.

Pipeline ordering I

The typical analysis order is:

Pipeline ordering I

1. `scripts/methods_analysis.py` — compiles every example method, runs all gates, exports worklist/CSV/Mermaid/JSON per method, demonstrates the provenance hash-chain, and writes `output/figures/step_counts.png`, printing each output path for manifest collection.
2. `scripts/z_generate_manuscript_variables.py` — reads `manuscript/config.yaml` and the analysis outputs, then resolves every generated variable in `manuscript/*.md`.
3. PDF rendering reads the resolved manuscript tree so figure paths and prose match the analysis that just completed.

Relation to results I

Result (sec. 4)	Producing function (`src/template_methods_paper/methods_dsl/`)	Primary inputs
Compiled-plan summary	`compile_method()`	`all_example_methods()`
Step-count figure	`len(plan.steps)` per method	`output/data/compiled_plans.json`
Gate pass tally	`run_all_gates()`	Each example method
Determinism check	`compile_method()` called twice	`all_example_methods()`
Trust-chain verification	`append_record()` / `verify_chain()`	Demonstration chain in `scripts/methods_analysis.py`

Relation to results I

This table is descriptive documentation only; it is not executed as code during the build.