Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves

Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I

The active composition depth is `deep`. The lexicon exposes 10 category list(s), and the slot declaration expands to 40 concrete token choice(s). Section switches are evaluated before composition so disabled sections cannot silently borrow enabled-section claims.

Configuration owns more than vocabulary. It also owns section titles, narrative moves, method protocol rows, contribution claims, and audit rules. That makes the manuscript shape visible in one YAML file while preserving the rule that source code, not hand-edited output, performs the composition.

Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I

The tables in this section expose the declared surface that controls rendering. They are useful during review because a title change, slot expansion, or disabled section appears as a small config diff and a regenerated artifact diff rather than as scattered prose edits.

The configured-field inventory separates 126 explicit YAML path(s) from 11 loader-defaulted path(s). That distinction matters for forks: a field that appears in the rendered manuscript may be intentionally authored in `config.yaml`, or it may be a documented default inherited from the template.

Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I




Figure 5: Configured field origin matrix

Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I



Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I

Figure 6: Section configuration heatmap

Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves I




Figure 7: Field origin summary

Declared Section Titles I

Section key	Rendered title	Enabled
`abstract`	Abstract	True
`introduction`	Introduction: Lexicon as Data and Manuscript as Build Artifact	True
`methods`	Methods: Source-Owned Token Injection and Conditional IMRAD Assembly	True
`results`	Results: Provenance, Density, and Resolved Manuscript Surface	True
`discussion`	Discussion: Accountability Boundaries for Generated Prose	True
`configuration`	Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves	True
`evaluation`	Evaluation: Gate Criteria, QA Probes, and Failure Discovery	True
`reproducibility`	Reproducibility: Seeded Regeneration and Artifact Trace	True

Declared Section Titles I

Section key	Rendered title	Enabled
`limitations`	Limitations: Non-Claims, Misuse Modes, and Human Review	True
`scope`	Scope: Related Generators and Responsible Forking	True
`authoring_contract`	Authoring Contract: Human Review and Forking Obligations	True

Configuration Counts I

- Seed: 431
- Composition depth: deep
- Lexicon categories: 10
- Slot rules: 22
- Token choices: 40
- Enabled sections: 11
- Method steps: 18
- Design principles: 13
- Pipeline phases: 17
- Quality probes: 14
- Authoring obligations: 8
- Explicit configured paths: 126
- Defaulted configured paths: 11
- Enabled visualization flags: 7
- Section-level configured paths: 33
- Lexicon-level configured paths: 10
- Slot-level configured paths: 66
- Narrative moves: 52
- Audit rules: 12
- Contribution claims: 9

Configured Field Summary I

Measure	Count
Total tracked field paths	137
Explicit YAML paths	126
Loader-defaulted paths	11
Enabled visualization flags	7
Section-level paths	33
Lexicon-level paths	10
Slot-level paths	66
Visualization-control paths	9

Configured Field Summary I

Measure	Count
Top-level schema paths	19

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib	explicit	schema	configured field
madlib.audit_rules	explicit	schema	12 entries
madlib.authoring_obligations	explicit	schema	8 entries
madlib.composition_depth	explicit	schema	deep
madlib.contribution_claims	explicit	schema	9 entries
madlib.design_principles	explicit	schema	13 entries
madlib.evaluation_criteria	explicit	schema	7 entries
madlib.failure_modes	explicit	schema	13 entries

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.hypothesis	explicit	schema	Deterministic lexical injection can generate a complete conditional IMRAD manuscript while preserving token provenance, section intent, and audit-ready method evidence.
madlib.lexicon	explicit	schema	10 categories
madlib.lexicon.adjectives	explicit	lexicon	7 tokens
madlib.lexicon.artifacts	explicit	lexicon	12 tokens
madlib.lexicon.audiences	explicit	lexicon	4 tokens
madlib.lexicon.constraints	explicit	lexicon	5 tokens
madlib.lexicon.failures	explicit	lexicon	5 tokens
madlib.lexicon.measures	explicit	lexicon	8 tokens

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.lexicon.methods	explicit	lexicon	5 tokens
madlib.lexicon.nouns	explicit	lexicon	7 tokens
madlib.lexicon.qualities	explicit	lexicon	5 tokens
madlib.lexicon.verbs	explicit	lexicon	7 tokens
madlib.method_protocol	explicit	schema	18 entries
madlib.narrative_moves	explicit	schema	configured field
madlib.narrative_moves.abstract	explicit	section	3 moves
madlib.narrative_moves.authoring_contract	explicit	section	5 moves

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.narrative_moves.configuration`	explicit	section	3 moves
`madlib.narrative_moves.discussion`	explicit	section	4 moves
`madlib.narrative_moves.evaluation`	explicit	section	4 moves
`madlib.narrative_moves.introduction`	explicit	section	4 moves
`madlib.narrative_moves.limitations`	explicit	section	4 moves
`madlib.narrative_moves.methods`	explicit	section	13 moves
`madlib.narrative_moves.reproducibility`	explicit	section	4 moves
`madlib.narrative_moves.results`	explicit	section	4 moves

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.narrative_moves.scope	explicit	section	4 moves
madlib.pipeline_phases	explicit	schema	17 entries
madlib.quality_probes	explicit	schema	14 entries
madlib.schema_version	explicit	schema	configured field
madlib.section_conditions	explicit	schema	configured field
madlib.section_conditions.abstract	explicit	section	enabled
madlib.section_conditions.authoring_contract	explicit	section	enabled
madlib.section_conditions.configuration	explicit	section	enabled

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.section_conditions.discussion`	explicit	section	enabled
`madlib.section_conditions.evaluation`	explicit	section	enabled
`madlib.section_conditions.introduction`	explicit	section	enabled
`madlib.section_conditions.limitations`	explicit	section	enabled
`madlib.section_conditions.methods`	explicit	section	enabled
`madlib.section_conditions.reproducibility`	explicit	section	enabled
`madlib.section_conditions.results`	explicit	section	enabled
`madlib.section_conditions.scope`	explicit	section	enabled

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.section_titles	explicit	schema	configured field
madlib.section_titles.abstract	explicit	section	Abstract
madlib.section_titles.authoring_contract	explicit	section	Authoring Contract: Human Review and Forking Obligations
madlib.section_titles.configuration	explicit	section	Configuration: Schema-Controlled Lexicon, Slots, and Narrative Moves
madlib.section_titles.discussion	explicit	section	Discussion: Accountability Boundaries for Generated Prose
madlib.section_titles.evaluation	explicit	section	Evaluation: Gate Criteria, QA Probes, and Failure Discovery
madlib.section_titles.introduction	explicit	section	Introduction: Lexicon as Data and Manuscript as Build Artifact
madlib.section_titles.limitations	explicit	section	Limitations: Non-Claims, Misuse Modes, and Human Review

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.section_titles.methods	explicit	section	Methods: Source-Owned Token Injection and Conditional IMRAD Assembly
madlib.section_titles.reproducibility	explicit	section	Reproducibility: Seeded Regeneration and Artifact Trace
madlib.section_titles.results	explicit	section	Results: Provenance, Density, and Resolved Manuscript Surface
madlib.section_titles.scope	explicit	section	Scope: Related Generators and Responsible Forking
madlib.seed	explicit	schema	431
madlib.slots	explicit	schema	22 slot rules, 40 token choices
madlib.slots.authoring_audience	explicit	slot	audiences -> authoring_contract (1)
madlib.slots.authoring_audience.count	defaulted	slot	1

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.slots.authoring_audience.section	explicit	slot	authoring_contract
madlib.slots.authoring_quality	explicit	slot	qualities -> authoring_contract (1)
madlib.slots.authoring_quality.count	defaulted	slot	1
madlib.slots.authoring_quality.section	explicit	slot	authoring_contract
madlib.slots.config_constraint	explicit	slot	constraints -> configuration (1)
madlib.slots.config_constraint.count	defaulted	slot	1
madlib.slots.config_constraint.section	explicit	slot	configuration
madlib.slots.discussion_adjective	explicit	slot	adjectives -> discussion (1)

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.slots.discussion_adjective.count`	defaulted	slot	1
`madlib.slots.discussion_adjective.section`	explicit	slot	discussion
`madlib.slots.discussion_audience`	explicit	slot	audiences -> discussion (2)
`madlib.slots.discussion_audience.count`	explicit	slot	2
`madlib.slots.discussion_audience.section`	explicit	slot	discussion
`madlib.slots.evaluation_artifact`	explicit	slot	artifacts -> evaluation (2)
`madlib.slots.evaluation_artifact.count`	explicit	slot	2
`madlib.slots.evaluation_artifact.section`	explicit	slot	evaluation

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.slots.evaluation_measure`	explicit	slot	measures -> evaluation (3)
`madlib.slots.evaluation_measure.count`	explicit	slot	3
`madlib.slots.evaluation_measure.section`	explicit	slot	evaluation
`madlib.slots.intro_nouns`	explicit	slot	nouns -> introduction (4)
`madlib.slots.intro_nouns.count`	explicit	slot	4
`madlib.slots.intro_nouns.section`	explicit	slot	introduction
`madlib.slots.intro_verbs`	explicit	slot	verbs -> introduction (4)
`madlib.slots.intro_verbs.count`	explicit	slot	4

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.slots.intro_verbs.section`	explicit	slot	introduction
`madlib.slots.limitation_failure`	explicit	slot	failures -> limitations (3)
`madlib.slots.limitation_failure.count`	explicit	slot	3
`madlib.slots.limitation_failure.section`	explicit	slot	limitations
`madlib.slots.method_artifact`	explicit	slot	artifacts -> methods (2)
`madlib.slots.method_artifact.count`	explicit	slot	2
`madlib.slots.method_artifact.section`	explicit	slot	methods
`madlib.slots.method_constraint`	explicit	slot	constraints -> methods (1)

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.slots.method_constraint.count`	defaulted	slot	1
`madlib.slots.method_constraint.section`	explicit	slot	methods
`madlib.slots.method_name`	explicit	slot	methods -> methods (1)
`madlib.slots.method_name.count`	defaulted	slot	1
`madlib.slots.method_name.section`	explicit	slot	methods
`madlib.slots.method_quality`	explicit	slot	qualities -> methods (2)
`madlib.slots.method_quality.count`	explicit	slot	2
`madlib.slots.method_quality.section`	explicit	slot	methods

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.slots.reproducibility_artifact	explicit	slot	artifacts -> reproducibility (2)
madlib.slots.reproducibility_artifact.count	explicit	slot	2
madlib.slots.reproducibility_artifact.section	explicit	slot	reproducibility
madlib.slots.result_artifact	explicit	slot	artifacts -> results (2)
madlib.slots.result_artifact.count	explicit	slot	2
madlib.slots.result_artifact.section	explicit	slot	results
madlib.slots.result_measure	explicit	slot	measures -> results (3)
madlib.slots.result_measure.count	explicit	slot	3

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.slots.result_measure.section	explicit	slot	results
madlib.slots.scope_audience	explicit	slot	audiences -> scope (1)
madlib.slots.scope_audience.count	defaulted	slot	1
madlib.slots.scope_audience.section	explicit	slot	scope
madlib.slots.scope_constraint	explicit	slot	constraints -> scope (1)
madlib.slots.scope_constraint.count	defaulted	slot	1
madlib.slots.scope_constraint.section	explicit	slot	scope
madlib.slots.study_adjective	explicit	slot	adjectives -> abstract (1)

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.slots.study_adjective.count`	defaulted	slot	1
`madlib.slots.study_adjective.section`	explicit	slot	abstract
`madlib.slots.study_noun`	explicit	slot	nouns -> abstract (1)
`madlib.slots.study_noun.count`	defaulted	slot	1
`madlib.slots.study_noun.section`	explicit	slot	abstract
`madlib.slots.study_verb`	explicit	slot	verbs -> abstract (1)
`madlib.slots.study_verb.count`	defaulted	slot	1
`madlib.slots.study_verb.section`	explicit	slot	abstract

Configured Field Inventory I

Path	Origin	Scope	Summary
madlib.visualizations	explicit	visualization	enabled
madlib.visualizations.configured_field_matrix	explicit	visualization	true
madlib.visualizations.enabled	explicit	visualization	true
madlib.visualizations.field_origin_summary	explicit	visualization	true
madlib.visualizations.provenance_trace_map	explicit	visualization	true
madlib.visualizations.quality_gate_matrix	explicit	visualization	true
madlib.visualizations.section_configuration_heatmap	explicit	visualization	true
madlib.visualizations.section_token_allocation	explicit	visualization	true

Configured Field Inventory I

Path	Origin	Scope	Summary
`madlib.visualizations.token_injection_flow`	explicit	visualization	true