

240605

렌스평선이용해서 만듦

게시판

홈 > 게시판

1

제목

검색

총 게시물 2건 | 현재페이지 1/1

번호	제목	작성자	작성일	조회수
2 공지	제목2	문성진	YYYY-MM-DD	1
2	제목2	문성진	YYYY-MM-DD	1
1	3 제목1	문성진	YYYY-MM-DD	0

4

< 1 2 3 4 ... 9 10 >

5 글쓰기

6

번호

제목

작성자

작성일

조회수

검색 데이터가 없습니다.

db


논리

물리

게시판

게시판ID
게시물제목
게시물설명
조회횟수
생성IP
공지여부
공개여부
사용여부
첨부파일ID
최초등록시점
최초등록자ID
최종수정시점
최종수정자ID

BOARD

 BOARD_ID: CHAR(20)
BOARD_SJ: VARCHAR(2000)
BOARD_CN: MEDIUMTEXT
INQUIRE_CO: INTEGER
CREAT_IP: VARCHAR(128)
NOTICE_AT: CHAR(1)
OTHBC_AT: CHAR(1)
USE_AT: CHAR(1)
ATCH_FILE_ID: CHAR(20)
FRST_REGIST_PNTTM: DATETIME
FRST_REGISTER_ID: VARCHAR(100)
LAST_UPDT_PNTTM: DATETIME
LAST_UPDUSR_ID: VARCHAR(20)

- 생성IP등 보이지 않는 정보들도 생성해줘야 한다.
 - IP : 보안때문에 사용. Ddos같은 경우 한 IP로 물밀듯 들어오는데 그럴 때 차단해야 함
 - 사용여부, 최초등록시점, 최종수정시점 등
- IP, 등록자ID 를 같이 사용해서 글 등록하는 이유
 - 같은 IP에서 구분하기 위해서
- 사용여부
 -

db만들기

```
CREATE TABLE BOARD
(
  BOARD_ID          CHAR(20) NOT NULL,
  BOARD_SJ          VARCHAR(2000) NULL,
  BOARD_CN          MEDIUMTEXT NULL,
  INQUIRE_CO       INTEGER NULL,
```

```

CREAT_IP          VARCHAR(30) NULL,
NOTICE_AT         CHAR(1) NULL,
OTHBC_AT         CHAR(1) NULL,
USE_AT           CHAR(1) NULL,
ATCH_FILE_ID     CHAR(20) NULL,
FRST_REGIST_PNTTM DATETIME NULL,
FRST_REGISTER_ID VARCHAR(100) NULL,
LAST_UPDT_PNTTM  DATETIME NULL,
LAST_UPDUSR_ID   VARCHAR(20) NULL
);

```

```

ALTER TABLE BOARD
ADD PRIMARY KEY (BOARD_ID);

```

```

ALTER TABLE BOARD COMMENT = '게시판';

```

```

ALTER TABLE BOARD CHANGE COLUMN BOARD_ID BOARD_ID CHAR(20)
ALTER TABLE BOARD CHANGE COLUMN BOARD_SJ BOARD_SJ VARCHAR(200)
ALTER TABLE BOARD CHANGE COLUMN BOARD_CN BOARD_CN MEDIUMTEXT
ALTER TABLE BOARD CHANGE COLUMN INQUIRE_CO INQUIRE_CO INTEGER
ALTER TABLE BOARD CHANGE COLUMN CREAT_IP CREAT_IP VARCHAR(30)
ALTER TABLE BOARD CHANGE COLUMN NOTICE_AT NOTICE_AT CHAR(1)
ALTER TABLE BOARD CHANGE COLUMN OTHBC_AT OTHBC_AT CHAR(1)
ALTER TABLE BOARD CHANGE COLUMN USE_AT USE_AT CHAR(1) NULL
ALTER TABLE BOARD CHANGE COLUMN ATCH_FILE_ID ATCH_FILE_ID CHAR(20)
ALTER TABLE BOARD CHANGE COLUMN FRST_REGIST_PNTTM FRST_REGIST_PNTTM DATETIME
ALTER TABLE BOARD CHANGE COLUMN FRST_REGISTER_ID FRST_REGISTER_ID VARCHAR(100)
ALTER TABLE BOARD CHANGE COLUMN LAST_UPDT_PNTTM LAST_UPDT_PNTTM DATETIME
ALTER TABLE BOARD CHANGE COLUMN LAST_UPDUSR_ID LAST_UPDUSR_ID VARCHAR(20)

```

db정보넣기

```

INSERT INTO BOARD (
    BOARD_ID
    , BOARD_SJ
    , INQUIRE_CO
    , NOTICE_AT

```

```

, OTHBC_AT
, USE_AT
, FRST_REGIST_PNTTM
, FRST_REGISTER_ID
, LAST_UPDT_PNTTM
, LAST_UPDUSR_ID
) VALUES (
'BOARD_X000000000000001'
, '제목1'
, 0
, 'Y'
, 'Y'
, 'Y'
, NOW()
, 'admin'
, NOW()
, 'admin'
);

```

```

INSERT INTO BOARD (
BOARD_ID
, BOARD_SJ
, INQUIRE_CO
, NOTICE_AT
, OTHBC_AT
, USE_AT
, FRST_REGIST_PNTTM
, FRST_REGISTER_ID
, LAST_UPDT_PNTTM
, LAST_UPDUSR_ID
) VALUES (
'BOARD_X000000000000002'
, '제목2'
, 0
, 'N'
, 'N'
, 'Y'
, NOW()

```

```

, 'admin'
, NOW()
, 'admin'
);

INSERT INTO BOARD (
BOARD_ID
, BOARD_SJ
, INQUIRE_CO
, NOTICE_AT
, OTHBC_AT
, USE_AT
, FRST_REGIST_PNTTM
, FRST_REGISTER_ID
, LAST_UPDT_PNTTM
, LAST_UPDUSR_ID
) VALUES (
'BOARD_X000000000000003'
, '제목3'
, 0
, 'Y'
, 'N'
, 'Y'
, NOW()
, 'admin'
, NOW()
, 'admin'
);

```

ids 생성

```

INSERT INTO ids
(TABLE_NAME, NEXT_ID)
VALUES('BOARD_ID', 1);

```

공지글 쿼리

```

SELECT
    A.BOARD_ID
  , A.BOARD_SJ
  , A.INQUIRE_CO
  , A.NOTICE_AT
  , A.OTHBC_AT
  , A.USE_AT
  , A.FRST_REGIST_PNTTM
  , A.FRST_REGISTER_ID
  , A.LAST_UPDT_PNTTM
  , A.LAST_UPDUSR_ID
FROM BOARD A
WHERE A.USE_AT = 'Y'
      AND A.NOTICE_AT = 'Y'
ORDER BY A.FRST_REGIST_PNTTM DESC;

```

일반글 검색쿼리

```

-- 일반글
SELECT
    A.BOARD_ID
  , A.BOARD_SJ
  , A.INQUIRE_CO
  , A.NOTICE_AT
  , A.OTHBC_AT
  , A.USE_AT
  , A.FRST_REGIST_PNTTM
  , A.FRST_REGISTER_ID
  , A.LAST_UPDT_PNTTM
  , A.LAST_UPDUSR_ID
FROM BOARD A
WHERE A.USE_AT = 'Y'
      -- 제목 AND A.BOARD_SJ LIKE CONCAT('%', '제목', '%')
      -- 게시글 AND A.BOARD_CN LIKE CONCAT('%', '내용', '%')
      AND A.FRST_REGISTER_ID LIKE CONCAT('%', 'admin', '%')
ORDER BY A.FRST_REGIST_PNTTM DESC;

```

context-idgen 추가

```
<!-- BOARD START -->
    <bean name="egovBoardIdGnrService" class="org.egovframe
        <property name="dataSource" ref="egov.dataSource"
        <property name="strategy" ref="boardStrategy" />
        <property name="blockSize" value="10" />
        <property name="table" value="IDS" />
        <property name="tableName" value="BOARD_ID" />
    </bean>

    <bean name="boardStrategy" class="org.egovframe.rte.f
        <property name="prefix" value="BOARD_" />
        <property name="cipers" value="14" />
        <property name="fillChar" value="0" />
    </bean>
<!-- BOARD END -->
```

BoardVO

Board_mysql.xml

BoardDAO















BoardServiceImpl

BoardService










BoardController

BoardSelectList.jsp


src/main/java

```
▼  > homepage2024 [DB connect master]
  ▼  > src/main/java
    ▼  > egovframework
      >  com.cmm
      ▼  > let
        ▼  > board
          ▼  > service
            ▼  > impl
              >  BoardDAO.java
              >  BoardServiceImpl.java
              >  BoardService.java
              >  BoardVO.java
            ▼  > web
              >  BoardController.java
```

src/main/resources

```
▼  > src/main/resources
  >  db
  ▼  > egovframework
    >  egovProps
    ▼  > mapper
      >  config
      ▼  > let
        ▼  > board
          >  board_mysql.xml
```

jsp



footer, header, template 만들기

header

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
<%@ taglib prefix="ui" uri="http://egovframework.gov/ctl/ui" %>
<%@ taglib uri="http://java.sun.com/jsp/jstl/functions" prefix="fn" %>
<%@ taglib prefix="spring" uri="http://www.springframework.org/tags" %>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Language" content="ko">
<meta http-equiv="X-UA-Compatible" content="IE=edge">
<meta name="viewport" content="width=device-width, initial-scale=1">
<title><c:out value="${param.title}" /></title>
<script src="http://code.jquery.com/jquery-latest.min.js"></script>

<!-- BBS Style '0' 12개 -->
<link href="/asset/BBSTMP_00000000000001/style.css" rel="stylesheet">
<!-- 공통 Style '0' 13개 -->
<link href="/asset/LYTTMP_00000000000000/style.css" rel="stylesheet">
<link href="/asset/TYPETMP_02/style.css" rel="stylesheet" />
```

```

</head>
<body>

<header class="site-header">
  <div class="util">
    <div class="wrap">
      <ul>
        <li><a href="/">HOME</a></li>
        <c:choose>
          <c:when test="${empty USER_INFO.id}">
            <li><a href="/uat/uia/egovLoginUsr.do"
            </c:when>
          <c:otherwise>
            <li><strong><c:out value="${USER_INFO"
            <li><a href="/uat/uia/actionLogout.do"
            </c:otherwise>
          </c:choose>
        </ul>
      </div>
    </div>
    <div class="header-cont wrap">
      <nav class="site-gnb">
        <ul>
          <li>
            <a href="/board/selectList.do">게시판</a>
          </li>
        </ul>
      </nav>
    </div>
  </header>

```

footer

```

<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core"

```

```

<%@ taglib prefix="ui" uri="http://egovframework.gov/ctl/ui" %>
<%@ taglib uri="http://java.sun.com/jsp/jstl/functions" prefix="fn" %>
<%@ taglib prefix="spring" uri="http://www.springframework.org/tags" %>

</body>
</html>

```

TemplateController

```

package egovframework.let.template.web;

import java.util.List;

import javax.annotation.Resource;
import javax.servlet.http.HttpServletRequest;

import org.egovframe.rte.fdl.string.EgovStringUtil;
import org.egovframe.rte.psl.dataaccess.util.EgovMap;
import org.springframework.stereotype.Controller;
import org.springframework.ui.ModelMap;
import org.springframework.web.bind.annotation.RequestMapping;

import egovframework.com.cmm.LoginVO;
import egovframework.com.cmm.util.EgovUserDetailsHelper;
import egovframework.let.temp.service.TempService;
import egovframework.let.temp.service.TempVO;

@Controller
public class TemplateController {

    //헤더
    @RequestMapping(value = "/template/header.do")
    public String header(HttpServletRequest request, ModelMap model) {

        LoginVO user = (LoginVO)EgovUserDetailsHelper.getAuthUser(request);
        model.addAttribute("USER_INFO", user);
    }
}

```

```

        return "/template/Header";
    }


    //푸터
    @RequestMapping(value = "/template/footer.do")
    public String footer(HttpServletRequest request, ModelMap

        return "/template/Footer";
    }


}

```

아래 파일 사용



Header.jsp, Footer.jsp



TemplateController

