




YW 1806




PRODUCT SIZE

Width	1100mm
Length	2600/2800/3000mm
Thickness	5mm/8mm/12mm






PRODUCT INFORMATION




Name	Material \ cross-section	Size(mm)	Process	Ep rating	Fire rating	Advantage	Splicing method
WPC wall panel	Crystal like co extruded layer+Bamboo charcoal fiber	Width: 1100 Length: 2800/ Customized length under 6000 Thickness: 5/8	PUR coating/ PUR flat sticker	ENF	B1	Eco-friendly/ Flame retardant/ waterproof/ bendable	Tight splicing/ metal profile connection/ process seam




PRODUCT PERFORMANCE REAL SHOT




MORE EMBOSSING COLORS




INTERNATIONAL CERTIFICATION





Environmental Test Report



EU Highly Concerned Substance Report





Flame Retardant Test Report



Formaldehyde Test Report

Eu Safety Certification

FACTORY STRENGTH





Mature Technology

- 1. Standardized, automated technology design
- 2. Real-time monitoring
- 3. PLC online control
- 4. 60 analysis

Equipment Operation

- 1. Famous brands, professional maintenance
- 2. Cutting, edge banding and other links have realized one-stop automatic production and real-time monitoring




Producing Workshops

Six major producing workshops. The fourth workshop is a larger intelligent production among the peers.
20 intelligent production lines


Environment

Keep executing 5S and lean production.
OHSAS18001, ISO14001, ISO9001

PACKING METHOD



Dimension	Cubic Capacity	Tare Weight	Payload
L : 5.89 m 19'4" W : 2.35 m 7'9" H : 2.39 m 7'10"	33.2 m³ 1,170 f³	2,220 kg 4,894 lb	21,850 kg 48,171 lb



20正常装货货柜尺寸

Dimension	Cubic Capacity	Tare Weight	Payload
L : 12.03 m 39'6" W : 2.35 m 7'9" H : 2.39 m 7'10"	67.7 m³ 2,391 f³	3,740 kg 8,245 lb	26,760 kg 58,996 lb

40正常装货货柜尺寸