


- SOLID COLOR -

3081

COLOR NUMBER









PRODUCT INFORMATION




Name	Material \ cross-section	Size(mm)	Process	Ep rating	Fire rating	Advantage	Splicing method
WPC wall panel	Crystal like co extruded layer+Bamboo charcoal fiber	Width: 1100 Length: 2800/ Customized length under 6000 Thickness: 5/8	PUR coating/ PUR flat sticker	ENF	B1	Eco-friendly/ Flame retardant/ waterproof/ bendable	Tight splicing/ metal profile connection/ process seam



PRODUCT PERFORMANCE REAL SHOT




MORE SOLID COLORS



INTERNATIONAL CERTIFICATION




FACTORY STRENGTH



Mature Technology

1. Standardized, automated technology design
2. Real-time monitoring
3. PLC online control
4. 60 analysis



Equipment Operation


1. Famous brands, professional maintenance
2. Cutting, edge banding and other links have realized one-stop automatic production and real-time monitoring



Producing Workshops

Six major producing workshops. The fourth workshop is a larger intelligent production among the peers.

20 intelligent production lines




Environment

Keep executing 5S and lean production.

OHSAS18001, ISO14001, ISO9001

PACKING METHOD



20正常装货货柜尺寸

40正常装货货柜尺寸