

KA 57502




PRODUCT SIZE

Width	1100mm
Length	2600/2800/3000mm
Thickness	5mm/8mm/12mm



WPC WALL PANEL
KA 57502




WPC WALL PANEL
KA 57502




WPC WALL PANEL
KA 57502

PRODUCT INFORMATION



Name	Material \ cross-section	Size(mm)	Process	Ep rating	Fire rating	Advantage	Splicing method
WPC wall panel	Crystal like co extruded layer+Bamboo charcoal fiber	Width: 1100 Length: 2800/ Customized length under 4000 Thickness: 5/8	PUR coating/ PUR flat sticker	ENF	B1	Eco-friendly/ Flame retardant/ waterproof/ bendable	Tight splicing/ metal profile connection/ process seam


PRODUCT PERFORMANCE REAL SHOT



Waterproof test



Bend forward



Bend backwards



EP LEVEL



FIRE RATING



WATERPROOF




BENDABLE

MORE STONE GRAIN COLORS



INTERNATIONAL CERTIFICATION



Environmental Test Report

Reach


EU Highly Concerned Substance Report

Flame Retardant Test Report

Formaldehyde Test Report


Eu Safety Certification

FACTORY STRENGTH




Mature Technology

1. Standardized, automated technology design
2. Real-time monitoring
3. PLC online control
4. 60 analysis



Equipment Operation

1. Famous brands, professional maintenance
2. Cutting-edge banding and other links have realized one-stop automatic production and real-time monitoring



Producing Workshops


Six major producing workshops. The fourth workshop is a larger intelligent production among the peers.
20 intelligent production lines



Environment

Keep executing 5S and lean production.
OHSAS18001, ISO14001, ISO9001

PACKING METHOD



20'正常装货货柜尺寸

40'正常装货货柜尺寸