



CLOTH GRAIN


6003
COLOR NUMBER




WPC WALL PANEL
6003



WPC WALL PANEL
6003




WPC WALL PANEL
6003




WPC WALL PANEL
6003

PRODUCT INFORMATION




Name	Material \ cross-section	Size(mm)	Process	Ep rating	Fire rating	Advantage	Splicing method
WPC wall panel	Crystal like co extruded layer-Bamboo charcoal fiber	Width: 1100 Length: 2800/ Customized length under 6000 Thickness: 5/8	PUR coating/ PUR flat sticker	ENF	B1	Eco-friendly/ Flame retardant/ waterproof/ bendable	Tight splicing/ metal profile connection/ process seam


PRODUCT PERFORMANCE REAL SHOT




Waterproof test




Bend forward




Bend backwards




EP LEVEL



FIRE RATING







WATERPROOF




BENDABLE


MORE CLOTH GRAIN COLORS




INTERNATIONAL CERTIFICATION




Environmental Test Report




EU Highly Concerned Substance Report



Flame Retardant Test Report




Formaldehyde Test Report




Eu Safety Certification

FACTORY STRENGTH




Mature Technology

1. Standardized, automated technology design
2. Real-time monitoring
3. PLC online control
4. 6.0 analysis




Equipment Operation

1. Famous brands, professional maintenance
2. Cutting, edge banding and other links have realized one-stop automatic production and real-time monitoring



Producing Workshops

Six major producing workshops. The fourth workshop is a larger intelligent production among the peers.
20 intelligent production lines




Environment

Keep executing 5S and lean production.
OHSAS18001, ISO14001, ISO9001

PACKING METHOD

20' STD	Dimension	Cubic Capacity	Tare Weight	Payload
	L : 5.89 m 19'4"			
	W : 2.35 m 7'9"	33.2 m³	2,220 kg	21,850 kg
	H : 2.39 m 7'10"	1,170 f³	4,894 lb	48,171 lb



20正常装货货柜尺寸

40' STD	Dimension	Cubic Capacity	Tare Weight	Payload
	L : 12.03 m 39'6"			
	W : 2.35 m 7'9"	67.7 m³	3,740 kg	26,760 kg
	H : 2.39 m 7'10"	2,391 f³	8,245 lb	58,996 lb



40正常装货货柜尺寸