



51005



PRODUCT SIZE

Width	1100mm
Length	2600/2800/3000mm
Thickness	5mm/8mm/12mm




PRODUCT INFORMATION



Name	Material \ cross-section	Size(mm)	Process	Ep rating	Fire rating	Advantage	Splicing method
WPC wall panel	Crystal like co extruded layer+Bamboo charcoal fiber	Width: 1100 Length: 2800/ Customized length under 6000 Thickness: 5/8	PUR coating/ PUR flat sticker	ENF	B1	Eco-friendly/ Flame retardant/ waterproof/ bendable	Tight splicing/ metal profile connection/ process seam

PRODUCT PERFORMANCE REAL SHOT



ENF

EP LEVEL

B1

FIRE RATING




WATERPROOF




BENDABLE


INTERNATIONAL CERTIFICATION




Environmental Test Report




EU Highly Concerned Substance Report



Flame Retardant Test Report




Formaldehyde Test Report




Eu Safety Certification

MORE METAL SERIES COLORS




FACTORY STRENGTH




Mature Technology

- 1. Standardized, automated technology design
- 2. Real-time monitoring
- 3. PLC online control
- 4. 60 analysis




Equipment Operation

- 1. Famous brands, professional maintenance
- 2. Cutting, edge banding and other links have realized one-stop automatic production and real-time monitoring



Producing Workshops


Six major producing workshops. The fourth workshop is a larger intelligent production among the peers.  
20 intelligent production lines




Environment

Keep executing 5S and lean production.  
OHSAS18001, ISO14001, ISO9001

PACKING METHOD



20正常装货货柜尺寸



40正常装货货柜尺寸