STA 35C: Statistical Data Science III

Lecture 7: Assessing Model Accuracy

Dogyoon Song

Spring 2025, UC Davis

Agenda

Quick review: The regression framework

Assessing a regression model:

- Training & test MSE
- The bias-variance tradeoff

Hints on Homework 1

Recap: Regression

Regression = Supervised learning with a quantitative response Y

- Given data $(x_1, y_1), \ldots, (x_n, y_n)$, we estimate f so that $Y \approx f(X)$
- Prediction: For x_{new} , predict $\hat{y}_{\text{new}} = \hat{f}(x_{\text{new}})$
- ullet Inference: Learn relationships among X and Y

(Simple) linear regression:

- Assume $f(X) = \beta_0 + \beta_1 X$; estimate β_0, β_1 by least squares
- Assessment:
 - Prediction fit: RSS or $R^2 = 1 \frac{RSS}{TSS}$
 - Inference: confidence intervals, hypothesis tests via RSE
- Extensions: multiple predictors, nonlinear terms, qualitative predictors
- Pitfalls: invalid linear model assumptions, outliers/high-leverage points, collinearity

Today's focus: We've learned to build regression models; let's see how to evaluate them

Mean squared error (MSE)

Motivation: Given a model \hat{f} , we need a metric to gauge how well \hat{f} predicts Y

Why?

- To evaluate the current model's accuracy
- To select among multiple candidate models

Mean squared error (MSE):

MSE =
$$\frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{f}(x_i))^2$$

In linear regression, MSE corresponds to the residual sum of squares (RSS)

• Minimizing MSE ⇔ minimizing RSS (least squares)

Training MSE vs. test MSE

Training MSE uses the same data that built the model:

$$MSE_{train} = \frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{f}(x_i))^2$$

However, we truly care about future performance on unseen test data

• Hypothetically, if we had a set of *new* test points $(x_j^{\text{test}}, y_j^{\text{test}})$:

$$ext{MSE}_{ ext{test}} = rac{1}{n_{ ext{test}}} \sum_{j=1}^{n_{ ext{test}}} (y_j^{ ext{test}} - \hat{f}(x_j^{ ext{test}}))^2.$$

Ideally, we might want to learn a model by minimizing test MSE directly, but...

The challenge in practice

Reality: We usually do not have a separate test set

- Minimizing test MSE is impossible
- Thus, we typically end up minimizing training MSE instead

However, low training MSE \Rightarrow low test MSE




Figure: As model flexibility grows, training MSE usually decreases, but test MSE can increase [JWHT21, Figure 2.9]

The bias-variance tradeoff

Question: Why does the U-shape in test error occur?

The expected¹ test MSE can be decomposed into Bias² + Variance + Irreducible Error

$$\begin{split} \mathbb{E}(y_{\mathsf{new}} - \hat{f}(x_{\mathsf{new}}))^2 &= \left(\mathbb{E}[\hat{f}(x_{\mathsf{new}})] - f(x_{\mathsf{new}})\right)^2 + \mathbb{E}\left[\left(\hat{f}(x_{\mathsf{new}}) - \mathbb{E}[\hat{f}(x_{\mathsf{new}})]\right)^2\right] + \mathrm{Var}(\epsilon) \\ &= \underbrace{\mathrm{Bias}^2(\hat{f}(x_{\mathsf{new}}))}_{\mathsf{model\ mismatch}} + \underbrace{\mathrm{Var}(\hat{f}(x_{\mathsf{new}}))}_{\mathsf{sensitivity\ to\ data}} + \underbrace{\mathrm{Var}(\epsilon)}_{\mathsf{irreducible}} \end{split}$$

As model flexibility increases:

- Bias tends to decrease
- Variance tends to increase

Takeaway: An optimal model should balance bias and variance for the lowest test error

 $^{^1 \}text{The expectation}$ is over random sampling of the training data and noise ϵ

Interpreting bias and variance

Bias:

- Systematic error due to an overly simplistic model class
- Example: A linear model used when the true f is highly nonlinear

Variance:

- ullet How much \hat{f} would fluctuate given a different training sample
- Complex and flexible models can vary greatly from one sample to another

Sweet spot:

- Balanced complexity—neither too simple nor too complex
- Techniques like cross-validation (future lecture) can help find it

Summary of the bias-variance tradeoff




Figure: Illustrations of bias-variance in different settings [JWHT21, Figures 2.10 & 2.11].

Bottom line:

- Overly simple models \Rightarrow high bias, low variance
- ullet Overly complex models \Rightarrow low bias, high variance
- Optimal model complexity finds a sweet spot balancing both
- This idea applies broadly to many supervised learning methods

Wrap-up

Summary of today's lecture:

- Assessing regression model accuracy via MSE
- Training vs. test MSE
- The bias-variance tradeoff

Recap of regression:

- Regression problem; setup and the objectives
- Linear regression
 - Model & interpretation of regression coefficients
 - Parameter estimation & inference
 - Assessing model fit using RSS and R^2
 - Extensions: multiple predictors, nonlinear terms, qualitative predictors
- Model assessment: importance of test performance, and the bias-variance tradeoff

Next lecture: Classification

Homework 1: What each problem is asking

Problem 1: Probability basics

- Recognizing that probabilities lie in [0,1] and sum to 1
- Visualizing a distribution
- Computing expectation and variance

Problem 2: Bayes' theorem and basic learning

- Estimating p_{true} from coin flips via Bayes' theorem
- Treating our "guess" as a random variable and updating its assigned probabilities using data
- ullet Understanding how learning occurs and its sensitivity to $p_{
 m true}$ and the initial guess

Problem 3: Simple linear regression

- Confirming the formula for least squares estimates
- Practicing basic computations on a simple dataset
- Running linear regression in R to see it in action

Problem 4: Model assessment

- Comparing training vs. test error as model complexity changes
- Exploring the bias-variance tradeoff and its subtle nuances

References



Gareth James, Daniela Witten, Trevor Hastie, and Robert Tibshirani.

An Introduction to Statistical Learning: with Applications in R, volume 112 of Springer Texts in Statistics.

Springer, New York, NY, 2nd edition, 2021.