



EMBEDDED SYSTEM COURSE

LECTURE 11: FREESCALE MQX RTOS TIMER

Learning Goals



- Understanding on how the MQX maintain the timing feature.
- Introduce about the MQX Timer component.
- Introduce about the MQX software Watchdog component.

2

- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ Watchdog
- ❖ Timer Exercise

Table of contents



- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ Watchdog
- ❖ Timer Exercise

Table of contents



❖ MQX Timing features

- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ Watchdog
- ❖ Timer Exercise

MQX Timing



- MQX Time used for:
 - Round-robin scheduling
 - Timeouts for MQX function calls (msg_rcv, etc)
 - Suspension of tasks for a specified amount of time (time_delay)
 - Time and date
- Can represent time in:
 - seconds/milliseconds
 - Date
 - extended date
 - Ticks
- Presenting in seconds or date is more CPU intensive

5

Time_delay not exact, just guarantee the minimum amount of delay. Ie if say delay 7ms, will delay for 10ms since tha'ts smaller than BSP resolution

MQX Timing



- Time is enabled at BSP level
 - Can describe absolute time or relative time
- Resolution depends on hardware and app settings
 - Uses 64-bit counter to count the number of tick interrupts since bootup (using PIT)
 - Then also returns at 32-bit number that represents the hardware ticks (PIT timer value) since the last tick for increased accuracy
- Resolution set during hardware config
 - Normally 200 ticks/second -> 5ms

6

Draw how this works on a board

Table of contents



- ❖ MQX Timing features
- ❖ **Deep look at how kernel handles time**
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ Watchdog
- ❖ Timer Exercise

Kernel Details



- Timer set up in `bsp_enable_card()` (located in `\mqx\source\bsp\<board>\init_bsp.c`)
 - PIT0 is used for KL46
 - The PIT module is configured in the function `_<board>_timer_init_freq` located in `mqx\source\io\timer\timer_<board>.c`
- The timer interrupt (`_bsp_timer_isr`) is also in `init_bsp.c`,
 - Clears PIT interrupt and then calls `_time_notify_kernel`
- `_time_notify_kernel` is found in `\mqx\kernel\ti_krn.c`
 - Increments counter
 - Checks timeout queue (used by `msg_recieve`, `sem_wait`, or `time_delay` for example)
 - Checks timesliced tasks to see if need to put at end of ready queue
 - Checks timer and light weight timers

8

And remember because an interrupt happened, it will re-look at the scheduling options, so if a higher priority task is found to be in the ready queue now, then it will run instead

Table of contents



- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ **Absolute versus Relative Time**
- ❖ Timer Component
- ❖ Watchdog
- ❖ Timer Exercise

Absolute versus Elapsed Time



- Initially, absolute time is the time since the reference date of 0:00:00.000 January 1, 1970.
- Unless an application changes the absolute time, the following pairs of functions return the same values:
 - `_time_get()` and `_time_get_elapsed()`
 - `_time_get_ticks()` and `_time_get_elapsed_ticks()`
- But because the absolute time could be updated, elapsed time should always be used to measure an interval

10

Many ways to see the time and many time functions. See MQXUG or MQXRM for the details

Table of contents



- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ **Timer Component**
- ❖ Watchdog
- ❖ Timer Exercise

Types of timers



- Light Weight timers are used for calling functions at periodic intervals
 - It creates a periodic queue
 - The function runs in an ISR, not blocking MQX calls not allowed
- Normal timers can do:
 - One shot
 - Start at specific time
 - Start after specific duration
 - Also allowed to send messages, set events, and do other synchronization
- Also have a watchdog time available to detect task starvation or deadlock
- All of these are optional

Normal Timer



- Creates a timer task
- When a timer expires, it causes a notification function to run
 - Notification function should not block or allocate resources
 - Kind of like an ISR
 - Runs at priority of the timer task, set when the timer was created, not the task that created that timer task
- A task can start a timer at a specific time or at some specific time after the current time. Timers can use elapsed time or absolute time.
- There are two types of timers:
 - One-shot timers, which expire once.
 - Periodic timers, which expire repeatedly at a specified interval. When a periodic timer expires, MQX resets the timer.

13

See MQXUG and MQXRM for API details

Lightweight Timers



- Provide periodic notification
- A task can create a periodic queue and add timers to it. The timers expire at the same rate as the queue's period, but offset from the period's expiry time.
- Only a data structure instead of a task

Table of contents



- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ **Watchdog**
- ❖ Timer Exercise

Watchdog



- Similar to hardware watchdog, but at a task layer
- If watchdog expires, then system-wide user-provided function is called, that is passed the task that was deadlocked
- Create and start the watchdog that has a specified timeout inside the task you want to watch
 - Then task needs to call `watchdog_start(time)` or `watchdog_stop` again within that time limit, or else the expiry function is called
- Can be used to make sure task is running in a quick enough time

Table of contents



- ❖ MQX Timing features
- ❖ Deep look at how kernel handles time
- ❖ Absolute versus Relative Time
- ❖ Timer Component
- ❖ Watchdog
- ❖ **Timer Exercise**

Timer Exercise



- ❖ Using timer to implement a counter, display a counter value on LCD

Summary



- Understanding about the MQX Timer Features and its components
- Have brief introduction on how the MQX Kernel handle the timer

Question & Answer



Thanks for your attention !

Copyright



- This course including **Lecture Presentations, Quiz, Mock Project, Syllabus, Assignments, Answers** are copyright by FPT Software Corporation.
- This course also uses some information from external sources and non-confidential training document from Freescale, those materials comply with the original source licenses.