Core C-TOP PORTAL

API Integration Documentation
Document Version 02.0

Confidential

Core Communication Retail Limited Company Confidential

Index

Document Summary	3
Revision History	3
API Overview	4
BASE URL	6
Generate a Token	9
Token Generation API	13
Network List API	14
Network SKU API	17
Transaction API	18
Callback URL	22
Frequently Asked Questions (FAQ's)	24
CORE - eSIM API Documentation	27
BASE URLs	27
Authtoken Creation	27
Get Bearer Token	28
Get Destinations	29
Get Package	34
Apply Package	36

Confidential

Fetch eSIM Detail	40
Error Code	42

Revision History

Version No.	Summary of Change
2.0	Parameters label change in the Token API

Document Summary

The main objective of this document is to empower business users with the ability to effectively configure the Core API. By providing detailed instructions, guidelines, and examples, this document aims to enable business users to customize and tailor the Interface according to their specific requirements and preferences.

Efficient configuration of the Core API is crucial for businesses as it allows them to optimize the functionality and performance of the API to align with their unique business processes and objectives.

This document serves as a comprehensive resource that equips business users with the knowledge and tools needed to make the necessary configurations.

Through clear and concise explanations, step-by-step instructions, and illustrative examples, the document ensures that business users can easily understand and implement the configuration options available to them.

It covers various aspects of the Core API configuration, such as authentication settings, data formatting, integration with existing systems, and other relevant parameters.

Confidential

API Overview

1. **Token Generation API (Authentication API) :** The Token Generation API, also known as the Authentication API, plays a critical role in the generation of tokens. Its primary function is to securely generate and provide authentication tokens that can be used for various purposes within an application or system.

   With the Token Generation API, developers and system administrators can seamlessly integrate token-based authentication into their applications. This API enables the generation of unique tokens that serve as credentials for users, granting them access to protected resources or performing specific actions within the system.

2. **Transaction API :** The Top Up Transactions API serves as a crucial component for managing and processing top-up transactions within an application or system. Its primary purpose is to facilitate the seamless and efficient execution of top-up transactions.

   The Top-Up Transaction API is designed to allow for the integration of top-up functionality into existing systems.
   The API provides a set of endpoints that enable users to initiate top-up transactions with network operators.

   When a user initiates a top-up transaction through the API, the API validates the request, authenticates the user, and processes the payment through the operator's system.

Confidential

Once the payment is processed, the API returns a response indicating the success or failure of the transaction.

3. **Call Back URL (to be provided by API user) :** The Call Back URL, which is to be provided by the API user, serves as a crucial element in the transaction update process. By integrating this functionality into their applications, API users can receive real-time updates on the status of their transactions, ensuring prompt notifications in both successful and failed scenarios.

   When utilizing the API for transaction updates, API users have the opportunity to specify a Call Back URL. This URL acts as a designated endpoint within their application where transaction update notifications will be sent.

   In the event of a successful transaction, the API will automatically trigger a notification to the provided Callback URL. This notification contains essential details, such as transaction IDs, timestamps, and any other pertinent information related to the successful completion of the transaction. By receiving these updates in real-time, API users can promptly process and acknowledge the success of the transaction within their application, providing a seamless user experience.

   Similarly, in the case of a failed transaction, the API will trigger a notification to the specified Callback URL, conveying the relevant information about the failure. This notification can include error codes, error messages, or any other details that can assist API users in understanding the cause of the failure. By promptly receiving this information, API users can take appropriate actions within their application to address the issue and provide necessary support to their users.

   By leveraging the Call Back URL functionality, API users can ensure that they are continuously informed about the progress and outcomes of their transactions. This real-time notification system fosters transparency and enables API users to effectively manage and respond to transaction updates.

   In summary, the Call Back URL is a critical component in the transaction update process. By providing this URL, API users can receive real-time

notifications on the status of their transactions, both in successful and failed scenarios. These notifications empower API users to promptly update their application, ensuring a seamless user experience and efficient transaction management.

BASE URL

1	UAT Environment	https://ctop-api.Core-retail.com/api/uat
2	Production Environment	https://ctop-api.Core-retail.com/api/v1

OAuth v2.0

Core UK mandates utilizing OAuth v2.0 as the authentication mechanism when accessing the Core's JSON RPC API. OAuth2 is available across all environments, ensuring consistent and secure authentication for API integration.

For detailed information on server endpoint URLs, please refer to the provided documentation.

To authenticate via OAuth, the following steps need to be followed:

1. **Create a Client:** Begin by creating a client application within the OAuth framework. This involves registering your application with the Core system and obtaining client credentials, such as a client ID and client secret. These credentials will be used in subsequent steps for authentication purposes.

2. **Generate a Token:** Once you have the client credentials, the next step is to generate an authentication token. This token serves as proof of authorization

and allows access to the Core JSON RPC API. To generate a token, your application needs to make a token request to the OAuth server, providing the client credentials. The server will verify the credentials and, upon successful authentication, issue an access token that can be used for subsequent API requests.

3. **Make Authenticated Requests:** With the access token obtained in the previous step, you can include it in the authorization header of your API requests to the Core JSON RPC API. This ensures that each request is properly authenticated and authorized. The Core system will validate the access token before processing the request, granting access only to authorized and authenticated clients.

   By following this OAuth-based authentication flow, users can securely access the Core JSON RPC API, ensuring that only authorized clients can interact with the system. This authentication process provides a layer of protection and enhances the overall security of your API integration.

Confidential

Create a Client

Core will create a dedicated API user or OAuth client will be created specifically for your application. This user/client will be configured with the necessary privileges and allocations based on the contractual agreements and requirements established with the partner on Core's API Gateway.

It's important to note that this setup is a one-time operation, ensuring a streamlined and secure integration between your application and Core's API ecosystem. The API user or OAuth client will be uniquely assigned to your application, providing exclusive access to the authorized resources and functionalities outlined in the contractual agreements.

Upon the completion of this setup, you will be provided with a Client Email ID and an API Token. These credentials are essential for authenticating and authorizing your application when making API requests to Core's services. It is crucial to securely store and safeguard this information, as it will be required for subsequent steps in the integration process.

The Client Email ID serves as a unique identifier for your application within Core's API ecosystem. It helps distinguish and associate API requests originating from your application.

The API Token is a secure authentication mechanism that verifies the identity of your application and grants access to the authorized resources and functionalities. This token will be included in the API requests to Core's services, ensuring secure and authorized communication.

Confidential

Please make sure to keep the Client Email ID and API Token in a safe and accessible location, as they will be necessary for further steps in the integration process.

Generate a Token

Once you have successfully been added up as a client within the Core system, the next step is to obtain a bearer token by making a call to the **Token URL**. This operation requires the following parameters to be included in the request:

client_email: This parameter will contain the registered email address of the API user. It is important to note that the API user must use their registered email address for authentication purposes. Providing any other email address will result in authentication failure. By using the registered email address, the Core system can verify the identity and authorization of the API user.

API_token: The API token required for this operation can be found within the API Panel. This token serves as a unique and secure authentication credential specific to your client. It is typically displayed in the API Panel, allowing you to retrieve it for use in the authentication process. Ensure that you accurately copy the API token as any discrepancies may lead to authentication errors.

When making the request to the Token URL with the specified parameters, the Core system will validate the client_email and API_token provided. If the credentials match the registered information and are valid, the system will generate a bearer token.

The bearer token serves as a temporary access credential that authorizes your application to interact with the Core API on behalf of the authenticated API user. It should be securely stored and included in the Authorization header of subsequent API requests, ensuring that your requests are properly authenticated and authorized.

By following these steps and providing the correct client_email and API_token parameters, you can obtain the necessary bearer token to access and utilize the Core API endpoints securely and effectively.

Make Authenticated Requests

To authenticate subsequent API requests and ensure secure communication with the Core API, it is essential to include a valid bearer token in the HTTP header of your requests. The bearer token serves as proof of authentication and authorization, granting access to the protected resources. The following format should be used in the HTTP header:

Authorization: Bearer {bearer_token}

Replace {bearer_token} with the actual bearer token obtained during the authentication process. By including this header in your API requests, you inform the Core system that you have been successfully authenticated and authorized to access the requested resources.

It's important to note that the bearer token should be kept confidential and securely stored. Any unauthorized access to the bearer token could lead to unauthorized access to your account and data.

Additionally, it's worth mentioning that if a user is deactivated in the Core system, all OAuth clients associated with that user will also be automatically deactivated. This ensures that deactivated users and their associated OAuth clients cannot continue to access the API or any other protected resources. It is a security measure to prevent unauthorized access and maintain the integrity of the system.

Confidential

By following these guidelines and including the valid bearer token in the Authorization header of your API requests, you can ensure that your subsequent requests are properly authenticated and authorized, allowing you to securely interact with the Core API and access the designated resources.

Scope:

There are 5 services exposed to API Retailers from Core API Integration:

1. Token Generation API: The Token Generation API enables API Retailers to generate tokens required for authentication and authorization purposes. This API is accessed through a POST method service, where partners must include an authentication token in the request for successful execution.
2. Network List API: The Network List API allows API Retailers to retrieve the list of supported networks along with the delivery methods available for each network.
3. Network SKU API: The Network SKU API allows API Retailers to retrieve the available top-up offers (SKUs) for a given network and delivery method.
4. Transaction API: The Transaction API allows API Retailers to perform transaction-related operations.
5. Call Back URL: The Call Back URL service enables API Retailers to receive transaction updates and notifications in real-time.

Query services (2,3,5) are exposed as GET method services with query parameters andother services (1,4) are exposed as POST method services with authentication token.

Confidential

If Authentication fails or gateway rejects the requests then "Other HTTP Codes" are returned in response (depending up on the error) without any response payload.

If service is executed then responses mentioned in the "Response" section are returned depending on success (HTTP Code 200 OK)/failure (HTTP Code 500) of service. If service is error then "Service Error Codes" are returned in ResponseBody (Header/Status/Code, Header/Status/Description).

1. **Token Generation API:**

A.) UAT Environment: BASEURL/token
B.) Production Environment: BASEURL/token

Post Parameter:

email : API User Registered email ID.

password : API User's Password

Response:

```
{
```

```
    "success": true/false,
    "data": {
      "name": "NAME",
      "token": "Bearer_TOKEN"
    },
    "message": "MESSAGE"
}
```

2. Network List API:

A.) UAT Environment: BASEURL/networklist
B.) Production Environment: BASEURL/networklist

Method:

GET (query string)

Header:

Authorization: Bearer {bearer_token}

Query Parameters:

None

Description:

This service returns the list of supported networks along with the delivery methods (Voucher, Direct, Bundle) available for each network, the operator image URL, and the top-up help instructions for each network.

Response:

```
{
   "success": true,
   "code": "200",
   "status": 2,
```

```
  "message": "Network List",
  "data": [
    {
      "name": "THREE",
      "op_code": "3NETWORK",
      "op_image": "https://topup.core-retail.com/uploads/operators/three311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 1,
      "direct_code": "Direct",
      "bundle": 1,
      "bundle_code": "Bundle",
      "help": "To top up call 444 and enter Voucher PIN number or Top-Up online at
THREE.CO.UK/Topup. Quesries ? Call 333"
    },
    {
      "name": "Vodafone",
      "op_code": "VOD",
      "op_image": "https://topup.core-retail.com/uploads/operators/voda311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 1,
      "direct_code": "Direct",
      "bundle": 1,
      "bundle_code": "Bundle",
      "help": "Top up over the phone on 2345 free from your Vodafone Pay as you go mobile."
    },
    {
      "name": "O2",
      "op_code": "O2",
      "op_image": "https://topup.core-retail.com/uploads/operators/o2311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 1,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Dial 4444 free from your mobile, or 08456 062 277 from a landline, enter the
number on your receipt and follow the instructions"
    },
    {
      "name": "EE",
      "op_code": "EE",
      "op_image": "https://topup.core-retail.com/uploads/operators/ee311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 1,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Text 150 with VO then a space and then the 16-digit voucher number or call 150
from your EE phone and follow the instructions"
```

```
    },
    {
      "name": "Lyca",
      "op_code": "Lyca",
      "op_image": "https://topup.core-retail.com/uploads/operators/lyca311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 0,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Text *131* on the mobile number where you want to top up, enter the code with # and press the send option or call 321 or #92 on the mobile and follow the instruction by the lycamobile care customer center, enter the code with #."
    },
    {
      "name": "Lebara",
      "op_code": "LEB",
      "op_image": "https://topup.core-retail.com/uploads/operators/lebara311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 0,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Dial *#1345* and enter voucher number, followed by # then press the call button. You can also top-up via the MyLebara app"
    },
    {
      "name": "giffgaff",
      "op_code": "GG",
      "op_image": "https://topup.core-retail.com/uploads/operators/giffgaff311x311.svg",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 0,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Call 43430 to top up your balance or go to giffgaff.com"
    },
    {
      "name": "VOXI",
      "op_code": "VOXI",
      "op_image": "https://topup.core-retail.com/uploads/operators/voxi.png",
      "voucher": 1,
      "voucher_code": "Voucher",
      "direct": 0,
      "direct_code": "Direct",
      "bundle": 0,
      "bundle_code": "Bundle",
      "help": "Thanks for buying a VOXI SIM with a prepaid voucher. Terms apply. This voucher is valid for a new VOXI customer for 1st time purchase. Activate: VOXI.co.uk/voucher. Expires 12 months from date of purchase."
```

```
      }
    ]
}
```

3. Network SKU API:

A.) UAT Environment: BASEURL/networksku?opcode=O2&type_txn=Voucher
B.) Production Environment: BASEURL/networksku?opcode=O2&type_txn=Voucher

Method:

GET (query string)

Header:

Authorization: Bearer {bearer_token}

Query Parameters:

Parameter	Data Type	Description	Mandatory/Optional
opcode	varchar(10)	Refer appendix A	M
type_txn	varchar(10)	Refer appendix B	M

Description:

This service returns the list of available top-up offers (SKUs) for the given network and delivery method.

Response:


```
{
   "success": true,
   "code": "200",
   "status": 2,
   "message": "Offer List",
   "data": [
      {
         "value": 10,
         "now_data": null,
         "text": "Unlimited",
         "calls": "Unlimited",
         "day": "30"
      },
      {
         "value": 15,
         "now_data": null,
         "text": "Unlimited",
         "calls": "Unlimited",
         "day": "30"
```

```
      },
      {
        "value": 20,
        "now_data": null,
        "text": "Unlimited",
        "calls": "Unlimited",
        "day": "30"
      },
      {
        "value": 25,
        "now_data": null,
        "text": "Unlimited",
        "calls": "Unlimited",
        "day": "30"
      },
      {
        "value": 30,
        "now_data": null,
        "text": "Unlimited",
        "calls": "Unlimited",
        "day": "30"
      },
      {
        "value": 35,
        "now_data": null,
        "text": "Unlimited",
        "calls": "Unlimited",
        "day": "30"
      },
      {
        "value": 50,
        "now_data": null,
        "text": "Unlimited",
        "calls": "Unlimited",
        "day": "30"
      }
    ]
}
```


4. Transaction API:

A.) UAT Environment: BASEURL/uat–transaction
B.) Production Environment: BASEURL/transaction

Post Parameter:

Parameter	Data Type	Description	Mandatory/Optional
mobile	Bigint (12)– for Three Network Bigint (11)– for other Network	Top up Mobile number (MSISDN)	M
opcode	varchar(10)	Refer appendix A	M
amount	double	Top up amount	M

type_txn	varchar(10)	Refer appendix B	M
ref_txn_id	varchar(20)	API user reference ID (length must be greater than 8 and less than 20)	M

Confidential

Response :

1. **Success Response -**


```
{
  "success": true,
  "status": 1,
  "message": "Transaction successfully completed.",
  "transaction_id": "Core_TRANSACTIONID",
  "date": "09:24:56 AM, June 23 2023"
}
```

2. **Processing Response -**


```
{
  "success": true,
  "status": 0,
  "message": "Transaction Will Complete When SIM is Active.",
  "transaction_id": "Core_TRANSACTIONID",
  "date": "09:29:25 AM, June 23 2023"
}
```


3. **Failed Response -**


```
{
  "success": false,
  "status": 2,
  "message": "Mobile number must be 12 digit and start with country Code!!"
}
```

Status Code	Description
0	Processing
1	Success
2	Failed

Confidential

5. Callback URL:

URL –

Callback URL to be provided by API user (API user should set up callback url in API panel).

Method –

GET(query string)

Parameters –

- **transaction_id**
- **status**

- **ref_txn_id**

Status Code	Description
0	Processing
1	Success
2	Failed

APPENDIX A - (Network list)

Network Name	Opcode
THREE	3NETWORK
Vodafone	VOD
O2	O2
EE	EE
Lyca	LY
Lebara	LEB
giffgaff	GG

APPENDIX B - (Delivery Method)

Delivery Method	type_txn
Voucher	Voucher
Direct	Direct
Bundle	Bundle

Confidential

Frequently Asked Questions (FAQ's):

1. What are the APIs mentioned in the document?

The document mentions the Token Generation API (Authentication API), Transaction API, and Call Back URL API as the main APIs provided by Core.

2. What is the purpose of the Token Generation API?

The Token Generation API securely generates and provides authentication tokens that can be used for various purposes within an application or system.

3. What is the Transaction API used for?

The Transaction API facilitates the seamless and efficient execution of top-up transactions within an application or system.

4. **How does the Call Back URL API benefit API users?**

   The Call Back URL API allows API users to receive real-time updates on the status of their transactions, ensuring prompt notifications in both successful and failed scenarios.

5. **What is the BASE URL for accessing the Core API in different environments?**

   The BASE URL for the UAT (testing) environment is "https://ctop-api.Core-retail.com/api/uat," and for the production environment, it is "https://ctop-api.Core-retail.com/api/v1."

6. **How can a client be created for OAuth authentication?**

   Core creates a dedicated API user or OAuth client specifically for the application, and the client credentials are provided to the user for authentication.

7. **What is the purpose of the bearer token in OAuth authentication?**

   The bearer token serves as proof of authentication and authorization, granting access to the Core JSON RPC API for subsequent requests.

8. **What services are exposed to API Retailers from the Core API Integration?**

   The services exposed to API Retailers are Token Generation API, Transaction API, and Call Back URL.https://documenter.getpostman.com/view/28301323/2s93zCZgJE

9. **What parameters are required for the Token Generation API?**

   The Token Generation API requires the client_email (registered email ID) and api_token (visible in the API Panel) as parameters.

10. **What are the possible responses for the Transaction API?**

    The Transaction API can return success response, processing response, or failed response, along with respective status codes and messages.

11. **How does the Callback URL service work?**

The Callback URL service allows API users to receive real-time transaction updates and notifications by specifying a callback URL in their application.

PostMan Details:

https://documenter.getpostman.com/view/28301323/2s93zCZgJE

Confidential

CORE - eSIM API Documentation

Introduction

The eSIM API allows seamless integration for managing eSIM services. This document provides the necessary details for interacting with the API endpoints, including authentication, request formats, and response structures.

Base URLs

1	UAT Environment	https://ctop-api.Core-retail.com/api/uat
2	Production Environment	https://ctop-api.Core-retail.com/api/live

IP Restriction

The API is restricted to known IP addresses. All inbound requests must originate from trusted addresses or use a proxy.
Authentication
The API uses Bearer Token authentication. You can generate a Bearer Token using the following endpoint:

- Bearer Token Generation API: BASEURL/token

Replace BASEURL with the appropriate environment URL (Production or UAT).

Authtoken Creation

BCRYPT => PASSWORD#YOURSERVERIP#DATETIME(DDMMYYHHMM)(BST/GMT TIMEZONE)
Ex: 123456#192.192.192.192#0101241210
After Encryption,
$2a$12$glDVwMdQfUEhDivbo.IqaO7BlwF2J8XQe2ei/Bqq6frRfrzklK46K

Note : Authtoken Password Integration team will share it with you.

Get Bearer Token

This method is used to obtain a Bearer Token, which is required for authenticating and authorizing subsequent API requests. The token is generated based on the user's credentials and must be included in the Authorization header of all API requests to ensure secure access.

Endpoint: v1/esim/token
Method: POST

Parameters:

email: (string) User's email address.
password: (string) User's password.

Response:

{
  “success”: true,
  “data”: {
    “name”: “NAME”,
    “access_token”: “ACCESS_TOKEN”
  }
}

EXAMPLE

email=testing3@gmail.com
password=Test%40123

FAIL

{
    "success": false,
    "message": "You are restricted to access the site."
}

SUCCESS

{
    "success": true,
    "data": {
        "name": "Testing3",
        "token":

"eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJhdWQiOiIxIiwianRpIjoiODYyODRjMTcwMjEwNTA0MThiYTdkYjQxODk4NTlkMTM1NmRlZWI5ZjM0NjFmMGRiOThmYjk1YjU2YWI1NDVkODkxNTg0NmZkMGY0NTQ4ZTEiLCJpYXQiOjE3MjAwMTUyMjguMzI4NzM4LCJuYmYiOjE3MjAwMTUyMjguMzI4NzQyLCJleHAiOjE3NTE1NTEyMjguMzI1NzgxLCJzdWIiOiIzMyIsInNjb3BlcyI6W119.jQK50Y1_7qxD_x5n0Npwvtq8gcps5cler4T23g6qtUs-foDo3etbPXb1arxPTRAX2FMe-mc1GQ4qRw_mJpkWbR66ZmaEiz7wWLnlzRIdR0UQSWUkdQf2kUjb9V2HfheuXTBK6iHEEKHznj-_CpFiz5NFqiGEXqLHiVpRuORZi8LbOtyDNxbbapvMsvb9A7MztoQfu36QPUM887IDVF8LbKVo-W73MqabPKtDHW6MMoWoV_xB6ee93W_UezzmHHTWLvWcHbM3WwGRMB4Nl6jXoqNml8mIV1lpgstxf3Nlz706NAxy6GNVg1YDghk6ZxSt2irEXkT7Iw7s3dSAWG0zENuemePQd0Jl-d03mv1kOHn151EOfk2E1gYyqPxw_jEdk_SHc2cOxwSCA1VcFPENd3a8_YgOqqQjeD0QKLAa8WC_zCJnyNXMb0oPumF9ih2xXFCDf5n2N0N2eJ4724Ino9uGbAUpEvzp0HrctbKhdY0-NyPkIaPoYQa-iEJDI1YBOgmBUSG1sL_VsibSKJgMIn-Mfdph793t2pT-DEnTHX_ejgBPthlrbUW4O-2tWN5eTQAMabujSylPf-Cq1XUDuCxRjfV9guCdI1_l0zAZJATwNO0q61wtzTSZuipVwlXUwKLblMIo81umwDaI9XfUbKJ3gF-JZNm5REfxSl0PDU"
    },
    "message": "You are successfully logged in."
}

Get Destinations

Endpoint: v1/esim/get-destinations
Method: POST

Parameters:

authtoken: (string) Authentication token.
type: (int) type of destination
1 = Countries
2 = Regions
3 = Global

Response:

{
    "success": true,
    "status": 1,
    "message": "success",
    "data": [
        {
            "name": "COUNTRY_NAME_1",
            "country_id": "COUNTRY_ID_1"
        },
        {

```
        "name": "COUNTRY_NAME_2",
        "country_id": "COUNTRY_ID_2"
    }
]
}
```


EXAMPLE:

authtoken=%242a%2412%24pe%2F6ScCNMeLZhxPHFRnJm.7B1tvbJk0jGGN7AlPmca1ARbVMdiA7m
type = 1

TYPE = 1 Response


```
{
   "success": true,
   "status": 1,
   "message": "success",
   "data": [
      {
         "name": "United Kingdom",
         "country_id": "gb"
      },
      {
         "name": "Belgium",
         "country_id": "be"
      },
      {
         "name": "Bulgaria",
         "country_id": "bg"
      }
]
}
```


TYPE = 2 OR 3 Response


```
{
   "success": true,
   "status": 1,
   "message": "success",
   "data": [
        {
         "name": "Mid East / N Africa",
         "country_id": "middle_east",
         "countries": [
            {
               "name": "Bahrain",
               "country_id": "bh",
```

```
    "first_network": "zain BH (d. MTC Vodafone)",
    "second_network": "--"
  },
  {
    "name": "Egypt",
    "country_id": "eg",
    "first_network": "Orange (d.MoBiNil)",
    "second_network": "Etisalat"
  },
  {
    "name": "Iran",
    "country_id": "ir",
    "first_network": "MCI (d. TCI)",
    "second_network": "RighTel"
  },
  {
    "name": "Israel",
    "country_id": "il",
    "first_network": "HotMobile",
    "second_network": "Pelephone"
  },
  {
    "name": "Jordan",
    "country_id": "jo",
    "first_network": "Zain",
    "second_network": "Umniah"
  },
  {
    "name": "Kuwait",
    "country_id": "kw",
    "first_network": "zain KW (d. MTC Vodafone/ MTCNet)",
    "second_network": "Viva"
  },
  {
    "name": "Morocco",
    "country_id": "ma",
    "first_network": "Orange",
    "second_network": "IAM"
  },
  {
    "name": "Palestine",
    "country_id": "ps",
    "first_network": "Jawwal",
    "second_network": "Ooredoo"
  },
  {
```

```
            "name": "Qatar",
            "country_id": "qa",
            "first_network": "Vodafone Qatar",
            "second_network": "--"
         },
         {
            "name": "Saudi Arabia",
            "country_id": "sa",
            "first_network": "Al Jawal",
            "second_network": "--"
         },
         {
            "name": "Tunisia",
            "country_id": "tn",
            "first_network": "Orange",
            "second_network": "Ooredo"
         },
         {
            "name": "United Arab Emirates",
            "country_id": "ae",
            "first_network": "du",
            "second_network": "--"
         }
      ]
   },
   {
      "name": "Latin America",
      "country_id": "latin_america",
      "countries": [
         {
            "name": "Argentina",
            "country_id": "ar",
            "first_network": "CLARO - AMX Group",
            "second_network": "--"
         },
         {
            "name": "Brazil",
            "country_id": "br",
            "first_network": "CLARO - AMX Group",
            "second_network": "--"
         },
         {
            "name": "Chile",
            "country_id": "cl",
            "first_network": "CLARO - AMX Group",
            "second_network": "--"
```

```
},
{
   "name": "Colombia",
   "country_id": "co",
   "first_network": "CLARO - AMX Group",
   "second_network": "--"
},
{
   "name": "Costa Rica",
   "country_id": "cr",
   "first_network": "Claro",
   "second_network": "--"
},
{
   "name": "Ecuador",
   "country_id": "ec",
   "first_network": "Claro Ecuador",
   "second_network": "--"
},
{
   "name": "Guatemala",
   "country_id": "gt",
   "first_network": "CLARO - AMX Group",
   "second_network": "--"
},
{
   "name": "Honduras",
   "country_id": "hn",
   "first_network": "CLARO - AMX Group",
   "second_network": "--"
},
{
   "name": "Mexico",
   "country_id": "mx",
   "first_network": "CLARO - AMX Group",
   "second_network": "--"
},
{
   "name": "Nicaragua",
   "country_id": "ni",
   "first_network": "CLARO - AMX Group",
   "second_network": "--"
},
{
   "name": "Paraguay",
   "country_id": "py",
```

```
            "first_network": "CLARO PARAGUAY",
            "second_network": "--"
         },
         {
            "name": "Peru",
            "country_id": "pe",
            "first_network": "CLARO - AMX Group",
            "second_network": "--"
         },
         {
            "name": "Uruguay",
            "country_id": "uy",
            "first_network": "CLARO - AMX Group",
            "second_network": "--"
         }
      ]
   },
   {
      "name": "N America",
      "country_id": "north_america",
      "countries": [
         {
            "name": "Canada",
            "country_id": "ca",
            "first_network": "TELUS Communications Inc.\n",
            "second_network": "--"
         },
         {
            "name": "United States",
            "country_id": "us",
            "first_network": "AT&T Mobility",
            "second_network": "--"
         }
      ]
   }
 ]
}
```


Get Package

This method retrieves a list of available eSIM packages that the user can apply. Each package typically includes details like package ID, name, and other relevant information necessary for selection. It requires valid authentication to fetch the packages associated with the authenticated user's account.

Endpoint: v1/esim/get-package
Method: POST

Parameters:

token: (string) Bearer token.
authtoken: (string) Authentication token generated.
country_id: (string) Country OR Region Code (Find from Get Destinations method.)

Response:


```
{
  "success": true,
“code” : 200,
  "message": "Done",
  "data": {
    "packages": [
      {
        "package_id": "123",
        "name": "PACKAGE_NAME",
        "data": "AMOUNT_IN_GB",
        "text": "TEXT_INCLUDED",
        "calls": "CALLS_INCLUDED",
        "day": "VALIDITY_IN_DAYS",
        "amount": "RETAIL_PRICE_IN_USERS_CURRENCY",
        "day": "VALIDITY_IN_DAYS",
        "plan_type": "INCLUDED_SERVICES",
        "speed": "AVAILABLE_NETWORK_SPEED",
        "network": "ARRAY_OF_MOBILE_NETWORKS_AVAILABLE",
        "country_id": "COUNTRY_OR_REGION_CODE",
        "product_code": "NAME_OF_MNO_OR_MVNO"
      }
    ]
  }
}
```


EXAMPLE

authtoken=%242a%2412%24gltS7BpwCYN9YYHnseGIVuKoZVkPbOneRVZSGoAG%2FUqTRDDwc3rhS


```
{
    "success": true,
“code” : 200,
    "status": 1,
    "message": "success",
```

```
  "data": [
    {
      "package_id": "1280742",
      "name": "Africa-  1GB-  14days",
      "data": "1",
      "text": null,
      "calls": null,
      "day": 14,
      "amount": 27, // GBP
      "plan_type": "Data Only",
      "speed": "Up to 5G - Will vary by location",
      "network": [
        {
          "network1": "NETWORK_NAME",
          "network2": "NETWORK_NAME"
        },
        ]
      "country_id": "africa",
      "product_code": Amigo
    }
  ]
}
```


Response Parameters

- package_id (varchar)
- name (varchar)
- Data (int)
- Text (int)
- Calls (int)
- Day (int)
- Amount (double)
- plan_type (varchar)
- Speed (varchar)
- Network (object)
- country_id (varchar)
- product_code (varchar)

Apply Package

This method is crucial for provisioning eSIM services. When a user selects a package from the available options, this API is used to generate an eSIM profile corresponding to that package. By providing the necessary parameters, such as the package ID and country code, the system allocates the selected package to the user's account and generates an associated eSIM profile. This process effectively activates the eSIM with the chosen data or service plan, ready for use on compatible devices.

Endpoint: v1/esim/apply-package
Method: POST

Parameters:

authtoken: (string) Authentication token.
package_id: (string) ID of the package to apply.
Origin_country_code: (string) Origin Country code.
email: (string) customer email.

Response:

{
  "success": true;false,
“code” : 200,
  "status": 1,
  "message": "Response detail",
  "transaction_id": "TRANSACTION_ID",
  "date": "DATE_TIME",
  "data": "",
  "esim": {
      "msisdn": "MOBILE_NUMBER";NULL,
      "iccid": "ICCID",
      "smdp": "SMDP",
      "matchingid": "MATCHING_ID",
      "activationCode": "ACTIVATION_CODE",
      "esim_id": "ESIM_ID",

  }
}

EXAMPLE

eSIM REQUEST
authtoken=%242a%2412%24gltS7BpwCYN9YYHnseGIVuKoZVkPbOneRVZSGoAG%2FUqTRDDwc3rhS
package_id=1093950
origin_country_code=us
email=test@gmail.com
package_id=5025743888239

AMIGO eSIM SUCCESS RESPONSE


```
{
  "success": true,
  "status": 1,
  "message": "Esim generated successfully done.",
  "iccid": {
    "msisdn": "",
    "iccid": "89103XXXXXXXXX8215934",
    "smdp": "consuXXXX.XXX.global",
    "matchingId": "TNXXXXXXXXXXXXXX",
    "activationCode": "LPA:1$consuXXXX.XXX.global$TNXXXXXXXXXXXXXX"
  },
  "transaction_id": "FRIES2406065465457852",
  "date": "01:36:07 AM, June 06 2024",
  "data": {
    "id": "f1ab9c8c-67ff-4cea-8457-ca265687895674645033e8",
    "sim": "89103XXXXXXXXX8215934",
    "window_activation_start": 1749170167000,
    "window_activation_end": 1780706170000,
    "status": "NOT_ACTIVE",
    "voice_usage_remaining": 0,
    "data_usage_remaining": 10737418240,
    "sms_usage_remaining": 0,
    "time_allowance": 2592000,
    "created_date": 1749170167000,
    "expiry_date": 1780706170000,
    "package_template": {
      "id": 1280187,
      "name": "Asia,  10GB,  30days",
      "voice_usage_allowance": 0,
      "data_usage_allowance": 10737418240,
      "sms_usage_allowance": 0,
      "time_allowance": {
        "duration": 2592000,
        "unit": "SECOND"
      },
      "activation_time_allowance": 31536003
    }
  }
}
```

EE eSIM SUCCESS RESPONSE


```
{
   "success": true,
“code” : 200,
   "status": 1,
   "message": "Esim generated successfully done.",
   "transaction_id": "WEDES240703167257",
   "date": "03:33:51 PM, July 03 2024",
   "esim": {
      "msisdn": "07XXXXXXXXX",
      "iccid": "X349326286731",
      "smdp": "consumer.rsp.global",
      "matchingId": "TNXXXXXXXXXXXXXXX",
      "activationCode": "LPA:1$consuXXXX.XXX.global$TNXXXXXXXXXXXXXXX",
      "esim_id": ""
   }
}
```


Three eSIM SUCCESS RESPONSE


```
{
  "success": true,
  "status": 1,
  "message": "Esim generated successfully done.",
  "transaction_id": "FRIES2404066122497",
  "date": "03:18:51 AM, June 06 2024",
  "iccid": {
    "iccid": "8944200208520012190",
    "msisdn": "07XXXXXXXXX",
    "matchingId": "XXXXXXXXXXXXXXX",
    "activationCode": "LPA:1$huk.XXX.ondemandconXXXXX.com$XXXXXXXXXXXXXXX ",
    "smdp": "LPA:1$huk. XXX. ondemandconXXXXX.com$",
    "confirmation_code": "1234"
  },
  "data": ""
}
```

FAIL

{
"success": false,
“code” : 401,
"status": 2,
"message": "Unauthorized access.",
"date": "03:36:10 PM, July 03 2024"
}

Fetch eSIM Detail

This endpoint fetches detailed information about a specific eSIM package that has been applied to the user’s account. It provides insights into the status, validity, and specifics of the applied package, helping users or applications to manage and monitor their eSIM configurations effectively.

NOTE – THIS API ONLY FOR AMIGO eSIMs

Endpoint: v1/esim/package-info
Method: POST

Parameters:

authtoken: (string) Authentication token.
esim_id: (string) ID of the applied package.

Response:

{
"success": true,
“code” : 200,
"message": "Done",
"data": {
...
}
}

EXAMPLE

authtoken=%242a%2412%24pe%2F6ScCNMeLZhxPHFRnJm.7B1tvbJk0jGGN7AlPmca1ARbVMdiA7m
package_id=090d6a3b-da42-4a64-9780-ed51c90c5ffe

SUCCESS

```
{
    "success": true,
“code” : 200,
    "status": 1,
    "message": "Pacakge Info Get",
    "date": "04:00:28 PM, July 03 2024",
    "data": {
        "packageId": "090d6a3b-da42-4a64-9780-ed51c90c5ffe",
        "simIccid": "8910300000008553383",
        "dateCreated": 1714799594000,
        "dateExpiry": 1717493766000,
        "dateActivated": 1714901766000,
        "dateTerminated": 1717493775000,
        "windowActivationStart": 1714799594000,
        "windowActivationEnd": 1746335594000,
        "status": "TERMINATED",
        "voiceUsageRemainingInSeconds": 0,
        "dataUsageRemainingInBytes": 15141953441,
        "smsUsageRemainingInNums": 0,
        "packageTypeId": 1164576,
        "timeAllowanceInSeconds": 2592000
    }
}
```


FAIL


```
{
    "success": false,
    “code” : 400,
    "status": 2,
    "message": "esim_id is mandatory!!",
    "date": "04:02:47 PM, July 03 2024"
}
```

Error Code

Code	Description
401	Unauthorized access.
204	Unknown Error | Internal Error
2041	<NETWORK NAME> is not available
2042	Three is not available
2043	Amigo is not available
2044	Out Of Stock, Please Try Other Network
403	User Disabled! Please Check With Admin
4031	Incorrect Environment - Please Check With Admin
4032	Production Environment Not Enabled - Please Check with Admin
4033	IP has been blocked
400	Parameter is missing - Please check your Request
4001	Incorrect Parameter Value
200	Transaction Success
422	Insufficient Balance. Please TOPUP Your Account.