Back Bar Coolers



Williams
Back Bar Coolers
Built to Last



About us

Williams refrigeration has been an Indian expert for over two decades, serving the HORECA industry providing premium fabrication and refrigeration solutions adapting recent trends in design and utilizing advanced technology equipment.

We offer comprehensive solutions with durable fabrication and refrigeration customized to your pastry shops, ice cream shops, bars, breweries, restaurants and supermarkets.

We align closely with our customer's requirements by delivering environment friendly products alongside exceptional service. Our foremost priority is continuous innovation, integrating novel technologies into our product line.

ISO 9001:2015 IAF UKAS

Back Bar Coolers

The back bar coolers are refrigerated appliances designed to store beverages also provide convenience in accessing the bottles. The bottles are maintained at a temperature of 2 to 8 °C . Back bar coolers are available in single, double and triple door variants. This equipment is completely made of AISI 304 food-grade stainless steel interior and exterior with PU foam thermal insulation.

Digital controller

Precise control and display of the temperature of the food items.

Forced air circulation system

Aids in quick and even circulation of cool air.



Removable and washable gasket

Prevents the infiltration of outside air into the refrigerated space.

Anti - skid leg

The anti-skid leg gives a strong firm and prevents movement of the cooler..

Anti - tilt tray slides

The anti-tilt tray slides are easy to remove,clean and also avoids tipping.

Self-Closing door

Prevents the loss of cooling from the system, also helps when both the hands are loaded.

105° door opening

This helps during loading and stock verification.

Mullion heater

Helps in preventing harmful dirt traps due to condensation.

Ventilation

Adequate ventilation is provided for the effective functioning of the refrigeration system.

Product Code



BBCL 2G LHS

Product Name

BBC- Back Bar Cooler

DOOR OPENING SIDE

Not mentioned
- Right hand side
LHS - Left hand side

Doors

1	-	1 Door
2	-	2 Door
3	-	3 Door
G	-	Glass Door
S	-	Solid Door



#8 Mirror



#4 Matt



Black Matt



BBCL1S - LHS
BBCL1S



BBCL1G - LHS
BBCL1G



BBCL2S



BBCL2G



BBCL3S



BBCL3G

Standard Features

- Door locks provide added security.
- High quality washable **magnetic door gasket.**
- Easy to use microprocessor control with digital display for easy visual reference.
- Stainless steel interior & exterior finish.
- The doors are easy to open and are self-closing.
- Removable **anti-tilt tray slides**.
- **Efficient and durable** compressor.
- **Automatic defrost** ensures the evaporator working to its optimum performance.
- Designed and engineered to operate up to **32° C ambient.**
- Adjustable racking system allows flexible storage.

Optional Features

- LED is provided in glass door models.
- Low-E, double pane, UV tinted glass.
- Front / side skirting.

Key Features

- **AISI 304** food grade stainless steel is used.
- **Balanced, forced air refrigeration system** enables rapid product pull down and even temperature throughout.
- **50mm** thick Polyurethane foam is used for thermal insulation.
- **Anti condensation** door mullion heaters.
- **Environmental friendly** CFC free refrigerant (R134a)

Internal LED lamp (Optional)

Lamp aids in visual appeal of the product.



Adjustable racks

The racks are adjustable as per the requirement.




Digital Controller

A digital controller of Italian make is used for precise control and display of the temperature of the food items.



Self-Closing door

Prevents the loss of cooling from the system, also helps when both the hands are loaded.



Two pane glass with Argon

Two pane Argon filled glass is provided which acts as a insulator.





Cylindrical Lock

The lock facilitates safety and control over the stock.



Tech Specs

Structural	 1 SS DOOR	 1 GLASS DOOR	 2 SS DOOR	 2 GLASS DOOR	 3 SS DOOR	 3 GLASS DOOR
Model	BBCL1S - LHS/RHS	BBCL1G - LHS/RHS	BBCL2S	BBCL2G	BBCL3S	BBCL3G
Dimension(WxDxH)	600 x 530x 800mm	600 x 530x 800mm	900x 530 x 800mm	900x 530 x 800mm	1350x 530 x 800mm	1350x 530 x 800mm
Gross Volume	100L	100L	185L	185L	340L	340L
Doors	1	1	2	2	3	3
Shelf Size	530x325mm	530x325mm	530x325mm	530x325mm	530x325mm	530x325mm
Weight	82kg	82kg	100kg	100kg	120kg	120kg

Refrigeration						
Temperature	2° C to 8° C	2° C to 8° C	2° C to 8° C	2° C to 8° C	2° C to 8° C	2° C to 8° C
Climate Class	NT	NT	NT	NT	NT	NT
Cooling System	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling
Defrost	Auto	Auto	Auto	Auto	Auto	Auto
Testing Standard	ISO 22041	ISO 22041	ISO 22041	ISO 22041	ISO 22041	ISO 22041
Operating Ambient	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a

Electrical @ 32°C Ambient						
Power	235W	235W	316W	316W	384W	384W
Current	1.8A	1.8A	1.8A	1.8A	2A	2A
Voltage	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz
Power Consumption 24hrs	1.52kWh	1.52kWh	2.3kWh	2.3kWh	3.1kWh	3.1kWh
Power Plug Type	Type D	Type D	Type D	Type D	Type D	Type D

Performance, Reliability and Quality

- Fibre optic laser is used in manufacturing, which provides more accurate and precise joints for improved product quality, performance and safety.
- The doors are held using reinforced 3 mm stainless hinges at the top and bottom for added durability and to eliminate the risk of door sag (tested to then standard ISO 22041).
- Self closing doors help to reduce the cooling loss due to infiltration.
- Anti tilt heavy duty racking system is provided, with each shelf capable of holding 40kg.

Energy Efficiency and Sustainability

- High thermal resistive Polyurethane foam is used which has high resistance to heat transfer increasing the energy efficiency, also lasts for longer period of time.
- The self closing door in-turn increases the energy efficiency, low cooling loss equals to low power consumption.
- The system is sustainable that zero ODP refrigerants are used .

Value

- Food grade high quality AISI 304 Stainless Steel is used with the finish suitable for handling food and beverages.

Hygiene & Safety

- Flush handle in the door which is easy for opening and cleaning.
- Hygienic and contactless magnetic fan cut-out door switch with no moving parts.

Common Features


32°C Ambient


Hermetic Compressor


Forced Air Circulation


Defrosting by Heating Element


R134a

Williams
refrigeration

Williams Refrigeration

UNIT-I
111 'C', KIADB Industrial Area
1st Phase, Bommasandra,
Hosur Main Road, Bangalore-560099, INDIA

UNIT-II
Plot No. 127&128, Bommasandra IV Phase,
Yarandahally,Bangalore-560099,
Karnataka, India.

+91-9844013768

sales@williamsrefrigeration.in
info@williamsrefrigeration.in

www.williamsrefrigeration.co.in

Facebook Youtube Instagram