Blast Freezers



Williams

Blast Freezers

Built to Last



About us

Williams refrigeration has been an Indian expert for over two decades, serving the HORECA industry providing premium fabrication and refrigeration solutions adapting recent trends in design and utilizing advanced technology equipment.

We offer comprehensive solutions with durable fabrication and refrigeration customized to your pastry shops, ice cream shops, bars, breweries, restaurants and supermarkets.

We align closely with our customer's requirements by delivering environment friendly products alongside exceptional service. Our foremost priority is continuous innovation, integrating novel technologies into our product line.

ISO 9001:2015 IAF UKAS

Blast Freezers

The Blast freezers are refrigerated appliances designed to quickly lower the temperature of the cooked food in order to maintain the taste and quality of the prepared food items also slows down the growth of bacteria. As the name indicates the cold air is blasted over the food items to cool them from 90°C to +3°C within 90 minutes and freeze them from 90°C to -18°C within 240 minutes. Blast freezers are available in 5, 20, 40 kg capacity variants. This equipment is completely made of AISI 304 food-grade stainless steel interior and exterior with PU foam thermal insulation.

Removable and washable gasket

Prevents the infiltration of outside air into the refrigerated space.

Forced air circulation system

Monoblock refrigeration system for easy maintenance.

105° door opening

This helps during loading and stock verification.



Digital controller

Precise control and display of the temperature of the food items.

Mullion heaters

Helps in preventing harmful dirt traps due to condensation.

Adjustable bullet feet

The leveling of the system can be done using the adjustable feet (range 130-170mm).

Ventilation

Adequate ventilation is provided for the effective functioning of the refrigeration system.

Product Code





#4 Matt

BCF 20

Product Type

Blast Chiller/Freezer

Capacity

5 - 5 kg
20 - 20kg
40 - 40kg



BCF5
BLAST FREEZER
5 KG



BCF20
BLAST FREEZER
20 KG



BCF40
BLAST FREEZER
40 KG

Standard Features


- Front ventilation provided in this system is suitable for enclosed areas.
- Door locks provide added security.
- High-quality washable **magnetic door gasket.**
- Easy to use microprocessor control with digital display for easy visual reference.
- Stainless steel interior & exterior finish.
- The doors are easy to open and are also **self-closing.**
- Removable **anti-tilt tray slides** to prevent tipping.
- Adjustable legs to ensure stability on an uneven floor.
- **Efficient and durable compressor.**
- **Automatic defrost** ensures the evaporator working to its optimum performance.
- Designed and engineered to operate up to **43° C ambient.**

Optional Features

- Front / side skirting.
- Accommodates GN 1/1, 1/2, 400x600 tray.

Key Features

- **AISI 304** food grade stainless steel is used.
- **Balanced, forced air refrigeration system** enables rapid product pull down and even temperature throughout.
- **80mm low density Polyurethane** foam is used for thermal insulation.
- **Anti condensation door** mullion heaters.
- **Environmental friendly** CFC free refrigerant (R134a)



Air flow

Powerful fans and the equalized air pressure chamber design ensures that the air flows evenly over all products




Digital Controller

Digital controller of Italian make is used for precise control and display of the temperature of the food items.



Adjustable racks

The racks are adjustable as per the requirement.




Food temperature probe

Single core food temperature probe for accurate measurement of food temperature



Self-Closing door


Prevents the loss of cooling from the system, also helps when both the hands are loaded.




Anti-condensation door mullion heaters

This prevents the condensation of atmospheric moisture

Tech Specs







Structural

	BCF5	BCF20	BCF40
Model	BCF5	BCF20	BCF40
Dimension(WxDxH)	930x700x420mm	800x800x1030mm	800x800x1815mm
Gross Volume	90L	110L	290L
Capacity R/F*	7/5kg	28/20kg	56/40kg
Shelf Size	354x325mm	530x325mm	530x325mm
No. of GN 1/1 shelves	2	5	12
Weight	74kg	122kg	202kg

Refrigeration

Temperature R/F*	90° C to +3° C / 90° C to - 18° C	90° C to +3° C / 90° C to - 18° C	90° C to +3° C / 90° C to - 18° C
Climate Class	T	T	T
Cooling System	Dynamic cooling	Dynamic cooling	Dynamic cooling
Defrost	Auto	Auto	Auto
Testing Standard	ISO 22041	ISO 22041	ISO 22041
Operating Ambient	10°C to 43°C	10°C to 43°C	10°C to 43°C
Refrigerant R/F*	R404A	R404A	R404A

Electrical @ 43°C Ambient

Power R/F*	560W	780W	1020W
Current R/F*	3.2A	4.5A	5.6A
Voltage	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz
Power consumption 24hrs R/F*	4.5kWh	6.3kWh	8.1kWh
Annual Energy consumption	1636kWh	2278kWh	2979kWh
Power Plug type	Type D	Type D	Type D

*R/F - Refrigerator / Freezer

Performance, Reliability and Quality

- Fibre optic laser is used in manufacturing, which provides more accurate and precise joins for improved product quality, performance and safety.
- The doors are held using reinforced 3 mm stainless hinges at the top and bottom for added durability and to eliminate the risk of door sag (tested to then standard ISO 22041).
- Self closing doors help to reduce the cooling loss due to infiltration.
- Anti tilt heavy duty racking system is provided, with each shelf capable of holding 40kg.

Energy Efficiency and Sustainability

- High thermal resistive Polyurethane foam is used which has high resistance to heat transfer increasing the energy efficiency, also lasts for longer period of time.
- The self closing door in-turn increases the energy efficiency, low cooling loss equals to low power consumption.
- The system is sustainable that zero ODP refrigerants are used .

Value

- Food grade high quality AISI 304 Stainless Steel is used with the finish suitable for handling food and beverages.

Hygiene & Safety

- Flush handle in the door which is easy for opening and cleaning.
- Hygienic and contactless magnetic fan cut-out door switch with no moving parts.

Common Features


43⁰ C Ambient


Hermetic Compressor


Forced Air Circulation


Defrosting by Heating Element


Evaporated by Hot Gas


R404A

Williams Refrigeration

UNIT-I
111 'C', KIADB Industrial Area
1st Phase, Bommasandra,
Hosur Main Road, Bangalore-560099, INDIA

UNIT-II
Plot No. 127&128, Bommasandra IV Phase,
Yarandahally,Bangalore-560099,
Karnataka, India.

+91-9844013768

sales@williamsrefrigeration.in
info@williamsrefrigeration.in

www.williamsrefrigeration.co.in

Facebook Youtube Instagram