Refrigerated Cabinets



Williams
Refrigerated Cabinets
Built to Last



About us

Williams refrigeration has been an Indian expert for over two decades, serving the HORECA industry providing premium fabrication and refrigeration solutions adapting recent trends in design and utilizing advanced technology equipment.

We offer comprehensive solutions with durable fabrication and refrigeration customized to your pastry shops, ice cream shops, bars, breweries, restaurants and supermarkets.

We align closely with our customer's requirements by delivering environment friendly products alongside exceptional service. Our foremost priority is continuous innovation, integrating novel technologies into our product line.

ISO 9001:2015 IAF UKAS

Refrigerated Cabinets

Introducing the premium refrigerated cabinets, available as chillers and freezers with identical cabinet dimensions. Choose from single/double full length doors or two/four half door variants. Crafted entirely from AISI 304 food-grade stainless steel with PU foam thermal insulation for optimal freshness.



Refrigeration system

Monoblock refrigeration system for easy maintenance.

Mullion heater

Helps in preventing harmful dirt traps due to condensation.

Anti – tilt tray slides

The anti-tilt tray slides are easy to remove and clean and also avoids tipping.

Caster wheels with lock

Provides flexibility and mobility

Adjustable bullet feet

The leveling of the system can be done using the adjustable feet (range 130-170mm).

Electronic controller

Digital controller with touch screen enables precise control and display of the temperature of the food items.

Ventilation

Adequate ventilation is provided for the effective functioning of the refrigeration system.

Forced air circulation system

Aids in quick and even circulation of cool air.

Removable and washable gasket

Prevents the infiltration of outside air into the refrigerated space.

105° door opening

This helps during loading and stock verification.

Product Code



GN 600 TN-G - LH

GN Pan Compatibilty

Gastro Norm

Capacity

600 - 600 Ltr
1.2 - 1200 Ltr

Cabinet Type

TN - Normal Temperature - Refrigerator (+2°C to +8°C)

BT- Low Temperature Freezer (-15°C to -21°C)

Door opening side

LH - Left hinged door
RH - Right hinged door

No. of Doors

Not mentioned - 1 Door
2 - 2 Full/Half Doors
4 - 4 Half doors

Door Type

G - Glass Door

GN600TN-LH/RH / GN600BT-LH/RH
REFRIGERATOR / FREEZER 600L





GN600TN2-LH/RH / GN600BT2 - LH/RH
REFRIGERATOR / FREEZER 600L

GN600TNG-LH/RH
REFRIGERATOR 600L



GN1.2TN2 / GN1.2BT2
REFRIGERATOR / FREEZER
1200L





GN1.2TN4 / GN1.2BT4
REFRIGERATOR / FREEZER
1200L

GN1.2TNG2
REFRIGERATOR 1200L



Standard Features

- Top ventilation in this system is suitable for usage in enclosed areas.
- Door locks provide added security.
- **High-quality washable magnetic door gasket.**
- Easy to use microprocessor control with digital display for easy visual reference.
- Stainless steel interior & exterior finish.
- Removable **anti-tilt tray** slides.
- **Adjustable legs** to ensure stability on an uneven floor.
- **Efficient and durable** compressor.
- **Automatic defrost** ensures the evaporator working to its optimum performance.
- Designed and engineered to operate up to **43° C ambient.**
- Low-E, double pane, UV tinted glass

Optional Features

- Fish file cabinets.
- Caster wheels.
- LED is provided in glass door models

Key Features

- **AISI 304** food grade stainless steel is used.
- **Balanced, forced air refrigeration system** enables rapid product pull down and even temperature throughout.
- **75mm low density Polyurethane** foam is used for thermal insulation.
- **Anti condensation** door mullion heaters.
- **Environmental friendly** CFC free refrigerant (R134a or R404A)



Common Features

- 43º C Ambient
- Hermetic Compressor
- Forced Air Circulation
- Defrosting by Heating Element
- R134a / R404A

Cabinet comes with standard colour



Tech Specs








Structural

	1 SS DOOR	1 GLASS DOOR	2 SS SEMI DOOR	2 SS DOOR	2 GLASS DOOR	4 SS SEMI DOOR
Model	GN600TN-LH/RH / GN600BT-LH/RH	GN600TNG-LH/RH	GN600TN2-LH/RH / GN600BT2-LH/RH	GN1.2TN2 / GN1.2BT2	GN1.2TNG2	GN1.2TN4 / GN1.2BT4
Dimension(WxDxH)	700 x 850 x 2050mm	700x850x2050mm	700x850x2050mm	1400x850x2050mm	1400x850x2050mm	1400x850x2050mm
Gross Volume	600L	600L	600L	1200L	1200L	1200L
Doors	1	1	2	2	2	4
No. of GN 1/1 shelves	4	5	4	8	10	8
Gn 1/1 pan accommodation per shelf	2	2	2	2	2	2
Weight	130kg	134kg	130kg	170kg	174kg	170kg
Shelf Size	530x612mm	530x612mm	530x612mm	530x612mm	530x612mm	530x612mm

Refrigeration

Temperature R/F*	2° C to 8° C / -15°C to -21°C	2° C to 8° C	2° C to 8° C / -15° C to - 21° C	2° C to 8° C / -15°C to -21°C	2° C to 8° C	2° C to 8° C / -15°C to -21°C
Climate Class	T	T	T	T	T	T
Cooling System	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling	Dynamic cooling
Defrost	Auto	Auto	Auto	Auto	Auto	Auto
Testing Standard	ISO 22041	ISO 22041	ISO 22041	ISO 22041	ISO 22041	ISO 22041
Operating Ambient	10°C to 43°C	10°C to 43°C	10°C to 43°C	10°C to 43°C	10°C to 43°C	10°C to 43°C
Refrigerant R/F*	R134a / R404A	R134a	R134a / R404A	R134a / R404A	R134a	R134a / R404A

Electrical @ 43°C Ambient

Power R/F*	390/727W	390W	390/727W	620/1210W	728W	620/1210W
Current R/F*	1.7/3.2A	1.7A	1.7/3.2A	2.7/5.2A	3.2A	2.7/5.2A
Voltage	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz	1ph / 230V / 50Hz
Power Consumption 24hrs R/F*	2.4/4.4kWh	2.4kWh	2.4/4.4kWh	3.8/7.3kWh	4.4kWh	3.8/7.3kWh
Power Plug type	Type D	Type D	Type D	Type D	Type D	Type D

*R/F - Refrigerator / Freezer

Performance, Reliability and Quality

- Fibre optic laser is used in manufacturing, which provides more accurate and precise joints for improved product quality performance and safety.
- The doors are held using reinforced 3 mm stainless hinges at the top and bottom for added durability and to eliminate the risk of door sag (tested to then standard ISO 22041).
- Self closing doors help to reduce the cooling loss due to infiltration.
- Anti tilt heavy duty racking system is provided, with each shelf capable of holding 40kg.

Energy Efficiency and Sustainability

- High thermal resistive Polyurethane foam is used which has high resistance to heat transfer increasing the energy efficiency, also lasts for longer period of time.
- The self closing door in-turn increases the energy efficiency, low cooling loss equals to low power.
- The system is sustainable that natural, low GWP and zero ODP refrigerant is used .

Value

- Food grade high quality AISI 304 Stainless Steel is used with the finish suitable for handling food and beverages.

Hygiene & Safety

- Flush handle in the door which is easy for opening and cleaning.
- Hygienic and contactless magnetic fan cut-out door switch with no moving parts.



Internal LED lamp (optional)

Lamp aids in visual appeal of the product.



Adjustable racks

The racks are adjustable as per the requirement.



Two pane glass with Argon

Two pane Argon filled glass is provided which acts as a insulator.



Digital Controller

Digital controller of Italian make is used for precise control and display of the temperature of the food items.



Self-Closing door

Prevents the loss of cooling from the system, also helps when both the hands are loaded.



Cylindrical Lock

The lock facilitates safety and control over the stock.

Williams Refrigeration

UNIT-I
111 ‘C’, KIADB Industrial Area
1st Phase, Bommasandra,
Hosur Main Road, Bangalore-560099, INDIA

UNIT-II
Plot No. 127&128, Bommasandra IV Phase,
Yarandahally,Bangalore-560099,
Karnataka, India.

+91-9844013768

sales@williamsrefrigeration.in
info@williamsrefrigeration.in

www.williamsrefrigeration.co.in

Facebook Youtube Instagram