

REQUEST FOR QUOTATION (RFQ) – PREMIUM AUTOMOTIVE COMPONENTS

Buyer / Company Name: DOME BMW Nation

Target Market: European Union (Premium/Classic Automotive Restoration & Aftermarket)
Quality Requirement: OEM Grade / High-Tech Premium Only (Zero-Defect Policy)

PRODUCT SPECIFICATIONS & TECHNICAL REQUIREMENTS

1. Intake Manifold Gaskets (BMW M73 V12 Application)

- ❑ **Component Type:** Carrier-type / Rubber-to-Metal Bonded Intake Gasket.
- ❑ **Elastomere Material:** FKM (Fluorocarbon Rubber / Viton) according to **ASTM D1418 / ISO 1629**. Continuous thermal resistance: -40°C to +220°C.
- ❑ **Carrier Plate Material:** **SUS 304 (Austenitic Stainless Steel)** only. Cold Rolled Carbon Steel (SPCC) is strictly rejected.
- ❑ **Vulkanization/Bonding:** Chemical primer application (**Chemlok®** or **Megum™**) required. Must pass **ISO 2409 (Cross-cut test)** Class 0/1.

2. Stabilizer Bushings (Anti-Roll Bar / Custom Size Application)

- ❑ **Base Material:** EPDM (Ethylene Propylene Diene Monomer) rubber according to **ASTM D2000**, Hardness: **70-75 Shore A**.
- ❑ **Inner Liner (Maintenance-Free):** Co-vulkanized **PTFE (Polytetrafluoroethylene / Teflon) Mesh/Liner** for self-lubricating, zero-grease, anti-squeak operation.
- ❑ **Tooling/Sizing Requirement:** Capability to produce custom Inner Diameters (ID) down to **0.2 mm increments** (to compensate for sway bar wear).

3. Tail Light Lenses & Exterior Moldings (Anti-Yellowing UV Protection)

- ❑ **Lens Base Material:** **PMMA (Polymethyl Methacrylate / Optical Grade)** according to **ISO 24025** with anti-UV additive masterbatch.
- ❑ **Surface Treatment:** **Siloxane-based Hard Coating** for permanent UV and scratch protection. Must pass 2000-hour Xenon-Arc weathering test (**ISO 4892-2**).
- ❑ **Molding Base:** Co-extruded EPDM with integrated **SUS 304 Stainless Steel core insert**.

4. Electrochromic Mirror Glasses (Auto-Dimming Application)

- ❑ **Active Agent:** Hermetically sealed **Viologen-based Electrochromic Gel**.
 - ❑ **Glass Quality:** **Float Glass** with high-reflectivity Chromium/Silver coating according to **ISO 9050**.
 - ❑ **Operating Voltage:** **1.2V – 1.5V DC** (OEM system compatible). Must pass 85°C / 85% RH for 5000 cycles.
-

COMMERCIAL & QUALITY TERMS

- **Initial Order Quantity (Validation Batch):** 20 – 50 units per item for real-world quality control, fitment testing, and reference build.
- **Future Volume Expansion:** Based on Validation Batch approval, target distribution across EU BMW Enthusiast Network.
- **Tooling Cost:** Please specify **Molding / Tooling Fees** separately for small-batch customization.
- **Certifications Required:** Please provide **ISO/TS 16949**, **CE Certificates / Declaration of Conformity**, and **ASTM/ISO Material Test Reports**.

Contact Person Email: domsodi.zoltan.mail@gmail.com

WeChat : dome_bmw_sourcing
