

BASS HORN SUBWOOFER

BC118

SINGLE 18" BASS HORN SUBWOOFER

Half-weight bass horn with a 380 cm path, built around the B&C 18DS115.

1 x 18"

B&C 18DS115

380 cm

HORN PATH LENGTH

OVERVIEW

BC118 is a single-driver folded bass horn subwoofer. It is one half of a dual-18 horn split into its own cabinet, so each box weighs half as much and is easier to transport. The horn is redesigned around the B&C 18DS115 with a 380 cm path, extending low-frequency loading and output beyond the dual-18 design it derives from. Two BC118s placed side by side form one full-size horn mouth.

SYSTEM SPECIFICATIONS

MAX SPL (CONT. / PEAK)	TBD
OPERATING RANGE	26 Hz - 150 Hz (-3 dB) 22 Hz - 185 Hz (-10 dB)
SENSITIVITY	TBD
POWER HANDLING	1700 W cont. / 6800 W peak
NOMINAL IMPEDANCE	8 Ω
RECOMMENDED PROCESSING	20 Hz HP, 24 dB/oct Butterworth

CONNECTION & MECHANICAL

SYSTEM OPERATION	1 amplifier channel with dedicated DSP processing
INPUT CONNECTORS	2 x Neutrik NL4, parallel link
HORN PATH LENGTH	380 cm, folded
ENCLOSURE MATERIAL	18 mm Baltic birch plywood
FINISH	Polyurea coating
DIMENSIONS / WEIGHT	1524 x 762 x 762 mm / 116 kg

SECTION SPECIFICATIONS

1 x 18 INCH LF SECTION B&C 18DS115 Power: TBD Sensitivity: TBD	380 CM FOLDED HORN PATH Designed around the 18DS115 parameters	2 x BC118 PAIRED CONFIGURATION Side by side, forms one full-size horn mouth
---	--	---



WIRING:

2x Neutrik NL4 Speakon, wired in parallel

LF: Pin 1+/- | 8Ω Nominal
Pin 2+/- | Not connected in the cabinet

Second NL4 links to the next cabinet.

OPERATIONAL REQUIREMENTS

- Processor preset:** Required. Apply the approved high-pass filter, equalisation, time alignment, polarity and limiter settings before operation. The stated operating range is only valid with the final approved system preset.

Deployment: Ground stacked. Place cabinets in pairs, side by side, for full-size horn loading. Stacking beyond two units high requires a verified, secured configuration.