

FULL-RANGE LOUDSPEAKER

DA46

4-WAY FULL-RANGE HORN LOUDSPEAKER

Compact 4-way single-horn system with B&C neodymium transducers.

4-WAY ACTIVE

B&C TRANSDUCERS

40° x 60°

NOMINAL COVERAGE

OVERVIEW

DA46 is a four-way full-range horn loudspeaker built around B&C transducers: two 12NDL88 12-inch low-frequency drivers, two 5NSM38 5-inch midrange drivers and a DCX354 dual-diaphragm coaxial compression driver covering the high and very-high bands. All four bands share a single 40° x 60° horn, each entering the flare at a position chosen for phase alignment at crossover. The fourth band gives more output and headroom than a conventional 3-way horn of the same size.

SYSTEM SPECIFICATIONS

MAX SPL (CONT. / PEAK)	138 dB / 144 dB, 1 m
OPERATING RANGE	65 Hz - 18 kHz (±3 dB) 55 Hz - 20 kHz (-10 dB)
SENSITIVITY (LF)	107 dB, 1 W / 1 m
POWER HANDLING	1760 W AES / 3520 W program
CROSSOVER POINTS	300 Hz / 1 kHz / 4.5 kHz
RECOMMENDED AMPLIFIER	D&A DAP-8 (2 cabinets per unit)

CONNECTION & MECHANICAL

SYSTEM OPERATION	4-way active, 4 amplifier channels with DSP
INPUT CONNECTORS	1 x Neutrik NL8 in + 1 x NL8 link
NOMINAL COVERAGE	40° horizontal / 60° vertical
ENCLOSURE MATERIAL	18 mm Baltic birch plywood
FINISH	Polyurea coating
DIMENSIONS / WEIGHT	737 x 567 x 577 mm / 53.5 kg

SECTION SPECIFICATIONS

2 x 12 INCH LF · 55 - 300 HZ B&C 12NDL88 1400 W AES, 4 Ω 107 dB, 1 W / 1 m	2 x 5 INCH MF · 300 HZ - 1 KHZ B&C 5NSM38 220 W AES, 4 Ω 110 dB, 1 W / 1 m	1.4 INCH COAX MF HMF · 1 - 4.5 KHZ B&C DCX354 (MF) 90 W AES, 8 Ω 113 dB, 1 W / 1 m	1.4 INCH COAX HF HF · 4.5 - 20 KHZ B&C DCX354 (HF) 50 W AES, 8 Ω 113 dB, 1 W / 1 m
---	---	---	---



WIRING:

1x Neutrik NL8 Speakon + 1x NL8 link

LF: Pin 1+/- | 4Ω Nominal
MF: Pin 2+/- | 4Ω Nominal
HMF: Pin 3+/- | 8Ω Nominal
HF: Pin 4+/- | 8Ω Nominal

OPERATIONAL REQUIREMENTS

Processor preset: Required. Apply the approved crossover filters, equalisation, time alignment, polarity and limiter settings before operation. The stated operating range is only valid with the final approved system preset.

Deployment: Flown or ground stacked. Any flown deployment requires approved, documented enclosure hardware and an independently verified rigging solution. Cabinet uses multiple M10 rigging points.