

HIGH-OUTPUT LOUDSPEAKER

DA610

3-WAY ACTIVE HORN-LOADED LOUDSPEAKER

High power density system for large-scale live sound reinforcement.

3-WAY ACTIVE

SYSTEM CONFIGURATION

80° x 45°

NOMINAL COVERAGE

OVERVIEW

DA610 is a high-output, three-way horn-loaded main loudspeaker system developed for primary FOH use. The architecture combines a six-driver 10-inch low-frequency section, horn-loaded mid-frequency section and multi-driver high-frequency section using optimized waveguide. It is intended for operation only with the approved DSP preset, matched amplification and protection limiters.

SYSTEM SPECIFICATIONS

MAX CONTINUOUS SPL	140 dB, 1 m, processed
LOW-FREQUENCY SECTION	6 x 10", 3.5" VC
MID-FREQUENCY SECTION	4 x 6.5", 2" VC
HIGH-FREQUENCY SECTION	8 x 1" exit, 2" diaphragm titanium drivers
OPERATING RANGE	55 Hz - 17 kHz (-6 dB, processed)

CONNECTION & MECHANICAL

SYSTEM OPERATION	4 amplifier channels with dedicated DSP processing
INPUT CONNECTORS	1 x Neutrik NL8
NOMINAL COVERAGE (-6 DB)	80° horizontal coverage / 45° vertical coverage
ENCLOSURE MATERIAL	18 mm birch plywood
FINISH	Textured Warnex coating
DIMENSIONS / WEIGHT	915 x 610 x 610 mm / 104Kg

SECTION SPECIFICATIONS

6 x 10 INCH LF SECTION 4800 W AES 103 dB SPL, 1 W / 1 m	4 x 6,5 INCH HORN-LOADED MID 1000 W AES 110 dB SPL, 1 W / 1 m	8 x 1 INCH HF SECTION 560 W AES 112 dB SPL, 1 W / 1 m
---	---	---



WIRING:

1x Neutrik NL8 Speakon

LF: Pin 1+/- | 12Ω Nominal, Bridge

MF: Pin 3+/- | 8Ω Nominal

HF: Pin 4+/- | 8Ω Nominal

Pins 1- and 2+ are not connected in the cabinet

OPERATIONAL REQUIREMENTS

Processor preset: Required. Apply the approved crossover filters, equalisation, time alignment, polarity and limiter settings before operation. The stated operating range is only valid with the final approved system preset.

Deployment: Flown or ground stacked. Any flown deployment requires approved, documented enclosure hardware and an independently verified rigging solution. Cabinet uses multiple M10 rigging points.