FAST FILL SYSTEMS

PRODUCT CATALOGUE **2027**

# FUEL FASTER. WORK LONGER.



MADE IN USA ★ PROUDLY ★

QUALITY. SERVICE. INNOVATION.



# FAST FILL SYSTEMS

Before Fast Fill Systems reached customers around the world, its story began with Dean Mackey in a small home garage, repairing and rebuilding diesel fuel nozzles.

Those early days were hands-on: taking worn equipment apart, understanding what had failed and putting it back to work. That attention to the details became part of the company's foundation—a commitment to craftsmanship and to the people who depend on the equipment every day.

What began as Nozzle Tech, USA grew into Fast Fill Systems, carrying that commitment into fueling and fluid transfer solutions for demanding operations worldwide.

This photograph captures a moment in those beginnings. Today, it reminds us that every product we build and every customer we support is part of a story that started small—and continues through the work we do together.

**Quality. Service. Innovation.**

2055 S. Tracy Hall Parkway, Provo, UT 84606

801.491.3600

orders@fastfillsystems.com

www.fastfillsystems.com

# ENGINEERED WITH PURPOSE. BUILT FOR THE FIELD.

Every component has a job to do—and people who depend on it. At Fast Fill Systems, we bring design, engineering and testing together to develop fueling and fluid transfer solutions for demanding operations.

We evaluate products before they reach the field and continue refining our range as customer needs evolve. Our focus is practical: helping crews fuel efficiently, service equipment and keep operations moving.








# FIND WHAT YOU NEED

## PRODUCTS

About Us 06
Fuel Nozzles 08
Rebuilds 24
Fuel Receivers 26
Pressureless 38
Vents & Breathers 46
Kits & Systems 58
Fluid Couplers 64
Matrix 72
FAQ 84
Distributor Network 86
Become a Distributor 87
How to Request a Quote 88

To offer you a more engaging visual experience, some images in this catalog have been created using Artificial Intelligence (AI). For this reason, the visual appearance may vary slightly from the actual product; however, Fast Fill Systems guarantees that all technical information and data provided are 100% real and accurate.

# ABOUT US



# It started with a fuel nozzle.


Our story began in a small home garage, where Nozzle Tech, USA LLC repaired and rebuilt diesel fuel nozzles. Working with equipment that had already spent time in the field gave the business a practical starting point: understanding the products people relied on and the demands they faced every day.

Today, Fast Fill Systems brings that focus to fueling and fluid-transfer equipment for heavy-duty operations. From the nozzle in your operator's hands to the components on your tank, our products serve the people who keep equipment working.

Quality. Service. Innovation. These values connect our beginnings with the work we do today.

# FUEL NOZZLES



## Make every fueling connection count.

Your operators handle a fuel nozzle every time a machine comes in to refuel. Its weight, grip and connection all become part of their working day. Fast Fill fuel nozzles bring together rugged construction and fast-fill functionality for demanding equipment and environments. Explore the range to find the handling characteristics, flow capacity and configuration that fit the way your operation works.

# ATLAS N150ATp

FUEL NOZZLES




**Front End Plug**
**P150T**

• Keeps the latching mechanism of the nozzle clean from dirt and grime for fast, clean coupling








Our state-of-the-art Atlas nozzle is rated for flow rates up to 567 LPM (150 GPM) and includes 1-1/2” NPT inlet threads for an easy retrofit into existing fueling systems. The N150ATp uses twelve stainless-steel ball bearings to ensure secure latching to the receiver, while its compact, lightweight design and stainless-steel castle provide durability for demanding fueling applications.

## 150 GPM
**FAST REFUELING (567 LPM)**

## BUILT FOR

Mining equipment ·
Construction equipment ·
Fuel trucks ·
Agriculture ·
Rail ·
Industrial fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | N150ATp |
| Minimum Flow | 95 LPM / 25 GPM |
| Maximum Flow | 567 LPM / 150 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 1-1/2 in NPT |
| Latching Mechanism | 12 stainless-steel ball bearings |

**View in room**

Scan the QR code below to view this product in room virtually.

# SURELOC

## N150SLp

FUEL NOZZLES




**Front End Plug**
**P150 - SureLoc**
• Keeps the latching mechanism of the nozzle clean from dirt and grime for fast, clean coupling








The SureLoc 150 diesel fuel nozzle delivers flow rates up to 567 LPM (150 GPM) through a 1-1/2” NPT inlet. Twelve stainless-steel ball bearings provide secure engagement with the receiver, while its thick-wall housing and all-metal construction support demanding daily use. A powder-coated, non-slip finish improves grip during handling, making the SureLoc 150 a practical choice for mining, construction and heavy-equipment fueling.

## 150 GPM
**FAST REFUELING (567 LPM)**

## BUILT FOR

Mining equipment ·
Construction equipment ·
Fuel trucks ·
Agriculture ·
Rail ·
Industrial fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | N150SLp |
| Minimum Flow | 95 LPM / 25 GPM |
| Maximum Flow | 567 LPM / 150 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 1-1/2 in NPT |
| Latching Mechanism | 12 stainless-steel ball bearings |

**View in room**

Scan the QR code below to view this product in room virtually.

# PITBOSS

# N150PBp

FUEL NOZZLES




**Front End Plug**
**P150 - PitBoss**

• Keeps the latching mechanism of the nozzle clean from dirt and grime for fast, clean coupling








The PitBoss diesel fuel nozzle is built for demanding field conditions, with flow rates up to 567 LPM (150 GPM) and a 1-1/2" NPT inlet. Its Elastodog latching clips support coupling in tough working environments, while a piston-driven shutoff mechanism and reduced internal component count keep the design straightforward. All-metal construction and a powder-coated, non-slip finish provide durability and a secure grip for everyday heavy-equipment fueling.

## 150 GPM
**FAST REFUELING (567 LPM)**

## BUILT FOR

Mining equipment ·
Construction equipment ·
Fuel trucks ·
Agriculture ·
Rail ·
Industrial fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | N150PBp |
| Minimum Flow | 95 LPM / 25 GPM |
| Maximum Flow | 567 LPM / 150 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 1-1/2 in NPT |
| Latching Mechanism | Elastodog clips |

**View in room**

Scan the QR code below to view this product in room virtually.

# ATTICUS

## N1200ATT

FUEL NOZZLES








The Atticus Heavy-Duty Nozzle (N1200ATT / VR300 Series) is engineered to endure and built to perform under the most adverse environmental conditions. Designed for high-volume fueling operations, it delivers up to 1200 liters per minute (317 GPM) while maximizing operator efficiency and ergonomics.

**317 GPM**

**FAST REFUELING (1.200 LPM)**

## BUILT FOR

Large mining equipment ·
Heavy construction equipment ·
Fuel trucks and service fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | Atticus N1200ATT / VR300 |
| Minimum Flow | 567 LPM / 150 GPM |
| Maximum Flow | 1,200 LPM / 317 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 2-1/2" NPT |
| Latching Mechanism | Dry Break / Quick Disconnect |

**View in room**

Scan the QR code below to view this product in room virtually.

# SURELOC 1000

## N1000PSLp

FUEL NOZZLES




**Front End Plug**
**P150 - SureLoc 1000**
• Keeps the latching mechanism of the nozzle clean from dirt and grime for fast, clean coupling








The SureLoc 1000 diesel fuel nozzle is designed for high-capacity equipment, delivering flow rates up to 1,000 LPM (264 GPM) when paired with the specified pressureless system. Its 2” NPT inlet supports high-flow fueling, while twelve stainless-steel ball bearings provide secure receiver engagement. A thick-wall, all-metal exterior and powder-coated, non-slip finish combine durability with confident handling in demanding mining and heavy-equipment applications.

## 264 GPM
**FAST REFUELING (1,000 LPM)**

## BUILT FOR

Mining equipment ·
Construction equipment ·
Fuel trucks ·
Agriculture ·
Rail ·
Industrial fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | N1000PSLp |
| Minimum Flow | 567 LPM / 150 GPM |
| Maximum Flow | 1,000 LPM / 264 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 2 in NPT |
| Latching Mechanism | 12 stainless-steel ball bearings |

**View in room**

Scan the QR code below to view this product in room virtually.

# ATLAS N800ATp

FUEL NOZZLES




**Front End Plug**
**P150T**

• Keeps the latching mechanism of the nozzle clean from dirt and grime for fast, clean coupling








The Atlas N800 diesel fuel nozzle delivers flow rates up to 800 LPM (211 GPM) through a 2” FNPT inlet for high-flow fueling applications. Twelve stainless-steel ball bearings provide secure engagement with the receiver, while its compact, lightweight design supports everyday handling. Available with a stainless-steel or aluminum castle, the Atlas N800 combines durable construction with a weight of 2.79 kg (6.15 lb).

## 211 GPM
**FAST REFUELING (800 LPM)**

## BUILT FOR

Mining equipment ·
Construction equipment ·
Fuel trucks ·
Agriculture ·
Rail ·
Industrial fleets ·




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | N800ATp |
| Minimum Flow | 95 LPM / 25 GPM |
| Maximum Flow | 800 LPM / 211 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Fuel Port | 2 in FNPT |
| Latching Mechanism | 12 stainless-steel ball bearings |

**View in room**

Scan the QR code below to view this product in room virtually.

FUEL NOZZLES



## Fuel Adapter

### Part No. A150A

Straight splash-fill adapter for directing fuel from a compatible Fast Fill nozzle into an open tank.

| Configuration | Application |
|---|---|
| Straight | Open-tank filling |



## Fuel Adapter

### Part No. A150B

Angled splash-fill adapter for directing fuel into an open tank where a 90-degree configuration suits access.

| Configuration | Application |
|---|---|
| 90° | Open-tank filling |



## Fuel Adapter

### Part No. A150C

Angled splash-fill adapter for directing fuel into an open tank where a 45-degree configuration suits access.

| Configuration | Application |
|---|---|
| 45° | Open-tank filling |



## Breakaway Coupler

### Part No. AB2

Hose breakaway coupler designed to separate under excessive pulling force, helping limit damage to the fueling connection.

| Connection | Available Sizes |
|---|---|
| Female NPT | 1 / 1-1/4 / 2 / 3 in |








## Straight Hose Swivel

### Part No. S150 / S200 / S215 / S512

Aluminum swivels connect the fueling hose to the nozzle, allowing rotation to reduce hose twisting during handling.

| Part No. | Female Connection | Male Connection |
|---|---|---|
| S150 | 1-1/2 in NPT | 1-1/2 in NPT |
| S200 | 2 in NPT | 2 in NPT |
| S215 | 1-1/2 in NPT | 2 in NPT |
| S512 | 2 in NPT | 1-1/2 in NPT |

## Replacement Fuel Nozzle Plug

### Part No. P150

Protects the nozzle's front-end latching area from dirt and debris between fueling operations.

| Material | Attachment |
|---|---|
| Aluminum | Aircraft cable |












# Give your nozzle a new working life.

Daily use takes its toll on fueling equipment. Wear, leaks and damaged components can make a dependable nozzle ready for service. Fast Fill Systems' rebuild service restores worn nozzles through a thorough process of disassembly, cleaning, refinishing and testing—helping you get more from the equipment you already own.

## The process

Each nozzle is logged by company and serial number before being fully disassembled. Components are separated for inspection, and metal parts are cleaned and prepared for rebuilding. Applicable exterior parts are powder coated for a durable finish and a secure, non-slip grip.

## Tested before return

Every completed rebuild goes through a 16-point testing process. Technicians check for leaks and other failures, verifying flow rate and shutoff pressure against the applicable requirements before the nozzle returns to service.


## READY FOR A REBUILD?

Tell us the nozzle model, serial number and the issue you're experiencing. Our team will help you confirm service eligibility and the next steps.

**contact@fastfillsystems.com**

# FUEL RECEIVERS



## A dependable connection starts at the tank.

The receiver is where your fueling equipment meets the machine. It needs to stand up to repeated connections while matching the requirements of the nozzle and tank-side system. Fast Fill offers receiver options for different mounting, material and service needs, including check-valve configurations designed to allow receiver replacement without draining the tank. Find the connection that fits your installation and maintenance approach.

# CHECK VALVE
## R800CVc

FUEL RECEIVERS




**Receiver Cap C150**

• Protects the receiver connection from dirt and debris between fueling operations for clean, reliable coupling.








Keep receiver maintenance from becoming a tank-draining job. The R800CVc High Flow Check Valve Receiver is documented for diesel fueling applications up to 800 LPM. Its internal one-way valve retains fuel in the tank when the matched receiver is removed, helping reduce fuel handling and service downtime. Designed for demanding equipment installations, it combines a high-flow connection with practical access for receiver replacement.

## BUILT FOR

Diesel equipment tanks · Service-intensive fleets · Mining and construction equipment

**NO TANK DRAINING**
FOR MATCHED RECEIVER REPLACEMENT




## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | R800CVc |
| Maximum Flow | 800 LPM / 211 GPM |
| Application | Diesel fueling |
| Valve Function | One-way check valve |
| Service Function | Receiver replacement without tank draining |
| **Installation Tool** | R150CVSW — Check Valve Wrench; R150SW — Deep Socket Tool |

**View in room**

Scan the QR code below to view this product in room virtually.

FUEL RECEIVERS




## Standard Aluminum Receiver

### Part No. R150Ac

All-aluminum receiver offered as an alternative to the steel version for applications specified for the standard receiver.

| Material | Reference Application |
|---|---|
| Aluminum | R150S-A |




## Replacement Receivers

### For Check Valves & Shutoff Valves

Replacement receivers for check valve and shutoff valve assemblies. Allow receiver replacement without draining the fuel tank when installed with the corresponding valve assembly.

| Part No. | Application |
|---|---|
| R150CVRc | Check valve |
| R150CVRc-J | Shutoff valve |



## Weld-On Flange

### Part No. FFF4C

Creates a recessed fill point to help protect compatible receivers and tank inlet components from external contact.

| Connection | Mounting |
|---|---|
| 2 in FNPT | Weld-on |



## Bolt-On Flange

### Part No. FFF5C

Provides a recessed, protected fill point with bolt-on mounting for compatible receivers, check valves and pressureless shutoff valves.

| Connection | Mounting |
|---|---|
| 2 in FNPT | Bolt-on |




## Deep Socket Tool

### Part No. R150SW

Deep socket tool for installing new receivers and removing worn or damaged receivers from the tank connection.

| Socket Size | Function |
|---|---|
| 2-1/2 in | Installation and removal |



## Check Valve Wrench

### Part No. R150CVSW

Service wrench for check valve installation and removal, with an open-back design for use with the R150SW socket.

| Companion Tool | Design |
|---|---|
| R150SW | Open back |



## CAT Adapter Flange

### Part No. FFF6C-CAT

Bolt-on flange for flush-mount bell housing installations, with 3/8"-16 TPI female mounting threads.

| Mounting Thread | Mounting |
|---|---|
| 3/8"-16 TPI female | Bolt-on |




## Check Valve Evacuation Tool

### Part No. R150CVEP

Provides an evacuation connection for draining fuel from compatible shutoff valve and check valve assemblies.

| Function | Application |
|---|---|
| Tank draining | Matched valve assembly |



## Receiver Caps

### Part No. C150 / C150A / C150BP

Protective caps help keep dirt and debris away from the fuel receiver connection between fueling operations. Available in plastic and aluminum, with a plastic option for flange-mounted receivers.

| Part No. | Material | Application |
|---|---|---|
| C150 | Plastic | Fuel receiver |
| C150A | Aluminum | Fuel receiver |
| C150BP | Plastic | Flange-mounted receiver |

FUEL RECEIVERS

# STANDARD RECEIVER

## R150Sc-A




**Receiver Cap C150**

• Protects the receiver connection from dirt and debris between fueling operations for clean, reliable coupling.








Give your fueling connection a durable foundation. The Standard Receiver is machined from solid steel and nickel-plated to withstand repeated coupling in demanding equipment service. Rated for diesel flow up to 800 LPM, it provides a practical connection point for compatible fast-fill nozzles. A protective plastic cap helps keep contamination away from the receiver when it is not in use.

## BUILT FOR

Mining equipment ·
Construction equipment ·
Agricultural equipment ·
Diesel fleets ·




## SOLID STEEL

NICKEL-PLATED FOR REPEATED COUPLING

## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | R150Sc-A |
| Maximum Flow | 800 LPM / 211 GPM |
| Maximum Operating Pressure | 8.6 bar / 125 PSI |
| Tank Installation Thread | 2 in NPT |
| Construction | Nickel-plated steel |
| Standard Shutoff Option | 9 PSI configuration |
| Protective Cap | Plastic cap included |
| **Installation Tool** | R150SW — 2-1/2 in Deep Socket Tool |

**View in room**

Scan the QR code below to view this product in room virtually.

FUEL RECEIVERS




## Standard Fuel Receiver

### Part No. R150Sc-B

For applications requiring a lower tank shutoff pressure.

| Spring Rating | Poppet Color |
|---|---|
| 7 PSI / 0.48 bar | Red |




## Standard Fuel Receiver

### Part No. R150Sc-D

For installations with high static head or back pressure.

| Spring Rating | Poppet Color |
|---|---|
| 11 PSI / 0.76 bar | Blue |






## Standard Fuel Receiver

### Part No. R150Sc-E

For installations with particularly high static head or back pressure.

| Spring Rating | Poppet Color |
|---|---|
| 13.5 PSI / 0.93 bar | Purple |





## Standard Fuel Receiver


### Part No. R150Sc-J

Designed exclusively for use with pressureless fueling systems.

| Spring Rating | Poppet Color |
|---|---|
| 13.5 PSI / 0.93 bar | Green |

# PRESSURELESS



## Lose the pressure. Not the performance.

Pressureless fill systems bring unique advantages to fast delivery of fuel and other fluids. The benefit is that your tank is protected from the internal pressures that are typically required to shut off a pressure-sensitive nozzle. In these Fast Fill systems, the pressure is isolated within the level control and signal lines to alleviate unnecessary strain on the tank walls. The level controllers are adjustable for higher or lower shutoff levels, according to your specific needs. Finally, in the two-part level control/shutoff valve, the fuel receiver can be replaced without the need to drain your tank, as it serves as a check valve to hold back the tank's fluid.

# HIGH FLOW PRESSURELESS

## PLA-M SV




PRESSURELESS






Fill large tanks at high flow without using tank pressurization as the shutoff signal. Paired with the SureLoc 1000 nozzle, a system equipped with the PLA-M SV shutoff valve supports flow rates up to 1,000 LPM. The level control sets the target fill level and transmits a hydraulic signal to close the inlet shutoff valve, while internal or external signal-line connections provide installation flexibility. The shutoff valve also allows the receiver to be serviced without draining the tank.

## BUILT FOR

Large diesel tanks ·
Mining equipment ·
High-volume equipment fueling ·




## 1000 LPM

**PRESSURELESS FILLING WITH SURELOC 1000**

## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| System | PLA-M SV |
| Maximum System Flow | 1,000 LPM / 264 GPM* |
| Maximum Operating Pressure | 8.6 bar / 125 PSI** |
| Tank Installation Thread | 2 in NPT |
| Level Control | Adjustable automatic shutoff |
| Signal-Line Routing | Internal or external |
| Required Nozzle | SureLoc 1000 — N1000PSLp |

** With the N1000PSLp nozzle and a correctly sized installation.*
*** Component operating limit; not an allowable tank pressure.*

**View in room**

Scan the QR code below to view this product in room virtually.

PRESSURELESS



## Bellhousing Replacement Shutoff Valve

### Part No. PLA150-M SVEBH

Flange-mounted inlet shutoff valve designed to replace the FFF5C bolt-on bellhousing in the specified pressureless installation.

| Mounting | Signal Connection |
|---|---|
| 6-bolt flange | External #6 JIC |



## Remote Mount Can

### Part No. PLA150-M RRM2

Allows the shutoff valve and receiver assembly to be mounted remotely to suit the equipment's fueling layout.

| Included Receiver | Signal Connection |
|---|---|
| R150CVRc-J | External #6 JIC |



## Plastic Tank Adapter

### Part No. PLA150-M PTF

Provides a 2" NPT connection on plastic fuel tanks for the installation of compatible pressureless system components.

| Connection | Tank Application |
|---|---|
| 2 in NPT | Plastic fuel tanks |




## Evacuation Port

### Part No. PLA150-M EP

Provides an evacuation connection for draining fuel from compatible shutoff valve and check valve assemblies.

| Function |
|---|
| Tank draining |



## Code 61 Inlet Shutoff Valve

### Part No. PLA150-M SV61-E

Flange-mounted shutoff valve with a Code 61 hose connection for installations using a remotely mounted receiver.

| Hose Connection | Signal Connection | Mounting |
|---|---|---|
| 2 in Code 61 | External #6 JIC | 6-bolt flange |




## Direct-Mount Inlet Shutoff Valve

### Part No. PLA150-M SVFE

Flange-mounted shutoff valve supplied with a two-piece direct-mount receiver and an external hydraulic signal-line connection.

| Mounting | Signal Connection | Includes |
|---|---|---|
| 6-bolt flange | External #6 JIC | Two-piece receiver |




## Vent & Receiver Flanges

### Part No. PLA150-M VF / PLA150-M RF

Six-bolt flanges for compatible pressureless systems. PLA150-M VF mounts the vent; PLA150-M RF mounts the receiver. Select according to mounting and connection requirements.

| Part No. | Type | Mounting / Connection |
|---|---|---|
| PLA150-M VF | Vent Flange | 120 mm reference size |
| PLA150-M RF | Receiver Flange | 2 in NPT · CAT 221-5303 |



## Hydraulic Signal Line

### Part No. PL-P-6 / PL-P-6-C /PL-P-6-B

Stainless-steel braided signal line with a PTFE liner for transmitting the hydraulic shutoff signal in internal or external installations.

| Part No. | Length | Construction |
|---|---|---|
| PL-P-6 | 10 ft / 3.05 m | PTFE liner / stainless braid |
| PL-P-6-C | 6 ft / 1.83 m | PTFE liner / stainless braid |
| PL-P-6-B | 3 ft / 0.91 m | PTFE liner / stainless braid |

PRESSURELESS

# SMALL TANK PRESSURELESS

## PLA 80-HVSC









Bring pressureless filling to compact tank installations. The PLA80 combines filling and venting through a single 2 in NPT tank opening, with an adjustable shutoff level to suit the installation. Its compact arrangement supports individual tank shutoff in correctly configured single- or multi-tank systems, while filtered venting helps limit contamination. Select the nozzle, vent and flow configuration to match the tank and fluid being handled.

## ONE TANK PORT

**FILL AND VENT THROUGH ONE OPENING**

## BUILT FOR

Agricultural equipment ·
Compact construction equipment ·
Transit fleets ·
Multi-tank installations ·




## KEY SPECIFICATIONS


| Parameter | Value |
|---|---|
| System | PLA80/PLA80-HVSC |
| Tank Installation Thread | 2 in NPT |
| Fluid Inlet Thread | 1-1/4 in FNPT |
| Vent Port Thread | 1 in FNPT |
| Level Control | Adjustable automatic shutoff |
| Tank Configuration | Single tank or configured multi-tank system |
| Venting Options | Low-profile or remote filter vent |

**View in room**

Scan the QR code below to view this product in room virtually.

# FUEL VENTS



## Control what you can’t see.

Vents, or breathers as they are commonly known, are another important component in a smoothly functioning fuel system. Vents play a vital role in the fill level and shutoff of your tank; however, they provide the easiest access point for dust and contaminants to enter your fuel system. Our filtered vents make use of check valves to ensure that outgoing air bypasses the filter, and incoming air is channeled through it. Fast Fill Systems pressurized vents also serve a dual purpose as a fail-safe pressure relief valve. Correct venting is pivotal in high-volume fueling.

# FILTERED FUEL VENT

## V150F


FILTERED FUEL VENT








Help keep airborne dirt out of the fuel tank with filtered breathing for pressurized fueling systems. The V150F directs incoming air through a 3-micron filter, while outgoing air and fuel vapor leave through a one-way valve. Available stem lengths support different fill-level requirements, combining tank venting, filtration and level control in a single assembly.




**3 MICRON**

**FILTERED AIR INTO THE TANK**

## BUILT FOR

Pressurized diesel fueling systems ·
Dusty worksites ·
Mining and construction equipment ·

## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | V150F |
| System Type | Pressurized fueling |
| Tank Installation Thread | 2 in NPT |
| Air Filter Rating | 3 micron |
| Published Relief Pressure | 13 PSI / approximately 0.90 bar |
| Level-Control Stem | 5 in standard; 7 in or 12 in optional |
| Replacement Filter | FFV-MF |

**View in room**

Scan the QR code below to view this product in room virtually.

FILTERED FUEL VENT




## Remote-Mount Filter Vent

### Part No. FFV150

Provides filtered tank breathing from a remote mounting location, with a universal bracket for installation flexibility.

| Mounting | Connection | Includes |
|---|---|---|
| Remote | Hose barb | Mounting bracket |




## High-Volume Vacuum Break

### Part No. FFV150-HV IR1

Filtered vent with a high-volume check valve designed to provide increased airflow area for the specified installation.

| Inlet Connection | Valve Type |
|---|---|
| 1 in NPT | High-volume check valve |




## Direct-Mount Filter Vent

### Part No. FFV150-PL

Provides filtered tank breathing through a direct connection to the compatible pressureless level-control assembly.

| Connection | Mounting |
|---|---|
| 1 in NPT | Direct |




## Low-Profile Filter Vent

### Part No. FFV150-LP

Provides filtered tank breathing in a low-profile arrangement for installations with limited space above the tank.

| Mounting | System Type |
|---|---|
| Low profile | Pressureless |




## Replacement Inlet Air Filter

### Part No. FFV-MF

Replacement filter element for compatible filtered vents, helping limit airborne contamination entering the tank.

| Filter Rating | Filtered Medium |
|---|---|
| 3 µm | Air |

FUEL VENTS

# STANDARD FUEL VENT

## V150








The V150 provides the venting and level-control function used in a traditional pressurized fast-fill system. Air escapes as fuel enters the tank. When fuel reaches the configured level, the vent closes so tank pressure can activate the matched nozzle's shutoff. Different stem lengths allow the installation to be configured for the required fill level.

## BUILT FOR

Pressurized diesel fueling systems ·
Tank retrofits ·
Heavy equipment ·




## SET THE FILL LEVEL

STEM OPTIONS FOR YOUR INSTALLATION

## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | V150 |
| System Type | Pressurized fast-fill fueling |
| Primary Function | Tank venting and fill-level control |
| Standard Stem Length | 5 in / 127 mm |
| Optional Stem Lengths | 7 in / 178 mm; 12 in / 305 mm |
| Shutoff Method | Vent closure enables pressure-based nozzle shutoff |

**View in room**

Scan the QR code below to view this product in room virtually.



## Fuel Vent with Bolt-On Flange

### Part No. V150B

Fuel vent configuration for tanks without an existing NPT port, using a bolt-on flange for mounting.

| Flange Connection | Includes | Bolts |
|---|---|---|
| 2 in NPT | Flange / nitrile gasket | Not included |



## Fuel Vent with Half Coupling

### Part No. V150A

Fuel vent configuration for retrofit installations requiring a welded threaded connection on the tank.

| Coupling Connection | Coupling Material | Mounting |
|---|---|---|
| 2 in FNPT | Steel | Weld-on coupling |



## Fuel Vent with Whistle Adapter

### Part No. V150W

Provides an audible signal as tank pressure rises during fueling, alerting the operator to the expected nozzle shutoff.

| Whistle Range |
|---|
| 5–7 PSI / 0.34–0.48 bar |



## High-Flow Fuel Vent

### Part No. V150H

Vent option for installations with higher fuel delivery rates, subject to matching the complete tank and fueling system.

| Published Fueling Range |
|---|
| Above 150 to 300 GPM |



## Safety Relief Fuel Vent

### Part No. V150SR

Provides an additional relief function alongside the V150 in installations specified for supplementary tank pressure relief.

| Cracking Pressure | Companion Vent |
|---|---|
| 13 PSI / 0.90 bar | V150 |



## Fuel Vent with NPT Adapter

### Part No. V150C

Vent configuration with a threaded swivel adapter for connecting a hose at the vent-cap opening.



## Fuel Vent with Anti-Vandalism Flange

### Part No. V150D

Protected mounting arrangement designed to help deter unauthorized removal of the vent from the tank.

| Mounting | Bolts |
|---|---|
| Locking flange arrangement | Not included |

# COMPLETE SYSTEM

PRESSURELESS SYSTEMS








# INSTALLED CONFIGURATION

## Controlled filling. Less tank stress.

Bring the fill connection, level control and tank venting together in one coordinated fueling system. Fast Fill Systems pressureless technology uses a hydraulic signal to close the inlet shutoff valve at the selected fuel level, without relying on tank pressurization to trigger shutoff. An adjustable level control sets the fill point, while a matched filter vent lets the tank breathe. In the two-part level-control and shutoff-valve arrangement, the receiver can be replaced without draining the tank.

### ADJUSTABLE FILL LEVEL

Set the shutoff point to suit the tank installation.

### FLEXIBLE INSTALLATION

Position the fill connection and level control to suit the equipment.

### SIMPLER RECEIVER SERVICE

Replace the matched receiver without draining the tank.

**View in room**

Scan the QR code below to view this product in room virtually.

PRESSURELESS SYSTEMS

# CONFIGURED AROUND YOUR TANK

## Part No. PLA150-IO KI


Each component has a clear role. Fuel enters through the receiver and shutoff valve while displaced air exits through the vent. When fuel reaches the selected level, the level control sends a hydraulic signal that closes the inlet valve and stops filling.

The shutoff signal stays within the control circuit, so the tank does not need to be pressurized to stop fuel delivery.

**FILL**
Fuel enters. Displaced air leaves.

**DETECT**
The level control responds at the selected fill level.

**STOP**
The hydraulic signal closes the inlet shutoff valve.




PRESSURELESS SYSTEMS

# COMPACT SYSTEM. CONTROLLED FILLING.

## FFV150-LP

*Allows displaced air to escape during filling and filters incoming air as the tank breathes.*




## Mounting Flange

*Provides the mounting interface between the assembly and the tank.*

## PLA80

*Combines fuel entry, venting and automatic fill-level control through one tank opening.*

## Fuel Receiver

*Provides the connection point for the matched fueling nozzle.*


Fuel travels from the receiver through the fill pipe to the PLA80 assembly. As the tank fills, displaced air leaves through the vent connection and FFV150-LP filter vent.

When fuel reaches the selected level, the integrated control stops incoming flow. Filling and venting share the same tank opening, simplifying the tank layout.

Typical installation shown. Receiver, piping and mounting hardware must be matched to the application.

# COUPLERS



## The right fluid. The right connection.

Four widely used couplers have been the primary means for fluid transfer of crankcase oils, coolant, hydraulic oils, and transmission oils. These couplers continue to provide a sturdy option and have been refined to be more reliable than ever. Options exist for remote bulkhead mounting, multiple thread options, and various latching mechanisms.


# SB100 SERVICE BOX









The SB100 Service Box brings multiple fluid service connections together in one organized location. By grouping receivers in a single panel, it helps technicians access service points more easily during routine maintenance. The receiver layout can be configured around the machine's service requirements, keeping essential connections together and clearly identified.




## ONE LOCATION

**CENTRALIZED ACCESS FOR ROUTINE SERVICE**



## KEY SPECIFICATIONS

| Parameter | Value |
|---|---|
| Model | SB100 |
| Product Type | Service Box |
| Configuration Shown | 5 service connections |
| Service Points Shown | Fuel, coolant, hydraulic, hydraulic tank drain and crankcase |
| Receiver Layout | Configurable to application requirements |

**View in room**

Scan the QR code below to view this product in room virtually.

# CRANKCASE COUPLERS




## Crankcase Nozzle

### Part No. N100p

Service nozzle for crankcase fluid transfer, compatible with the corresponding Standard and R-series receivers.

| Connection |
|---|
| 3/4 in MNPT |



## Crankcase Receiver

### Part No. R100c / R100Rc

Tank-side receiver providing the connection point for the N100p service nozzle.

| Type | R100c | R100Rc |
|---|---|---|
| Connection | 3/4 in MNPT | **External:** 1-5/8 in · 12 TPI<br>**Internal:** -16 ORB |



## Crankcase JIC Receiver

### Part No. R100Jc

Extended receiver for bulkhead mounting, allowing a female JIC hose connection on the opposite side of the panel.

| Connection Type | Mounting |
|---|---|
| JIC | Bulkhead |



## Receiver Jam Nut

### Part No. JN100

Jam nut for securing the corresponding R Series receiver in the specified mounting arrangement.

| Associated Receiver |
|---|
| R100Rc |





# COOLANT COUPLERS




## Coolant Nozzle

### Part No. N200p

Service nozzle for coolant fluid transfer, compatible with the corresponding Standard and R-series receivers.

| Connection |
|---|
| 1/2 in MNPT |



## Coolant Receiver

### Part No. R200c / R200Rc

Tank-side receiver providing the connection point for the N200p service nozzle.

| Type | R200c | R200Rc |
|---|---|---|
| Connection | 1/2 in MNPT | **External:** 1-3/16 in · 12 TPI<br>**Internal:** -10 ORB |



## Coolant JIC Receiver

### Part No. R200Jc

Extended receiver for bulkhead mounting, allowing a female JIC hose connection on the opposite side of the panel.

| Connection Type | Mounting |
|---|---|
| JIC | Bulkhead |



## Receiver Jam Nut

### Part No. JN200

Jam nut for securing the corresponding R Series receiver in the specified mounting arrangement.

| Associated Receiver |
|---|
| R200Rc |

# HYDRAULIC COUPLERS



## Hydraulic Nozzle

### Part No. N300p

Service nozzle for hydraulic fluid transfer, designed for use with the corresponding compatible receiver.

| Connection |
|---|
| 3/4 in FNPT |



## Hydraulic Receiver

### Part No. R300c / R300Rc

Tank-side receiver providing the connection point for a compatible hydraulic service nozzle.

| Type | R300c | R300Rc |
|---|---|---|
| Connection | 3/4 in MNPT | **External:** 1-7/8 in · 12 TPI<br>**Internal:** -20 ORB |



## Hydraulic JIC Receiver

### Part No. R300Jc

Extended receiver for bulkhead mounting, allowing a female JIC hose connection on the opposite side of the panel.

| Connection Type | Mounting |
|---|---|
| JIC | Bulkhead |



## Receiver Jam Nut

### Part No. JN300

Jam nut for securing the corresponding R Series receiver in the specified mounting arrangement.

| Associated Receiver |
|---|
| R300Rc |





# TRANSMISSION COUPLERS



## Transmission Nozzle

### Part No. N400p

Service nozzle for transmission fluid transfer, designed for use with the corresponding compatible receiver.

| Connection |
|---|
| 1/2 in MNPT |



## Transmission Receiver

### Part No. R400c / R400Rc

Tank-side receiver providing the connection point for a compatible transmission service nozzle.

| Type | R400c | R400Rc |
|---|---|---|
| Connection | 1/2 in MNPT | **External:** 1-5/16 in · 12 TPI<br>**Internal:** -12 ORB |



## Transmission JIC Receiver

### Part No. R400Jc

Extended receiver for bulkhead mounting, allowing a female JIC hose connection on the opposite side of the panel.

| Connection Type | Mounting |
|---|---|
| JIC | Bulkhead |



## Receiver Jam Nut


### Part No. JN400

Jam nut for securing the corresponding R Series receiver in the specified mounting arrangement.

| Associated Receiver |
|---|
| R400Rc |

# MATRIX



## No guesswork.
## No mix-ups.

Managing multiple fluids starts with making the right connection. Matrix couplers help organize fluid service points through color identification and matched nozzle-and-receiver configurations, helping reduce connection errors and the risk of cross-contamination.

The range includes Flat Face Matrix, Matrix 300 Series, MX High Flow, High Flow 3/4” Matrix, and Grease Matrix, with features tailored to different fluid-transfer requirements.

Available pairs, connection options, and operating specifications vary by family. Dedicated evacuation tools are available for selected families to support tank draining. Refer to each family’s product page for matching components and compatible accessories.

# FLAT FACE MATRIX




**Protective Plugs & Caps**

• Help keep nozzle and receiver connections free from dirt and debris between uses for clean, reliable coupling.








Flat Face Matrix couplers make cleaning before connection straightforward. The flat coupling surface wipes clean easily, while 12 color-coded, mechanically matched nozzle–receiver pairs help prevent incorrect connections and reduce cross-contamination during fluid transfer.

## Nozzle & Receiver Selection

| Nozzle Part No. | Matching Receiver Part No. | Color Code |
|---|---|---|
| FFN210 | FFR210c | |
| FFN220 | FFR220c | |
| FFN230 | FFR230c | |
| FFN240 | FFR240c | |
| FFN250 | FFR250c | |
| FFN255 | FFR255c | |
| FFN260 | FFR260c | |
| FFN265 | FFR265c | |
| FFN270 | FFR270c | |
| FFN275 | FFR275c | |
| FFN280 | FFR280c | |
| FFN285 | FFR285c | |

## Accessories

| Accessory | Part No. | Color Code |
|---|---|---|
| Flat Face Matrix Evacuation Tool | FFET290 | |

## KEY SPECIFICATIONS


| Operating Pressure | Standard Nozzle Thread | Standard Receiver Thread | Latching Mechanism | Construction |
|---|---|---|---|---|
| 103 bar / 1,500 PSI | 3/4 in FNPT | 3/4 in MNPT | Ball latching | Anodized aluminum and nickel-plated steel |

# MATRIX 300 SERIES




**Protective Plugs & Caps**

- Help keep nozzle and receiver connections free from dirt and debris between uses for clean, reliable coupling.








Matrix 300 Series couplers help keep fluid connections correctly matched across multi-fluid service operations. Ten color-coded nozzle–receiver pairs use mechanically matched interfaces to help prevent incorrect connections, with additional thread options available for different installations.

## Nozzle & Receiver Selection

| Nozzle Part No. | Matching Receiver Part No. | Color Code |
|---|---|---|
| N305p | R305c | |
| N307p | R307c | |
| N310p | R310c | |
| N320p | R320c | |
| N330p | R330c | |
| N340p | R340c | |
| N350p | R350c | |
| N360p | R360c | |
| N370p | R370c | |
| N380p | R380c | |

## Accessories

| Accessory | Part No. | Color Code |
|---|---|---|
| Matrix 300 Evacuation Tool | ET290 | |

## KEY SPECIFICATIONS

| Operating Pressure | Standard Nozzle Thread | Standard Receiver Thread | Construction |
|---|---|---|---|
| 103 bar / 1,500 PSI | 3/4 in FNPT | 3/4 in MNPT | Anodized aluminum and nickel-plated steel |

# MATRIX HIGH FLOW




**Protective Plugs & Caps**

• Help keep nozzle and receiver connections free from dirt and debris between uses for clean, reliable coupling.








MX High Flow dry-break couplers combine durable construction with easy-to-identify fluid connections. Seven color-coded, mechanically keyed nozzle–receiver pairs help prevent incorrect pairing, while grip-enhancing actuating rings and solid aluminum caps and plugs support everyday handling.

## Nozzle & Receiver Selection

| Nozzle Part No. | Matching Receiver Part No. | Color Code |
|---|---|---|
| MXN1-1p | MXR1-1c | |
| MXN2-1p | MXR2-1c | |
| MXN3-1p | MXR3-1c | |
| MXN4-1p | MXR4-1c | |
| MXN5-1p | MXR5-1c | |
| MXN6-1p | MXR6-1c | |
| MXN7-1p | MXR7-1c | |

Part numbers shown are for 1 in connections. Also available with **1¼ in NPT** connections; contact Fast Fill Systems for part numbers.

## Accessories

| Accessory | Part No. | Color Code |
|---|---|---|
| MX High Flow Evacuation Tool | MXET | |

## KEY SPECIFICATIONS


| Operating Pressure | Standard Nozzle Thread | Standard Receiver Thread | Construction |
|---|---|---|---|
| 34.5 bar / 500 PSI | 1 in FNPT | 1 in MNPT | Anodized aluminum and nickel-plated steel |

# MATRIX HIGH FLOW 3/4”




**Protective Plugs & Caps**

• Help keep nozzle and receiver connections free from dirt and debris between uses for clean, reliable coupling.








High Flow 3/4” Matrix couplers combine color-coded pairing with a single-body receiver designed to reduce potential leak points. Retained caps and plugs help protect connections between uses, while pull cords support easier handling during routine fluid service.

## Nozzle & Receiver Selection

| Nozzle Part No. | Matching Receiver Part No. | Color Code |
|---|---|---|
| N100U | R100-C | |
| N102-P | R102-C | |
| N103-P | R103-C | |
| N104-P | R104-C | |
| N105-P | R105-C | |
| N106-P | R106-C | |

## KEY SPECIFICATIONS

| Operating Pressure | Flow Area | Nozzle Thread | Receiver Thread | Latching Mechanism |
|---|---|---|---|---|
| 34.5 bar / 500 PSI | 0.421 in² | 3/4 in NPT | 1-3/8-18 UNEF | Ball latching |

# GREASE MATRIX




**Protective Plugs & Caps**

• Help keep nozzle and receiver connections free from dirt and debris between uses for clean, reliable coupling.



RECEIVER CAP





Grease Matrix flat-face dry-break couplers simplify bulk grease filling with a connection designed to couple and uncouple while maintaining supply pressure. An integrated valve prevents grease transfer until the nozzle and receiver are properly connected.

## Nozzle & Receiver Selection

| Nozzle Part No. | Matching Receiver Part No. | Color Code |
|---|---|---|
| GN210 | GR210 | |
| GN220 | GR220 | |

## KEY SPECIFICATIONS

| Maximum Deadhead Pressure | Nozzle Thread | Receiver Thread | Construction | Connection Guide |
|---|---|---|---|---|
| 345 bar / 5,000 PSI*<br>*At the integrated ball valve. | 3/4 in FNPT | 3/4 in MNPT | Nickel-plated steel and anodized aluminum | Dimple-and-groove system |

# FAQ

FAQ

## FUEL NOZZLES & RECEIVERS

**How do I choose the right fuel nozzle?**
Start with your required flow range, available pump pressure and receiver configuration. Consider handling, operating conditions and service needs as well. The right nozzle must work with the complete fueling system—not just meet a maximum flow rating.

**Will a higher-flow nozzle make fueling faster?**
Only if the rest of the system supports it. Pump capacity, hose size, fittings, receivers and tank venting all affect actual flow. A restriction elsewhere can limit the benefit of a higher-flow nozzle.

**Does the nozzle detect when the tank is full?**
Not on its own. The nozzle responds to the system's shutoff signal. In pressurized systems, this comes from tank pressure; in pressureless systems, level-control and shutoff components work together to stop filling.

**Are Fast Fill products compatible with other brands?**
Certain products are designed to work with other manufacturers' equipment. Compatibility must be checked for the specific models, connection interfaces and operating requirements. Similar appearance alone does not confirm a match.

**Why should the nozzle and receiver be inspected together?**
They work as a pair. A worn or damaged receiver can affect sealing, cause leaks and damage nozzle seals. Inspecting both helps identify the cause rather than repeatedly replacing the same parts.

## PRESSURELESS SYSTEMS & VENTING

**What does "pressureless" fueling mean?**
It means the system stops filling without relying on pressure buildup throughout the tank. A level control signals a shutoff valve when fuel reaches the intended level. The supply line still operates under pressure.

**Can existing equipment be converted to pressureless fueling?**
Retrofit options are available for many installations. The configuration depends on tank geometry, available ports, flow requirements and component placement. FFS can help review your equipment and identify a suitable arrangement.

**Can pressurized and pressureless components be mixed?**
Only where compatibility is specifically confirmed. These systems use different shutoff principles, so the nozzle, receiver, vent and control components must be selected as a compatible assembly.

**Why is tank venting important?**
Air must leave the tank during filling and enter as fuel is consumed. Restricted or incorrectly sized venting can slow fueling, cause premature shutoff and expose the tank to excessive pressure or vacuum.

**Does a filtered vent keep all contamination out?**
A filtered vent helps reduce airborne contamination entering the tank. Clean connections, protective caps and plugs, and proper maintenance remain essential because contamination can enter through other points in the system.





**Practical answers.**
**Better decisions.**

## FLUID COUPLERS & MATRIX

**How is a fluid coupler different from a fuel nozzle?**
Fluid couplers serve applications such as crankcase oil, coolant, hydraulic fluid, transmission fluid and grease transfer. Their pressure ratings, seals and connection designs vary. Select each coupler for its intended fluid and application.

**How does Matrix help prevent fluid mix-ups?**
Matrix combines visual color identification with mechanically keyed connections. Matching nozzle and receiver pairs help prevent incorrect connections and reduce cross-contamination risk when used with a documented fluid-assignment system.

**Is matching the color enough to select a coupling?**
No. Confirm the product family, matching codes, assigned fluid and operating limits. Color supports identification, but it does not establish compatibility between different coupling families.

**What does "universal" mean for a coupler?**
It describes compatibility with a defined set of interfaces. It does not mean the coupler fits every receiver or can be used with every fluid. Check the specific model's documented compatibility before selection.

**Why use protective caps and plugs?**
They help keep dirt and moisture away from connection surfaces and latching mechanisms between uses. Keeping these areas clean supports reliable coupling and helps reduce contamination and premature wear.

## SERVICE & SUPPORT

**Can a worn nozzle be rebuilt?**
A rebuild may be suitable when the housing and other critical components remain serviceable. Inspection determines whether rebuilding or replacement is the better option. Contact FFS with the model, serial number and symptoms.

**How often should components be inspected?**
Inspection frequency depends on operating conditions, usage and the component's maintenance instructions. Dust, abrasive contamination and heavy use may require more frequent checks. Include the complete fueling system in your maintenance plan.

**What should I do if a nozzle leaks or shuts off abnormally?**
Stop fueling and have the system inspected before returning it to normal service. The cause may involve the nozzle, receiver, vent or shutoff components. Follow the applicable service instructions rather than modifying parts or bypassing controls.

**What information helps FFS recommend a configuration?**
Share the equipment make and model, fluid type, required flow, pump capacity, tank details and existing part numbers. Photos of the installation and a description of the problem help our team understand your application.

### STILL HAVE A QUESTION?

Tell us about your equipment and what you need to achieve. Our team can help you review product options, compatibility and service requirements.
**contact@fastfillsystems.com**
**fastfillsystems.com**

DISTRIBUTOR NETWORK

# OUR DISTRIBUTOR NETWORK

**Connecting our experience with your market.**

## Over 30 years of Fast Fill Experience

NORTH AMERICA

SOUTH AMERICA

EUROPE

AFRICA

ASIA

OCEANIA

For over 30 years, Fast Fill Systems has developed fueling and fluid transfer solutions for demanding operations. Our distributors help bring that experience closer to the people who keep equipment running—connecting customers with FFS products and a purchasing contact who understands their market.



# BECOME A DISTRIBUTOR

Your customers rely on you to keep their operations moving. Bring Fast Fill Systems fueling and fluid transfer solutions to your product offering.

If your company serves mining, construction or heavy equipment operations, we'd like to hear from you. Tell us about your business and the region you serve, and let's explore how we can work together.

## Contact our team

orders@fastfillsystems.com
fastfillsystems.com



# HOW TO REQUEST A QUOTE

## Tell us what you need. Let's get started.

Every operation has its own requirements. Whether you need help selecting a product, reviewing a configuration, or requesting a quote, the Fast Fill Systems team is here to help. Share your application and the equipment you're working with so we can better understand your needs and guide the next step.

## Start your inquiry.


| EMAIL US | CALL US | VISIT OUR WEBSITE |
|---|---|---|
| contact@fastfillsystems.com | 801.491.3600 | www.fastfillsystems.com |



MADE IN USA ★ PROUDLY ★ HEAVY DUTY ★ HIGH QUALITY ★

***Quality, Service, Innovation***

# FAST FILL SYSTEMS




**Fast Fill Systems**
**2055 S. Tracy Hall Parkway,**
**Provo, Utah 84606**


| | |
|---|---|
| **Monday – Thursday** | 8:00 AM – 5:00 PM |
| **Friday** | 8:00 AM – 3:00 PM |


| | |
|---|---|
| **Phone**: | 801-491-3600 |
| **Web:** | www.fastfillsystems.com |

| | |
|---|---|
| **Technical Questions:** | fguzman@fastfillsystems.com |
| **Sales information:** | ignavillanueva@fastfillsystems.com |
| **Shipping Department:** | shipping@fastfillsystems.com |
| **Orders Department:** | orders@fastfillsystems.com |
| **Marketing:** | marketing@fastfillsystems.com |