



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Regularization

Leonid Mill, Tobias Würfl, Katharina Breininger, Nishant Ravikumar, Sebastian Gündel, Mathis Hoffmann, Florian Thamm, Felix Denzinger
Pattern Recognition Lab, Friedrich-Alexander University of Erlangen-Nürnberg
December 3, 2018





FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Loss function augmentation



General outline

- Implement it **independent** of loss function
 - **Only need** current weights
- Add it to the optimizer
- Change Neural Network container class to **gather regularization loss**
 - Instead of λ we use α as a name, because lambda is a python keyword

L_2 regularization

- Forward pass:

$$\tilde{L}(\mathbf{w}) = L(\mathbf{w}) + \lambda \|\mathbf{w}\|_2^2$$

- Backward pass:

$$\mathbf{w}^{(k+1)} = \underbrace{(1 - \eta \lambda) \mathbf{w}^{(k)}}_{\text{Shrinkage}} - \eta \frac{\partial L}{\partial \mathbf{w}^{(k)}}$$

L_1 regularization

- Forward pass:

$$\tilde{L}(\mathbf{w}) = L(\mathbf{w}) + \lambda \|\mathbf{w}\|_1$$

- Backward pass:

$$\mathbf{w}^{(k+1)} = \underbrace{\mathbf{w}^{(k)} - \eta \lambda \text{sign}(\mathbf{w}^{(k)})}_{\text{Other shrinkage}} - \eta \frac{\partial L}{\partial \mathbf{w}^{(k)}}$$



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Dropout



Method




Figure: Dropout

- Implement this as a **fixed-function layer**

Method




Figure: Dropout

- Implement this as a **fixed-function layer**
- Randomly set **activations** $\mapsto 0$ with probability $1 - p$

Method




Figure: Dropout

- Implement this as a **fixed-function layer**
- Randomly set **activations** $\mapsto 0$ with probability $1 - p$
- **Test-time**: multiply activations with p

Inverted Dropout

- Can we get rid of the dropout layer at Test-time?

Inverted Dropout

- Can we get rid of the dropout layer at Test-time?
- change the forward-pass
- Multiply activations in forward-pass by $\frac{1}{p}$



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Batch normalization



Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

$$\tilde{\mathbf{X}} = \frac{\mathbf{X} - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

μ_B and σ_B from **mini-batch**

Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

$$\tilde{\mathbf{X}} = \frac{\mathbf{X} - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

μ_B and σ_B from **mini-batch**

$$\hat{\mathbf{Y}} = \gamma \tilde{\mathbf{X}} + \beta$$

Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

$$\tilde{\mathbf{X}} = \frac{\mathbf{X} - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

μ_B and σ_B from **mini-batch**

$$\hat{\mathbf{Y}} = \gamma \tilde{\mathbf{X}} + \beta$$

- μ, σ have the **same dimension** as the **input vectors**

Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

$$\tilde{\mathbf{X}} = \frac{\mathbf{X} - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

μ_B and σ_B from **mini-batch**

$$\hat{\mathbf{Y}} = \gamma \tilde{\mathbf{X}} + \beta$$

- μ, σ have the **same dimension** as the **input vectors**
- β, γ and μ_B, σ_B have same **dimension** to be able to preserve **identity**

Forward pass

→ Normalization as a new layer with 2 parameters, γ and β

$$\tilde{\mathbf{X}} = \frac{\mathbf{X} - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

μ_B and σ_B from **mini-batch**

$$\hat{\mathbf{Y}} = \gamma \tilde{\mathbf{X}} + \beta$$

- μ, σ have the **same dimension** as the **input vectors**
- β, γ and μ_B, σ_B have same **dimension** to be able to preserve **identity**
- Notice that β is a **bias**

Test time

- Test-time: replace μ_B and σ_B with μ and σ of the **training set**

Test time

- Test-time: replace μ_B and σ_B with μ and σ of the **training set**
- It's **expensive** to calculate the true training set mean and variance

Test time

- Test-time: replace μ_B and σ_B with μ and σ of the **training set**
- It's **expensive** to calculate the true training set mean and variance
- Therefore a **moving average** is common:

$$\tilde{\mu}^{(k)} \approx (1 - \alpha)\mu_B^{(k-1)} + \alpha\mu_B^{(k)}$$

$$\tilde{\sigma}^{(k)} \approx (1 - \alpha)\sigma_B^{(k-1)} + \alpha\sigma_B^{(k)}$$

Test time

- Test-time: replace μ_B and σ_B with μ and σ of the **training set**
- It's **expensive** to calculate the true training set mean and variance
- Therefore a **moving average** is common:

$$\tilde{\mu}^{(k)} \approx (1 - \alpha)\mu_B^{(k-1)} + \alpha\mu_B^{(k)}$$

$$\tilde{\sigma}^{(k)} \approx (1 - \alpha)\sigma_B^{(k-1)} + \alpha\sigma_B^{(k)}$$

- Moving average **decay** α (i.e. 0.8)

Backward pass

- Gradient **with respect to weights** is simply:

$$\frac{\partial L}{\partial \gamma} = \sum_{b=1}^B \frac{\partial L}{\partial \hat{\mathbf{Y}}_b} \tilde{\mathbf{X}}_b = \sum_{b=1}^B \mathbf{E}_b \tilde{\mathbf{X}}_b$$

- For the **bias** likewise we have:

$$\frac{\partial L}{\partial \beta} = \sum_{b=1}^B \frac{\partial L}{\partial \hat{\mathbf{Y}}_b} = \sum_{b=1}^B \mathbf{E}_b$$

Backward pass

The **gradient with respect to the input** is more complicated, but here it is:

$$\frac{\partial L}{\partial \tilde{\mathbf{X}}} = \frac{\partial L}{\partial \hat{\mathbf{Y}}} \gamma$$

$$\frac{\partial L}{\partial \sigma_B^2} = \sum_{b=1}^B \frac{\partial L}{\partial \tilde{\mathbf{x}}_b} \cdot (\mathbf{x}_b - \mu_B) \cdot \frac{-1}{2} (\sigma_B^2 + \epsilon)^{\frac{-3}{2}}$$

$$\frac{\partial L}{\partial \mu_B} = \left(\sum_{b=1}^B \frac{\partial L}{\partial \tilde{\mathbf{x}}_b} \cdot \frac{-1}{\sqrt{\sigma_B^2 + \epsilon}} \right) + \underbrace{\frac{\partial L}{\partial \sigma_B^2} \cdot \frac{\sum_{b=1}^B -2(\mathbf{x}_b - \mu_B)}{B}}_0$$

$$\frac{\partial L}{\partial \mathbf{X}} = \frac{\partial L}{\partial \tilde{\mathbf{X}}} \cdot \frac{1}{\sqrt{\sigma_B^2 + \epsilon}} + \frac{\partial L}{\partial \sigma_B^2} \cdot \frac{2(\mathbf{X} - \mu_B)}{B} + \frac{\partial L}{\partial \mu_B} \cdot \frac{1}{B}$$

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**
- A scalar μ, σ is calculated for the H **channels**

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**
- A scalar μ, σ is calculated for the H **channels**
- Implementation can be reused, by observing
 - that **spatial dimensions M, N** can be treated **like the batch dimension B**

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**
- A scalar μ, σ is calculated for the H **channels**
- Implementation can be reused, by observing
 - that **spatial dimensions** M, N can be treated **like the batch dimension** B
 - we can **reshape** the $B \times H \times M \times N$ tensor to a $B \times H \times M \cdot N$
 - because of our format we have to **transpose** from $B \times H \times M \cdot N$ to $B \times M \cdot N \times H$
 - and afterwards **reshape again** to have a $B \cdot M \cdot N \times H$ tensor

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**
- A scalar μ, σ is calculated for the H **channels**
- Implementation can be reused, by observing
 - that **spatial dimensions** M, N can be treated **like the batch dimension** B
 - we can **reshape** the $B \times H \times M \times N$ tensor to a $B \times H \times M \cdot N$
 - because of our format we have to **transpose** from $B \times H \times M \cdot N$ to $B \times M \cdot N \times H$
 - and afterwards **reshape again** to have a $B \cdot M \cdot N \times H$ tensor
- Consequently we have to **reverse this** before returning the **output**

Convolutional Batch Normalization

- In CNNs batch normalization is adjusted to work **similar to convolution**
- A scalar μ, σ is calculated for the H **channels**
- Implementation can be reused, by observing
 - that **spatial dimensions** M, N can be treated **like the batch dimension** B
 - we can **reshape** the $B \times H \times M \times N$ tensor to a $B \times H \times M \cdot N$
 - because of our format we have to **transpose** from $B \times H \times M \cdot N$ to $B \times M \cdot N \times H$
 - and afterwards **reshape again** to have a $B \cdot M \cdot N \times H$ tensor
- Consequently we have to **reverse this** before returning the **output**
- ... and do the **same** in the **backward pass**



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

LeNet



LeNet architecture




Figure: LeNet

Modified LeNet architecture

Deviations

- Input is 28×28
- Our conv only supports “same” padding - so C3 has **larger activation maps**
- Input to **C5** is also **larger**
- We only implemented ReLUs, so **no** TanH
- We also use the implemented SoftMax **instead of** RBF units



Thanks for listening.
Any questions?