

Bayesian Data Analysis for REACH

2nd Global 21cm Workshop 2019


Dominic Anstey PhD Student

Bayesian Analysis


PolyChord – Bayesian Nested Sampling Algorithm (Handley, Hobson & Lasenby 2015)

- Model comparison through Bayesian Evidence
- Ranking parameter evaluation speeds

Varying B sky model




$$\ln(T_{foreground}(v)) = \sum_{i=0}^{4} a_i \left(\ln\left(\frac{v}{v_0}\right) \right)^i$$




- Remazeilles et al. 2015
- de Oliveira-Costa et al 2008

Elliptical Dipole Antenna




Antenna designs not finalised



Antenna patterns and images provided by John Cumner and Quentin Gueuning

Log Spiral Antenna




Antenna designs not finalised




Antenna patterns and images provided by John Cumner and Quentin Gueuning

Conical Sinuous Antenna





Antenna designs not finalised




Antenna patterns and images provided by John Cumner and Quentin Gueuning

Narrow Frequency Band







Elliptical Dipole

Log Spiral

Conical Sinuous


General Modelling Protocol


- Generate a parameterised model of the entire sky across the whole frequency range

- Generate a parameterised model of the antenna pattern

- Fit a foreground model of the convolution of the pattern model with the sky model

Sky Division






Foreground Model Function

$$K_i(v) = \frac{1}{4\pi} \int_{sky} G(\theta, \varphi, v) M_i(\theta, \varphi) \int_{time} [T_{base}(\theta, \varphi) - T_{CMB}] dt d\Omega$$

$$T_{foreground}(v) = A \sum_{i=1}^{N} K_{i}(v) \left(\frac{v}{v_{base}}\right)^{-\left(B_{i} + C_{i} ln\left(\frac{v}{v_{0}}\right)\right)}$$

Chromatic Functions




Foreground Model Function


$$K_i(v) = \frac{1}{4\pi} \int_{sky} G(\theta, \varphi, v) M_i(\theta, \varphi) \int_{time} [T_{base}(\theta, \varphi) - T_{CMB}] dt d\Omega$$

$$T_{foreground}(v) = A \sum_{i=1}^{N} K_{i}(v) \left(\frac{v}{v_{base}}\right)^{-\left(B_{i} + C_{i} ln\left(\frac{v}{v_{0}}\right)\right)}$$

Results




Inefficiencies



Conical Sinuous Antenna


Numbers of sky regions




Log Spiral Antenna

Inefficiencies


4 Regions



8 Regions



11 Regions



Conical Sinuous Antenna

Summary

- Even smooth, simple antennae produce enough chromatic distortion to conceal the 21cm signal when the spectral index varies
- The proposed method of fitting the foregrounds via modelling can correct for this distortion sufficiently for the 21cm signal to be identified, provided the antenna is quite smooth.
- Increasing the number of regions the sky model is divided into improves the quality of the chromaticity correction
- The distortion cannot be accurately modelled if too few regions are used

Acknowledgements

Eloy de Lera Acedo Will Handley John Cumner Quentin Gueuning Nicolas Fagnoni Nima Razavi-Ghods Anastasia Fialkov **Richard Hills** Paul Alexander

Plots produced using fgivenx tool: Handley, 2018









The Kavli **Foundation**



Cavendish Stellenbosch University **Astrophysics**



National Research Foundation South African Radio Astronomy Observatory





Leibniz-Institut für **Astrophysik Potsdam**



Tata Institute for **Fundamental Research**



University Carlos III Madriid











Groningen University







University of Malta



Rhodes University



Université catholique de Louvain

UCL

Université catholique de Louvain

Sussex University